

This is a preview of "PD 6697:2019". [Click here to purchase the full version from the ANSI store.](#)

PD 6697:2019



BSI Standards Publication

**Recommendations for the design of
masonry structures to BS EN 1996-1-1
and BS EN 1996-2**

bsi.

This is a preview of "PD 6697:2019". [Click here to purchase the full version from the ANSI store.](#)

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2019

Published by BSI Standards Limited 2019

ISBN 978 0 580 52401 1

ICS 91.080.30

The following BSI references relate to the work on this document:

Committee reference B/525

Draft for comment 18/30376287 DC

This is a preview of "PD 6697:2019". [Click here to purchase the full version from the ANSI store.](#)

CONTENTS

	Page
Foreword	iii
0 Introduction	1
1 Scope	1
2 Normative references	1
3 Terms and definitions	4
4 Symbols	7
5 Materials and components	9
<i>Table 1 — Physical properties and performance of materials for DPCs</i>	11
<i>Table 2 — Selection of ancillary components in relation to material/coating specification and situation</i>	15
<i>Table 3 — Sill materials</i>	18
<i>Table 4 — Lintels</i>	18
<i>Table 5 — Copings</i>	19
<i>Table 6 — Flashings and weatherings</i>	19
<i>Table 7 — Insulation products</i>	20
6 Design	20
<i>Figure 1 — Timber floor bearing directly on to a wall</i>	22
<i>Figure 2 — Timber floor using typical joist hanger</i>	23
<i>Figure 3 — Timber floor using nailed or bolted joist hangers acting as tie</i>	23
<i>Figure 4 — In-situ concrete floor bearing directly on to wall</i>	23
<i>Figure 5 — In-situ concrete floor abutting external cavity wall</i>	24
<i>Figure 6 — Beam and block floor abutting external cavity wall</i>	24
<i>Figure 7 — Timber floor abutting external cavity wall</i>	25
<i>Figure 8 — Timber floor using double joist hanger acting as tie</i>	25
<i>Figure 9 — Timber floor using typical joist hanger</i>	26
<i>Figure 10 — Timber floors abutting internal wall</i>	26
<i>Figure 11 — In-situ floors abutting internal wall</i>	27
<i>Figure 12 — Beam and block floor abutting internal wall</i>	27
<i>Figure 13 — Precast units abutting internal wall</i>	28
<i>Table 8 — Elastic modulus for concrete infill, E_{cm}</i>	30
<i>Figure 14 — Typical short-term design stress-strain curves for normal and low stress tendons</i>	31
<i>Figure 15 — Spacing of wall ties</i>	32
<i>Table 9 — Selection of wall ties: Types, categories and lengths</i>	33
<i>Table 10 — Classification of wall ties by end use</i>	34
<i>Figure 16 — Definitions for functional sections of masonry–masonry wall ties in an external cavity wall</i>	35
<i>Table 11 — Functional sections</i>	36
<i>Table 12 — Minimum declared tensile load capacity and compression load capacity for tie type for design embedment length</i>	36
<i>Figure 17 — Extent of corbelling</i>	37
<i>Figure 18 — Short returns in clay masonry</i>	40
<i>Figure 19 — Recommended allowances for differential movement between the timber frame structure and brick cladding</i>	43
<i>Table 13 — Categories of exposure to local wind-driven rain</i>	44
<i>Table 14 — Single-leaf masonry — Recommended thickness of masonry for different types of construction and categories of exposure</i>	46
<i>Figure 20 — Cavity parapet walls</i>	51
<i>Figure 21 Detail of typical chimney stack</i>	52

This is a preview of "PD 6697:2019". [Click here to purchase the full version from the ANSI store.](#)

	<i>Figure 22 — Freestanding and earth retaining wall (continued)</i>	54
	<i>Table 15 — Durability of masonry in finished construction</i>	59
	<i>Figure 23 — Typical cross sections of copings</i>	69
	<i>Table 16 — Values of the moment of resistance factor, Q, for various values of f_d and lever arm factor, c</i>	72
	<i>Figure 24 — Moment of resistance factor, Q</i>	73
	<i>Table 17 — Values of the coefficient j</i>	76
	<i>Table 18 — Loadbearing elements</i>	83
	<i>Table 19 — Detailed accidental damage recommendations</i>	84
	<i>Table 20 — Recommendations for full peripheral, internal and column or wall ties</i>	86
	<i>Table 21 — Recommendations for full vertical ties</i>	87
	<i>Figure 25 — Limiting dimensions of walls for stability</i>	91
7	Lintels: method of assessment of load	93
	<i>Figure 26 — Load triangle and interaction zone</i>	95
	<i>Figure 27 — Dispersion of loads</i>	96
	<i>Figure 28 — Effect of openings above the lintel</i>	97
	<i>Figure 29 — Example showing the loads on lintel with floor, partition and opening above the lintel</i>	98
	<i>Figure 30 — Example showing the loads on lintels supporting walls</i>	99
	<i>Table 22 — Conversion factors for determining equivalent UDLs from assessed UDLs^{A)}</i>	100
	<i>Table 23 — Conversion factors for determining equivalent UDLs from point loads close to the lintel^{A)}</i>	101
8	Work on site	101
	<i>Table 24 — Permissible deviations in masonry (other than stone masonry)</i>	103
	<i>Table 25 — Permissible deviations in stone masonry</i>	103
	<i>Figure 31 — Wall tie for high-lift grouted-cavity wall</i>	105
	Bibliography	107

Summary of pages

This document comprises a front cover, and inside front cover, pages i to iv, pages 1 to 107, an inside back cover and a back cover.

This is a preview of "PD 6697:2019". [Click here to purchase the full version from the ANSI store.](#)

Foreword

Publishing information

This Published Document is published by BSI and came into effect on 31 July 2019. It was prepared by Subcommittee B/525/6, *Use of masonry*, under the authority of Technical Committee B/525, *Building and civil engineering structures*. A list of organizations represented on these committees can be obtained on request to their secretary.

Supersession

This Published Document supersedes PD 6697:2010, which is withdrawn.

Information about this document

This Published Document is a background paper that gives non-contradictory complementary information for use in the UK with the following parts of BS EN 1996 *Design of masonry structures*, and their UK National Annexes:

- Part 1-1: General rules for reinforced and unreinforced masonry structures;
- Part 2: Design considerations, selection of materials and execution of masonry.

This new edition of PD 6697 incorporates technical changes only. It does not represent a full review or revision of the standard, which will be undertaken in due course.

Use of this document

This publication is not to be regarded as a British Standard.

Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its recommendations are expressed in sentences in which the principal auxiliary verb is "should".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

The word "should" is used to express recommendations of this standard. The word "may" is used in the text to express permissibility, e.g. as an alternative to the primary recommendation of the clause. The word "can" is used to express possibility, e.g. a consequence of an action or an event.

Notes and commentaries are provided throughout the text of this standard. Notes give references and additional information that are important but do not form part of the recommendations. Commentaries give background information.

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This is a preview of "PD 6697:2019". [Click here to purchase the full version from the ANSI store.](#)

This is a preview of "PD 6697:2019". [Click here to purchase the full version from the ANSI store.](#)

0 Introduction

When there is a need for guidance on a subject that is not covered by the Eurocode, a country can choose to publish documents that contain non-contradictory complementary information that supports the Eurocode. This Published Document provides just such information and has been cited as a reference in the UK National Annex to BS EN 1996-1-1.

1 Scope

This Published Document contains non-contradictory complementary information and additional guidance for use in the UK with BS EN 1996-1-1 and BS EN 1996-2.

BS EN 1996-1-2 and BS EN 1996-3 are not specifically dealt with, but this Published Document may be relevant.

Most of the material in this Published Document is taken from those parts of BS 5628-1, BS 5628-2, BS 5628-3 and BS EN 845 (all parts) that were not contradictory to the new BS EN 1996 series, but had to be withdrawn when those British Standards were withdrawn.

This Published Document does not cover the detailing of components for seismic design.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

BS 493, *Specification for air bricks and gratings for wall ventilation*

BS 1186-2, *Timber and workmanship in joinery – Part 2: Specification for workmanship*

BS 1186-3, *Timber and workmanship in joinery – Part 3: Specification for wood trim and its fixing*

BS 4486, *Specification for hot rolled and hot rolled and processed high tensile alloy steel bars for the prestressing of concrete*

BS 4729, *Clay bricks of special shapes and sizes – Recommendations*

BS 5440-1, *Fluing and ventilation for gas appliances of rated input not exceeding 70 kW net (1st, 2nd and 3rd family gases) – Part 1: Specification for installation of gas appliances to chimneys and for maintenance of chimneys*

BS 5617, *Specification for urea-formaldehyde (UF) foam systems suitable for thermal insulation of cavity walls with masonry or concrete inner and outer leaves*

BS 5618, *Code of practice for thermal insulation of cavity walls (with masonry or concrete inner and outer leaves) by filling with urea-formaldehyde (UF) foam systems*

BS 5642-1, *Sills, copings and cappings – Part 1: Specification for window sills of precast concrete, cast stone, clayware, slate and natural stone*

BS 5642-2, *Sills, copings and cappings – Part 2: Specification for copings and cappings of precast concrete, cast stone, clayware, slate and natural stone*

BS 5896, *High tensile steel wire and strand for the prestressing of concrete – Specification*

BS 6213, *Selection of construction sealants – Guide*

BS 6510, *Steel framed windows and glazed doors – Specification*