

This is a preview of "PD 5304:2019". [Click here to purchase the full version from the ANSI store.](#)

**PD 5304:2019**



**BSI Standards Publication**

## **Guidance on safe use of machinery**

**bsi.**

This is a preview of "PD 5304:2019". [Click here to purchase the full version from the ANSI store.](#)

**Publishing and copyright information**

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2019

Published by BSI Standards Limited 2019

ISBN 978 0 539 03706 7

ICS 13.110

The following BSI references relate to the work on this document:

Committee reference MCE/3

**Amendments/corrigenda issued since publication**

Date	Text affected
------	---------------

---

This is a preview of "PD 5304:2019". [Click here to purchase the full version from the ANSI store.](#)

## CONTENTS

	Page
<b>Foreword</b>	<b>ix</b>
<b>Section 1: General</b>	<b>1</b>
1 Scope	1
2 Normative references	1
3 Terms and definitions	3
<b>Section 2: Strategy for selecting protective measures</b>	<b>7</b>
4 General	7
<i>Figure 1 — Enclosed tools at a power press</i>	8
5 Selection of protective measures	10
6 Avoidance of reasonably foreseeable misuse of guards and protective devices	10
7 Phases of machine life	10
<b>Section 3: Risk assessment</b>	<b>11</b>
8 General	11
<i>Figure 2 — Iterative process to reduce risk</i>	12
9 Severity of harm	12
10 Probability of occurrence of harm	13
11 Risk evaluation	13
12 Documentation	13
<b>Section 4: Identification of hazards</b>	<b>15</b>
13 Hazards at machinery	15
14 Mechanical hazards	16
14.1 General	16
<i>Figure 3 — Individual parts of machines causing one or more types of injury, e.g. hazards at an abrasive wheel</i>	16
14.2 Entanglement	16
<i>Figure 4 — Entanglement caused by contact with a single rotating surface</i>	17
<i>Figure 5 — Entanglement caused by catching on projections or in gaps</i>	17
<i>Figure 6 — Drawing-in hazards between two counter-rotating parts</i>	18
<i>Figure 7 — Entanglement caused by catching between rotating and other moving parts (1 of 2)</i>	18
<i>Figure 7 — Entanglement caused by catching between rotating and other moving parts (2 of 2)</i>	18
<i>Figure 8 — Entanglement caused by catching between rotating and fixed parts</i>	19
<i>Figure 9 — Entanglement caused by catching in materials in motion (swarf)</i>	19
14.3 Friction and abrasion	19
<i>Figure 10 — Friction and abrasion hazards</i>	20
14.4 Cutting or severing	20
<i>Figure 11 — Cutting hazards</i>	21
14.5 Shearing	21
<i>Figure 12 — Shear hazards between two machine parts</i>	22
<i>Figure 13 — Shear hazards between a machinery part and a workpiece</i>	22
<i>Figure 14 — Removal of shear trap by design</i>	23
<i>Figure 15 — Gap cover to prevent shear trap</i>	23
14.6 Stabbing or puncture	23
<i>Figure 16 — Stabbing and puncture by flying objects</i>	24
<i>Figure 17 — Stabbing and puncture by rapidly moving parts of machinery or pieces of material</i>	24
14.7 Impact	24
<i>Figure 18 — Impact hazards</i>	25
14.8 Crushing	25
<i>Figure 19 — Crushing hazards</i>	26

This is a preview of "PD 5304:2019". [Click here to purchase the full version from the ANSI store.](#)

	<i>Figure 20 — Drawing-in hazards between rotating and tangentially moving surfaces</i>	27
	<i>Figure 21 — Roller conveyor: first idle roller free to prevent drawing-in</i>	27
14.10	Injury by compressed air or high-pressure fluid injection	27
15	Non-mechanical hazards	28
15.1	General	28
15.2	Electricity, including static electricity	28
15.3	Thermal	28
15.4	Noise	28
15.5	Radiation	29
15.6	Use of harmful materials and substances	29
15.7	Vibration	30
15.8	Poor ergonomics	30
15.9	Inadequate access	30
15.10	Environment	30
15.11	Hygiene	30
	<b>Section 5: Aspects of machine design to eliminate or reduce risks</b>	<b>31</b>
16	Design for safe use	31
17	Checks by user	31
18	Further considerations for safeguards	32
18.1	General	32
18.2	Corrosion	32
18.3	Coolant and swarf	32
18.4	Waste and spillage removal	32
18.5	Mist, fumes and dust	32
19	Controls	32
19.1	Position	32
	<i>Figure 22 — Foot pedal protected from accidental operation by means of a cover</i>	33
19.2	Identification	33
19.3	Operation	34
19.4	Controls for machinery setting or adjustment and for feeding material	34
19.5	Handles and hand-wheels	34
19.6	Warning signals	34
19.7	Program or sequence control	35
20	Indicators	35
21	Unexpected/unintended start-up	35
22	Measures for the escape and rescue of trapped persons	36
23	Clutches	37
24	Braking systems	37
24.1	General	37
24.2	Mechanical (friction) braking systems	37
24.3	Electrodynamic braking systems	38
25	Safety catches, overrun, runback and fall-back protection devices	39
26	Counterweights and similar devices	39
27	Rotating shafts, spindles and couplings	39
	<i>Figure 23 — Guarding of shafts and couplings: Fixed guard for a transmission shaft and coupling</i>	40
	<i>Figure 24 — Tractor power take-off drives</i>	40
	<i>Figure 25 — Telescopic type guard</i>	41
28	Feeding and take-off devices	41
29	Hydraulic and pneumatic systems	41

This is a preview of "PD 5304:2019". [Click here to purchase the full version from the ANSI store.](#)

31	Workholding devices	41
31.1	Power loss during operation	41
31.2	Workholding devices for automatic machinery	42
31.3	Prevention of inadvertent unclamping of the workpiece	42
32	Lifting, handling and transport	42
33	Static and dynamic stability	42
34	Lubrication	43
35	Lighting	43
36	Hygiene and guard design	43
37	Safety markings, signs (pictograms) and written warnings	43
38	Access (see also Section 11)	44
38.1	Operating stations	44
38.2	Platforms, steps and ladders	44
38.3	Access for adjustment, lubrication and maintenance	44
39	Programmable systems	44
	<b>Section 6: Selection of safeguards</b>	<b>46</b>
40	General	46
	<i>Figure 26 — Fundamental considerations involved in guarding a machine (1 of 3)</i>	46
	<i>Figure 26 — Fundamental considerations involved in guarding a machine (2 of 3)</i>	47
	<i>Figure 26 — Fundamental considerations involved in guarding a machine (3 of 3)</i>	48
41	Where access to the hazard zone is not required during normal operation	49
42	Where access to the hazardous area can be required during normal operation	49
43	Where access to the hazard zone is required during normal operation	49
44	Access to the hazardous area for infrequent operation	50
	<b>Section 7: Guard design and construction</b>	<b>51</b>
45	General	51
46	Types of guard	51
46.1	Fixed guard (see Figure 27 to Figure 36)	51
	<i>Figure 27 — Fixed enclosing guard constructed of wire mesh and angle section preventing access to transmission machinery from all directions</i>	52
	<i>Figure 28 — Fixed guards for chains and chain wheels</i>	53
	<i>Figure 29 — Example of a quick release fixed guard</i>	54
	<i>Figure 30 — Use of flat plate or angle section to prevent access to in-running nips</i>	54
	<i>Figure 31 — Feeding material to a pair of rollers</i>	55
	<i>Figure 32 — Small horizontal Table, stiffened to prevent deflection, spanning the full width of a calender</i>	55
	<i>Figure 33 — Use of fixed curve metal plates to prevent access to in-running nips</i>	56
	<i>Figure 34 — Fixed guard that allows continuous observation of the in-running nip point</i>	56
	<i>Figure 35 — Captive drawer</i>	57
	<i>Figure 36 — Feeding of bulk material from the floor above the machine</i>	58
	<i>Figure 37 — Transparent tunnel guard over conveyor belt</i>	59
	<i>Figure 38 — Example of interlocked tunnel guard</i>	59
	<i>Figure 39 — Example of interlocking tunnel guard on food preparation machinery</i>	60
	<i>Figure 40 — Fixed distance guard fitted to a press brake</i>	61
	<i>Figure 41 — Example of guarding an industrial robot with a perimeter fence type guard</i>	62
	<i>Figure 42 — Close contour perimeter fence guard</i>	63
46.2	Movable guard	63
	<i>Figure 43 — Power-operated guards and doors</i>	64
	<i>Figure 44 — Balance weights to reduce the effort required to open a rise and fall guard</i>	65

This is a preview of "PD 5304:2019". [Click here to purchase the full version from the ANSI store.](#)

	<i>no balance weight</i>	65
46.3	Interlocking guard	65
	<i>Figure 46 — Sensing guard fitted to a riveting machine</i>	67
	<i>Figure 47 — Example of interlock on a hopper extension</i>	68
46.4	Push-away and sweep-away guards	69
46.5	Adjustable guard (see Figure 48, Figure 49 and Figure 50)	70
	<i>Figure 48 — Adjustable guard for a radial or pedestal drilling machine</i>	71
	<i>Figure 49 — Adjustable guard on a circular sawing machine</i>	72
	<i>Figure 50 — Adjustable guard for the cutters of horizontal milling machines</i>	72
46.6	Self-adjusting guard	73
	<i>Figure 51 — Self-adjusting guard arrangements for snipper cross-cut sawing machine</i>	73
46.7	False Table (see Figure 52 and Figure 53)	73
	<i>Figure 52 — False Table and fixed guard applied to a milling machine</i>	74
	<i>Figure 53 — False Table and interlocking guard applied to a rotating Table pie and tart machine</i>	75
47	Guard construction	75
47.1	General	75
47.2	Material	76
47.3	Supports	77
	<i>Figure 54 — Support for a horizontally sliding guard</i>	78
47.4	Cover plates	78
48	Anthropometric considerations	78
48.1	General	78
48.2	Openings in a guard	78
	<i>Figure 55 — Opening in a fixed guard at a metal cutting guillotine</i>	79
48.3	Barriers	79
	<b>Section 8: Protective devices</b>	<b>80</b>
49	Trip devices (see Figure 56 to Figure 60)	80
49.1	General	80
49.2	Mechanical trip device	80
	<i>Figure 56 — Distance bar trip guard</i>	81
	<i>Figure 57 — Trip device on a flat work ironing machine (calender) used in laundries</i>	82
	<i>Figure 58 — Trip device for horizontal two-roll mills used in the rubber industry</i>	83
	<i>Figure 59 — Trip bar for mitigating the risk of trapping between a down-running conveyor and the casing of a final prover</i>	84
	<i>Figure 60 — Trip device for drilling machines</i>	85
49.3	Electro-sensitive protective equipment	85
	<i>Figure 61 — Electro-sensitive protective equipment using light curtains (AOPDs) as a trip and presence-sensing device at a press brake</i>	87
	<i>Figure 62 — Electro-sensitive protective equipment using light curtains (AOPDs) as a trip device at a depalletizer</i>	87
	<i>Figure 63 — Electro-sensitive protective equipment using light curtains (AOPDs) as presence-sensing devices at a robot-served pressure die casting machine</i>	88
	<i>Figure 64 — Electro-sensitive protective equipment equipped with active opto-electronic devices responsive to diffuse reflection (AOPDDR) used as trip and presence-sensing devices on an automated guided vehicle (AGV)</i>	89
49.4	Pressure-sensitive mats (see Figure 65)	90
	<i>Figure 65 — Pressure-sensitive mat safeguarding the clamping and bending jaws of an automatic horizontal tube bender</i>	91
50	Pressure-sensitive cables (see Figure 66)	91

This is a preview of "PD 5304:2019". [Click here to purchase the full version from the ANSI store.](#)

51	Hold-to-run control	91
52	Enabling device	93
53	Two-hand control device (see Figure 67)	93
	<i>Figure 67 — Two-hand control device</i>	94
54	Limiting and limited movement control devices	94
54.1	General	94
54.2	Timed impulse device	95
54.3	Controlled movement device	95
55	Mechanical restraint device (see Figure 68 and Figure 69)	95
55.1	General	95
55.2	Down-stroking platens	95
	<i>Figure 68 — Augmenting an interlocking guard with a mechanical restraint device</i>	96
	<i>Figure 69 — Mechanical restraint</i>	97
56	Emergency operation – emergency stop and emergency switching off	98
56.1	General	98
	<i>Figure 70 — Emergency stop button</i>	98
56.2	Emergency stop	98
56.3	Emergency switching off	99
56.4	Pull-cord actuators (see Figure 71 and BS EN 60947-5-5:1998+A2:2017, 6.4.2)	99
	<i>Figure 71 — Emergency stopping of conveyors (1 of 2)</i>	100
	<i>Figure 71 — Emergency stopping of conveyors (2 of 2)</i>	101
	<b>Section 9: Interlocking</b>	<b>102</b>
57	Functions of an interlock	102
58	Interlocking energy sources	102
59	Interlocking methods for power interruption	102
59.1	General	102
59.2	Interlocking guard without guard locking	103
59.3	Interlocking guard with guard locking	103
59.4	Mechanical trapped-key guard interlock (see Figure 85)	103
60	Interlocking methods incorporating braking, purging, etc., and/or guard locking	103
60.1	General	103
60.2	Braking system	104
60.3	Guard locking systems	104
61	Security of interlocking	105
	<i>Figure 72 — Defeatability of sliding interlocking guards</i>	106
	<i>Figure 73 — Defeatability of hinged interlocking guards</i>	107
62	Electrical interlocking devices	106
62.1	General	106
62.2	Cam-operated position switch	108
	<i>Figure 74 — Mounting of individual position switches</i>	109
	<i>Figure 75 — Position switches or valves actuated by rotary cams</i>	110
	<i>Figure 76 — Actuation of roller-operated position switches or valves by a cam</i>	112
	<i>Figure 77 — Position switches actuated by rotary cams (guard in open position)</i>	112
	<i>Figure 78 — Large hinged guards</i>	113
	<i>Figure 79 — Position switch operating in the non-positive mode (incorrect application)</i>	113
	<i>Figure 80 — Two position switches operating in opposite modes, mounted side-by-side, each actuated by its own cam mounted on the guard hinge</i>	114
	<i>Figure 81 — Mounting of position switches in opposite modes</i>	114
62.3	Tongue-operated switch	115

This is a preview of "PD 5304:2019". [Click here to purchase the full version from the ANSI store.](#)

62.4	Captive-key switch (see Figure 83)	115
	<i>Figure 83 — Captive-key switch</i>	116
	<i>Figure 84 — Timed delay captive-key unit</i>	116
62.5	Trapped-key interlocking system (key exchange)	116
	<i>Figure 85 — Trapped-key interlocking systems (1 of 2)</i>	118
	<i>Figure 85 — Trapped-key interlocking systems (2 of 2)</i>	119
	<i>Figure 86 — Practical application of the trapped-key interlocking system shown diagrammatically in Figure 85a)</i>	120
	<i>Figure 87 — Internal mixing machine: example of the use of a trapped-key interlocking system (1 of 2)</i>	121
	<i>Figure 87 — Internal mixing machine: example of the use of a trapped-key interlocking system (2 of 2)</i>	122
62.6	Uncoded non-contact switches	123
62.7	Coded non-contact switches (see Figure 88)	123
	<i>Figure 88 — Example use of a non-contact switch where an interlocking guard has to be removed</i>	123
62.8	Magnetic switch	123
62.9	Plug and socket system	124
62.10	Manually-operated delay device (see Figure 89)	124
	<i>Figure 89 — Manually-operated delay device</i>	125
62.11	Shotbolt (see Figure 90)	125
	<i>Figure 90 — Locking a guard closed with a shotbolt</i>	126
62.12	Power interlocking (see Figure 91)	126
	<i>Figure 91 — Guard locking power interlocking</i>	127
63	Mechanical interlocking devices	127
63.1	General	127
	<i>Figure 92 — Interlocking guard for positive clutch power press</i>	128
	<i>Figure 93 — Principles of mechanical interlocking</i>	129
63.2	Design	129
64	Pneumatic interlocking devices	129
64.1	General	129
64.2	Cam-operated valve	130
	<i>Figure 94 — Diagrams for a cam-operated pneumatic interlocking valve</i>	131
64.3	Captive-key valve	131
64.4	Trapped-key interlocking system (key exchange)	131
64.5	Pneumatically-operated shotbolt	132
64.6	Power interlocking	132
	<i>Figure 95 — Interlocking guard with and without guard locking (1 of 2)</i>	132
	<i>Figure 95 — Interlocking guard and interlocking guard with guard locking interlocking (2 of 2)</i>	133
65	Hydraulic interlocking devices	133
65.1	General	133
65.2	Cam-operated valves	133
65.3	Hydraulically-operated shotbolt	134
65.4	Power interlocking	134
	<i>Figure 96 — Power interlocking in hydraulic systems</i>	135
	<b>Section 10: Safety-related control systems associated with protective devices</b>	<b>136</b>
66	General	136
67	Architectural considerations	136
67.1	Types of control systems	136
	<i>Figure 97 — Designated architecture</i>	137

This is a preview of "PD 5304:2019". [Click here to purchase the full version from the ANSI store.](#)

67.3	Integrity of interlocking control systems	139
67.4	Choice of interlocking control system	139
67.5	Electrical considerations	139
	<i>Figure 98 — Prevention of earth fault (1 of 2)</i>	141
	<i>Figure 98 — Prevention of earth fault (2 of 2)</i>	141
	<i>Figure 99 — Example of single-control system interlocking</i>	142
67.6	Mechanical considerations	144
67.7	Pneumatic considerations	145
	<i>Figure 100 — Single-control system interlocking for arresting the motion of a cylinder</i>	146
	<i>Figure 101 — Dual-control system interlocking without cross-monitoring: both channels pneumatic</i>	147
	<i>Figure 102 — Principles of pneumatic and electrical circuits: dual-control system interlocking with cross-monitoring, one control channel pneumatic, one electric (monitoring channel electric)</i>	148
	<i>Figure 103 — Use of an equalizing valve</i>	150
	<i>Figure 104 — Locking a guard closed (see also 60.3)</i>	152
67.8	Hydraulic considerations	153
	<i>Figure 105 — Single-control system interlocking used to interrupt the main hydraulic supply to the actuator</i>	153
	<i>Figure 106 — Dual-control system interlocking without cross-monitoring</i>	154
	<i>Figure 107 — Dual-control system interlocking with cross-monitoring</i>	155
	<i>Figure 108 — Hydraulic press: control of stroke</i>	157
	<i>Figure 109 — Rapid closing of an upstroking press</i>	159
68	Safety-related control systems	159
69	Cyber security	160
	<b>Section 11: Installation considerations</b>	<b>161</b>
70	Layout of machinery and plant	161
71	Moving parts of machinery	161
72	Services	161
72.1	Lighting	161
72.2	Cables and pipes	162
72.3	Access to machinery for maintenance (see 38.3)	162
	<b>Section 12: Maintenance and safe systems of work</b>	<b>163</b>
73	General	163
74	Maintenance	163
74.1	Safeguards	163
74.2	Waste and spillage removal	164
75	Safe systems of work	164
75.1	General	164
75.2	Machinery operation	164
75.3	Isolation of power and dissipation of energy	165
	<i>Figure 110 — Multi-padlockable hasp</i>	167
	<i>Figure 111 — Example of padlock complete with danger board for locking-off after isolation</i>	168
	<i>Figure 112 — Gravity or spring-operated latch</i>	169
75.4	Practices for restricted operation	169
76	Supervisory control	169
76.1	General	169
76.2	Permit to work systems	170
77	Information and training	172
77.1	General	172

This is a preview of "PD 5304:2019". [Click here to purchase the full version from the ANSI store.](#)

77.3	Installation, operation and maintenance instructions	172
77.4	Training	173
77.5	Personal protection	173
<b>Annex A</b>	<b>(normative) Ergonomic data</b>	<b>174</b>
	<i>Figure A.1 — Safety distance for reaching upwards</i>	175
	<i>Figure A.2 — Diagram showing dimensions a, b and c used in Table A.1 and Table A.2</i>	176
	<i>Table A.1 — Low risk values of a, b and c for Figure A.2</i>	177
	<i>Table A.2 — High risk values of a, b and c for Figure A.2</i>	178
	<i>Table A.3 — Safety distances</i>	179
	<i>Table A.4 — Safety distances, <math>s_p</math>, through regular openings of size e</i>	180
	<i>Figure A.3 — Safety distances for openings of irregular shape</i>	181
<b>Annex B</b>	<b>(informative) Common types of failures associated with safety-related interlocking control systems</b>	<b>182</b>
<b>Annex C</b>	<b>(informative) Essentials of a permit to work form</b>	<b>190</b>
	<i>Figure C.1 — Example of a permit to work form</i>	190
	<b>Bibliography</b>	<b>191</b>

### Summary of pages

This document comprises a front cover, and inside front cover, pages i to x, pages 1 to 192, an inside back cover and a back cover.

This is a preview of "PD 5304:2019". [Click here to purchase the full version from the ANSI store.](#)

## Foreword

### Publishing information

This Published Document is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 December 2019. It was prepared by Technical Committee MCE/3, *Safeguarding of machinery*. A list of organizations represented on this committee can be obtained on request to its secretary.

### Supersession

This Published Document supersedes PD 5304:2014, which is withdrawn.

### Information about this document

BS 5304:1988 was withdrawn following publication of a series of harmonized European machinery safety standards. Recognizing that BS 5304 contained valuable practical advice, PD 5304:2000, followed by PD 5304:2005 and PD 5304:2014, was published to retain the advice contained in BS 5304, with the addition of references to those relevant harmonized European machinery safety standards.

This edition takes account of the requirements of the current harmonized European machinery safety standards, to help the user maintain those safety requirements when upgrading, refurbishing or changing the use of machinery.

*NOTE* The bibliography provides a link to an online list of harmonized European standards relevant to machinery safety.

Ensuring that risks associated with the use of machinery are eliminated or reduced is a task that requires unremitting and careful attention at all times. It is hoped that this Published Document will make a worthwhile contribution to the prevention of harm arising from the use of machinery. It is intended to serve as a useful guide to all those with responsibility for safe use of machinery and duties under the Health and Safety at Work etc. Act 1974 and the Provision and Use of Work Equipment Regulations 1998.

Figures are used to illustrate the general application of these principles. However, solutions other than those illustrated can be equally effective.

The safeguarding of machinery is continually being improved. Users of machinery need to make themselves aware of any new codes of practice, etc., which might be published from time to time and any other relevant new developments.

This Published Document can be withdrawn, revised, partially superseded or superseded. Information regarding the status of this Published Document can be found in the Standards Catalogue on the BSI website at [bsigroup.com/standards](https://bsigroup.com/standards), or by contacting the Customer Services team.

Where websites and webpages have been cited, they are provided for ease of reference and are correct at the time of publication. The location of a webpage or website, or its contents, cannot be guaranteed.

This is a preview of "PD 5304:2019". [Click here to purchase the full version from the ANSI store.](#)

The guidance in this Published Document is presented in roman (i.e. upright) type. Any recommendations are expressed in sentences in which the principal auxiliary verb is "should".

The word "may" is used in the text to express permissibility, e.g. as an alternative to the primary recommendation of the Clause. The word "can" is used to express possibility, e.g. a consequence of an action or an event.

*Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.*

### **Contractual and legal considerations**

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

**Compliance with a Published Document cannot confer immunity from legal obligations.**

This is a preview of "PD 5304:2019". [Click here to purchase the full version from the ANSI store.](#)

## Section 1: General

---

### 1 Scope

This Published Document provides guidance on the safe use (see [3.21](#)) of machinery, including that supplied prior to the implementation of the Supply of Machinery (Safety) Regulations 2008 [\[1\]](#).

It provides guidance on:

- a) the basic principles of safeguarding, with reference to current harmonized European machinery safety standards; and
- b) the continuing safe use of machinery manufactured in accordance with harmonized European machinery safety standards, in conjunction with the machine supplier's instructions for use.

This Published Document is intended to promote a high standard of machinery safety. It describes and illustrates a variety of protective measures and explains methods by which it is possible to assess which measure(s) it is reasonable to adopt in particular circumstances. It is necessary, however, to consult specific legislation in applying the principles set down. Although reference is made to particular types of machine, specific recommendations are not given for every type of machine.

The guidance can be applied to machinery during its modification, refurbishment, upgrading or change of use in order to satisfy the Provision and Use of Work Equipment Regulations (PUWER) 1998 [\[2\]](#).

*NOTE 1 See also HSE Approved Code of Practice L22: Safe use of work equipment [\[3\]](#).*

*NOTE 2 Significant modification, refurbishment, upgrading or change of use to existing machinery that results in, for example, changes in the measures used to reduce risk(s) or the introduction of a new hazard(s), can make it necessary to satisfy relevant requirements from the Supply of Machinery (Safety) Regulations 2008 [\[1\]](#), in particular Schedule 3.*

*NOTE 3 PD 5304 is not intended to be used as an alternative to the current harmonized European machinery safety standards for machinery supplied in accordance with the Supply of Machinery (Safety) Regulations 2008 [\[1\]](#).*

---

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes provisions of this document.<sup>1</sup> For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

BS 6753, *Specification for shotbolts (solenoid operated) for guarding machinery*

BS EN 349, *Safety of machinery – Minimum gaps to avoid crushing of parts of the human body*

BS EN 981, *Safety of machinery – System of auditory and visual danger and information signals*

BS EN 1299, *Mechanical vibration and shock – Vibration isolation of machines – Information for the application of source isolation*

BS EN 1550, *Machine-tools safety – Safety requirements for the design and construction of work holding chucks*

BS EN 1672-2, *Food processing machinery – Basic concepts – Part 2: Hygiene requirements*

BS EN 1837, *Safety of machinery – Integral lighting of machines*

---

<sup>1</sup> Documents that are referred to solely in an informative manner are listed in the Bibliography.