BS 5410-1:2019 Incorporating corrigendum No. 1



BSI Standards Publication

Code of practice for liquid fuel firing

Part 1: Installations for space heating and hot water supply purposes for domestic buildings



Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2019

Published by BSI Standards Limited 2019

ISBN 978 0 539 05852 9

ICS 27.060.10

The following BSI references relate to the work on this document: Committee reference RHE/13 Draft for comment 18/30359025 DC

Amendments/corrigenda issued since publication

Date	Text affected
August 2019	C1:Figure 8

CUIICI	115	rage
	Foreword	
1		iv
1 2	Scope Normative references	1 1
3	Terms and definitions	2
4	Liquid fuels	4
4.1	Types of liquid fuel	4
4.2	Liquid fuel characteristics	4
5	Installation of liquid fuel fired appliances	4
5.1	General	4
5.2	Selection of appliance	5
5.3	Siting of appliance	5
5.4	Provision of air for combustion and ventilation	6
	Figure 1 — Combustion and ventilation air supply for room sealed balanced flued liquid fuel fired	-
	appliances	7
	Figure 2 — Combustion and ventilation air supply for open flued liquid fuel fired appliances	8
5.5	Water circulating heating systems	10
5.6	Special installations	10
5.7	Appliance temperature and its relation to surrounding building materials	14
6	Liquid fuel storage tanks and equipment	14
6.1	Liquid fuel tank construction	14
	Table 1.A — Types of above ground liquid fuel storage tank and locations for which they	
	are suitable	15
	Table 1.B — Types of below ground liquid fuel storage tank and locations for which they	
	are suitable	15
6.2	Capacity	15
	Table 2 — Recommended liquid fuel storage tank capacities	15
6.3	Provision for measurement of contents of liquid fuel storage tanks — tank contents	
	display systems	15
6.4	Overfilling alarm and signalling system	16
6.5	Filling pipes and connection	17
6.6	Vent pipes	17
6.7	Filtration system	17
	Figure 3 — Liquid fuel supply system with bottom of oil storage tank above burner — Single	
	pipe supply	18
	Figure 4 — Liquid fuel supply system with a single pipe connected through top of tank to a liquid	
	fuel lifter	19
	Figure 5 — Liquid fuel supply system with a single pipe connected through top of tank to a de-	
	aeration device	20
7	Positioning and protection for liquid fuel storage tanks	17
7.1	Siting of liquid fuel storage tanks	17
7.2	Methods of tank protection	21
	Table 3 — Protection of a liquid fuel storage tank located externally to a building	21
7.3	Tank accommodation	22
7.4	Secondary containment (bunds)	25
8	Installation of liquid fuel storage tanks	25
8.1	General	25
8.2	Supports for steel tanks	26
	Table 4 — Distance between supports for steel liquid fuel storage tanks	26

This is a preview of "BS 5410-1:2019". Click here to purchase the full version from the ANSI store. 27 8.4 Painting and cleaning of steel tanks 8.5 Tank inspection access 27 8.6 Tank screening 27 8.7 Multiple storage tank installations 28 9 Liquid fuel system from storage tank to burner 29 9.1 Fuel supply systems 29 *Figure 6 — Fire valve positioning for a vaporizing range cooker* 30 *Figure 7* — *Positions of de-aerators in relation to a flue terminal* 32 9.2 Fuel feed pipework 32 9.3 Fire valve types and installation 34 10 Flues and chimneys 35 10.1 Chimneys and connecting flue pipes 35 Table 5 — Minimum performance designations for chimney and flue pipe components for use with liquid fuel fired appliances with a flue gas temperature of less than 250 °C 35 10.2 Choice of materials 36 10.3 Construction of masonry or flueblock chimneys 36 10.4 Factory made insulated chimneys (system chimneys) 36 10.5 Plastic chimney systems 37 10.6 Connecting flue pipes 37 10.7 Chimney terminals 37 10.8 Position of chimney terminals for open flued appliances (see Figure 8) 37 10.9 Flue terminals 38 *Figure 8 — Flue terminal positions for liquid fuel fired appliances* 38 11 Design and installation of flues and chimneys 39 11.1 General 39 11.2 Size of flues 40 11.3 Shared flues 40 11.4 Masonry chimneys 40 11.5 Installation of flue pipes 41 42 11.6 Dampers 11.7 Inspection and cleaning 42 11.8 Inspection on site 42 12 Room sealed balanced flue appliances 43 12.1 General 43 12.2 Mounting 43 12.3 Sizing 43 12.4 Terminal location 43 13 Special categories of flue systems for use with condensing appliances 44 13.1 Flue materials 44 13.2 Condensate disposal 44 14 Electrical installation and system controls 44 15 Commissioning 45 15.1 General 45 15.2 Appliance commissioning 45 15.3 System commissioning 46 16 Maintenance 46 16.1 General 46 16.2 Appliance maintenance 47 16.3 Liquid fuel storage tank maintenance 47

	Bibliography	57
Annex B	(informative) Example of a chimney designation in accordance with BS EN 1443:2003	56
	Figure A.4 — Typical Modulation Pressure Jet Burner	55
	Figure A.3 — Typical High/Low Pressure Jet Burner	54
	Figure A.2 — Typical On/Off Pressure Jet Burner	53
	Figure A.1 — Schematic diagram of a natural draught perforated sleeve burner	52
Annex A	(informative) Types of appliances and burners covered by this British Standard	51
18.5	Servicing and inspection	50
18.4	Liquid fuel storage	50
18.3	Liquid fuel supply system	50
18.2	Liquid fuel burners	49
18.1	General	49
18	Biofuels	49
17	Conversion of appliances to liquid fuel firing	49
16.6	Maintenance records	
16.5	System maintenance	48

Summary of pages

This document comprises a front cover, and inside front cover, pages i to vi, pages 1 to 59, an inside back cover and a back cover.

Foreword

Publishing information

This part of BS 5410 is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 30 June 2019. It was prepared by Technical Committee RHE/13, *Liquid fuel firing*. A list of organizations represented on this committee can be obtained on request to its secretary.

Supersession

This part of BS 5410 supersedes BS 5410-1:2014 which is withdrawn.

Relationship with other publications

BS 5410 is published in three parts:

- Part 1: Installations for space heating and hot water supply purposes for domestic buildings
- Part 2: Installations providing space heating, hot water and steam supply services to nondomestic buildings
- Part 3: Installations for furnaces, kilns, ovens, oil-fuelled standby generators and other industrial purposes.

Hazard warnings

WARNING. Decommissioning and disposal of liquid fuel storage tanks

The decommissioning and disposal of liquid fuel storage tanks can become necessary as part of the maintenance cycle of a liquid fuelled system. This is not covered in the present standard. It is a very hazardous procedure, and it is imperative that it is only undertaken by specialist operatives who have the right equipment, expertise and insurance. Building owners should never attempt to cut up old liquid fuel storage tanks themselves.

NOTE 1 Attention is drawn to the Construction (Design and Management) Regulations 2007 (as amended, 2015) [1], which class such work as a "demolition project".

NOTE 2 Detailed guidance on decommissioning and disposal of liquid fuel storage tanks is given in OFTEC Technical Book 3 [N4].

NOTE 3 Attention is drawn to The Dangerous Substances and Explosive Atmospheres Regulations 2002 (DSEAR), as amended [2] and the need to risk assess the selection of equipment to ensure safety in use and maintenance operations.

Information about this document

Text introduced or altered by Corrigendum No. 1 is indicated in the text by tags c_1 (c_1). Minor editorial corrections are not tagged.

This is a full revision of the document and introduces the following changes:

- the Scope has been revised to cover all sizes of installations serving domestic buildings up to those with an output of 70 kW;
- secondary containment fitted to storage tanks is required to be ventilated directly to atmosphere;
- a requirement to use a carbon monoxide detector with all internally installed combustion appliances has been added;

rated output; and

• additional clarifications and guidance have been added for those carrying out installation, commissioning, service and maintenance works.

Where websites and webpages have been cited, they are provided for ease of reference and are correct at the time of publication. The location of a webpage or website, or its contents, cannot be guaranteed.

Use of this document

As a code of practice, this part of BS 5410 takes the form of guidance and recommendations. It should not be quoted as if it were a specification and particular care should be taken to ensure that claims of compliance are not misleading.

Any user claiming compliance with this part of BS 5410 is expected to be able to justify any course of action that deviates from its recommendations.

It has been assumed in the preparation of this part of BS 5410 that the execution of its provisions will be entrusted to appropriately qualified and experienced people, for whose use it has been produced.

Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its recommendations are expressed in sentences in which the principal auxiliary verb is "should".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

Where words have alternative spellings, the preferred spelling of the Shorter Oxford English Dictionary is used (e.g. "organization" rather than "organisation").

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

Particular attention is drawn to the following specific regulations:

- The Construction (Design and Management) Regulations 2007 (as amended, 2015) [1].
- The Dangerous Substances and Explosive Atmospheres Regulations 2002 (DSEAR), as amended [2].
- The Boiler (Efficiency) Regulations 1993 as amended by the Boiler (Efficiency) (Amendment) Regulations 1994 and the Boiler (Efficiency) (Amendment) Regulations 2006 [3].
- The Building Regulations [4], [5], [6].
- The Control of Pollution (Special Waste) (Amendment) Regulations 1988 [7].
- The Control of Pollution (Oil Storage) (England) Regulations 2001 [8].
- The Control of Pollution (Oil Storage) (Amendment) Regulations (Northern Ireland) 2010 [9].
- Water Resources (Control of Pollution) (Oil Storage) (Wales) Regulations 2016 [10].
- The Water Environment (Miscellaneous) (Scotland) Regulations 2017 [11].

Attention is drawn also to amendments which may be made from time to time in these regulations.

1 Scope

This part of BS 5410 gives recommendations and guidance on the design, installation, commissioning and maintenance of liquid fuel burning installations for space heating and hot water supply purposes in domestic buildings with an output not exceeding 70 kW. It also gives recommendations and guidance on the selection and installation of liquid fuel storage tanks of capacity up to 3 500 l, when installed at domestic buildings. This British Standard is also applicable to liquid fuel fired cookers where these are connected to flues. This part of BS 5410 is not applicable to liquid fuel fired systems for marine and transportable installations, or for flueless heaters.

This part of BS 5410 is applicable to installations burning liquid fuel conforming to BS 2869, including biofuels conforming to BS EN 14214, and blends thereof.

This British Standard is intended for use by designers, specifiers, installers, and service and commissioning engineers.

NOTE 1 The types of appliances and burners covered by this part of BS 5410 are described in Annex A.

NOTE 2 Liquid fuel tank installations at domestic buildings, with a storage capacity greater than 3 500 l, are covered by BS 5410-2.

NOTE 3 Liquid fuel tank installations at non-domestic buildings, with a storage capacity up to 3 500 l, are covered by BS 5410-2.

NOTE 4 Where a domestic building has a boiler capacity in excess of 70 kW installed in a dedicated boiler or plant room, see BS 5410-2.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

Standards publications

BS 799-5, Oil burning equipment — Part 5: Carbon steel oil storage tanks — Specification

BS 2869:2017, Fuel oils for agricultural, domestic and industrial engines and boilers — Specification

BS 5410-2:2018, Code of practice for liquid fuel firing — Part 2: Installations providing space heating, hot water and steam supply services to non-domestic buildings

BS 7671, Requirements for Electrical Installations — IET Wiring Regulations

BS EN 977:1998, Underground tanks of glass-reinforced plastics (GRP) — Method for one side exposure to fluids

BS EN 1057:2006+A1:2010, Copper and copper alloys — Seamless, round copper tubes for water and gas in sanitary and heating applications

BS EN 1254-2:1998, Copper and copper alloys — Plumbing fittings — Part 2: Fittings with compression ends for use with copper tubes

BS EN 1856-1:2009, Chimneys - Requirements for metal chimneys - Part 1: System chimney products

BS EN 1856-2:2009, Chimneys – Requirements for metal chimneys – Part 2: Metal flue liners and connecting flue pipes

BS EN 12285-3, Workshop fabricated steel tanks — Part 3: Horizontal cylindrical single skin and double skin tanks for the underground storage of flammable and nonflammable water polluting liquids for heating and cooling of buildings