

This is a preview of "BS EN 15544:2023". [Click here to purchase the full version from the ANSI store.](#)



BSI Standards Publication

One off Kachelgrundöfen/Putzgrundöfen (tiled/mortared stoves) — Dimensioning

This is a preview of "BS EN 15544:2023". [Click here to purchase the full version from the ANSI store.](#)

National foreword

This British Standard is the UK implementation of EN 15544:2023. It supersedes BS EN 15544:2009, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee RHE/28, Domestic solid mineral fuel appliances.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2023
Published by BSI Standards Limited 2023

ISBN 978 0 539 16440 4

ICS 97.100.30

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 28 February 2023.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

This is a preview of "BS EN 15544:2023". [Click here to purchase the full version from the ANSI store.](#)

EUROPÄISCHE NORM

February 2023

ICS 97.100.30

Supersedes EN 15544:2009

English Version

One off Kachelgrundöfen/Putzgrundöfen (tiled/mortared stoves) - Dimensioning

Poêles en faïence, poêles en maçonnerie fabriqués in situ - Dimensionnement

Ortsfest gesetzte Kachelgrundöfen/Putzgrundöfen - Auslegung

This European Standard was approved by CEN on 2 January 2023.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

This is a preview of "BS EN 15544:2023". [Click here to purchase the full version from the ANSI store.](#)

Contents	Page
European foreword.....	3
Introduction	4
1 Scope.....	5
2 Normative references.....	6
3 Terms and definitions	6
4 Calculations.....	8
4.1 Nominal heat output	8
4.2 Load of fuel	9
4.2.1 Maximum load.....	9
4.2.2 Minimum load	9
4.3 Design of the essential dimensions	9
4.3.1 Combustion chamber dimensions	9
4.3.2 Calculated flue pipe length	11
4.3.3 Minimum flue pipe length.....	11
4.3.4 Gas slot profile.....	13
4.4 Calculation of the burning rate	14
4.5 Fixing of the air ratio	14
4.6 Combustion air flue gas.....	14
4.6.1 General.....	14
4.6.2 Combustion air flow rate.....	15
4.6.3 Flue gas flow rate	16
4.6.4 Flue gas mass flow rate	16
4.7 Calculations of the density.....	17
4.7.1 Combustion air density	17
4.7.2 Flue gas density.....	17
4.8 Calculation of the outside air temperature combustion air temperature and flue gas temperature	17
4.8.1 Mean outside air temperature and combustion air temperature.....	17
4.8.2 Mean combustion chamber temperature.....	18
4.8.3 Flue gas temperature in the flue pipe.....	18
4.8.4 Flue gas temperature in the connecting pipe.....	18
4.8.5 Flue gas temperature at chimney entrance mean flue gas temperature of the chimney and temperature of the chimney wall at the top of the chimney	19
4.9 Calculation of flow mechanics	19
4.9.1 General.....	19
4.9.2 Calculation of the standing pressure	19
4.9.3 Calculation of the flow velocity	19
4.9.4 Calculation of the static friction.....	20
4.9.5 Calculation of the resistance due to direction change.....	21
4.10 Operation control.....	22
4.10.1 Pressure condition	22
4.10.2 Dew point condition.....	23
4.10.3 Energy efficiency η	23
4.10.4 Flue gas triple of variates	23
Bibliography.....	24

This is a preview of "BS EN 15544:2023". [Click here to purchase the full version from the ANSI store.](#)

European foreword

This document (EN 15544:2023) has been prepared by Technical Committee CEN/TC 295 "Residential solid fuel burning appliances", the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by August 2023, and conflicting national standards shall be withdrawn at the latest by August 2023.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 15544:2009.

The main changes compared to the previous edition are listed below:

- a) correction of editorial mistakes;
- b) correction of mistakes in formulae;
- c) calculation of the fuel load based on a variable efficiency instead of a fixed efficiency of 78 %;
- d) introduction of calculated flue pipe length;
- e) introduction of factors to calculate minimum flue pipe length depending on efficiency (Table 1);
- f) specification of water content and dimensions of the used log wood;
- g) calculation of the minimum load;
- h) specification how to deal with type tested combustion chambers;
- i) change of the portion of the glass plate compared to the inner surface of the combustion chamber;
- j) definitions of fair fuel ratio and calculated flue pipe length added;
- k) definitions of "construction with air gap" and "construction without air gap" updated;
- l) specification of the relation between nominal heat output and full house as well as partial heating;
- m) specification that in divergence to EN 13384-1 the dew point condition is calculated only for nominal heat output.

Any feedback and questions on this document should be directed to the users' national standards body. A complete listing of these bodies can be found on the CEN website.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.

This is a preview of "BS EN 15544:2023". [Click here to purchase the full version from the ANSI store.](#)

Introduction

This document specifies a calculation method for the dimensioning of Kachelgrundöfen/Putzgrundöfen (tiled/mortared stoves).

This calculation method for the dimensioning of Kachelgrundöfen/Putzgrundöfen (tiled/mortared stoves) is based on appropriate literature as well as EN 13384-1, and where empirically determined correlations are used in addition to physical and chemical formulas.

In case of a calculation method for different interior materials than fireclay the proof of the compliance of the emission values and the efficiency shall be delivered separately. Also, the empiric data of the combustion chamber dimensions, the minimum flue pipe length, the burning rate as well as the combustion chamber temperature and the decrease of the temperature along the flue pipe shall also be separately determined.

This is a preview of "BS EN 15544:2023". [Click here to purchase the full version from the ANSI store.](#)

1 Scope

The application of the calculations of this document enables a verification of the emission values carbon monoxide, nitrogen dioxide, organically bound carbon as well as dust and the energy efficiency.

Complying with the calculations of this document results in emission values less or equal for carbon monoxide $1\,500\text{ mg/m}_n^3$ ($1\,000\text{ mg/MJ}$), nitrogen dioxide 225 mg/m_n^3 (150 mg/MJ), organically bound carbon 120 mg/m_n^3 (80 mg/MJ) and dust 90 mg/m_n^3 (60 mg/MJ). If the calculations of this document are used in combination with suitable combustion chambers that prove lower emission values in a type test, these values are also considered to be complied with.

There might be national or local regulations, which impose stricter legal emissions and/or efficiency requirements.

This document specifies calculations for the dimensioning of Kachelgrundöfen/Putzgrundöfen (tiled/mortared stoves) based upon the required nominal heat output of the stove as declared by the producer. The Kachelgrundöfen/Putzgrundöfen (tiled/mortared stoves) are of individual one-off construction design. The document can be used for log wood fired Kachelgrundöfen/Putzgrundöfen (tiled/plastered stoves) that burn one fuel load per storage period with a maximum load between 10 kg and 40 kg (log wood with water content from 12 % to 20 %, thickness of 5 cm to 10 cm in diameter, length varies usually from 25 cm to 50 cm, and is oriented toward the combustion chamber dimensions) and a storage period (nominal heating time) between 8 h and 24 h.

This document is applicable for Kachelgrundöfen/Putzgrundöfen (tiled/mortared stoves) equipped with fireclay as interior material, with an apparent density between $1\,750\text{ kg/m}^3$ and $2\,300\text{ kg/m}^3$, a degree of porosity from 17 % up to 33 % by volume and a heat conductivity from $0,90\text{ W/mK}$ up to $1,35\text{ W/mK}$ (temperature range 20 °C to 400 °C).

This document is applicable for Kachelgrundöfen/Putzgrundöfen (tiled/mortared stoves) with combustion air supply from the side via a firebox door frame or the standing grate of the heating door into the combustion chamber. The document is applicable for an inflow speed of the combustion air between 2 m/s and 4 m/s.

This document also applies to the combination with combustion chambers that are suitable for one-off Kachelgrundöfen/Putzgrundöfen (tiled/mortared stoves) and for which compliance with the legally required emission values has been verified as part of a type test by an accredited and/or notified body.

The following general conditions apply to such combustion chambers:

- with an air-fuel ratio of between 1,95 and 3,95 according to the type test;
- with a maximum load from 5 kg to 40 kg;
- using other suitable materials as well as fireclay.

With regard to the type test, this document is applicable for combustion chambers which are tested:

- according to EN 15250 (or EN 16510-2-5¹);
- according to EN 13229 (or EN 16510-2-2); or
- according to respective national standards (e.g. ÖNORM B 8303).

¹ Under preparation. Stage at the time of publication: prEN 16510-2-5:2023.