

ANSI/CEA Standard

Standard Method of Measurement
for Subwoofers

ANSI/CEA-2010-B

November 2014



CEA[®]
Consumer Electronics Association
www.CE.org

NOTICE

Consumer Electronics Association (CEA[®]) Standards, Bulletins and other technical publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards, Bulletins and other technical publications shall not in any respect preclude any member or nonmember of CEA from manufacturing or selling products not conforming to such Standards, Bulletins or other technical publications, nor shall the existence of such Standards, Bulletins and other technical publications preclude their voluntary use by those other than CEA members, whether the standard is to be used either domestically or internationally.

Standards, Bulletins and other technical publications are adopted by CEA in accordance with the American National Standards Institute (ANSI) patent policy. By such action, CEA does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the Standard, Bulletin or other technical publication.

This document does not purport to address all safety problems associated with its use or all applicable regulatory requirements. It is the responsibility of the user of this document to establish appropriate safety and health practices and to determine the applicability of regulatory limitations before its use.

This document is copyrighted by the Consumer Electronics Association (CEA[®]) and may not be reproduced, in whole or part, without written permission. Federal copyright law prohibits unauthorized reproduction of this document by any means. Organizations may obtain permission to reproduce a limited number of copies by entering into a license agreement. Requests to reproduce text, data, charts, figures or other material should be made to CEA.

(Formulated under the cognizance of the CEA **R3 Audio Systems Committee.**)

Published by
©CONSUMER ELECTRONICS ASSOCIATION 2014
Technology & Standards Department
www.CE.org

All rights reserved

FOREWORD

The purpose of the tests described in this standard is to provide data that will help the consumer understand how loud in volume, and how low in frequency, the subwoofer is capable of operating. The reporting format of the test results should also help the consumer determine which subwoofers may work well with different full-range loudspeaker systems which carry ANSI/CEA-2034 ratings.

This standard describes how to measure and report the maximum usable sound pressure level of a subwoofer, and how to measure and report the input impedance of a passive subwoofer. It also describes how to calculate and report the required output power of the amplifier needed for the consumer to get the desired SPL from a passive subwoofer.

Finally, it includes a number of informational annexes to help readers gain a more thorough understanding of techniques for acquiring loudspeaker data in both anechoic and non-anechoic environments.

When used properly this standard should assist manufacturers in accurately measuring the capabilities of a subwoofer and specifying them to consumers. Using this in conjunction with ANSI/CEA-2034 Standard Method of Measurement for In-Home Loudspeakers for full-range loudspeaker systems, the ANSI/CEA-2010-B subwoofer ratings should make it easier for the consumer to select, purchase, and enjoy a subwoofer that will complement their main full-range loudspeaker system.

This standard was developed by the Consumer Electronics Association's Audio Systems Committee (CEA R3 Committee).

(This page intentionally left blank.)

CONTENTS

1 Scope	1
2 Revision History	1
2.1 CEA-2010-A	1
2.2 CEA-2010-B	1
3 References	1
3.1 Normative References.....	1
3.1.1 Normative Reference List	2
3.1.2 Normative Reference Acquisition	2
3.2 Informative References	2
3.2.1 Informative Reference List.....	2
3.2.2 Informative Reference Acquisition	3
3.3 Definitions	3
3.4 Symbols and Abbreviations	3
3.5 Compliance Notation.....	4
4 Test Setup and Conditions	4
4.1 General Test Setup and Conditions.....	4
4.2 Verification of Frequency Response at DUT Input Terminals	4
4.3 Measurement Resolution and Calibration	5
5 Frequency Response and Crossover Category	5
5.1 Data Acquisition	5
5.2 Upper Frequency Limit	5
5.3 Crossover Category Qualification	5
5.4 Crossover Category Data Presentation.....	6
6 Maximum Usable Sound Pressure Level – Continuous	7
6.1 Input Signal	7
6.2 Data Acquisition	9
6.2.1 Measurement Set-up	9
6.2.2 Measurement Procedure.....	10
7 Maximum Usable Sound Pressure Level - Peak	12
7.1 Input Signal	12
7.2 Data Acquisition	12
7.3 Maximum Peak SPL Data Post-Processing for Broadband Peak SPL.....	15
8 Maximum SPL Data Presentation	16
9 Powered Subwoofer Rating	17
9.1 Calculation	17
9.2 Data Presentation	17
10 Impedance	19
10.1 Data Acquisition	19
10.2 Data Presentation	20
11 Required Power Amplifier Size	21
11.1 Calculation	21
11.2 Data Presentation	22

12 Matching a Subwoofer to a Full-Range Loudspeaker System	23
13 Consolidated Reporting Requirements – Example Data Sheet.....	24
Appendix A. Ground Plane Test Procedure	27
Appendix B. Calibrating the Amplitude Response of Anechoic Chambers and Other Spaces (Room Correction Factor)	29
Appendix C. Calculating Maximum Usable Continuous SPL in a Non-Anechoic Environment ...	30
Appendix D. List of Equipment Needed to Perform Tests Described in This Standard	34

Figures

Figure 1: Spectral content of ANSI/CEA-2034 noise compared to IEC 60268 shaped noise	8
Figure 2: Filter processing blocks for generating input signal.....	8
Figure 3: Signal Flow Diagram	9
Figure 4: Harmonic Distortion + Noise Threshold vs. Frequency	15
Figure 5: Impedance measurement schematic, R_{Sense} method	19
Figure 6: Impedance measurement schematic, current monitor method.....	19
Figure 7: Basic ground plane measurement set-up for a subwoofer system whose driver and port are located on the same face of the enclosure (cut-away side view)	27
Figure 8: Two examples of ground plane measurement set-ups for subwoofer systems with major radiating elements on multiple faces of their enclosures (cut-away view from above)	28
Figure 9: Windowed & Unwindowed IR of the DUT	30
Figure 10: FFT of the windowed IR from Step 1.....	31
Figure 11: Spectral content of the test signal	31
Figure 12: Spectral content of the test signal and the frequency response of the DUT	32
Figure 13: Calculated spectral content of the output from the DUT at the termination of the test	32

Tables

Table 1: Upper frequency limit of Crossover Categories	5
Table 2: Power spectrum of input signal.....	7
Table 3: Peak SPL Limits.....	13
Table 4: Subwoofer In-Room Listening Level	18
Table 5: Required Amplifier Power and Voltage	22
Table 6: Minimum required distance between DUT and acoustically reflective boundaries (walls) ¹	28

(This page intentionally left blank.)

This is a preview of "CEA 2010-B-2014 (ANS...)". Click here to purchase the full version from the ANSI store.

STANDARD METHOD OF MEASUREMENT FOR SUBWOOFERS

1 Scope

This standard defines a method for measuring the audio performance of subwoofers, both passive and powered.

2 Revision History

2.1 CEA-2010-A

Increased measurement distance from 1 m to 3 m

Corrected procedure for averaging to be done using pressure

Added Table A-3 showing example invoking rule of non-measurable SPL within one of the bandwidths

2.2 CEA-2010-B

Modified the Forward

Include passive subwoofer

Added section for testing the maximum continuous SPL

Added 80 Hz to 160 Hz test frequencies to the maximum peak SPL test

Modified the distortion threshold for the maximum peak SPL test and separated the thresholds into three separate bands. These thresholds correspond to masking thresholds for test tones of 100 dB SPL.

Added a procedure to correlate the maximum peak SPL results with the maximum continuous SPL in order to derive a broad band (from 20 Hz to 160 Hz) SPL.

Added a section for impedance measurement of passive subwoofers

Added a section for recommended amplifier size for passive subwoofers

Added a section about frequency response overlap between the subwoofer & full-range systems to gauge usefulness together

Added an appendix listing the test equipment required for the measurements specified in CEA-2010-B

Moved the section on Ground Plane Measurements to an appendix

Moved the section on Room Correction Factor to an appendix

Added an appendix for the alternate determination of maximum continuous SPL in a non-anechoic environment

Added a section for matching a subwoofer to a full-range system using ANSI/CEA-2034 ratings

Added a section for consolidated reporting requirements

Added Normative References section

Added Definitions

Added Symbols & Abbreviations

Added requirement for recording environmental conditions during testing

3 References

3.1 Normative References

The following standards contain provisions that, through reference in this text, constitute normative provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of the standards listed here.