

ANSI/CEA Standard

Service Selection Information for
Digital Storage Media Interoperability

ANSI/CEA-775.2-A R-2013

August 2008



CEA[®]
Consumer Electronics Association
www.CE.org

NOTICE

Consumer Electronics Association (CEA[®]) Standards, Bulletins and other technical publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards, Bulletins and other technical publications shall not in any respect preclude any member or nonmember of CEA from manufacturing or selling products not conforming to such Standards, Bulletins or other technical publications, nor shall the existence of such Standards, Bulletins and other technical publications preclude their voluntary use by those other than CEA members, whether the standard is to be used either domestically or internationally.

Standards, Bulletins and other technical publications are adopted by CEA in accordance with the American National Standards Institute (ANSI) patent policy. By such action, CEA does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the Standard, Bulletin or other technical publication.

This document does not purport to address all safety problems associated with its use or all applicable regulatory requirements. It is the responsibility of the user of this document to establish appropriate safety and health practices and to determine the applicability of regulatory limitations before its use.

This document is copyrighted by the Consumer Electronics Association (CEA[®]) and may not be reproduced, in whole or part, without written permission. Federal copyright law prohibits unauthorized reproduction of this document by any means. Organizations may obtain permission to reproduce a limited number of copies by entering into a license agreement. Requests to reproduce text, data, charts, figures or other material should be made to CEA.

(Formulated under the cognizance of the CEA **R4.8 DTV Interface Subcommittee**.)

Published by
©CONSUMER ELECTRONICS ASSOCIATION 2013
Technology & Standards Department
www.CE.org

All rights reserved

FOREWORD

Users of this standard should be aware that ongoing standardization work in the 1394 Trade Association may have a future impact on this standard. CEA has stated its intention to harmonize its standards with those developed within the 1394 Trade Association, and likewise the TA has indicated its willingness to coordinate standards development with CEA.

This standard was developed under the auspices of the CEA R4.8 DTV Interface Subcommittee.

CEA-775.2-A

(This page intentionally left blank.)

Contents

1.	INTRODUCTION	1
2.	GENERAL	2
2.1	Scope.....	2
2.2	Normative References	2
2.2.1	Normative Reference List	2
2.2.2	Normative Reference Acquisition	2
2.3	Informative References.....	3
2.4	Informative Reference Acquisition	3
2.5	Definitions	3
2.6	Symbols and Abbreviations	4
2.7	Compliance Notation	5
3.	SYSTEM OVERVIEW.....	6
4.	SECTION SYNTAX AND SEMANTICS	7
4.1	Selection Information Table	7
4.1.1	Partial Transport Stream Descriptor.....	10
4.1.2	Future Expansion (Informative)	11
4.2	PSIP Tables.....	11
4.2.1	Master Guide Table (MGT).....	12
4.2.2	Virtual Channel Table (VCT).....	12
4.2.3	Event Information Table (EIT)	12
4.2.4	Extended Text Table (ETT)	13
4.3	Discontinuity Information Table (DIT)	13
4.3.1	DIT Bit stream syntax and semantics (Normative)	13
4.3.2	DIT Usage.....	13
4.3.3	Procedure for DIT Insertion	15
4.3.4	Strategies for Inserting DIT (Informative).....	15
4.4	System Time Table (STT).....	16
4.5	Rating Region Table (RRT)	16
4.6	Program Association Table (PAT)	16
4.7	Program Map Table (PMT)	16
5.	ADDITIONAL REQUIREMENTS.....	17
5.1	Partial Transport Streams	17
5.2	MPEG-2 Network PID	17
5.3	Buffer Model for SIT Packet Stream	17
	ANNEX A EXAMPLE USAGE SCENARIOS	18
	(Informative)	18
A.1.	Introduction.....	18
A.2.	Recording an ATSC Digital Television Terrestrial Broadcast	18
A.3.	Recording a Digital Signal from an OpenCable Cable Set-Top Box.....	19
A.3.1	In-band Navigation Case	20
A.3.2	Out-of-band Navigation Case	20
A.4.	Recording a Digital Signal from a Digital Satellite Receiver	20

CEA-775.2-A

A.5.	<i>Recording a Signal from a Digital Video Camera</i>	22
ANNEX B PSIP VERSUS SIT INTEROPERABILITY		24
B.1.	<i>Introduction</i>	24
B.2.	<i>PSIP and SIT Scenarios</i>	24
ANNEX C STORAGE MEDIA INTEROPERABILITY		26
C.1.	<i>Introduction</i>	26
C.1.1	Limited Bandwidth on the Storage System	26
C.1.2	Limited Bandwidth on the Digital Interface	27
C.1.3	Bit Rates of the MPEG-TS	27
C.1.4	The Partial Transport Stream.....	27
C.2.	<i>Determination of the Bit Rate of a Selected Program</i>	28
C.2.1	Smoothing Buffer Descriptor (IEC13818-1)	29
C.2.2	Maximum Bit Rate Descriptor (IEC13818-1).....	29
C.2.3	Short Smoothing Buffer Descriptor	29
C.2.4	Partial Transport Stream Descriptor	29
C.3.	<i>Handling Unknown Bit Rates</i>	30
C.3.1	Allocating Bandwidth on the Interface	30
C.3.2	Bit rate on the Storage Device	30
C.4.	<i>More About Partial Transport Streams</i>	31
C.4.1	The DIT table	31
C.4.2	The Byte Rate in the Partial Transport Stream	31
C.4.3	Partial Transport Stream from a Camera.....	32

Table of Figures

Figure 3.1	Example Home Audio/Video Equipment Setup	6
Figure A.1	ATSC Terrestrial Broadcast Example—Derivation of SIT	18
Figure A.2	ATSC Terrestrial Broadcast Example—PSIP Stored As-is	19
Figure A.3	OpenCable Set-top Box Example Using Out-of-band Navigation Data	20
Figure A.4	Digital Satellite Receiver Example Using SIT	21
Figure A.5	Digital Satellite Receiver Example Using PSIP	22
Figure A.6	Digital Video Camera Example Using SIT	23
Figure A.7	Digital Video Camera Example Using PSIP	23
Figure C.1	Storage System Example	26
Figure C.2	Partial Transport Stream Processing.....	28
Figure C.3	Example Discontinuities.....	31
Figure C.4	Example Partial Transport Stream	31

CEA-775.2-A

Table of Tables

Table 4.1 Bit Stream Syntax of Selection Information Section	8
Table 4.2 Source Type.....	9
Table 4.3 Descriptors Allowed in SIT Program Info Descriptors Loop	10
Table 4.4 Descriptors Allowed in SIT Additional Descriptors Loop	10
Table 4.5 Bit Stream Syntax of Discontinuity Information Section	13
Table 4.6 Rules for DIT Insertion.....	14
Table B.1 PSIP and SIT Interoperability Scenarios.....	24

1. INTRODUCTION

CEA-775-C [1] standardizes the IEEE 1394 [3][4] High Performance Serial Bus interface for the Digital Television (DTV) receiver. A digital storage device such as a D-VHS or hard disk digital recorder may be used by the DTV or by another source device such as a cable set-top box to record or time-shift digital television signals. The present standard supports the use of such storage devices by defining Service Selection Information (SSI), methods for managing discontinuities that occur during recording and playback, and rules for management of partial Transport Streams.

For purposes of digital storage, it is desirable that SSI is stored along with program audio/video/data material. SSI supplements the program material by describing one or more selected services. Information can include:

- the name of the source channel (for example, the name and number of ATSC PSIP virtual channel)
- the title of the selected program
- a multi-lingual textual description of the program (optional)
- the program duration
- the start time of the original broadcast
- any descriptors pertinent to the program, such as content advisories
- the type of source (camcorder, broadcast source, etc.)
- an optional reference to further descriptive information

When a digital recording that includes SSI is played back, channel name and program title information is available for display. If system time is also recorded, using the time of day, start time and duration data, playback equipment can display the time remaining in the program at any point during playback. When several services are present in the transport multiplex, SSI data can be used to support user selection of the desired program.

SSI may be provided in one of two possible formats: as an MPEG-2 compliant data structure defined in this standard called the Selection Information Table (SIT), or as Service Information tables compliant with the ATSC A/65C PSIP [2] standard.

A device preparing an MPEG Transport Stream for recording may delete transport packets corresponding to unwanted programs or services, thus creating a *partial* Transport Stream. This standard discusses the necessary signaling required for proper construction of a partial TS.

In addition to information describing service and program selections present in the multiplex, this standard defines a mechanism to signal discontinuities in the recorded material. The presence of an MPEG table section called the Discontinuity Information Table (DIT) indicates, upon playback, the location of a point of discontinuity in the system timebase, Service Information, or Elementary Stream.

Note that any device processing an MPEG-2 Transport Stream must handle discontinuities in the timebase (PCR discontinuities) or within Elementary Streams that are not signaled by a DIT. The primary function of the DIT is to minimize the recovery time in an MPEG-2 decoder following a point of known discontinuity, and enable the decoder to reduce the disruption in audio and video output.

When present, SIT sections shall be carried in the MPEG-2 Transport Stream multiplex in transport packets with PID value given in the **network_PID** in the Program Association Table. For the SIT sections, this PID value shall not be 0x1FFB. Furthermore, the SIT sections shall not appear in transport packets used by any PSIP tables in the case that PSIP tables are present in the multiplex. When present, the DIT shall be carried in transport packets with PID value 0x001E. PSIP tables use transport packets with PID values as defined in [2].