

ANSI/CEA Standard

Tunneling Device Area Network Protocols Over Internet Protocol Channels

ANSI/CEA-852-B

August 2010



CEA[®]
Consumer Electronics Association
www.CE.org

NOTICE

Consumer Electronics Association (CEA®) Standards, Bulletins and other technical publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards, Bulletins and other technical publications shall not in any respect preclude any member or nonmember of CEA from manufacturing or selling products not conforming to such Standards, Bulletins or other technical publications, nor shall the existence of such Standards, Bulletins and other technical publications preclude their voluntary use by those other than CEA members, whether the standard is to be used either domestically or internationally.

Standards, Bulletins and other technical publications are adopted by CEA in accordance with the American National Standards Institute (ANSI) patent policy. By such action, CEA does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the Standard, Bulletin or other technical publication.

This CEA Standard is considered to have International Standardization implication, but the International Electrotechnical Commission activity has not progressed to the point where a valid comparison between the CEA Standard and the IEC document can be made.

This Standard does not purport to address all safety problems associated with its use or all applicable regulatory requirements. It is the responsibility of the user of this Standard to establish appropriate safety and health practices and to determine the applicability of regulatory limitations before its use.

This document is copyrighted by the Consumer Electronics Association (CEA®) and may not be reproduced, in whole or part, without written permission. Federal copyright law prohibits unauthorized reproduction of this document by any means. Organizations may obtain permission to reproduce a limited number of copies by entering into a license agreement. Requests to reproduce text, data, charts, figures or other material should be made to CEA.

(Formulated under the cognizance of the CEA's **R7.1 Home Control Systems Subcommittee**.)

Published by
©CONSUMER ELECTRONICS ASSOCIATION 2011
Technology & Standards Department
www.CE.org

All rights reserved

This is a preview of "CEA 852-B-2010 (ANSI...)". [Click here to purchase the full version from the ANSI store.](#)

CEA-852-B

FOREWORD

This standard was developed under the auspices of the CEA R-7.1 Home Control Systems Subcommittee.

CEA-852-B supersedes CEA-852 and CEA-852-A.

Unless otherwise indicated, the designator 852 refers to the latest revision of CEA-852, which at the time of this writing was CEA-852-B.

CONTENTS

1	General	1
1.1	Scope	1
1.2	Revision History	1
1.2.1	CEA-852 Revision B	1
1.3	Definitions	2
1.4	Acronyms	3
2	Normative References	4
2.1	Reference Acquisition	5
3	Introduction	5
4	Requirements	6
5	CN/IP Device Specification	7
5.1	IP Related Device Specifications	7
5.2	CN Related Device Specifications	7
5.2.1	Packet Formats	7
5.2.2	Addressing Schemes	7
6	IP Channel Specification	8
6.1	IP Transport Mechanisms	10
6.1.1	Informative Considerations	12
7	CN/IP Device Configuration	12
7.1	Configuration Parameters	12
7.1.1	Channel Definition Parameters	13
7.1.2	Send List Parameters	13
7.1.3	Device Parameters	14
7.2	Configuration Techniques	14
7.2.1	Manual Configuration	14
7.2.2	BOOTP and DHCP	14
7.2.3	Configuration Servers	14
8	CN/IP Messages and Modes of Operation	15
8.1	Common Message Header	16
8.2	Packet Segmentation	17
8.2.1	Overview	17
8.2.2	Segment Exchange	18
8.2.3	Discussion	19
8.3	Data Packet Exchange	20
8.3.1	Out of Order Packets	21
8.3.2	Duplicate Packet Detection	22
8.3.3	Stale Packet Detection	22
8.4	Configuration Server Interactions	23
8.4.1	General Device Interaction	23
8.4.2	General Protocol Interaction	25
8.4.3	Packet Segmentation	25
8.4.4	Device Registration	26
8.4.5	Channel Membership	28
8.4.6	Send List	28
8.4.7	Channel Routing	30

8.5 Miscellaneous Status Messages.....	31
8.5.1 CN/IP Device Status	32
8.5.2 Device Registration.....	33
8.5.3 Device Send List.....	33
8.5.4 Channel Membership List.....	33
8.5.5 Channel Routing Information.....	34
8.6 Vendor Specific Messages	34
8.7 Packet Authentication.....	34
9 Packet Formats	36
9.1 Packet Types.....	37
9.2 Common CN/IP Header	37
9.3 Segment Packet.....	39
9.4 CN Data Packets	40
9.5 CN/IP Device Registration Packets.....	40
9.6 Channel Membership Packet.....	45
9.7 Channel Routing Packet	46
9.8 Request Packet.....	49
9.9 Acknowledge Packet.....	50
9.10 Send List Packet.....	51
9.11 Node Status/Health/Statistics Response Message.....	52
10 Annex A Specifications for ANSI/CEA-709.1-B (Normative)	55
11 Annex B Specifications for CEA-709 (Informative).....	56
12 Annex C Specifications for CEA-600 (Normative).....	56
13 Annex D Specifications for CEA-600 (Informative).....	56

Figures

Figure 1 Typical CN/IP Application.....	6
Figure 2 IP Protocol Stack.....	11
Figure 3 Packet Aggregation.....	17
Figure 4 Packet Authentication Encoding and Decoding	35
Figure 5 Packet Aggregation with Authentication.....	36

Tables

Table 1 Device Registration with Configuration Server Protocol.....	27
Table 2 Server to Device Unsolicited Registration Message Protocol.....	27
Table 3 Device to Server Channel Membership Request Protocol.....	28
Table 4 Device to Server Send List Request Protocol	29
Table 5 Device to Server Channel Routing Update Protocol	30
Table 6 Device to Server Channel Routing Request Protocol	30
Table 7 Protocol for Requesting a Device's Registration.....	33
Table 8 Protocol for Requesting a Device's Send List.....	33
Table 9 Protocol for Requesting a Device's Channel Definition	34
Table 10 Protocol for Requesting a Device's Channel Routing Information	34
Table 11 Message Type Cross Reference	37
Table 12 Common Packet Header Format.....	38

CEA-852-B

Table 13 Segment Packet Format.....	39
Table 14 Data Packet Format	40
Table 15 Device Registration Packet Format	41
Table 16 Channel Membership Packet Format	45
Table 17 Channel Routing Packet Formats.....	47
Table 18 Configuration Request Packet Format.....	49
Table 19 Request Reason Codes	49
Table 20 Request Amount Codes.....	49
Table 21 Request Action Codes	49
Table 22 Acknowledge Packet Formats	50
Table 23 Send List Packet Format.....	51
Table 24 Node Status/Health/Statistics Response Message.....	53

CEA-852-B

Tunneling Device Area Network Protocols Over Internet Protocol Channels

1 General

1.1 Scope

The CEA-852 standard specifies a communications method that allows networked data acquisition and control devices to communicate with each other over the internet. The purpose of such devices are widely varying and include functions such as appliance monitoring, meter reading, and HVAC and lighting control to name a few. CEA-852 does not replace existing device communications protocols, but instead allows those protocols to use the internet as a communications medium. CEA-852 currently supports the existing device protocols CEA-600 (CEBus) and CEA-709 (LonTalk®) and was designed to allow the support of others.

Unless otherwise indicated, the designator 852 refers to the latest revision of CEA-852, which at the time of this writing was CEA-852-B.

1.2 Revision History

Since the original CEA-852 standard specification was released in 2001, several vendors have released implementations of the standard and more are in development. Unfortunately, as is the case with almost any new specification, experience in its use and interoperation between different implementations has brought to light several errors, omissions, unforeseen limitations and poorly defined requirements. Moreover, the CEA-852 specification is being adopted by other International standards bodies. As part of an ongoing effort to refine the standard, revisions to the original CEA-852 specification have been developed.

1.2.1 CEA-852 Revision B

Because CEA-852 Revision A was limited to modifications that would maintain a high degree of backwards compatibility with the installed base of 852 devices, it did not address all of the limitations that have been discovered in the original specification. As a result, CEA-852 Revision B has been developed.

The major change between CEA-852-A and CEA-852-B is the addition of a new flag. This flag is called the Protocol Escape Bit. When set, the Protocol Escape Bit indicates that the device or configuration server sending the 852-B packet, supports and is allowed to operate using a different protocol such as the CEA-852.1 [13.] protocol. An 852 device or configuration server that supports both CEA-852 and another related protocol is called *Bilingual*. This protocol escape bit allows Bilingual configuration servers to correctly form channels with devices that support CEA-852, another protocol, or are Bilingual. (For reference see the Hybrid Channel Bootstrap Algorithm in the CEA-852.1 [13.] specification).

The description of packet authentication in CEA-852-A is ambiguous especially with regard to segmented packets and aggregated packets. This ambiguity is removed in CEA-852-B. Other typos and minor clarifications were also added in CEA-852-B:

- Defined Bit 6 in the protocol flags field of the common header as the Protocol Escape Bit.
- Clarified the description of packet authentication especially with regard to segmented packets and aggregated packets.