

ANSI/CEA Standard

Remote Starter Safety

ANSI/CEA-885 R-2013

April 2007



CEA[®]
Consumer Electronics Association
www.CE.org

NOTICE

Consumer Electronics Association (CEA[®]) Standards, Bulletins and other technical publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards, Bulletins and other technical publications shall not in any respect preclude any member or nonmember of CEA from manufacturing or selling products not conforming to such Standards, Bulletins or other technical publications, nor shall the existence of such Standards, Bulletins and other technical publications preclude their voluntary use by those other than CEA members, whether the standard is to be used either domestically or internationally.

Standards, Bulletins and other technical publications are adopted by CEA in accordance with the American National Standards Institute (ANSI) patent policy. By such action, CEA does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the Standard, Bulletin or other technical publication.

This document does not purport to address all safety problems associated with its use or all applicable regulatory requirements. It is the responsibility of the user of this document to establish appropriate safety and health practices and to determine the applicability of regulatory limitations before its use.

This document is copyrighted by the Consumer Electronics Association (CEA[®]) and may not be reproduced, in whole or part, without written permission. Federal copyright law prohibits unauthorized reproduction of this document by any means. Organizations may obtain permission to reproduce a limited number of copies by entering into a license agreement. Requests to reproduce text, data, charts, figures or other material should be made to CEA.

(Formulated under the cognizance of the CEA **R6 Portable, Handheld and In-Vehicle Electronics Committee.**)

Published by
©CONSUMER ELECTRONICS ASSOCIATION 2013
Technology & Standards Department
www.CE.org

All rights reserved

FOREWORD

This standard was developed under the auspices of the Consumer Electronics Association (CEA) R6.1 Vehicle Security Subcommittee. It is being maintained by the CEA R6 Mobile Electronics Committee.

CONTENTS

1 Scope	1
2 Normative References	1
2.1 Normative References	1
2.2 Reference Acquisition	1
3 Run Time	1
4 In-Gear Detection	1
5 Safety Inputs	1
5.1 Hood Input	1
5.2 Brake Input	1
5.3 Service “Valet” Mode	1
6 Vehicle Security Integrity	1
7 Power Handling	2
8 Product Labelling	2
9 Government Regulations	2
10 Package Labelling	2

Remote Starter Safety

1 Scope

This standard addresses the automotive accessories that allow the operator to start a vehicle while away from the vehicle, and the safety of such devices when installed.

Remote starters that are designed for installation in manual transmission vehicles are not compliant with this standard, and shall not be labeled or promoted as such.

2 Normative References

The following standards contain provisions that, through reference in this text, constitute normative provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of the standards listed in Section 2.1.

2.1 Normative References

47 CFR 15, Radio Frequency Devices

2.2 Reference Acquisition

- FCC

FCC Regulations, U.S. Government Printing Office, Washington, D.C. 20401; Internet
<http://www.access.gpo.gov/cgi-bin/cfrassemble.cgi?title=199847>

3 Run Time

Any remote starter complying with this standard shall not have a run-time of greater than continuous 30 minutes under any circumstances. In addition, cumulative run times (without customer intervention) – for example, in a self starting mode which may be looking to start the vehicle when the temperature or battery voltage drops--shall not exceed more than 30 minutes in any two hour period, excepting where the vehicle stalls.

4 In-Gear Detection

Any remote starter complying with this standard shall incorporate a feature preventing a vehicle from starting or driving off after starting the remote starter. In particular, a remote starter shall not start if the vehicle is in-gear. And, if the vehicle is shifted into gear, then the vehicle shall immediately shut down. If any special steps are necessary for the installer to insure this is met – these steps in the directions shall be clearly marked in bold print and with some wording giving the installer ample warning of the issues.

5 Safety Inputs

Provisions for each of the safety inputs identified in Sections 5.1, 5.2 or 5.3 shall be directed in the manual as required inputs on the product. In addition, before starting the vehicle for the first time, the remote starter shall verify that at least one of the safety inputs is connected.

5.1 Hood Input

Activating an input after the vehicle has been started via remote start control should terminate remote start operation. If the hood input is active (for example, the hood is opened) at the time a start sequence is initiated, the vehicle shall not start.

5.2 Brake Input

An input shall be provided from the brake switch to terminate an existing run cycle or prevent the vehicle from starting via remote start.

5.3 Service “Valet” Mode

The service or “valet” mode can contribute to the safety of the vehicle when it is in service to prevent injury. If a start sequence is initiated while the system is in service mode, the system shall not start.

6 Vehicle Security Integrity

Many vehicles that will have a remote starter installed will have an existing security system already in place. The installed remote starter shall interface with the vehicle security system in a manner that does not disable, or compromise, the existing vehicle security system, except during run-time.