CEA Standard

Web-based Protocol and Framework for Remote User Interface on UPnPTM Networks and the Internet (Web4CE)

CEA-2014-A

July 2007



NOTICE

Consumer Electronics Association (CEA®) Standards, Bulletins and other technical publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards, Bulletins and other technical publications shall not in any respect preclude any member or nonmember of CEA from manufacturing or selling products not conforming to such Standards, Bulletins or other technical publications, nor shall the existence of such Standards, Bulletins and other technical publications preclude their voluntary use by those other than CEA members, whether the standard is to be used either domestically or internationally.

Standards, Bulletins and other technical publications are adopted by CEA in accordance with the American National Standards Institute (ANSI) patent policy. By such action, CEA does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the Standard, Bulletin or other technical publication.

Note: The user's attention is called to the possibility that compliance with this standard may require use of an invention covered by patent rights.

By publication of this standard, no position is taken with respect to the validity of this claim or of any patent rights in connection therewith. The patent holder has, however, filed a statement of willingness to grant a license under these rights on reasonable and nondiscriminatory terms and conditions to applicants desiring to obtain such a license. Details may be obtained from the publisher.

This CEA Standard is considered to have International Standardization implication, but the International Electrotechnical Commission activity has not progressed to the point where a valid comparison between the CEA Standard and the IEC document can be made.

This Standard does not purport to address all safety problems associated with its use or all applicable regulatory requirements. It is the responsibility of the user of this Standard to establish appropriate safety and health practices and to determine the applicability of regulatory limitations before its use.

(Formulated under the cognizance of the CEA R7 Home Network Committee.)

Published by
©CONSUMER ELECTRONICS ASSOCIATION 2007
Technology & Standards Department
1919 S. Eads Street
Arlington, Virginia 22202

PRICE: Please call Information Handling Services, USA and Canada (1-800-854-7179) International (303-397-7956), or

http://global.ihs.com
All rights reserved
Printed in U.S.A.

PLEASE!

DON'T VIOLATE THE LAW!

This document is copyrighted by the Consumer Electronics Association (CEA®) and may not be reproduced without permission.

Organizations may obtain permission to reproduce a limited number of copies by entering into a license agreement. For information contact:

Information Handling Services
15 Inverness Way East
Englewood, Colorado 80112-5704
or call U.S.A. and Canada 1-800-854-7179, International (303) 397-7956
See http://global.ihs.com or email global@ihs.com

This is a preview of "CEA 2014-A-2013". Click here to purchase the full version from the ANSI store.

CEA-2014-A

FOREWORD

The current version of this standard was developed under the auspices of the Consumer Electronics Association (CEA) R7 Home Network Committee.

CEA-2014-A

Table of Contents

1	Scope	1
	1.1 Purpose	1
	1.2 Features	2
	1.3 Revision History	2
2	References	
	2.1 Normative References	2
	2.2 Informative References	
	2.3 Reference Acquisition	
3	Conventions and Definitions	
Ŭ	3.1 Conventions	
	3.2 Definitions and Acronyms	
4	Architectural Overview (informative)	
•	4.1 Remote UI Configuration Models	
	4.1.1 i-Box Remote UI Model	<i>,</i> 7
	4.1.2 2-Box Remote UI Model	
	4.1.3 3-Box Remote UI Model	
	4.2 Background: DLNA A/V 2-Box and 3-Box Models	
	4.3 Configuration Models for combining Remote UI with A/V	9 Q
	4.4 Remote UI Server and Client Types	9 1∩
	4.5 Detailed Architecture	
	4.5.1 Remote UI Client Architecture	
	4.5.2 Remote UI Server Architecture	
_	Requirements (normative)	
J	5.1 Setup: Discovery and Connection of Remote UI Devices	
	5.1.1 General Remote UI Server Requirements	
	5.1.2 General Remote UI Client Requirements	
	5.2.1 UI Capability Profiles	
	5.2.2 Profile Matching	
	5.2.3 Browser Area	
	5.3 HTTP Headers	
	5.4 XHTML Profile (CE-HTML)	
	5.4.1 Key-events	
	5.4.2 Window / UIContentFrame scripting object	
	5.5 In-session Notifications	
	5.5.1 NotifSocket Scripting Object	
	5.5.2 XMLHttpRequest Scripting Object	51
	5.6 3 rd Party Notifications	
	5.6.1 Multicast Notifications	
	5.6.2 Polling-based Notifications	
	5.6.3 Notification Content and Window	
	5.7 A/V Control	58
	5.7.1 Streamed A/V content	
	5.7.2 Local video content	
	5.7.3 Full-screen video	
	5.8 Save and Restore	
	5.9 Cookie Support	73
	5.10 Robustness Guidelines	74

This is a preview of "CEA 2014-A-2013". Click here to purchase the full version from the ANSI store.

CEA-2014-A

Annex A: Remote UI Server UPnP Device Extension Schema (Normative)75 Annex B: Remote UI Client UPnP Device Extension Schema (Normative)78 Annex C: Remote UI Client Capability Description Schema (Normative) 80 Annex D: Remote UI Server Capability Description Schema (Normative)83 Annex E: XHTML DTD with Tagged Opcodes (Informative)	133
List of Figures	
Figure 1: i-Box UI Model	
Figure 2: 2-Box UI Model	8
Figure 3: 3-Box UI Model	9
Figure 4: Possible 2-Box Configurations For Combining A/V And UI Functionality Figure 5: Architecture Overview	
Figure 6: Detailed Remote UI Client Architecture	
Figure 7: Detailed Remote UI Server Architecture	
rigure 7. Detailed Nemote Of Server Architecture	i ɔ

CEA-2014-A

Web-based Protocol and Framework for Remote User Interface on UPnP™ Networks and the Internet (Web4CE)

1 Scope

This standard defines the necessary mechanisms to allow a user interface to be remotely displayed on and controlled by devices or control points other than the one hosting the logic. The basic device operations are based on the UPnP Device Architecture v1.0 for UPnP networks and UPnP devices in the home. The standard also allows the remote display of user interfaces provided by third party internet services on UPnP devices in the home, and covers a wide range of UI capabilities for TVs, mobile phones and portable devices. This standard attempts to specify solutions that are identical to the relevant parts of CEA-2027-A *A User Interface for Home Networks Using Web-based Protocols* in the common areas not specific to the underlying network, to enable the two standards to be similar to the fullest extent reasonable.

This standard includes mechanisms intended to enable flow of content that might be under the control of a content protection system, such as a Digital Rights Management (DRM) system. In such cases certain capabilities defined by this standard may depend on proper, parallel implementation of the appropriate content protection system. Specification of content protection and any interaction between elements of this standard and any content protection system is beyond the scope of this standard.

1.1 Purpose

The CEA-2014 protocol provides a structured way of accessing consumer electronics friendly XHTML (and related) content over an IP network.

The main goals of CEA-2014 are based on the following principles:

- a) Provide a mechanism that allows remote presentation and control of user interfaces directed to consumer devices.
- b) Handle remote UI content that may reside either:
 - On UPnP UI server devices
 - On Internet-based services
- c) Use existing web standards for UI content (e.g. XHTML)
 - Define extensions only when necessary
- d) Support a variety of different consumer client devices
 - STBs, TVs, mobile phones
- e) Allow for dynamic interaction between Remote UI Clients and Servers
 - Provide timely, partial UI updates from a Remote UI Server
- f) Allow clients to receive important UI notifications from server devices at any time (if permitted by the user)
- g) Allow for A/V functionality to be part of the UI experience

Note that server devices that support CEA-2014 can also expose their functionality through other means in addition to Remote UI (such as through UPnP DCPs).