

<b>Contents</b>	<b>Page</b>
1 Introduction.....	1
2 Scope and purpose .....	1
2.1 Scope .....	1
2.2 Purpose .....	1
3 Definitions.....	1
4 Compliance schedule .....	3
5 Necessary inspection experience.....	3
6 Construction of acetylene cylinders.....	3
6.1 Porous mass (filler).....	3
6.2 Solvent.....	4
6.3 Core-hole with packing.....	4
6.4 Fusible metal pressure relief device (fuse plug).....	5
6.5 Shell.....	5
7 Acetylene cylinder inspection .....	5
7.1 Prefill cylinder inspection .....	5
7.2 Filling and postfilling inspection.....	6
8 Acetylene cylinder requalification .....	6
8.1 Authorized inspectors .....	6
8.2 Cylinder inspection equipment .....	6
8.3 Inspection for unauthorized cylinder shell repairs .....	7
8.4 External inspection of acetylene cylinder shells .....	7
8.5 Inspection of acetylene cylinder porous mass.....	16
8.6 Inspection markings.....	18
8.7 Sample visual inspection and requalification report .....	19
9 References .....	19
10 Additional references.....	19
 <b>Tables</b>	
Table 1—Minimum allowable wall thickness required by DOT or TC specifications.....	2
Table 2—Compliance schedule .....	3
Table 3—Minimum wall thickness at defect for acetylene cylinders Specification 8AL .....	7
Table 4—Minimum wall thickness at defect for acetylene cylinders Specification 8.....	8
Table 5—Maximum allowable defect depth for acetylene cylinders Specification 8AL.....	8
Table 6—Maximum allowable defect depth for acetylene cylinders Specification 8 .....	9
Table 7—Maximum top head-to-porous mass clearance for nonmonolithic and monolithic porous mass cylinders.....	17
 <b>Figures</b>	
Figure 1—Top clearance of monolithic filler cylinder .....	4
Figure 2—Isolated pitting .....	9
Figure 3—Line corrosion.....	10
Figure 4—Crevice corrosion near the cylinder footring.....	10
Figure 5—General corrosion with isolated pitting on cylinder sidewall .....	11
Figure 6—General corrosion with pitting on bottom head.....	11
Figure 7—Measuring the length and depth of typical dent.....	12

Figure 8—Cylinders manufactured with bottom head convex to pressure that have become bulged (partial bulge or reverse bending of the bottom) ..... 14  
Figure 9—Press-fit footing cylinder head-to-sidewall inside weld ..... 15  
Figure 10—Typical clearance gauge ..... 17  
Figure 11—Method of checking B and MC cylinders ..... 18

**Appendices**

Appendix A—Chart of chronological history of acetylene cylinder construction (Informative) ..... 20  
Appendix B—Acetylene cylinder periodic visual inspection and requalification report (Informative) ..... 21