

Contents	Page
1 Introduction.....	1
2 Scope and purpose	1
2.1 Scope	1
2.2 Purpose	1
3 Required publications.....	2
4 Definitions.....	2
5 General design information	5
5.1 Composite cylinders	5
5.2 Carbon composite cylinders	6
5.3 Cylinder components.....	6
6 Recommended inspection equipment.....	6
7 Exterior inspection.....	6
7.1 Inspection procedure for composite cylinders	6
7.2 Preparation for inspection	7
8 Types of damage.....	8
8.1 Abrasion damage	8
8.2 Cut damage.....	11
8.3 Impact damage.....	11
8.4 Structural damage.....	15
8.5 Chemical exposure.....	15
8.6 Heat or fire damage.....	15
9 Levels of damage	16
9.1 Level 1 damage (acceptable).....	16
9.2 Level 2 damage (rejectable—additional inspection or rework required).....	16
9.3 Level 3 damage (condemned—not reworkable)	16
10 Acceptance criteria.....	17
10.1 Abrasions.....	17
10.2 Cuts	17
10.3 Impact damage.....	18
10.4 Structural damage (level 3)	19
10.5 Chemical exposure damage (level 3).....	19
10.6 Heat exposure	19
10.7 General acceptable conditions	20
10.8 Rework	23
11 Manufacturer's label	25
11.1 Marking examples	25
11.2 Canadian equivalency certificates.....	25
12 Interior inspection	25
12.1 Preparation for internal inspection.....	25
12.2 Threads	26
12.3 O-ring gland.....	26
12.4 Interior	26
12.5 Dents	26
13 Hydrostatic test (requalification)	26
13.1 General.....	26
13.2 Test pressure.....	26
13.3 Test adapter	27
13.4 Test equipment.....	27
13.5 Test procedures.....	27
13.6 Test criteria.....	27

14	Special requirements for composite cylinders.....	27
14.1	Condemned cylinder.....	27
14.2	Marking of cylinders.....	27
14.3	Service life.....	28
15	References	28

Table

Table 1—Typical service and test pressures	26
--	----

Figures

Figure 1—Full-wrapped cylinder with one port.....	3
Figure 2—Full-wrapped cylinder with two ports	3
Figure 3—Hoop-wrapped cylinder with flat bottom	4
Figure 4—Hoop-wrapped cylinder with round bottom.....	4
Figure 5—Hoop-wrapped cylinder with two ports	4
Figure 6—Paint stripping (condemned)	7
Figure 7—Cylinder with protective end boots	8
Figure 8—Abrasion level 1 (glass fiber).....	8
Figure 9—Abrasion level 2 (glass fiber)	9
Figure 10—Abrasion level 2 (aramid fiber)	9
Figure 11—Abrasion level 3 (glass fiber)	10
Figure 12—Abrasion level 3 (aramid fiber)	10
Figure 13—Abrasion level 3 (carbon fiber)	10
Figure 14—Cut level 1 (glass fiber).....	11
Figure 15—Cut level 1 (carbon fiber)	11
Figure 16—Cut level 3 (glass fiber with delamination and lifting fiber)	12
Figure 17—Cut level 3 (aramid fiber)	12
Figure 18—Cut level 3 (carbon fiber)	12
Figure 19—Cut level 3 (carbon fiber)—dome	13
Figure 20—Impact level 1 (glass fiber)	13
Figure 21—Impact level 1 (carbon fiber).....	13
Figure 22—Impact level 3 (glass fiber) with cuts	14
Figure 23—Impact level 3 (glass fiber) with cut and fiber lifting.....	14
Figure 24—Impact level 3 (carbon fiber) with liner indentation	14
Figure 25—Structural damage level 3 (glass fiber).....	15
Figure 26—Heat damage level 3 (carbon fiber)	16
Figure 27—Fire damage level 3 (carbon fiber)	16
Figure 28—Cut length definition.....	18
Figure 29—Cut level 2 (repairable delamination of glass fiber over a label).....	18
Figure 30—Heat exposure level 1 (carbon fiber)	19
Figure 31—Heat exposure level 1 (carbon fiber)	20
Figure 32—Level 1 bottom filler material expansion cracking (acceptable).....	21
Figure 33—Level 1 resin expansion crack (acceptable)	21
Figure 34—Level 1 water seepage (acceptable)	22
Figure 35—Examples of variations in cylinder dome shapes	22
Figure 36—Length measurement of level 2 cut (glass fiber)	23
Figure 37—Depth measurement.....	23
Figure 38—Resin mixing.....	24
Figure 39—Resin application	24
Figure 40—After cure.....	24

Appendices

Appendix A—Hoop-wrapped cylinders (Informative)	29
Appendix B—Full-wrapped aramid and glass fiber cylinders (Informative).....	30