

Contents	Page
1 Introduction.....	1
2 Scope	1
3 Nomenclature.....	1
4 Preventing overpressurization.....	3
4.1 Methods.....	3
4.2 External protection device	3
4.3 Tank fill and relief system.....	3
5 Calculations.....	4
5.1 Step 1: Input tank and piping data.....	5
5.2 Step 2: Determine tank emergency overpressure, P_{eop}	5
5.3 Step 3: Determine maximum frictional pressure loss through the relief system, ΔP_{rel_max}	5
5.4 Step 4: Determine flow resistance of the pressure relief system, K_{rel}	6
5.5 Step 5: Calculate maximum flow rate through the relief system, Q_{rel_max}	6
5.6 Step 6: Determine flow resistance of the truck and tank fill system, K_{truck} and K_{fill}	7
5.7 Step 7: Determine pressure loss through the fill system, ΔP_{fill_line}	7
5.8 Step 8: Determine fill line orifice pressure drop, ΔP_{ori}	7
5.9 Step 9: Determine required fill orifice flow resistance, K_{ori} and size, d_{ori}	8
6 References	8
 Table	
Table 1—Definition of variables	1
 Figure	
Figure 1—System configuration.....	4
 Appendices	
Appendix A—Equation sets for the analysis and prevention of overpressure during refilling of cryogenic storage tanks (Normative).....	10
Appendix B—Sample calculation 1—orifice is required (Informative).....	13
Appendix C—Sample calculation 2—orifice is not required (Informative).....	26
Appendix D—Blank calculation forms for the analysis and prevention of overpressure during refilling of cryogenic storage tanks (Informative).....	39
Appendix E—Reference data (Informative)	51
 Appendices Figures	
Figure B-1—Sample calculation 1—relief line sketch	13
Figure B-2—Sample calculation 1—fill line sketch.....	13
Figure C-1—Sample calculation 2—relief line sketch	26
Figure C-2—Sample calculation 2—fill line sketch	26
 Appendices Tables	
Table E-1—Fluid density.....	51
Table E-2—Overall height for typical tanks.....	51
Table E-3—Pipe and tube inside diameters and inside diameters to the 4th power.....	52
Table E-4—Typical hydraulic truck pump performance	53
Table E-5—Fill line orifice sizes and flow resistance coefficient referenced to 1.481 in (37.6 mm) internal diameter	53