

CSA 3.11:15 (reaffirmed 2020)

Lever operated pressure lubricated plug type gas shut-off valves



Legal Notice for Standards

Canadian Standards Association (operating as "CSA Group") develops standards through a consensus standards development process approved by the Standards Council of Canada. This process brings together volunteers representing varied viewpoints and interests to achieve consensus and develop a standard. Although CSA Group administers the process and establishes rules to promote fairness in achieving consensus, it does not independently test, evaluate, or verify the content of standards.

Disclaimer and exclusion of liability

This document is provided without any representations, warranties, or conditions of any kind, express or implied, including, without limitation, implied warranties or conditions concerning this document's fitness for a particular purpose or use, its merchantability, or its non-infringement of any third party's intellectual property rights. CSA Group does not warrant the accuracy, completeness, or currency of any of the information published in this document. CSA Group makes no representations or warranties regarding this document's compliance with any applicable statute, rule, or regulation.

IN NO EVENT SHALL CSA GROUP, ITS VOLUNTEERS, MEMBERS, SUBSIDIARIES, OR AFFILIATED COMPANIES, OR THEIR EMPLOYEES, DIRECTORS, OR OFFICERS, BE LIABLE FOR ANY DIRECT, INDIRECT, OR INCIDENTAL DAMAGES, INJURY, LOSS, COSTS, OR EXPENSES, HOWSOEVER CAUSED, INCLUDING BUT NOT LIMITED TO SPECIAL OR CONSEQUENTIAL DAMAGES, LOST REVENUE, BUSINESS INTERRUPTION, LOST OR DAMAGED DATA, OR ANY OTHER COMMERCIAL OR ECONOMIC LOSS, WHETHER BASED IN CONTRACT, TORT (INCLUDING NEGLIGENCE), OR ANY OTHER THEORY OF LIABILITY, ARISING OUT OF OR RESULTING FROM ACCESS TO OR POSSESSION OR USE OF THIS DOCUMENT, EVEN IF CSA GROUP HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, INJURY, LOSS, COSTS, OR EXPENSES.

In publishing and making this document available, CSA Group is not undertaking to render professional or other services for or on behalf of any person or entity or to perform any duty owed by any person or entity to another person or entity. The information in this document is directed to those who have the appropriate degree of experience to use and apply its contents, and CSA Group accepts no responsibility whatsoever arising in any way from any and all use of or reliance on the information contained in this document.

CSA Group is a private not-for-profit company that publishes voluntary standards and related documents. CSA Group has no power, nor does it undertake, to enforce compliance with the contents of the standards or other documents it publishes.

Intellectual property rights and ownership

As between CSA Group and the users of this document (whether it be in printed or electronic form), CSA Group is the owner, or the authorized licensee, of all works contained herein that are protected by copyright, all trade-marks (except as otherwise noted to the contrary), and all inventions and trade secrets that may be contained in this document, whether or not such inventions and trade secrets are protected by patents and applications for patents. Without limitation, the unauthorized use, modification, copying, or disclosure of this document may violate laws that protect CSA Group's and/or others' intellectual property and may give rise to a right in CSA Group and/or others to seek legal redress for such use, modification, copying, or disclosure. To the extent permitted by licence or by law, CSA Group reserves all intellectual property rights in this document.

Patent rights

Attention is drawn to the possibility that some of the elements of this standard may be the subject of patent rights. CSA Group shall not be held responsible for identifying any or all such patent rights. Users of this standard are expressly advised that determination of the validity of any such patent rights is entirely their own responsibility.

Authorized use of this document

This document is being provided by CSA Group for informational and non-commercial use only. The user of this document is authorized to do only the following:

If this document is in electronic form:

- load this document onto a computer for the sole purpose of reviewing it;
- search and browse this document; and
- print this document if it is in PDF format.

Limited copies of this document in print or paper form may be distributed only to persons who are authorized by CSA Group to have such copies, and only if this Legal Notice appears on each such copy.

In addition, users may not and may not permit others to

- alter this document in any way or remove this Legal Notice from the attached standard;
- sell this document without authorization from CSA Group; or
- make an electronic copy of this document.

If you do not agree with any of the terms and conditions contained in this Legal Notice, you may not load or use this document or make any copies of the contents hereof, and if you do make such copies, you are required to destroy them immediately. Use of this document constitutes your acceptance of the terms and conditions of this Legal Notice.



Standards Update Service

CSA 3.11:15 November 2015

Title: Lever operated pressure lubricated plug type gas shut-off valves

To register for e-mail notification about any updates to this publication

- go to store.csagroup.org
- click on **Product Updates**

The List ID that you will need to register for updates to this publication is 2422950.

If you require assistance, please e-mail techsupport@csagroup.org or call 416-747-2233.

Visit CSA Group's policy on privacy at www.csagroup.org/legal to find out how we protect your personal information.

CSA 3.11:15

Lever operated pressure lubricated plug type gas shut-off valves



*A trademark of the Canadian Standards Association, operating as "CSA Group"

Approved on October 20, 2015 by IGAC
Effective in Canada March 2017
Published in November 2015 by CSA Group
A not-for-profit private sector organization
178 Rexdale Boulevard, Toronto, Ontario, Canada M9W 1R3

To purchase standards and related publications, visit our Online Store at store.csagroup.org or call toll-free 1-800-463-6727 or 416-747-4044.

ISBN 978-1-77139-535-9

© 2015 Canadian Standards Association All rights reserved. No part of this publication may be reproduced in any form whatsoever without the prior permission of the publisher.

Contents

Technical Committee on Gas Appliances and Related Accessories 2

Z21/CSA Joint Technical Subcommittee on Standards for Manually Operated Gas Valves 4

Preface 7

- **1 Scope** 8
- 2 Reference publications 9
- 3 Definitions 9
- 4 Construction 10
- 4.1 General construction 10
- 4.2 Materials 11
- 4.3 Marking *12*
- 4.4 Preparation for shipment 13
- **5 Performance** 13
- 5.1 General *13*
- 5.2 Leakage 14
- 5.3 Continued operation 15
- 5.4 Temperature resistance 15
- 5.5 Flow capacity 16
- 5.6 Strength 19
- 5.7 Lubrication 21
- 5.8 Classification of marking material 22
- 5.9 Marking material adhesion and legibility 23
- 6 Additional provisions for -40 °C (-40°F) service 23
- 7 Additional provisions for -60 °C (-76°F) service 24
- 8 Additional provisions for 120 °C (248°F) service 25
- 9 Additional provisions for 180 °C (356°F) service 26
- 10 Manufacturing and production tests 27

Chair

Technical Committee on Gas Appliances and Related Accessories

Z.J. Fraczkowski Technical Standards & Safety Authority (TSSA),

Toronto, Ontario

Category: Government and/or Regulatory Authority

A. Gould Reliance Comfort Ltd. Partnership dba Reliance Vice-Chair

Home Comfort, Cambridge, Ontario Category: User Interest

A. Abdel-Rehim A.O. Smith Enterprises Ltd., Associate

Fergus, Ontario

J.M.A. Associates Representing EnerCare Solutions,

Midland, Ontario

Category: General Interest

P.A. Baker Maxitrol Company,

Hamilton, Ontario

Category: Producer Interest

D. Baxter Enbridge Gas Distribution,

Thorold, Ontario Category: User Interest

J. Boros Rheem Sales Co Inc AKA Rheem Manufacturing Co.,

Montgomery, Alabama, USA Category: Producer Interest

T. Brennan Natural Resources Canada, Associate

Ottawa, Ontario

C. Côté Gaz Métro,

Montréal, Québec Category: User Interest

C. Gibbs Guelph, Ontario

Category: General Interest

D.N. Hird SaskPower,

Regina, Saskatchewan

Category: Government and/or Regulatory Authority

D.R. Jamieson GHP Group Inc,

Oakville, Ontario

Category: Producer Interest

C.E. Jorgenson British Columbia Safety Authority (BCSA),

New Westminster, British Columbia

Category: Government and/or Regulatory Authority

S. Katz S. Katz and Associates Inc., Associate

North Vancouver, British Columbia

J.R. Marshall Technical Standards & Safety Authority (TSSA), Associate

Toronto, Ontario

J. Melling SaskPower, Associate

Saskatoon, Saskatchewan

J. Overall Union Gas Limited, Associate

Toronto, Ontario

T.W. Poulin A.O. Smith Enterprises Ltd.,

Fergus, Ontario

Category: Producer Interest

G.B. Prociw Union Gas Limited,

Chatham, Ontario Category: User Interest

E. Scott British Columbia Safety Authority (BCSA), Associate

New Westminster, British Columbia

B.J. Swiecicki National Propane Gas Association, Associate

Frankfort, Illinois, USA

M. Thomas Natural Resources Canada CANMET Energy, Associate

Ottawa, Ontario

M. Travers Reliance Comfort L.P., Associate

Cambridge, Ontario

C. Bielawski CSA Group, Project Manager

Cleveland, Ohio, USA

Z21/CSA Joint Technical Subcommittee on Standards for Manually Operated Gas Valves

P.A. Baker Maxitrol Company,

Hamilton, Ontario

Chair

B. Diel M.B. Sturgis Inc.,

St. Louis, Missouri, USA

Vice-Chair

M. Angus Dormont Manufacturing Co.,

Export, Pennsylvania, USA

T. Bukowski Weber-Stephen Products Co.,

Palatine, Illinois, USA

S.R. Caudle Southern California Gas Company,

Los Angeles, California, USA

E. Ceo Eaton Hydraulics Group,

Cleveland, Ohio, USA

C.V. Childers Weber-Stephen Products LLC,

Palatine, Illinois, USA

M. Deegan Clearwater Gas System,

Clearwater, Florida, USA

D.C. Delaquila Aquila Consulting, LLC,

Warren, Ohio, USA

Associate

R. Dominguez Brass-Craft Manufacturing Co,

Novi, Michigan, USA

Z.J. Fraczkowski Technical Standards & Safety Authority (TSSA),

Associate

Toronto, Ontario

A. Gafford Char-Broil, LLC,

Columbus, Georgia, USA

G. Goodson Conbraco Industries,

Pageland, South Carolina, USA

A.C. Granzow NIBCO Incorporated,

Elkhart, Indiana, USA

R. Green Brass-Craft Manufacturing Co.,

Novi, Michigan, USA

D. Hopson Parker Hannifin Corporation,

Union City, Pennsylvania, USA

J.P. Jollay Char-Broil, LLC,

Columbus, Georgia, USA

R. Mateos Martin Copreci S. Coop,

Marietta, Georgia, USA

J. McGinnis Omega Flex, Inc.,

Exton, Pennsylvania, USA

T.D. Mulligan Brass-Craft Manufacturing Co.,

Novi, Michigan, USA

R. Nardoni White-Rodgers Division,

St. Louis, Missouri, USA

M. Pablo Orkli, S. Coop,

Ordizia-Gipuzkoa, , Spain

K. Patil White-Rodgers Division,

St. Louis, Missouri, USA

W. Ring Fairview Fittings & Manufacturing Limited,

Toronto, Ontario

C.R. Sarson Eaton Hydraulics Group,

Cleveland, Ohio, USA

J.J. Schlachter Maxitrol Company,

Southfield, Michigan, USA

Associate

CSA 3.11:15

Dever operated pressure tubricated plug type gas situt ojj valves

F.A. Stanonik Air-Conditioning, Heating, and Refrigeration Institute,

Arlington, Virginia, USA

R. Ten Bruin Weber-Stephen Products LLC,

Palatine, Illinois, USA

R.N. Torbin Omega Flex Inc.,

Middletown, Connecticut, USA

T.A. Williams American Gas Association Inc.,

Washington, , USA

C. Bielawski CSA Group,

Cleveland, Ohio, USA

Project Manager

Preface

This is the third edition of CSA 3.11, Lever operated pressure lubricated plug type gas shut-off valves. It supersedes the previous editions published in 1985 and 1988.

This Standard was prepared by the Z21/CSA Joint Technical Subcommittee on Standards for Manually Operated Gas Valves, under the jurisdiction of the Technical Committee on Performance and Installation of Gas Burning Appliances and Related Accessories and the Strategic Steering Committee on Standards for Gas Appliances and Related Accessories, and had been formally approved by the CSA Technical Committee and Interprovincial Gas Advisory Council.

Interpretations: The Strategic Steering Committee on Standards for Standards for Gas Appliances and Related Accessories has provided the following direction for the interpretation of standards under its jurisdiction: "The literal text shall be used in judging compliance of products with the safety requirements of this Standard. When the literal text cannot be applied to the product, such as for new materials or construction, and when a relevant committee interpretation has not already been published, CSA Group's procedures for interpretation shall be followed to determine the intended safety principle."

Notes:

- 1) Use of the singular does not exclude the plural (and vice versa) when the sense allows.
- 2) This Standard contains SI (Metric) units corresponding to the yard/pound quantities, the purpose being to allow the standard to be used in SI (Metric) units. (IEEE/ASTM SI 10, American National Standard for Metric Practice, or ISO 80000-1:2009, Quantities and units Part 1: General, is used as a guide in making metric conversion from yard/pound quantities.) If a value for a measurement and a corresponding value in other units are stated, the first stated value is to be regarded as the requirement. The given corresponding value may be approximate. If a value for a measurement and a corresponding value in other units are both specified as a quoted marking requirement, the first stated unit, or both, are to be provided.
- 3) Although the intended primary application of this Standard is stated in its Scope, it is important to note that it remains the responsibility of the users of the Standard to judge its suitability for their particular purpose.
- 4) This publication was developed by consensus, which is defined by CSA Policy governing standardization Code of good practice for standardization as "substantial agreement. Consensus implies much more than a simple majority, but not necessarily unanimity." It is consistent with this definition that a member may be included in the Technical Committee list and yet not be in full agreement with all clauses of this publication.
- 5) This Standard is subject to review five years from the date of publication, and suggestions for its improvement will be referred to the appropriate committee. To submit a proposal for change, please send the following information to inquiries@csagroup.org and include "Proposal for change" in the subject line:
 - a) Standard designation (number);
 - b) relevant clause, table, and/or figure number;
 - c) wording of the proposed change; and
 - d) rationale for the change.
- 6) To submit a request for interpretation of this Standard, please send the following information to inquiries@csagroup.org and include "Request for interpretation" in the subject line:
 - a) define the problem, making reference to the specific clause, and, where appropriate, include an illustrative sketch;
 - b) provide an explanation of circumstances surrounding the actual field condition; and
 - c) where possible, phrase the request in such a way that a specific "yes" or "no" answer will address the issue.

Committee interpretations are processed in accordance with the CSA Directives and guidelines governing standardization and are available on the Current Standards Activities page at standardsactivities.csa.ca.

CSA 3.11:15

Lever operated pressure lubricated plug type gas shut-off valves

1 Scope

1.1

This Standard applies to manual lever operated, pressure lubricated, straight way gas shut-off valves, sizes NPS $\frac{1}{2}$ inch to 8 inch, of metallic construction with welded, or flanged, or threaded ends, for use with natural gas, manufactured gas, and liquefied petroleum gases (distributed as vapour with or without the admixture of air), or mixtures thereof that are suitable for use between service temperatures of -60 °C (-76°F) to 180 °C (356°F) over a pressure range of zero to 860 kPa (125 psig) and withstand field pressure testing to a maximum pressure of 1290 kPa (187 psig).

Notes:

- 1) Valves covered by this Standard may be used on "digester gas" (methane produced during sewage treatment), but because of entrained contaminants their use is to be subject to agreement between the manufacturer and the purchaser.
- 2) Valves covered by this Standard may not be used on "sour gas" (gas with entrained hydrogen sulphide) without additional modifications. Manufacturers should be consulted for their recommendation(s).

1.2

A valve covered by this Standard will be limited to the service temperature and/or special provisions in accordance with Clauses $\underline{5}$ through $\underline{9}$.

```
Clause \underline{5} -30 °C to 65 °C (-22°F to 149°F)

Clause \underline{6} -40 °C to 65 °C (-40°F to 149°F)

Clause \underline{7} -60 °C to 65 °C (-76°F to 149°F)

Clause \underline{8} -30 °C to 120 °C (-22°F to 248°F)

Clause \underline{9} -30 °C to 180 °C (-22°F to 356°F)
```

1.3

All references to kPa (psi) throughout this Standard are considered as gauge pressure unless otherwise specified.

1.4

This Standard contains SI (Metric) units corresponding to the yard/pound quantities, the purpose being to allow the standard to be used in SI (Metric) units. (IEEE/ASTM SI 10, American National Standard for Metric Practice, or ISO 80000-1:2009, Quantities and units – Part 1: General, is used as a guide in making metric conversion from yard/pound quantities.) If a value for a measurement and a corresponding value in other units are stated, the first stated value is to be regarded as the requirement. The given corresponding value may be approximate. If a value for a measurement and a