

# USB-grænseflader for data og energi – Del 1-2: Fælles komponenter – USB-strømforsynings-specifikation

Universal serial bus interfaces for data and power –  
Part 1-2: Common components –  
USB Power Delivery specification

**DANSK STANDARD**  
Danish Standards Association

Göteborg Plads 1  
DK-2150 Nordhavn

Tel: +45 39 96 61 01  
[dansk.standard@ds.dk](mailto:dansk.standard@ds.dk)  
[www.ds.dk](http://www.ds.dk)

This is a preview of DS/EN IEC 62680-1-2:2025. [Click here to purchase the full version from the ANSI store.](#)

DS projekt: M385553  
ICS: 29.220; 33.120; 35.200

**Første del af denne publikations betegnelse er:**  
DS/EN IEC, hvilket betyder, at det er en international standard, der har status som europæisk og dansk standard.

**Denne publikations overensstemmelse er:**  
IDT med: IEC 62680-1-2:2024 ED7  
IDT med: EN IEC 62680-1-2:2025

DS-publikationen er på engelsk.

Denne publikation erstatter: [DS/EN IEC 62680-1-2:2022](#)

---

I tilfælde af redaktionelle fejl i DS-publikationen kan der skrives til:  
[editorial-mistakes@ds.dk](mailto:editorial-mistakes@ds.dk)

**ADVARSEL:** DS-publikationer revideres over tid. Derudover kan sådanne publikationer ændres ved rettelsesblade og/eller tillæg. Der kan også udgives rettelsesblade, der udelukkende angår oversættelsen af en publikation. Det er derfor vigtigt at sikre sig, at man benytter en gældende udgave, medmindre fx lovgivning kræver andet. Den enkelte publikations status fremgår af <https://webshop.ds.dk/>. Her kan man desuden tilmelde sig en gratis notifikationservice og følge en udgivet DS-publikations udvikling ved at klikke på "Følg standarden".

En oversigt over forskellige DS-publikationstyper og -betegnelser findes her:  
<https://www.ds.dk/publikationstyper>.

This is a preview of DS/EN IEC 62680-1-2:2025. [Click here to purchase the full version from the ANSI store.](#)

## EUROPÄISCHE NORM

January 2025

ICS 29.220; 33.120; 35.200

Supersedes EN IEC 62680-1-2:2022

English Version

Universal serial bus interfaces for data and power - Part 1-2:  
Common components - USB Power Delivery specification  
(IEC 62680-1-2:2024)

Interfaces de bus universel en série pour les données et  
l'alimentation électrique - Partie 1-2: Composants communs  
- Spécification de l'alimentation électrique par port USB  
(IEC 62680-1-2:2024)

Universelle Bus-Schnittstellen für Daten und Energie -  
Teil 1-2: Gemeinsame Komponenten - Festlegung  
für die Energieübertragung über USB  
(IEC 62680-1-2:2024)

This European Standard was approved by CENELEC on 2025-01-17. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

## **European foreword**

The text of document 100/4138/CDV, future edition 7 of IEC 62680-1-2, prepared by TC 100/Technical Area 18 "Multimedia home systems and applications for end-user networks" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 62680-1-2:2025.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2026-01-31 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the (dow) 2028-01-31 document have to be withdrawn

This document supersedes EN IEC 62680-1-2:2022 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

## **Endorsement notice**

The text of the International Standard IEC 62680-1-2:2024 was approved by CENELEC as a European Standard without any modification.



# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



**Universal serial bus interfaces for data and power –  
Part 1-2: Common components – USB Power Delivery specification**

**Interfaces de bus universel en série pour les données et l'alimentation  
électrique –  
Partie 1-2: Composants communs – Spécification de l'alimentation électrique  
par port USB**



This is a preview of DS/EN IEC 62680-1-2:2025. [Click here to purchase the full version from the ANSI store.](#)



**THIS PUBLICATION IS COPYRIGHT PROTECTED**

**Copyright © 2024 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

**About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

**About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

**IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)**

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

**IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

**IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

**IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)**

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

**Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

---

**A propos de l'IEC**

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

**A propos des publications IEC**

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

**Recherche de publications IEC -**

**[webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)**

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

**IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

**Service Clients - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: [sales@iec.ch](mailto:sales@iec.ch).

**IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)**

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications, symboles graphiques et le glossaire. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

**Electropedia - [www.electropedia.org](http://www.electropedia.org)**

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 500 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 25 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.



# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



**Universal serial bus interfaces for data and power –  
Part 1-2: Common components – USB Power Delivery specification**

**Interfaces de bus universel en série pour les données et l'alimentation  
électrique –  
Partie 1-2: Composants communs – Spécification de l'alimentation électrique  
par port USB**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

ICS 29.220, 33.120, 35.200

ISBN 978-2-8327-0040-2

**Warning! Make sure that you obtained this publication from an authorized distributor.  
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

### UNIVERSAL SERIAL BUS INTERFACES FOR DATA AND POWER –

### Part 1-2: Common components – USB Power Delivery specification

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62680-1-2 has been prepared by technical area 18: Multimedia home systems and applications for end-user networks, of IEC technical committee 100: Audio, video and multimedia systems and equipment. It is an International Standard.

The text of this standard was prepared by the USB Implementers Forum (USB-IF). The structure and editorial rules used in this publication reflect the practice of the organization which submitted it.

The text of this International Standard is based on the following documents:

Draft	Report on voting
100/4138/CDV	100/4176/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

A list of all parts in the IEC 62680 series, published under the general title *Universal serial bus interfaces for data and power*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

**IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

# *Universal Serial Bus*

## *Power Delivery Specification*

---

<i>Revision:</i>	<b>3.2</b>
<i>Version:</i>	<b>1.0</b>
<i>Release date:</i>	<b>2023-10</b>

## LIMITED COPYRIGHT LICENSE

THE USB 3.0 PROMOTERS GRANT A CONDITIONAL COPYRIGHT LICENSE UNDER THE COPYRIGHTS EMBODIED IN THE USB POWER DELIVERY SPECIFICATION TO USE AND REPRODUCE THE SPECIFICATION FOR THE SOLE PURPOSE OF, AND SOLELY TO THE EXTENT NECESSARY FOR, EVALUATING WHETHER TO IMPLEMENT THE SPECIFICATION IN PRODUCTS THAT WOULD COMPLY WITH THE SPECIFICATION. WITHOUT LIMITING THE FOREGOING, USE THE OF SPECIFICATION FOR THE PURPOSE OF FILING OR MODIFYING ANY PATENT APPLICATION TO TARGET THE SPECIFICATION OR USB COMPLIANT PRODUCTS IS NOT AUTHORIZED. EXCEPT FOR THIS EXPRESS COPYRIGHT LICENSE, NO OTHER RIGHTS OR LICENSES ARE GRANTED, INCLUDING WITHOUT LIMITATION ANY PATENT LICENSES. IN ORDER TO OBTAIN ANY ADDITIONAL INTELLECTUAL PROPERTY LICENSES OR LICENSING COMMITMENTS ASSOCIATED WITH THE SPECIFICATION A PARTY MUST EXECUTE THE USB 3.0 ADOPTERS AGREEMENT. NOTE: BY USING THE SPECIFICATION, YOU ACCEPT THESE LICENSE TERMS ON YOUR OWN BEHALF AND, IN THE CASE WHERE YOU ARE DOING THIS AS AN EMPLOYEE, ON BEHALF OF YOUR EMPLOYER.

## INTELLECTUAL PROPERTY DISCLAIMER

THIS SPECIFICATION IS PROVIDED TO YOU "AS IS" WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE AUTHORS OF THIS SPECIFICATION DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OF INFORMATION IN THIS SPECIFICATION. THE PROVISION OF THIS SPECIFICATION TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS.

Please send comments via electronic mail to [techsup@usb.org](mailto:techsup@usb.org).

For industry information, refer to the USB Implementers Forum web page at <http://www.usb.org>.

USB Type-C® and USB4® are trademarks of the Universal Serial Bus Implementers Forum (USB-IF). Thunderbolt™ is a trademark of Intel Corporation.

You may only use the Thunderbolt™ trademark or logo in conjunction with products designed to this specification that complete proper certification and executing a Thunderbolt™ trademark license – see <http://usb.org/compliance> for further information.

All product names are trademarks, registered trademarks, or service marks of their respective owners.

Copyright © 2010-2023, USB 3.0 Promoter Group: Apple Inc., Hewlett-Packard Inc., Intel Corporation, Microsoft Corporation, Renesas, STMicroelectronics, and Texas Instruments.  
All rights reserved.

## Editors

Bob Dunstan  
Richard Petrie

## Contributors

Charles Wang	ACON, Advanced-Connectek, Inc.	Sameer Kelkar	Apple
Conrad Choy	ACON, Advanced-Connectek, Inc.	Sasha Tietz	Apple
Dennis Chuang	ACON, Advanced-Connectek, Inc.	Scott Jackson	Apple
Steve Sedio	ACON, Advanced-Connectek, Inc.	Sree Raman	Apple
Sunney Yang	ACON, Advanced-Connectek, Inc.	William Ferry	Apple
Vicky Chuang	ACON, Advanced-Connectek, Inc.	Zaki Moussaoui	Apple
Joseph Scanlon	Advanced Micro Devices	Jeff Liu	ASMedia Technology Inc.
Sujan Thomas	Advanced Micro Devices	Kuo Lung Li	ASMedia Technology Inc.
Caspar Lin	Allion Labs, Inc.	Ming-Wei Hsu	ASMedia Technology Inc.
Casper Lee	Allion Labs, Inc.	PS Tseng	ASMedia Technology Inc.
Danny Shih	Allion Labs, Inc.	Sam Tzeng	ASMedia Technology Inc.
Howard Chang	Allion Labs, Inc.	Thomas Hsu	ASMedia Technology Inc.
Greg Stewart	Analogix Semiconductor, Inc.	Weikao Chang	ASMedia Technology Inc.
Mehran Badii	Analogix Semiconductor, Inc.	Yang Cheng	ASMedia Technology Inc.
Alexei Kosut	Apple	Aaron Hou	Bizlink Technology Inc.
Bill Cornelius	Apple	Shawn Meng	Bizlink Technology Inc.
Carlos Colderon	Apple	Bernard Shyu	Bizlink Technology, Inc.
Chris Uiterwijk	Apple	Eric Wu	Bizlink Technology, Inc.
Colin Whitby-Strevens	Apple	Morphy Hsieh	Bizlink Technology, Inc.
Corey Axelowitz	Apple	Sean O'Neal	Bizlink Technology, Inc.
Corey Lange	Apple	Tiffany Hsiao	Bizlink Technology, Inc.
Dave Conroy	Apple	Weichung Ooi	Bizlink Technology, Inc.
David Sekowski	Apple	Rahul Bhushan	Broadcom Corp.
Girault Jones	Apple	Asila nahas	Cadence Design Systems, Inc.
James Orr	Apple	Claire Ying	Cadence Design Systems, Inc.
Jason Chung	Apple	Jie min	Cadence Design Systems, Inc.
Jay Kim	Apple	Mark Summers	Cadence Design Systems, Inc.
Jeff Wilcox	Apple	Michal Staworko	Cadence Design Systems, Inc.
Jennifer Tsai	Apple	Sathish Kumar Ganesan	Cadence Design Systems, Inc.
Karl Bowers	Apple	Alessandro Ingrassia	Canova Tech
Keith Porthouse	Apple	Andrea Colognese	Canova Tech
Kevin Hsiue	Apple	Antonio Orzelli	Canova Tech
Matt Mora	Apple	Davide Ghedin	Canova Tech
Paul Baker	Apple	Matteo Casalin	Canova Tech
Reese Schreiber	Apple	Michael Marioli	Canova Tech
Ricardo Janezic Pregitzer	Apple	Nicola Scantamburlo	Canova Tech
Ruchi Chaturvedi	Apple	Paolo Pilla	Canova Tech

Ray Huang	Canyon Semiconductor	KE Hong	Dialog Semiconductor (UK) Ltd
Yi-Feng Lin	Canyon Semiconductor	Kevin Mori	Dialog Semiconductor (UK) Ltd
YuHung Lin	Canyon Semiconductor	Larry Ping	Dialog Semiconductor (UK) Ltd
David Tsai	Chrontel, Inc.	Mengfei Liu	Dialog Semiconductor (UK) Ltd
Anshul Gulati	Cypress Semiconductor	Scott Brown	Dialog Semiconductor (UK) Ltd
Anup Nayak	Cypress Semiconductor	Yimin Chen	Dialog Semiconductor (UK) Ltd
Benjamin Kropf	Cypress Semiconductor	Yong Li	Dialog Semiconductor (UK) Ltd
Dhanraj Rajput	Cypress Semiconductor	Justin Lee	Diodes Incorporated
Ganesh Subramaniam	Cypress Semiconductor	Dan Ellis	DisplayLink (UK) Ltd.
Jagadeesan Raj	Cypress Semiconductor	Jason Young	DisplayLink (UK) Ltd.
Junjie cui	Cypress Semiconductor	Kevin Jacobs	DisplayLink (UK) Ltd.
Manu Kumar	Cypress Semiconductor	Paulo Alcobia	DisplayLink (UK) Ltd.
Muthu M	Cypress Semiconductor	Peter Burgers	DisplayLink (UK) Ltd.
Nicholas Bodnaruk	Cypress Semiconductor	Richard Petrie	DisplayLink (UK) Ltd.
Pradeep Bajpai	Cypress Semiconductor	Chien-Cheng Kuo	eEver Technology, Inc.
Rajaram R	Cypress Semiconductor	Shyanjia Chen	eEver Technology, Inc.
Rama Vakkantula	Cypress Semiconductor	Abel Astley	Ellisys
Rushil Kadakia	Cypress Semiconductor	Chuck Trefts	Ellisys
Simon Nguyen	Cypress Semiconductor	Emmanuel Durin	Ellisys
Steven Wong	Cypress Semiconductor	Mario Pasquali	Ellisys
Subu Sankaran	Cypress Semiconductor	Tim Wei	Ellisys
Sumeet Gupta	Cypress Semiconductor	Chien-Cheng Kuo	Etron Technology, Inc.
Tejender Sheoran	Cypress Semiconductor	Jack Yang	Etron Technology, Inc.
Venkat Mandagulathar	Cypress Semiconductor	Richard Crisp	Etron Technology, Inc.
Xiaofeng Shen	Cypress Semiconductor	Shyanjia Chen	Etron Technology, Inc.
Zeng Wei	Cypress Semiconductor	TsungTa Lu	Etron Technology, Inc.
Adie Tan	Dell Inc.	Christian Klein	Fairchild Semiconductor
Adolfo Montero	Dell Inc.	Oscar Freitas	Fairchild Semiconductor
Bruce Montag	Dell Inc.	Souhib Harb	Fairchild Semiconductor
Gary Verdun	Dell Inc.	Amanda Ying	Feature Integration Technology Inc.
Ken Nicholas	Dell Inc.	Jacky Chan	Feature Integration Technology Inc.
Marcin Nowak	Dell Inc.	Kenny Hsieh	Feature Integration Technology Inc.
Merle Wood	Dell Inc.	KungAn Lin	Feature Integration Technology Inc.
Mohammed Hijazi	Dell Inc.	Paul Yang	Feature Integration Technology Inc.
Siddhartha Reddy	Dell Inc.	Su Jaden	Feature Integration Technology Inc.
Terry Matula	Dell Inc.	Yu-Lin Chu	Feature Integration Technology Inc.
Jay Hu	Derun Semiconductor	Yulin Lan	Feature Integration Technology Inc.
Shelly Liu	Derun Semiconductor	AJ Yang	Foxconn / Hon Hai
Bindhu Vasu	Dialog Semiconductor (UK) Ltd	Bob Hall	Foxconn / Hon Hai
Chanchal Gupta	Dialog Semiconductor (UK) Ltd	Chihyin Kan	Foxconn / Hon Hai
Dipti Baheti	Dialog Semiconductor (UK) Ltd	Fred Fons	Foxconn / Hon Hai
Duc Doan	Dialog Semiconductor (UK) Ltd	Jie Zheng	Foxconn / Hon Hai
Holger Petersen	Dialog Semiconductor (UK) Ltd	Patrick Casher	Foxconn / Hon Hai
Jianming Yao	Dialog Semiconductor (UK) Ltd	Shruti Deore	Foxconn / Hon Hai
John Shi	Dialog Semiconductor (UK) Ltd	Steve Sedio	Foxconn / Hon Hai

Terry Little	Foxconn / Hon Hai	Vishal Kakade	Granite River Labs
Bob McVay	Fresco Logic Inc.	Yogeshwaran Venkatesan	Granite River Labs
Christopher Meyers	Fresco Logic Inc.	Jerry Qin	GuangDong OPPO Mobile
Dian Kurniawan	Fresco Logic Inc.	Alan Berkema	Hewlett Packard
Tom Burton	Fresco Logic Inc.	Lee Atkinson	Hewlett Packard
Abraham Levkoy	Google Inc.	Rahul Lakdawala	Hewlett Packard
Adam Rodriguez	Google Inc.	Robin Castell	Hewlett Packard
Alec Berg	Google Inc.	Ron Schooley	Hewlett Packard
Benson Leung	Google Inc.	Steve Chen	Hewlett Packard
Chao Fei	Google Inc.	Suketa Partiwala	Hewlett Packard
Dave Bernard	Google Inc.	Vaibhav Malik	Hewlett Packard
David Schneider	Google Inc.	Walter Fry	Hewlett Packard
Diana Zigterman	Google Inc.	Hideyuki HAYAFUJI	Hosiden Corporation
Eric Herrmann	Google Inc.	Keiji Mine	Hosiden Corporation
Jameson Thies	Google Inc.	Masaki Yamaoka	Hosiden Corporation
Jim Guerin	Google Inc.	Takashi Muto	Hosiden Corporation
Juan Fantin	Google Inc.	Yasunori Nishikawa	Hosiden Corporation
Ken Wu	Google Inc.	Alan Berkema	HP Inc.
Kyle Tso	Google Inc.	Kenneth Chan	HP Inc.
Mark Hayter	Google Inc.	Lee Atkinson	HP Inc.
Nathan Kolluru	Google Inc.	Lee Leppo	HP Inc.
Nithya Jagannathan	Google Inc.	Rahul Lakdawala	HP Inc.
Srikanth Lakshmikanthan	Google Inc.	Robin Castell	HP Inc.
Todd Broch	Google Inc.	Roger Benson	HP Inc.
Toshak Singhal	Google Inc.	Steve Chen	HP Inc.
Vincent Palatin	Google Inc.	Bai Sean	Huawei Technologies Co., Ltd.
Xuelin Wu	Google Inc.	Chunjiang Zhao	Huawei Technologies Co., Ltd.
Zhenxue Xu	Google Inc.	JianQuan Wu	Huawei Technologies Co., Ltd.
Alan Kinningham	Granite River Labs	Li Zongjian	Huawei Technologies Co., Ltd.
Anand Murugan	Granite River Labs	Liansheng Zheng	Huawei Technologies Co., Ltd.
Balamurugan Manialagan	Granite River Labs	Lihua Duan	Huawei Technologies Co., Ltd.
Medipalli Sowmya	Granite River Labs	Min Chen	Huawei Technologies Co., Ltd.
Mike Engbretson	Granite River Labs	Wang Feng	Huawei Technologies Co., Ltd.
Mike Wu	Granite River Labs	Wei Haihong	Huawei Technologies Co., Ltd.
Mukesh Tatiya	Granite River Labs	Zhenning Shi	Huawei Technologies Co., Ltd.
Naresh Botsa	Granite River Labs	James Xie	Hynetek Semiconductor Co., Ltd
PoornaKumar M.	Granite River Labs	Yingyang Ou	Hynetek Semiconductor Co., Ltd
Prajwal Rathod	Granite River Labs	Robert Heaton	Indie Semiconductor
Rajaraman V	Granite River Labs	Vincent Wang	Indie Semiconductor
Saai Ghoutham Revathi	Granite River Labs	Benjamin Kropf	Infineon Technologies
Sivan Perumal	Granite River Labs	Sie Boo Chiang	Infineon Technologies
Sivaram Murugesan	Granite River Labs	Tue Fatt David Wee	Infineon Technologies
Tim Lin	Granite River Labs	Wee Tar Richard Ng	Infineon Technologies
Vijay S.	Granite River Labs	Wolfgang Furtner	Infineon Technologies
Vijayakumar P	Granite River Labs	Aruni Nelson	Intel Corporation

Bob Dunstan	Intel Corporation	Babu Mailachalam	Lattice Semiconductor Corp
Brad Saunders	Intel Corporation	Gianluca Mariani	Lattice Semiconductor Corp
Chee Lim Nge	Intel Corporation	Joel Coplen	Lattice Semiconductor Corp
Christine Krause	Intel Corporation	Thomas Watza	Lattice Semiconductor Corp
Chuen Ming Tan	Intel Corporation	Vesa Lauri	Lattice Semiconductor Corp
Dan Froelich	Intel Corporation	Bruce Chuang	Leadtrend
David Harriman	Intel Corporation	Eilian Liu	Leadtrend
David Hines	Intel Corporation	Chetan Kopalle	LeCroy Corporation
David Thompson	Intel Corporation	Daniel H Jacobs	LeCroy Corporation
Guobin Liu	Intel Corporation	Jake Jacobs	LeCroy Corporation
Harry Skinner	Intel Corporation	Kimberley McKay	LeCroy Corporation
Henrik Leegaard	Intel Corporation	Mike Engbretson	LeCroy Corporation
Jenn Chuan Cheng	Intel Corporation	Mike Micheletti	LeCroy Corporation
Jervis Lin	Intel Corporation	Roy Chestnut	LeCroy Corporation
John Howard	Intel Corporation	Tyler Joe	LeCroy Corporation
Karthi Vadivelu	Intel Corporation	Phil Jakes	Lenovo
Leo Heiland	Intel Corporation	Do Kyun Kim	LG electronics
Maarit Harkonen	Intel Corporation	Won-Jong Choi	LG electronics
Nge Chee Lim	Intel Corporation	Won-Jong Choi	LG Electronics Ltd.
Paul Durley	Intel Corporation	Aaron Melgar	Lion Semiconductor
Rahman Ismail	Intel Corporation	Chris Zhou	Lion Semiconductor
Rajaram Regupathy	Intel Corporation	Sehyung Jeon	Lion Semiconductor
Ronald Swartz	Intel Corporation	Wonyoung Kim	Lion Semiconductor
Sarah Sharp	Intel Corporation	Yongho Kim	Lion Semiconductor
Scott Brenden	Intel Corporation	Dave Thompson	LSI Corporation
Sridharan Ranganathan	Intel Corporation	Alan Kinningham	Luxshare-ICT
Steve McGowan	Intel Corporation	Alan Liu	Luxshare-ICT
Tim McKee	Intel Corporation	Daniel Chen	Luxshare-ICT
Toby Opferman	Intel Corporation	Eric Wen	Luxshare-ICT
Uma Medepalli	Intel Corporation	James Kirk	Luxshare-ICT
Venkataamani Gopalakrishnan	Intel Corporation	James Stevens	Luxshare-ICT
Ziv Kabiry	Intel Corporation	Josue Castillo	Luxshare-ICT
Jia Wei	Intersil Corporation	Pat Young	Luxshare-ICT
Weijie Huang	iST - Integrated Service Technology Inc.	Scott Shuey	Luxshare-ICT
Al Hsiao	ITE Tech. Inc.	Stone Lin	Luxshare-ICT
Greg Song	ITE Tech. Inc.	Chikara Kakizawa	Maxim Integrated Products
Richard Guo	ITE Tech. Inc.	Jacob Scott	Maxim Integrated Products
Victor Lin	ITE Tech. Inc.	Ken Helfrich	Maxim Integrated Products
Y.C. Chou	ITE Tech. Inc.	Michael Miskho	Maxim Integrated Products
Kenta Minejima	Japan Aviation Electronics Industry Ltd.	Chris Yokum	MCCI Corporation
Mark Saubert	Japan Aviation Electronics Industry Ltd.	Geert Knapen	MCCI Corporation
Toshio Shimoyama	Japan Aviation Electronics Industry Ltd.	Terry Moore	MCCI Corporation
Brian Fetz	Keysight Technologies Inc.	Velmurugan Selvaraj	MCCI Corporation
Jit Lim	Keysight Technologies Inc.	Tung-Sheng Lin	MediaTek Inc.
Koji Asakawa	Kinetic Technologies Inc.	Tung-Sheng Lin	MediaTek Inc.

Satoru Kumashiro	MegaChips Corporation	Ben Crowe	MQP Electronics Ltd.
Brian Marley	Microchip Technology Inc.	Pat Crowe	MQP Electronics Ltd.
Dave Perchlik	Microchip Technology Inc.	Sten Carlsen	MQP Electronics Ltd.
Don Perkins	Microchip Technology Inc.	Kenji Oguma	NEC Corporation
Fernando Gonzalez	Microchip Technology Inc.	ChinJui Lin	Nexperia B.V.
John Sisto	Microchip Technology Inc.	Max Guan	Nexperia B.V.
Josh Averyt	Microchip Technology Inc.	Frank Borngläber	Nokia Corporation
Kiet Tran	Microchip Technology Inc.	Kai Inha	Nokia Corporation
Mark Bohm	Microchip Technology Inc.	Pekka Leinonen	Nokia Corporation
Matthew Kalibat	Microchip Technology Inc.	Richard Petrie	Nokia Corporation
Mick Davis	Microchip Technology Inc.	Sten Carlsen	Nokia Corporation
Prasanna Vengateshan	Microchip Technology Inc.	Abhijeet Kulkarni	NXP Semiconductors
Rich Wahler	Microchip Technology Inc.	Ahmad Yazdi	NXP Semiconductors
Richard Petrie	Microchip Technology Inc.	Bart Vertenten	NXP Semiconductors
Ronald Kunin	Microchip Technology Inc.	Dennis Ha	NXP Semiconductors
Shannon Cash	Microchip Technology Inc.	Dong Nguyen	NXP Semiconductors
Thomas Farkas	Microchip Technology Inc.	Guru Prasad	NXP Semiconductors
Venkataraman	Microchip Technology Inc.	Ken Jaramillo	NXP Semiconductors
Andrew Yang	Microsoft Corporation	Krishnan TN	NXP Semiconductors
Anthony Chen	Microsoft Corporation	Michael Joehren	NXP Semiconductors
Arvind Murching	Microsoft Corporation	Robert de Nie	NXP Semiconductors
Dave Perchlik	Microsoft Corporation	Rod Whitby	NXP Semiconductors
David Voth	Microsoft Corporation	Vijendra Kuroodi	NXP Semiconductors
Geoff Shew	Microsoft Corporation	Winston Langeslag	NXP Semiconductors
Jayson Kastens	Microsoft Corporation	Robert Heaton	Obsidian Technology
Kai Inha	Microsoft Corporation	Andrew Yoo	ON Semiconductor
Marwan Kadado	Microsoft Corporation	Brady Maasen	ON Semiconductor
Michelle Bergeron	Microsoft Corporation	Bryan McCoy	ON Semiconductor
Nathan Sherman	Microsoft Corporation	Christian Klein	ON Semiconductor
Rahul Ramadas	Microsoft Corporation	Cor Voorwinden	ON Semiconductor
Randy Aull	Microsoft Corporation	Edward Berrios	ON Semiconductor
Shiu Ng	Microsoft Corporation	Michael Smith	ON Semiconductor
Tieyong Yin	Microsoft Corporation	Oscar Freitas	ON Semiconductor
Timo Toivola	Microsoft Corporation	Tom Duffy	ON Semiconductor
Toby Nixon	Microsoft Corporation	Brian Collins	Parade Technologies Inc.
Vahid Vassey	Microsoft Corporation	Craig Wiley	Parade Technologies Inc.
Vivek Gupta	Microsoft Corporation	Hung-Chih Chiu	Power Forest Technology Corporation
Yang You	Microsoft Corporation	Jay Tu	Power Forest Technology Corporation
Adib Al Abaji	Molex LLC	Adel Lahham	Power Integrations
Aaron Xu	Monolithic Power Systems Inc.	Aditya Kulkarni	Power Integrations
Bo Zhou	Monolithic Power Systems Inc.	Akshay Nayaknur	Power Integrations
Christian Sporck	Monolithic Power Systems Inc.	Amruta Patra	Power Integrations
Di Han	Monolithic Power Systems Inc.	K R Rahul Raj	Power Integrations
Zhihong Yu	Monolithic Power Systems Inc.	Kaushik Raam	Power Integrations
Dan Wagner	Motorola Mobility Inc.	Rahul Joshi	Power Integrations

Ricardo Pregiteer	Power Integrations	Hidenori Nishimoto	Rohm Co. Ltd.
Shruti Anand	Power Integrations	Kris Bahar	Rohm Co. Ltd.
Amit gupta	Qualcomm, Inc	Manabu Miyata	Rohm Co. Ltd.
George Paparrizos	Qualcomm, Inc	Ruben Balbuena	Rohm Co. Ltd.
Giovanni Garcea	Qualcomm, Inc	Takashi Sato	Rohm Co. Ltd.
Jack Pham	Qualcomm, Inc	Vijendra Kuroodi	Rohm Co. Ltd.
James Goel	Qualcomm, Inc	Yusuke Kondo	Rohm Co. Ltd.
Joshua Warner	Qualcomm, Inc	Kazuomi Nagai	ROHM Co., Ltd.
Karyn Vuong	Qualcomm, Inc	Matti Kulmala	Salcomp Plc
Lalan Mishra	Qualcomm, Inc	Toni Lehimo	Salcomp Plc
Nicholas Cadieux	Qualcomm, Inc	Edward Lee	Samsung Electronics Co. Ltd.
Vamsi Samavedam	Qualcomm, Inc	Tong Kim	Samsung Electronics Co. Ltd.
Vatsal Patel	Qualcomm, Inc	Amit Bouzaglo	Scosche Industries
Chris Sporck	Qualcomm, Inc.	Alvin Cox	Seagate Technology LLC
Craig Aiken	Qualcomm, Inc.	Emmanuel Lemay	Seagate Technology LLC
Narendra Mehta	Qualcomm, Inc.	John Hein	Seagate Technology LLC
Terry Remple	Qualcomm, Inc.	Marc Noblitt	Seagate Technology LLC
Will Kun	Qualcomm, Inc.	Michael Morgan	Seagate Technology LLC
Yoram Rimoni	Qualcomm, Inc.	Ronald Rueckert	Seagate Technology LLC
Fan-Hau Hsu	Realtek Semiconductor Corp.	Tony Priborsky	Seagate Technology LLC
Tsung-Peng Chuang	Realtek Semiconductor Corp.	Chin Chang	Semtech Corporation
Atsushi Mitamura	Renesas Electronics Corp.	Tom Farkas	Semtech Corporation
Bob Dunstan	Renesas Electronics Corp.	Ankit Garg	Siemens Industry Software Inc.
Brian Allen	Renesas Electronics Corp.	Ning Dai	Silergy Corp.
Dan Aoki	Renesas Electronics Corp.	Wanfeng Zhang	Silergy Corp.
Fengshuan Zhou	Renesas Electronics Corp.	Kafai Leung	Silicon Laboratories, Inc.
Hajime Nozaki	Renesas Electronics Corp.	Kok Hong Soh	Silicon Laboratories, Inc.
John Carpenter	Renesas Electronics Corp.	Sorin Badiu	Silicon Laboratories, Inc.
Kiichi Muto	Renesas Electronics Corp.	Steven Ghang	Silicon Laboratories, Inc.
Masami Katagiri	Renesas Electronics Corp.	Abhishek Sardeshpande	SiliConch Systems Private Limited
Nobuo Furuya	Renesas Electronics Corp.	Aniket Mathad	SiliConch Systems Private Limited
Patrick Yu	Renesas Electronics Corp.	Chandana N	SiliConch Systems Private Limited
Peter Teng	Renesas Electronics Corp.	Jaswanth Ammineni	SiliConch Systems Private Limited
Philip Leung	Renesas Electronics Corp.	Jinisha Patel	SiliConch Systems Private Limited
Steve Roux	Renesas Electronics Corp.	Kaustubh Kumar	SiliConch Systems Private Limited
Tetsu Sato	Renesas Electronics Corp.	Nitish	SiliConch Systems Private Limited
Toshifumi Yamaoka	Renesas Electronics Corp.	Pavitra Balasubramanian	SiliConch Systems Private Limited
Yimin Chen	Renesas Electronics Corp.	Rakesh Polasa	SiliConch Systems Private Limited
Chunan Kuo	Richtek Technology Corporation	Satish Anand Verkila	SiliConch Systems Private Limited
Heinz Wei	Richtek Technology Corporation	Shubham Paliwal	SiliConch Systems Private Limited
Max Huang	Richtek Technology Corporation	Vishnu Pusuluri	SiliConch Systems Private Limited
TZUHSIEN CHUANG	Richtek Technology Corporation	John Sisto	SMSC
Tatsuya Irisawa	Ricoh Company Ltd.	Ken Gay	SMSC
Akihiro Ono	Rohm Co. Ltd.	Mark Bohm	SMSC
Chris Lin	Rohm Co. Ltd.	Richard Wahler	SMSC

Shannon Cash	SMSC	Javed Ahmad	Texas Instruments
Tim Knowlton	SMSC	Jean Picard	Texas Instruments
William Chiechi	SMSC	John Perry	Texas Instruments
Shigenori Tagami	Sony Corporation	Kasthuri Annamalai	Texas Instruments
Shinichi Hirata	Sony Corporation	Martin Patoka	Texas Instruments
Amanda Hosler	Specwerkz	Mike Campbell	Texas Instruments
Bob Dunstan	Specwerkz	Scott Jackson	Texas Instruments
Brad Saunders	Specwerkz	Shafiuddin Mohammed	Texas Instruments
Diane Lenox	Specwerkz	Srinath Hosur	Texas Instruments
Michael Munn	StarTech.com Ltd.	Steven Tom	Texas Instruments
Fabien Friess	ST-Ericsson	Yoon Lee	Texas Instruments
Giuseppe Platania	ST-Ericsson	Tim Wilhelm	The Silanna Group Pty. Ltd.
Jean-Francois Gatto	ST-Ericsson	Tod Wolf	The Silanna Group Pty. Ltd.
Milan Stamenkovic	ST-Ericsson	Chris Yokum	Total Phase
Nicolas Florenchie	ST-Ericsson	Dylan Su	UL LLC
Patrizia Milazzo	ST-Ericsson	Eric Wall	UL LLC
Christophe Cochard	STMicroelectronics	Jason Smith	UL LLC
Christophe Lorin	STMicroelectronics	Terry Kao	UL LLC
Filippo Bonaccorso	STMicroelectronics	Steven Chen	Unigraf OY
Jessy Guilbot	STMicroelectronics	Topi Lampiranta	Unigraf OY
Joel Huloux	STMicroelectronics	Brad Cox	Ventev Mobile
John Bloomfield	STMicroelectronics	Colin Vose	Ventev Mobile
Massimo Panzica	STMicroelectronics	Dydron Lin	VIA Technologies, Inc.
Meriem Mersel	STMicroelectronics	Fong-Jim Wang	VIA Technologies, Inc.
Nathalie Ballot	STMicroelectronics	Jay Tseng	VIA Technologies, Inc.
Pascal Legrand	STMicroelectronics	Rex Chang	VIA Technologies, Inc.
Patrizia Milazzo	STMicroelectronics	Terrance Shih	VIA Technologies, Inc.
Richard O'Connor	STMicroelectronics	Ho Wen Tsai	Weltrend Semiconductor
Morten Christiansen	Synopsys, Inc.	Hung Chiang	Weltrend Semiconductor
Nivin George	Synopsys, Inc.	Jeng Cheng Liu	Weltrend Semiconductor
Prishkit Abrol	Synopsys, Inc.	Priscilla Lee	Weltrend Semiconductor
Zongyao Wen	Synopsys, Inc.	Wayne Lo	Weltrend Semiconductor
Joan Marrinan	Tektronix	Charles Neumann	Western Digital Technologies, Inc.
Kimberley McKay	Teledyne-LeCroy	Curtis Stevens	Western Digital Technologies, Inc.
Matthew Dunn	Teledyne-LeCroy	John Maroney	Western Digital Technologies, Inc.
Tony Minchell	Teledyne-LeCroy	Joe O'Brien	Wilder Technologies
Anand Dabak	Texas Instruments	Will Miller	Wilder Technologies
Annamalai Kasthuri	Texas Instruments	Juejia Zhou	Xiaomi Communications Co., Ltd.
Bill Waters	Texas Instruments	Xiaoxing Yang	Xiaomi Communications Co., Ltd.
Bing Lu	Texas Instruments	Liu Qiong	Zhuhai Smartware Technology Co., Ltd.
Deric Waters	Texas Instruments	Long Zhang	Zhuhai Smartware Technology Co., Ltd.
Grant Ley	Texas Instruments	Yuanchao Liang	Zhuhai Smartware Technology Co., Ltd.
Gregory Watkins	Texas Instruments		
Ingolf Frank	Texas Instruments		
Ivo Huber	Texas Instruments		

## Revision History

Revision	Version	Comments	Issue Date
1.0	1.0	Initial release Revision 1.0	5 July, 2012
1.0	1.1	Including errata through 31-October-2012	31 October 2012
1.0	1.2	Including errata through 26-June-2013	26 June, 2013
1.0	1.3	Including errata through 11-March-2014	11 March 2014
2.0	1.0	Initial release Revision 2.0	11 August 2014
2.0	1.1	Including errata through 7-May 2015	7 May 2015
2.0	1.2	Including errata through 25-March-2016	25 March 2016
2.0	1.3	Including errata through 11-January-2017	11 January 2017
3.0	1.0	Initial release Revision 3.0	11 December 2015
3.0	1.0a	Including errata through 25-March-2016	25 March 2016
3.0	1.1	Including errata through 12-January-2017	12 January 2017
3.0	1.2	Including errata through 21-June-2018	21 June 2018
3.0	2.0	Including errata through 29-August-2019	29 August 2019
3.1	1.0	Including errata through May 2021	May 2021
3.1	1.1	Including errata through July 2021 This version incorporates the following ECNs: <ul style="list-style-type: none"> <li>EPR Clarifications</li> <li>Define AMS starting point</li> </ul>	July 2021
3.1	1.2	Including errata through October 2021 This version incorporates the following ECNs: <ul style="list-style-type: none"> <li>Clarify use of Retries</li> <li>Battery Capabilities</li> <li>FRS timing problem</li> <li>PPS power rule clarifications</li> <li>Peak current support for EPR AVS APDO</li> </ul>	October 2021
3.1	1.3	This version incorporates the following ECNs: <ul style="list-style-type: none"> <li>Robust EPR Source Operation</li> <li>EPR Source Caps Editorial</li> <li>SRC PPS behavior in low current request</li> <li>Enter USB</li> </ul>	January 2022

3.1	1.4	<p>Editorial changes</p> <p>This version incorporates the following ECNs:</p> <ul style="list-style-type: none"> <li>• Capabilities Mismatch Update</li> <li>• Chunking Timing Issue</li> <li>• OT Mitigation</li> </ul>	April 2022
3.1	1.5	<p>Editorial changes</p> <p>This version incorporates the following ECNs:</p> <ul style="list-style-type: none"> <li>• Timer Description Corrections</li> <li>• Change Source_Info Requirements</li> <li>• AMS Update</li> </ul>	July 2022
3.1	1.6	<p>Editorial changes</p> <p>This version incorporates the following ECNs:</p> <ul style="list-style-type: none"> <li>• USB4® V2 Updates</li> <li>• Data Reset Issues</li> <li>• Increase tSenderResponse</li> <li>• PPS Power Limit Bit Update</li> <li>• Support for Asymmetric Mode</li> <li>• Timer Description Corrections Revisited</li> </ul>	October 2022
3.1	1.7	<p>Editorial Changes</p> <p>This version incorporates the following ECNs:</p> <ul style="list-style-type: none"> <li>• Data Reset Invalid Reject Handling</li> <li>• Source request</li> <li>• Source Transition</li> <li>• EPR Entry</li> </ul>	January 2023
3.1	1.8	<p>Editorial Changes</p> <p>This version incorporates the following ECNs:</p> <ul style="list-style-type: none"> <li>• Slew rate exemption for Power Role Swap.</li> <li>• EUDO cable speed clarification.</li> <li>• Update to PPS Requirements.</li> <li>• Deprecate Interruptibility.</li> <li>• Section 7.3 restructure and update.</li> </ul>	April 2023

3.2	1.0	<p>Editorial Changes</p> <p>This version incorporates the following ECNs:</p> <ul style="list-style-type: none"><li>• VDM use conditions</li><li>• tTypeCSinkWaitCap</li><li>• tFirstSourceCap clarification</li><li>• Hard Reset clarification</li><li>• Unrecognized Country Code</li><li>• EPR Entry Process</li><li>• SPR AVS Definition</li><li>• EPR Power Rules Clarifications</li></ul>	October 2023.
-----	-----	---	---------------

# Table of Contents

## Contents

- Universal Serial Bus .....2
- Power Delivery Specification.....4
- LIMITED COPYRIGHT LICENSE .....5
- INTELLECTUAL PROPERTY DISCLAIMER .....5
- Editors .....6
- Contributors .....6
- Revision History .....13
- Table of Contents.....16
- List of Tables .....23
- List of Figures .....30
- 1. Introduction.....38**
  - 1.1 Overview .....38
  - 1.2 Purpose.....39
    - 1.2.1 Scope.....40
  - 1.3 Section Overview.....40
  - 1.4 Conventions .....41
    - 1.4.1 Precedence .....41
    - 1.4.2 Keywords .....41
    - 1.4.3 Numbering .....42
  - 1.5 Related Documents.....43
  - 1.6 Terms and Abbreviations.....45
  - 1.7 Parameter Values.....55
  - 1.8 Changes from Revision 3.0 .....55
  - 1.9 Compatibility with Revision 2.0.....55
- 2. Overview .....56**
  - 2.1 Introduction.....56
    - 2.1.1 Power Delivery Source Operational Contracts.....56
    - 2.1.2 Power Delivery Contracts .....56
    - 2.1.3 Other Uses for Power Delivery .....57
  - 2.2 Compatibility with Revision 2.0.....58
  - 2.3 USB Power Delivery Capable Devices.....58
  - 2.4 SOP\* Communication .....60
    - 2.4.1 Introduction.....60
    - 2.4.2 SOP\* Collision Avoidance.....60
    - 2.4.3 SOP Communication.....60
    - 2.4.4 SOP'/SOP'' Communication with Cable Plugs.....60
  - 2.5 Operational Overview .....62
    - 2.5.1 Source Operation.....62
    - 2.5.2 Sink Operation .....65

- 2.5.3 Cable Plugs ..... 68
- 2.6 Architectural Overview..... 69
  - 2.6.1 Policy..... 72
  - 2.6.2 Message Formation and Transmission ..... 73
  - 2.6.3 Collision Avoidance ..... 74
  - 2.6.4 Power supply..... 74
  - 2.6.5 DFP/UFP..... 75
  - 2.6.6 Cable and Connectors..... 75
  - 2.6.7 Interactions between Non-PD, BC, and PD devices..... 75
  - 2.6.8 Power Rules ..... 76
- 2.7 Extended Power Range (EPR) Operation ..... 77
- 2.8 Charging Models ..... 79
  - 2.8.1 Fixed Voltage Charging Models ..... 79
  - 2.8.2 Programmable Power Supply (PPS) Charging Models ..... 79
  - 2.8.3 Adjustable Voltage Supply (AVS) Charging Models..... 80
- 3. USB Type-A and USB Type-B Cable Assemblies and Connectors ..... 81**
- 4. Electrical Requirements ..... 82**
  - 4.1 Interoperability with other USB Specifications ..... 82
  - 4.2 Dead Battery Detection / Unpowered Port Detection ..... 82
  - 4.3 Cable IR Ground Drop (IR Drop) ..... 82
  - 4.4 Cable Type Detection ..... 82
- 5. Physical Layer..... 84**
  - 5.1 Physical Layer Overview ..... 84
  - 5.2 Physical Layer Functions ..... 84
  - 5.3 Symbol Encoding..... 85
  - 5.4 Ordered Sets..... 86
  - 5.5 Transmitted Bit Ordering ..... 88
  - 5.6 Packet Format..... 89
    - 5.6.1 Packet Framing..... 89
    - 5.6.2 CRC..... 92
    - 5.6.3 Packet Detection Errors..... 94
    - 5.6.4 Hard Reset ..... 94
    - 5.6.5 Cable Reset..... 95
  - 5.7 Collision Avoidance ..... 96
  - 5.8 Biphase Mark Coding (BMC) Signaling Scheme..... 97
    - 5.8.1 Encoding and signaling..... 97
    - 5.8.2 Transmit and Receive Masks ..... 101
    - 5.8.3 Transmitter Load Model..... 109
    - 5.8.4 BMC Common specifications..... 111
    - 5.8.5 BMC Transmitter Specifications ..... 111
    - 5.8.6 BMC Receiver Specifications ..... 116
  - 5.9 Built in Self-Test (BIST)..... 119
    - 5.9.1 BIST Carrier Mode..... 119
    - 5.9.2 BIST Test Data..... 119
- 6. Protocol Layer ..... 120**
  - 6.1 Overview ..... 120
  - 6.2 Messages ..... 120
    - 6.2.1 Message Construction ..... 120
  - 6.3 Control Message..... 134

6.3.1	GoodCRC Message .....	135
6.3.2	GotoMin Message .....	135
6.3.3	Accept Message .....	136
6.3.4	Reject Message .....	136
6.3.5	Ping Message .....	137
6.3.6	PS_RDY Message .....	137
6.3.7	Get_Source_Cap Message.....	137
6.3.8	Get_Sink_Cap Message.....	137
6.3.9	DR_Swap Message .....	138
6.3.10	PR_Swap Message.....	138
6.3.11	VCONN_Swap Message.....	139
6.3.12	Wait Message.....	140
6.3.13	Soft Reset Message.....	141
6.3.14	Data_Reset Message .....	142
6.3.15	Data_Reset_Complete Message.....	142
6.3.16	Not_Supported Message .....	143
6.3.17	Get_Source_Cap_Extended Message.....	143
6.3.18	Get_Status Message.....	143
6.3.19	FR_Swap Message.....	143
6.3.20	Get_PPS_Status.....	144
6.3.21	Get_Country_Codes .....	144
6.3.22	Get_Sink_Cap_Extended Message.....	144
6.3.23	Get_Source_Info Message .....	144
6.3.24	Get_Revision Message.....	144
6.4	Data Message.....	145
6.4.1	Capabilities Message .....	146
6.4.2	Request Message .....	162
6.4.3	BIST Message .....	169
6.4.4	Vendor Defined Message.....	172
6.4.5	Battery_Status Message .....	213
6.4.6	Alert Message.....	215
6.4.7	Get_Country_Info Message .....	219
6.4.8	Enter_USB Message .....	220
6.4.9	EPR_Request Message.....	223
6.4.10	EPR_Mode Message .....	224
6.4.11	Source_Info Message.....	231
6.4.12	Revision Message .....	233
6.5	Extended Message .....	234
6.5.1	Source_Capabilities_Extended Message .....	236
6.5.2	Status Message .....	242
6.5.3	Get_Battery_Cap Message .....	248
6.5.4	Get_Battery_Status Message .....	249
6.5.5	Battery_Capabilities Message .....	250
6.5.6	Get_Manufacturer_Info Message.....	252
6.5.7	Manufacturer_Info Message.....	253
6.5.8	Security Messages .....	255
6.5.9	Firmware Update Messages.....	257
6.5.10	PPS_Status Message.....	258
6.5.11	Country_Codes Message.....	260
6.5.12	Country_Info Message .....	261
6.5.13	Sink_Capabilities_Extended Message .....	262

6.5.14	Extended_Control Message .....	268
6.5.15	EPR Capabilities Message .....	270
6.5.16	Vendor_Defined_Extended Message.....	272
6.6	Timers .....	274
6.6.1	CRCReceiveTimer .....	274
6.6.2	SenderResponseTimer .....	274
6.6.3	Capability Timers .....	275
6.6.4	Wait Timers and Times.....	277
6.6.5	Power Supply Timers .....	278
6.6.6	NoResponseTimer.....	280
6.6.7	BIST Timers .....	281
6.6.8	Power Role Swap Timers .....	282
6.6.9	Soft Reset Timers.....	283
6.6.10	Data Reset Timers .....	284
6.6.11	Hard Reset Timers .....	285
6.6.12	Structured VDM Timers.....	286
6.6.13	VCONN Timers .....	288
6.6.14	tCableMessage .....	288
6.6.15	DiscoverIdentityTimer .....	288
6.6.16	Collision Avoidance Timers .....	289
6.6.17	Fast Role Swap Timers .....	290
6.6.18	Chunking Timers .....	291
6.6.19	Programmable Power Supply Timers .....	293
6.6.20	tEnterUSB .....	293
6.6.21	EPR Timers.....	294
6.6.22	Time Values and Timers.....	295
6.7	Counters .....	299
6.7.1	MessageID Counter.....	299
6.7.2	Retry Counter .....	300
6.7.3	Hard Reset Counter .....	300
6.7.4	Capabilities Counter.....	300
6.7.5	Discover Identity Counter .....	300
6.7.6	VDMBusyCounter .....	300
6.7.7	Counter Values and Counters.....	301
6.8	Reset.....	302
6.8.1	Soft Reset and Protocol Error .....	302
6.8.2	Data Reset.....	304
6.8.3	Hard Reset .....	304
6.8.4	Cable Reset.....	305
6.9	Accept, Reject and Wait .....	306
6.10	Collision Avoidance .....	306
6.11	Message Discarding.....	306
6.12	State behavior .....	308
6.12.1	Introduction to state diagrams used in Chapter 6 .....	308
6.12.2	State Operation.....	309
6.12.3	List of Protocol Layer States .....	331
6.13	Message Applicability.....	333
6.13.1	Applicability of Control Messages.....	334
6.13.2	Applicability of Data Messages.....	336
6.13.3	Applicability of Extended Messages.....	338
6.13.4	Applicability of Extended Control Messages .....	340

6.13.5	Applicability of Structured VDM Commands .....	341
6.13.6	Applicability of Reset Signaling.....	342
6.13.7	Applicability of Fast Role Swap signal.....	342
6.14	Value Parameters.....	343
<b>7.</b>	<b>Power Supply .....</b>	<b>344</b>
7.1	Source Requirements .....	344
7.1.1	Behavioral Aspects .....	344
7.1.2	Source Bulk Capacitance .....	344
7.1.3	Types of Sources .....	345
7.1.4	Source Transitions .....	346
7.1.5	Response to Hard Resets.....	359
7.1.6	Changing the Output Power Capability .....	360
7.1.7	Robust Source Operation .....	361
7.1.8	Output Voltage Tolerance and Range.....	363
7.1.9	Charging and Discharging the Bulk Capacitance on $V_{BUS}$ .....	364
7.1.10	Swap Standby for Sources .....	364
7.1.11	Source Peak Current Operation .....	365
7.1.12	Source Capabilities Extended Parameters .....	366
7.1.13	Fast Role Swap.....	369
7.1.14	Non-application of $V_{BUS}$ Slew Rate Limits.....	371
7.1.15	VCONN Power Cycle.....	372
7.2	Sink Requirements.....	374
7.2.1	Behavioral Aspects .....	374
7.2.2	Sink Bulk Capacitance .....	374
7.2.3	Sink Standby.....	375
7.2.4	Suspend Power Consumption.....	375
7.2.5	Zero Negotiated Current .....	375
7.2.6	Transient Load Behavior.....	375
7.2.7	Swap Standby for Sinks.....	376
7.2.8	Sink Peak Current Operation.....	376
7.2.9	Robust Sink Operation .....	377
7.2.10	Fast Role Swap .....	379
7.3	Transitions .....	380
7.3.1	Transitions caused by a Request Message .....	382
7.3.2	Transitions Caused by Power Role Swap.....	418
7.3.3	Transitions Caused by GotoMin .....	424
7.3.4	Transitions Caused by Hard Reset.....	426
7.3.5	Transitions Caused by Fast Role Swap.....	430
7.4	Electrical Parameters .....	433
7.4.1	Source Electrical Parameters .....	433
7.4.2	Sink Electrical Parameters .....	441
7.4.3	Common Electrical Parameters.....	443
<b>8.</b>	<b>Device Policy .....</b>	<b>444</b>
8.1	Overview .....	444
8.2	Device Policy Manager .....	444
8.2.1	Capabilities.....	445
8.2.2	System Policy.....	446
8.2.3	Control of Source/Sink.....	446
8.2.4	Cable Detection .....	446
8.2.5	Managing Power Requirements.....	447

- 8.2.6 Use of “Unconstrained Power” bit with Batteries and AC supplies.....449
- 8.2.7 Interface to the Policy Engine .....451
- 8.3 Policy Engine..... 453
  - 8.3.1 Introduction.....453
  - 8.3.2 Atomic Message Sequence Diagrams.....453
  - 8.3.3 State Diagrams.....865
- 9. States and Status Reporting .....1021**
  - 9.1 Overview .....1021
    - 9.1.1 PDUSB Device and Hub Requirements .....1023
    - 9.1.2 Mapping to USB Device States .....1024
    - 9.1.3 PD Software Stack .....1026
    - 9.1.4 PDUSB Device Enumeration .....1027
  - 9.2 PD Specific Descriptors .....1029
    - 9.2.1 USB Power Delivery Capability Descriptor .....1029
    - 9.2.2 Battery Info Capability Descriptor .....1031
    - 9.2.3 PD Consumer Port Capability Descriptor .....1032
    - 9.2.4 PD Provider Port Capability Descriptor .....1033
  - 9.3 PD Specific Requests and Events .....1034
    - 9.3.1 PD Specific Requests .....1034
  - 9.4 PDUSB Hub and PDUSB Peripheral Device Requests .....1035
    - 9.4.1 GetBatteryStatus.....1035
    - 9.4.2 SetPDFeature.....1036
- 10. Power Rules.....1039**
  - 10.1 Introduction.....1039
  - 10.2 Source Power Rules.....1039
    - 10.2.1 Source Power Rule Considerations .....1039
    - 10.2.2 Normative Voltages and Currents .....1041
    - 10.2.3 Optional Voltages/Currents.....1051
    - 10.2.4 Power sharing between ports.....1060
  - 10.3 Sink Power Rules.....1061
    - 10.3.1 Sink Power Rule Considerations.....1061
    - 10.3.2 Normative Sink Rules .....1061
- A. CRC calculation .....1063**
  - A.1 C code example.....1063
- B. PD Message Sequence Examples .....1066**
  - B.1 External power is supplied downstream.....1066
  - B.2 External power is supplied upstream .....1070
  - B.3 Giving back power .....1076
- C. VDM Command Examples.....1086**
  - C.1 Discover Identity Example .....1086
    - C.1.1 Discover Identity Command request.....1086
    - C.1.2 Discover Identity Command response – Active Cable.....1087
    - C.1.3 Discover Identity Command response – Hub. ....1089
  - C.2 Discover SVIDs Example .....1090
    - C.2.1 Discover SVIDs Command request .....1090
    - C.2.2 Discover SVIDs Command response .....1091
  - C.3 Discover Modes Example .....1092
    - C.3.1 Discover Modes Command request.....1092
    - C.3.2 Discover Modes Command response.....1093

- C.4 Enter Mode Example.....1094
  - C.4.1 Enter Mode Command request .....1094
  - C.4.2 Enter Mode Command response .....1095
  - C.4.3 Enter Mode Command request with additional VDO.....1096
- C.5 Exit Mode Example.....1097
  - C.5.1 Exit Mode Command request.....1097
  - C.5.2 Exit Mode Command response.....1098
- C.6 Attention Example .....1099
  - C.6.1 Attention Command request.....1099
  - C.6.2 Attention Command request with additional VDO.....1100
- D. BMC Receiver Design Examples..... 1101**
- D.1 Finite Difference Scheme .....1101
  - D.1.1 Sample Circuitry .....1101
  - D.1.2 Theory .....1101
  - D.1.3 Data Recovery .....1103
  - D.1.4 Noise Zone and Detection Zone .....1104
- D.2 Subtraction Scheme.....1105
  - D.2.1 Sample Circuitry .....1105
  - D.2.2 Output of Each Circuit Block .....1105
  - D.2.3 Subtractor Output at Power Source and Power Sink.....1105
  - D.2.4 Noise Zone and Detection Zone .....1106
- E. FRS System Level Example..... 1107**
- E.1 Overview .....1107
- E.2 FRS Initial Setup.....1110
- E.3 FRS Process.....1113

## List of Tables

Table 1.1 Section Overview .....	40
Table 1.2 Document References .....	43
Table 1.3 Terms and Abbreviations .....	45
Table 2.1 “Fixed Voltage Power Ranges” .....	79
Table 2.2 “PPS Voltage Power Ranges” .....	80
Table 2.3 “Adjustable Voltage Supply Voltage Ranges” .....	80
Table 5.1 “4b5b Symbol Encoding Table” .....	85
Table 5.2 “Ordered Sets” .....	86
Table 5.3 “Validation of Ordered Sets” .....	87
Table 5.4 “Data Size” .....	88
Table 5.5 “SOP ordered set” .....	89
Table 5.6 “SOP’ ordered set” .....	90
Table 5.7 “SOP” ordered set” .....	90
Table 5.8 “SOP’_Debug ordered set” .....	91
Table 5.9 “SOP”_Debug ordered set” .....	91
Table 5.10 “CRC-32 Mapping” .....	93
Table 5.11 “Hard Reset ordered set” .....	94
Table 5.12 “Cable Reset ordered set” .....	95
Table 5.13 “R <sub>p</sub> values used for Collision Avoidance” .....	96
Table 5.14 “BMC Tx Mask Definition, X Values” .....	102
Table 5.15 “BMC Tx Mask Definition, Y Values” .....	103
Table 5.16 “BMC Rx Mask Definition” .....	108
Table 5.17 “BMC Common Normative Requirements” .....	111
Table 5.18 “BMC Transmitter Normative Requirements” .....	112
Table 5.19 “BMC Receiver Normative Requirements” .....	116
Table 6.1 “Message Header” .....	122
Table 6.2 “Revision Interoperability during an Explicit Contract” .....	125
Table 6.3 “Extended Message Header” .....	126
Table 6.4 “Use of Unchunked Message Supported bit” .....	128
Table 6.5 “Control Message Types” .....	134
Table 6.6 “Data Message Types” .....	145
Table 6.7 “Power Data Object” .....	147
Table 6.8 “Augmented Power Data Object” .....	147
Table 6.9 “Fixed Supply PDO – Source” .....	150
Table 6.10 “Fixed Power Source Peak Current Capability” .....	152
Table 6.11 “Variable Supply (non-Battery) PDO – Source” .....	153
Table 6.12 “Battery Supply PDO – Source” .....	153
Table 6.13 “SPR Programmable Power Supply APDO – Source” .....	154
Table 6.14 “EPR Adjustable Voltage Supply APDO – Source “ .....	154
Table 6.15 “EPR AVS Power Source Peak Current Capability” .....	155
Table 6.16 “SPR Adjustable Voltage Supply APDO – Source” .....	156
Table 6.17 “Fixed Supply PDO – Sink” .....	158
Table 6.18 “Variable Supply (non-Battery) PDO – Sink” .....	159
Table 6.19 “Battery Supply PDO – Sink” .....	160
Table 6.20 “Programmable Power Supply APDO – Sink” .....	160
Table 6.21 “EPR Adjustable Voltage Supply APDO – Sink” .....	161
Table 6.22 “Fixed and Variable Request Data Object” .....	162
Table 6.23 “Fixed and Variable Request Data Object with GiveBack Support” .....	163
Table 6.24 “Battery Request Data Object” .....	163

Table 6.25 “Battery Request Data Object with GiveBack Support” .....	163
Table 6.26 “PPS Request Data Object” .....	164
Table 6.27 “AVS Request Data Object” .....	164
Table 6.28 “BIST Data Object” .....	170
Table 6.29 “Unstructured VDM Header” .....	173
Table 6.30 “Structured VDM Header” .....	175
Table 6.31 “Structured VDM Commands” .....	176
Table 6.32 “SVID Values” .....	176
Table 6.33 “Commands and Responses” .....	179
Table 6.34 “ID Header VDO” .....	182
Table 6.35 “Product Types (UFP)” .....	183
Table 6.36 “Product Types (Cable Plug/VPD)” .....	183
Table 6.37 “Product Types (DFP)” .....	184
Table 6.38 “Cert Stat VDO” .....	184
Table 6.39 “Product VDO” .....	185
Table 6.40 “UFP VDO” .....	186
Table 6.41 “DFP VDO” .....	188
Table 6.42 “Passive Cable VDO” .....	190
Table 6.43 “Active Cable VDO 1” .....	193
Table 6.44 “Active Cable VDO 2” .....	195
Table 6.45 “VPD VDO” .....	199
Table 6.46 “Discover SVIDs Responder VDO” .....	201
Table 6.47 “Battery Status Data Object (BSDO)” .....	213
Table 6.48 “Alert Data Object (ADO)” .....	216
Table 6.49 “Country Code Data Object (CCDO)” .....	219
Table 6.50 “Enter_USB Data Object (EUDO)” .....	221
Table 6.51 “EPR Mode Data Object (EPRMDO)” .....	225
Table 6.52 “Source_Info Data Object (SIDO)” .....	231
Table 6.53 “Revision Message Data Object (RMDO)” .....	233
Table 6.54 “Extended Message Types” .....	235
Table 6.55 “Source Capabilities Extended Data Block (SCEDB)” .....	236
Table 6.56 “SOP Status Data Block (SDB)” .....	243
Table 6.57 “SOP/SOP” Status Data Block (SDB)” .....	247
Table 6.58 “Get Battery Cap Data Block (GBCDB)” .....	248
Table 6.59 “Get Battery Status Data Block (GBSDB)” .....	249
Table 6.60 “Battery Capability Data Block (BCDB)” .....	250
Table 6.61 “Get Manufacturer Info Data Block (GMIDB)” .....	252
Table 6.62 “Manufacturer Info Data Block (MIDB)” .....	253
Table 6.63 “PPS Status Data Block (PPSSDB)” .....	258
Table 6.64 “Country Codes Data Block (CCDB)” .....	260
Table 6.65 “Country Info Data Block (CIDB)” .....	261
Table 6.66 “Sink Capabilities Extended Data Block (SKEDB)” .....	263
Table 6.67 “Extended Control Data Block (ECDB)” .....	268
Table 6.68 “Extended Control Message Types” .....	268
Table 6.69 “Time Values” .....	296
Table 6.70 “Timers” .....	298
Table 6.71 “Counter parameters” .....	301
Table 6.72 “Counters” .....	301
Table 6.73 “Response to an incoming Message (except VDM)” .....	303
Table 6.74 “Response to an incoming VDM” .....	303
Table 6.75 “Message discarding” .....	307

Table 6.76 “Protocol Layer States” .....	331
Table 6.77 “Message Applicability Abbreviations” .....	333
Table 6.78 “Applicability of Control Messages” .....	334
Table 6.79 “Applicability of Data Messages” .....	336
Table 6.80 “Applicability of Extended Messages” .....	338
Table 6.81 “Applicability of Extended Control Messages” .....	340
Table 6.82 “Applicability of Structured VDM Commands” .....	341
Table 6.83 “Applicability of Reset Signaling” .....	342
Table 6.84 “Applicability of Fast Role Swap signal” .....	342
Table 6.85 “Value Parameters” .....	343
Table 7.1 “Sequence Description for Changing the Source to another (A)PDO” .....	384
Table 7.2 “Sequence Description for Increasing the Voltage” .....	386
Table 7.3 “Sequence Diagram for Increasing the Voltage and Current” .....	388
Table 7.4 “Sequence Description for Increasing the Voltage and Decreasing the Current” .....	390
Table 7.5 “Sequence Description for Decreasing the Voltage and Increasing the Current” .....	392
Table 7.6 “Sequence Description for Decreasing the Voltage” .....	394
Table 7.7 “Sequence Description for Decreasing the Voltage and the Current” .....	396
Table 7.8 “Sequence Description for no change in Current or Voltage” .....	398
Table 7.9 “Sequence Description for Increasing the Current” .....	400
Table 7.10 “Sequence Description for Decreasing the Current” .....	402
Table 7.11 “Sequence Description for Increasing the Programmable Power Supply Voltage” .....	404
Table 7.12 “Sequence Description for Decreasing the Programmable Power Supply Voltage” .....	406
Table 7.13 “Sequence Description for increasing the Current in PPS mode” .....	408
Table 7.14 “Sequence Description for decreasing the Current in PPS mode” .....	410
Table 7.15 “Sequence Description for no change in Current or Voltage in PPS mode” .....	412
Table 7.16 “Sequence Description for Increasing the Adjustable Voltage Supply Voltage” .....	414
Table 7.17 “Sequence Description for Decreasing the Adjustable Voltage Supply Voltage” .....	416
Table 7.18 “Sequence Description for no change in Current or Voltage in AVS mode” .....	417
Table 7.19 “Sequence Description for a Sink Requested Power Role Swap” .....	419
Table 7.20 “Sequence Description for a Source Requested Power Role Swap” .....	422
Table 7.21 “Sequence Description for a GotoMin Current Decrease” .....	425
Table 7.22 “Sequence Description for a Source Initiated Hard Reset” .....	427
Table 7.23 “Sequence Description for a Sink Initiated Hard Reset” .....	429
Table 7.24 “Sequence Description for Fast Role Swap” .....	431
Table 7.25 “Source Electrical Parameters” .....	433
Table 7.26 “Sink Electrical Parameters” .....	441
Table 7.27 “Common Source/Sink Electrical Parameters” .....	443
Table 8.1 “Basic Message Flow” .....	454
Table 8.2 “Potential issues in Basic Message Flow” .....	456
Table 8.3 “Basic Message Flow with CRC failure” .....	458
Table 8.4 “Atomic Message Sequences” .....	460
Table 8.5 “AMS: Power Negotiation (SPR)” .....	461
Table 8.6 “AMS: Power Negotiation (EPR)” .....	462
Table 8.7 “AMS: Unsupported Message” .....	463
Table 8.8 “AMS: Ping” .....	464
Table 8.9 “AMS: Soft Reset” .....	464
Table 8.10 “AMS: Data Reset” .....	465
Table 8.11 “AMS: Power Role Swap” .....	466
Table 8.12 “AMS: Fast Role Swap” .....	466
Table 8.13 “AMS: Data Role Swap” .....	467
Table 8.14 “AMS: VCONN Swap” .....	468

Table 8.15 “AMS: Alert” .....	468
Table 8.16 “AMS: Status” .....	469
Table 8.17 “AMS: Source/Sink Capabilities (SPR)” .....	470
Table 8.18 “AMS: Source/Sink Capabilities (EPR)” .....	471
Table 8.19 “AMS: Extended Capabilities” .....	472
Table 8.20 “AMS: Battery Capabilities” .....	472
Table 8.21 “AMS: Manufacturer Information” .....	473
Table 8.22 “AMS: Country Codes” .....	473
Table 8.23 “AMS: Country Information” .....	474
Table 8.24 “AMS: Revision Information” .....	474
Table 8.25 “AMS: Source Information” .....	474
Table 8.26 “AMS: Security” .....	475
Table 8.27 “AMS: Firmware Update” .....	475
Table 8.28 “AMS: Structured VDM” .....	476
Table 8.29 “AMS: Built-In Self-Test (BIST)” .....	477
Table 8.30 “AMS: Enter USB” .....	477
Table 8.31 “AMS: Unstructured VDM” .....	477
Table 8.32 “AMS: Hard Reset” .....	478
Table 8.33 “Steps for a successful Power Negotiation” .....	481
Table 8.34 “Steps for a rejected Power Negotiation” .....	485
Table 8.35 “Steps for a Wait response to a Power Negotiation” .....	488
Table 8.36 “Steps for a GotoMin Negotiation” .....	491
Table 8.37 “Steps for SPR PPS Keep Alive” .....	494
Table 8.38 “Steps for SPR Sink Makes Request (Accept)” .....	498
Table 8.39 “Steps for SPR Sink Makes Request (Reject)” .....	501
Table 8.40 “Steps for SPR Sink Makes Request (Wait)” .....	504
Table 8.41 “Steps for Entering EPR Mode (Success)” .....	507
Table 8.42 “Steps for Entering EPR Mode (Failure due to non-EPR cable)” .....	510
Table 8.43 “Steps for Entering EPR Mode (Failure of VCONN Swap)” .....	513
Table 8.44 “Steps for a successful EPR Power Negotiation” .....	517
Table 8.45 “Steps for a Rejected EPR Power Negotiation” .....	521
Table 8.46 “Steps for a Wait response to an EPR Power Negotiation” .....	524
Table 8.47 “Steps for EPR Keep Alive” .....	527
Table 8.48 “Steps for Exiting EPR Mode (Sink Initiated)” .....	530
Table 8.49 “Steps for Exiting EPR Mode (Source Initiated)” .....	533
Table 8.50 “Steps for EPR Sink Makes Request (Accept)” .....	536
Table 8.51 “Steps for EPR Sink Makes Request (Reject)” .....	539
Table 8.52 “Steps for EPR Sink Makes Request (Wait)” .....	542
Table 8.53 “Steps for an Unsupported Message” .....	545
Table 8.54 “Steps for a Ping” .....	548
Table 8.55 “Steps for a Soft Reset” .....	550
Table 8.56 “Steps for a DFP Initiated Data Reset where the DFP is the VCONN Source” .....	553
Table 8.57 “Steps for a DFP Receiving a Data Reset where the DFP is the VCONN Source” .....	557
Table 8.58 “Steps for a DFP Initiated Data Reset where the UFP is the VCONN Source” .....	561
Table 8.59 “Steps for a DFP Receiving a Data Reset where the UFP is the VCONN Source” .....	566
Table 8.60 “Steps for Source initiated Hard Reset” .....	571
Table 8.61 “Steps for Sink initiated Hard Reset” .....	574
Table 8.62 “Steps for Source initiated Hard Reset – Sink long reset” .....	577
Table 8.63 “Steps for a Successful Source Initiated Power Role Swap Sequence” .....	581
Table 8.64 “Steps for a Rejected Source Initiated Power Role Swap Sequence” .....	585
Table 8.65 “Steps for a Source Initiated Power Role Swap with Wait Sequence” .....	588

Table 8.66 “Steps for a Successful Sink Initiated Power Role Swap Sequence” .....592

Table 8.67 “Steps for a Rejected Sink Initiated Power Role Swap Sequence” .....596

Table 8.68 “Steps for a Sink Initiated Power Role Swap with Wait Sequence” .....599

Table 8.69 “Steps for a Successful Fast Role Swap Sequence” .....603

Table 8.70 “Steps for Data Role Swap, UFP operating as Sink initiates” .....607

Table 8.71 “Steps for Rejected Data Role Swap, UFP operating as Sink initiates” .....610

Table 8.72 “Steps for Data Role Swap with Wait, UFP operating as Sink initiates” .....613

Table 8.73 “Steps for Data Role Swap, UFP operating as Source initiates” .....616

Table 8.74 “Steps for Rejected Data Role Swap, UFP operating as Source initiates” .....619

Table 8.75 “Steps for Data Role Swap with Wait, UFP operating as Source initiates” .....622

Table 8.76 “Steps for Data Role Swap, DFP operating as Source initiates” .....625

Table 8.77 “Steps for Rejected Data Role Swap, DFP operating as Source initiates” .....628

Table 8.78 “Steps for Data Role Swap with Wait, DFP operating as Source initiates” .....631

Table 8.79 “Steps for Data Role Swap, DFP operating as Sink initiates” .....634

Table 8.80 “Steps for Rejected Data Role Swap, DFP operating as Sink initiates” .....637

Table 8.81 “Steps for Data Role Swap with Wait, DFP operating as Sink initiates” .....640

Table 8.82 “Steps for Source to Sink VCONN Source Swap” .....643

Table 8.83 “Steps for Rejected VCONN Source Swap” .....646

Table 8.84 “Steps for VCONN Source Swap with Wait” .....649

Table 8.85 “Steps for VCONN Source Swap, Initiated by non- VCONN Source” .....652

Table 8.86 “Steps for Rejected VCONN Source Swap, Initiated by non- VCONN Source” .....655

Table 8.87 “Steps for VCONN Source Swap with Wait, Initiated by non- VCONN Source” .....658

Table 8.88 “Steps for Source Alert to Sink” .....661

Table 8.89 “Steps for Sink Alert to Source” .....663

Table 8.90 “Steps for a Sink getting Source Status Sequence” .....665

Table 8.91 “Steps for a Source getting Sink Status Sequence” .....668

Table 8.92 “Steps for a VCONN Source getting Cable Plug Status Sequence” .....671

Table 8.93 “Steps for a Sink getting Source PPS status Sequence” .....674

Table 8.94 “Steps for a Sink getting Source Capabilities Sequence” .....677

Table 8.95 “Steps for a Dual-Role Source getting Dual-Role Sink’s capabilities as a Source Sequence” .....680

Table 8.96 “Steps for a Source getting Sink Capabilities Sequence” .....683

Table 8.97 “Steps for a Dual-Role Sink getting Dual-Role Source capabilities as a Sink Sequence” .....686

Table 8.98 “Steps for a Sink getting EPR Source Capabilities Sequence” .....689

Table 8.99 “Steps for a Dual-Role Source getting Dual-Role Sink’s capabilities as an EPR Source Sequence” .....692

Table 8.100 “Steps for a Source getting Sink EPR Capabilities Sequence” .....695

Table 8.101 “Steps for a Dual-Role Sink getting Dual-Role Source capabilities as an EPR Sink Sequence” .....698

Table 8.102 “Steps for a Sink getting Source extended capabilities Sequence” .....701

Table 8.103 “Steps for a Dual-Role Source getting Dual-Role Sink extended capabilities Sequence” .....704

Table 8.104 “Steps for a Source getting Sink extended capabilities Sequence” .....707

Table 8.105 “Steps for a Dual-Role Sink getting Dual-Role Source extended capabilities Sequence” .....710

Table 8.106 “Steps for a Sink getting Source Battery capabilities Sequence” .....713

Table 8.107 “Steps for a Source getting Sink Battery capabilities Sequence” .....716

Table 8.108 “Steps for a Sink getting Source Battery status Sequence” .....719

Table 8.109 “Steps for a Source getting Sink Battery status Sequence” .....722

Table 8.110 “Steps for a Source getting Sink’s Port Manufacturer Information Sequence” .....725

Table 8.111 “Steps for a Source getting Sink’s Port Manufacturer Information Sequence” .....728

Table 8.112 “Steps for a Source getting Sink’s Battery Manufacturer Information Sequence” .....731

Table 8.113 “Steps for a Source getting Sink’s Battery Manufacturer Information Sequence” .....734

Table 8.114 “Steps for a VCONN Source getting Sink’s Port Manufacturer Information Sequence” .....737

Table 8.115 “Steps for a Source getting Country Codes Sequence” .....740

Table 8.116 “Steps for a Source getting Sink’s Country Codes Sequence” .....743

Table 8.117 “Steps for a VCONN Source getting Sink’s Country Codes Sequence” .....	746
Table 8.118 “Steps for a Source getting Country Information Sequence” .....	749
Table 8.119 “Steps for a Source getting Sink’s Country Information Sequence” .....	752
Table 8.120 “Steps for a VCONN Source getting Sink’s Country Information Sequence” .....	755
Table 8.121 “Steps for a Source getting Revision Information Sequence” .....	758
Table 8.122 “Steps for a Source getting Sink’s Revision Information Sequence” .....	761
Table 8.123 “Steps for a VCONN Source getting Sink’s Revision Information Sequence” .....	764
Table 8.124 “Steps for a Sink getting Source Information Sequence” .....	767
Table 8.125 “Steps for a Dual-Role Source getting Dual-Role Sink’s Information as a Source Sequence” .....	770
Table 8.126 “Steps for a Source requesting a security exchange with a Sink Sequence” .....	773
Table 8.127 “Steps for a Sink requesting a security exchange with a Source Sequence” .....	776
Table 8.128 “Steps for a VCONN Source requesting a security exchange with a Cable Plug Sequence” .....	779
Table 8.129 “Steps for a Source requesting a firmware update exchange with a Sink Sequence” .....	782
Table 8.130 “Steps for a Sink requesting a firmware update exchange with a Source Sequence” .....	785
Table 8.131 “Steps for a VCONN Source requesting a firmware update exchange with a Cable Plug Sequence” .....	788
Table 8.132 “Steps for Initiator to UFP Discover Identity (ACK)” .....	791
Table 8.133 “Steps for Initiator to UFP Discover Identity (NAK)” .....	794
Table 8.134 “Steps for Initiator to UFP Discover Identity (BUSY)” .....	797
Table 8.135 “Steps for DFP to UFP Discover SVIDs (ACK)” .....	800
Table 8.136 “Steps for DFP to UFP Discover SVIDs (NAK)” .....	803
Table 8.137 “Steps for DFP to UFP Discover SVIDs (BUSY)” .....	806
Table 8.138 “Steps for DFP to UFP Discover Modes (ACK)” .....	809
Table 8.139 “Steps for DFP to UFP Discover Modes (NAK)” .....	812
Table 8.140 “Steps for DFP to UFP Discover Modes (BUSY)” .....	815
Table 8.141 “Steps for DFP to UFP Enter Mode” .....	818
Table 8.142 “Steps for DFP to UFP Exit Mode” .....	821
Table 8.143 “Steps for DFP to Cable Plug Enter Mode” .....	824
Table 8.144 “Steps for DFP to Cable Plug Exit Mode” .....	827
Table 8.145 “Steps for Initiator to Responder Attention” .....	830
Table 8.146 “Steps for BIST Carrier Mode Test” .....	832
Table 8.147 “Steps for BIST Test Data Test” .....	835
Table 8.148 “Steps for BIST Shared Capacity Test Mode Test” .....	839
Table 8.149 “Steps for UFP USB4® Mode Entry (Accept)” .....	842
Table 8.150 “Steps for UFP USB4® Mode Entry (Reject)” .....	845
Table 8.151 “Steps for UFP USB4® Mode Entry (Wait)” .....	848
Table 8.152 “Steps for Cable Plug USB4® Mode Entry (Accept)” .....	851
Table 8.153 “Steps for Cable Plug USB4® Mode Entry (Reject)” .....	854
Table 8.154 “Steps for Cable Plug USB4® Mode Entry (Wait)” .....	857
Table 8.155 “Steps for Unstructured VDM Message Sequence” .....	860
Table 8.156 “Steps for VDEM Message Sequence” .....	863
Table 8.157 Policy Engine States .....	1013
Table 9.1 “USB Power Delivery Type Codes” .....	1029
Table 9.2 USB Power Delivery Capability Descriptor .....	1029
Table 9.3 “Battery Info Capability Descriptor” .....	1031
Table 9.4 “PD Consumer Port Descriptor” .....	1032
Table 9.5 “PD Provider Port Descriptor” .....	1033
Table 9.6 “PD Requests” .....	1034
Table 9.7 “PD Request Codes” .....	1034
Table 9.8 “PD Feature Selectors” .....	1034
Table 9.9 “Get Battery Status Request” .....	1035
Table 9.10 “Battery Status Structure” .....	1035

Table 9.11 “Set PD Feature” .....1036

Table 9.12 “Battery Wake Mask” .....1037

Table 9.13 “Charging Policy Encoding” .....1038

Table 10.1 “Considerations for Sources” .....1040

Table 10.2 “SPR Normative Voltages and Minimum Currents” .....1041

Table 10.3 “SPR Source Capabilities When Port Present PDP is less than Port Maximum PDP” .....1042

Table 10.4 “SPR Source Port Present PDP less than Port Maximum PDP Examples” .....1043

Table 10.5 “Fixed Supply PDO – Source 5V” .....1046

Table 10.6 “Fixed Supply PDO – Source 9V” .....1046

Table 10.7 “Fixed Supply PDO – Source 15V” .....1047

Table 10.8 “Fixed Supply PDO – Source 20V” .....1047

Table 10.9 “SPR Adjustable Voltage Supply (AVS) Voltage Ranges” .....1050

Table 10.10 “SPR Programmable Power Supply PDOs and APDOs based on the Port Maximum PDP” .....1052

Table 10.11 SPR “Programmable Power Supply Voltage Ranges” .....1052

Table 10.12 “EPR Source Capabilities based on the Port Maximim PDP and using an EPR Capable Cable” .....1056

Table 10.13 “EPR Source Capabilities when Port Present PDP is less than Port Maximum PDP and using an EPR-capable cable” .....1056

Table 10.14 “EPR Source Examples when Port Present PDP is less than Port Maximum PDP” .....1058

Table 10.15 “EPR Adjustable Voltage Supply (AVS) Voltage Ranges” .....1059

Table A-1 “Table showing the full calculation over one Message” .....1065

Table B-1 External power is supplied downstream.....1067

Table B.2 External power is supplied upstream.....1070

Table B.3 Giving back power. ....1077

Table C-1 “Discover Identity Command request from Initiator Example” .....1086

Table C.2 “Discover Identity Command response from Active Cable Responder Example” .....1087

Table C-3 “Discover Identity Command response from Hub Responder Example” .....1089

Table C-4 “Discover SVIDs Command request from Initiator Example” .....1090

Table C-5 “Discover SVIDs Command response from Responder Example” .....1091

Table C-6 “Discover Modes Command request from Initiator Example” .....1092

Table C-7 “Discover Modes Command response from Responder Example” .....1093

Table C-8 “Enter Mode Command request from Initiator Example” .....1094

Table C-9 “Enter Mode Command response from Responder Example” .....1095

Table C-10 “Enter Mode Command request from Initiator Example” .....1096

Table C-11 “Exit Mode Command request from Initiator Example” .....1097

Table C-12 “Exit Mode Command response from Responder Example” .....1098

Table C-13 “Attention Command request from Initiator Example” .....1099

Table C-14 “Attention Command request from Initiator with additional VDO Example” .....1100

Table E-1 “Sequence Table for setup of a Fast Role Swap (Hub connected to Power Adapter first)” .....1111

Table E-2 “Sequence Table for setup of a Fast Role Swap (Hub connected to Notebook before Power Adapter)” .....1112

Table E-3 Sequence Table for slow Vbus discharge (it discharges after FR\_Swap message is sent) .....1114

Table E-4 “Vbus discharges quickly after adapter disconnected” .....1116

## List of Figures

Figure 2-1 “Logical Structure of USB Power Delivery Capable Devices” .....	58
Figure 2-2 “Example SOP’ Communication between VCONN Source and Cable Plug(s)” .....	61
Figure 2-3 “USB Power Delivery Communications Stack” .....	70
Figure 2-4 “USB Power Delivery Communication Over USB” .....	71
Figure 2-5 “High Level Architecture View” .....	72
Figure 2-6 “Example of a Normal EPR Mode Operational Flow” .....	78
Figure 5-1 “Interpretation of ordered sets” .....	86
Figure 5-2 “Transmit Order for Various Sizes of Data” .....	88
Figure 5-3 “USB Power Delivery Packet Format” .....	89
Figure 5-4 “CRC 32 generation” .....	92
Figure 5-5 “Line format of Hard Reset” .....	95
Figure 5-6 “Line format of Cable Reset” .....	95
Figure 5-7 “BMC Example” .....	97
Figure 5-8 “BMC Transmitter Block Diagram” .....	97
Figure 5-9 “BMC Receiver Block Diagram” .....	98
Figure 5-10 “BMC Encoded Start of Preamble” .....	98
Figure 5-11 “Transmitting or Receiving BMC Encoded Frame Terminated by Zero with High-to-Low Last Transition” .....	99
Figure 5-12 “Transmitting or Receiving BMC Encoded Frame Terminated by One with High-to-Low Last Transition” .....	99
Figure 5-13 “Transmitting or Receiving BMC Encoded Frame Terminated by Zero with Low to High Last Transition” .....	100
Figure 5-14 “Transmitting or Receiving BMC Encoded Frame Terminated by One with Low to High Last Transition” .....	100
Figure 5-15 “BMC Tx ‘ONE’ Mask” .....	101
Figure 5-16 “BMC Tx ‘ZERO’ Mask” .....	102
Figure 5-17 “BMC Rx ‘ONE’ Mask when Sourcing Power” .....	104
Figure 5-18 “BMC Rx ‘ZERO’ Mask when Sourcing Power” .....	105
Figure 5-19 “BMC Rx ‘ONE’ Mask when Power neutral” .....	105
Figure 5-20 “BMC Rx ‘ZERO’ Mask when Power neutral” .....	106
Figure 5-21 “BMC Rx ‘ONE’ Mask when Sinking Power” .....	106
Figure 5-22 “BMC Rx ‘ZERO’ Mask when Sinking Power” .....	107
Figure 5-23 “Transmitter Load Model for BMC Tx from a Source” .....	109
Figure 5-24 “Transmitter Load Model for BMC Tx from a Sink” .....	109
Figure 5-25 Transmitter diagram illustrating zDriver .....	113
Figure 5-26 “Inter-Frame Gap Timings” .....	114
Figure 5-27 “Example Multi-Drop Configuration showing two DRPs” .....	117
Figure 5-28 “Example Multi-Drop Configuration showing a DFP and UFP” .....	118
Figure 5-29 “Test Data Frame” .....	119
Figure 6-1 “USB Power Delivery Packet Format including Control Message Payload” .....	121
Figure 6-2 “USB Power Delivery Packet Format including Data Message Payload” .....	121
Figure 6-3 “USB Power Delivery Packet Format including an Extended Message Header and Payload” .....	121
Figure 6-4 “Example Security_Request sequence Unchunked (Chunked bit = 0)” .....	129
Figure 6-5 “Example byte transmission for Security_Request Message of Data Size 7 (Chunked bit is set to zero)” .....	129
Figure 6-6 “Example byte transmission for Security_Response Message of Data Size 7 (Chunked bit is set to zero)” .....	130
Figure 6-7 “Example Security_Request sequence Chunked (Chunked bit = 1)” .....	131
Figure 6-8 “Example Security_Request Message of Data Size 7 (Chunked bit set to 1)” .....	132
Figure 6-9 “Example Chunk 0 of Security_Response Message of Data Size 30 (Chunked bit set to 1)” .....	132

Figure 6-10 "Example byte transmission for a Security\_Response Message Chunk request (Chunked bit is set to 1)" .....133

Figure 6-11 "Example Chunk 1 of Security\_Response Message of Data Size 30 (Chunked bit set to 1)" .....133

Figure 6-12 "Example Capabilities Message with 2 Power Data Objects" .....146

Figure 6-13 "BIST Message" .....169

Figure 6-14 "Vendor Defined Message" .....172

Figure 6-15 "Discover Identity Command response" .....181

Figure 6-16 "Discover Identity Command response for a DRD" .....181

Figure 6-17 "Example Discover SVIDs response with 3 SVIDs" .....202

Figure 6-18 "Example Discover SVIDs response with 4 SVIDs" .....202

Figure 6-19 "Example Discover SVIDs response with 12 SVIDs followed by an empty response" .....202

Figure 6-20 "Example Discover Modes response for a given SVID with 3 Modes" .....203

Figure 6-21 "Successful Enter Mode sequence" .....205

Figure 6-22 "Unsuccessful Enter Mode sequence due to NAK" .....206

Figure 6-23 "Exit Mode sequence" .....207

Figure 6-24 "Attention Command request/response sequence" .....208

Figure 6-25 "Command request/response sequence" .....209

Figure 6-26 "Enter/Exit Mode Process" .....211

Figure 6-27 "Battery\_Status Message" .....213

Figure 6-28 "Alert Message" .....215

Figure 6-29 "Get\_Country\_Info Message" .....219

Figure 6-30 "Enter\_USB Message" .....220

Figure 6-31 "EPR\_Request Message" .....223

Figure 6-32 "EPR Mode DO Message" .....224

Figure 6-33 "Illustration of process to enter EPR Mode" .....227

Figure 6-34 "Source\_Info Message" .....231

Figure 6-35 "Revision Message Data Object" .....233

Figure 6-36 "Source\_Capabilities\_Extended Message" .....236

Figure 6-37 "SOP Status Message" .....242

Figure 6-38 "SOP'/SOP" Status Message" .....247

Figure 6-39 "Get\_Battery\_Cap Message" .....248

Figure 6-40 "Get\_Battery\_Status Message" .....249

Figure 6-41 "Battery\_Capabilities Message" .....250

Figure 6-42 "Get\_Manufacturer\_Info Message" .....252

Figure 6-43 "Manufacturer\_Info Message" .....253

Figure 6-44 "Security\_Request Message" .....255

Figure 6-45 "Security\_Response Message" .....256

Figure 6-46 "Firmware\_Update\_Request Message" .....257

Figure 6-47 "Firmware\_Update\_Response Message" .....257

Figure 6-48 "PPS\_Status Message" .....258

Figure 6-49 "Country\_Codes Message" .....260

Figure 6-50 "Country\_Info Message" .....261

Figure 6-51 "Sink\_Capabilities\_Extended Message" .....262

Figure 6-52 "Extended\_Control Message" .....268

Figure 6-53 "Mapping SPR Capabilities to EPR Capabilities" .....270

Figure 6-54 "Vendor\_Defined\_Extended Message" .....272

Figure 6-55 "Outline of States" .....308

Figure 6-56 "References to states" .....308

Figure 6-57 "Chunking architecture Showing Message and Control Flow" .....310

Figure 6-58 "Chunked Rx State Diagram" .....311

Figure 6-59 "Chunked Tx State Diagram" .....314

Figure 6-60 “Chunked Message Router State Diagram” .....	318
Figure 6-61 “Common Protocol Layer Message Transmission State Diagram” .....	320
Figure 6-62 “Source Protocol Layer Message Transmission State Diagram” .....	323
Figure 6-63 “Sink Protocol Layer Message Transmission State Diagram” .....	325
Figure 6-64 “Protocol layer Message reception” .....	326
Figure 6-65 “Hard/Cable Reset” .....	328
Figure 7-1 “Placement of Source Bulk Capacitance” .....	344
Figure 7-2 “Transition Envelope for Positive Voltage Transitions” .....	346
Figure 7-3 “Transition Envelope for Negative Voltage Transitions” .....	347
Figure 7-4 “PPS Positive Voltage Transitions” .....	349
Figure 7-5 “PPS Negative Voltage Transitions” .....	350
Figure 7-6 “Expected PPS Ripple Relative to an LSB” .....	350
Figure 7-7 “Allowed DNL errors and tolerance of Voltage and Current in PPS mode” .....	351
Figure 7-8 “SPR PPS Programmable Voltage and Current Limit” .....	353
Figure 7-9 “SPR PPS Constant Power” .....	354
Figure 7-10 “AVS Positive Voltage Transitions” .....	356
Figure 7-11 “AVS Negative Voltage Transitions” .....	357
Figure 7-12 “Expected AVS Ripple Relative to an LSB” .....	357
Figure 7-13 “Source $V_{BUS}$ and $V_{CONN}$ Response to Hard Reset” .....	359
Figure 7-14 “Application of $v_{SrcNew}$ and $v_{SrcValid}$ limits after $t_{SrcReady}$ ” .....	363
Figure 7-15 “Source Peak Current Overload” .....	365
Figure 7-16 “Holdup Time Measurement” .....	367
Figure 7-17 “ $V_{BUS}$ Power during Fast Role Swap” .....	369
Figure 7-18 “ $V_{BUS}$ detection and timing during Fast Role Swap, initial $V_{BUS}$ (at new source) > $v_{Safe5V(min)}$ ” .....	370
Figure 7-19 “ $V_{BUS}$ detection and timing during Fast Role Swap, initial $V_{BUS}$ (at new source) < $v_{Safe5V(min)}$ ” .....	370
Figure 7-20 “Data Reset UFP $V_{CONN}$ Power Cycle” .....	372
Figure 7-21 “Data Reset DFP $V_{CONN}$ Power Cycle” .....	373
Figure 7-22 “Placement of Sink Bulk Capacitance” .....	374
Figure 7-23 “Generic Change for the Source to another (A)PDO” .....	383
Figure 7-24 “Transition Diagram for Increasing the Voltage” .....	385
Figure 7-25 “Transition Diagram for Increasing the Voltage and Current” .....	387
Figure 7-26 “Transition Diagram for Increasing the Voltage and Decreasing the Current” .....	389
Figure 7-27 “Transition Diagram for Decreasing the Voltage and Increasing the Current” .....	391
Figure 7-28 “Transition Diagram for Decreasing the Voltage” .....	393
Figure 7-29 “Transition Diagram for Decreasing the Voltage and the Current” .....	395
Figure 7-30 “Transition Diagram for no change in Current or Voltage” .....	397
Figure 7-31 “Transition Diagram for Increasing the Current” .....	399
Figure 7-32 “Transition Diagram for Decreasing the Current” .....	401
Figure 7-33 “Transition Diagram for Increasing the Programmable Power Supply Voltage” .....	403
Figure 7-34 “Transition Diagram for Decreasing the Programmable Power Supply Voltage” .....	405
Figure 7-35 “Transition Diagram for increasing the Current in PPS mode” .....	407
Figure 7-36 “Transition Diagram for decreasing the Current in PPS mode” .....	409
Figure 7-37 “Transition Diagram for no change in Current or Voltage in PPS mode” .....	411
Figure 7-38 “Transition Diagram for Increasing the Adjustable Power Supply Voltage” .....	413
Figure 7-39 “Transition Diagram for Decreasing the Adjustable Voltage Supply Voltage” .....	415
Figure 7-40 “Transition Diagram for no change in Current or Voltage in AVS mode” .....	417
Figure 7-41 “Transition Diagram for a Sink Requested Power Role Swap” .....	418
Figure 7-42 “Transition Diagram for a Source Requested Power Role Swap” .....	421
Figure 7-43 “Transition Diagram for a GotoMin Current Decrease” .....	424
Figure 7-44 “Transition Diagram for a Source Initiated Hard Reset” .....	426
Figure 7-45 “Transition Diagram for a Sink Initiated Hard Reset” .....	428

Figure 7-46 “Transition Diagram for Fast Role Swap” .....	430
Figure 8-1 “Example of daisy chained displays” .....	450
Figure 8-2 “Basic Message Exchange (Successful)” .....	454
Figure 8-3 “Basic Message flow indicating possible errors” .....	455
Figure 8-4 “Basic Message Flow with Bad CRC followed by a Retry” .....	457
Figure 8-5 “Successful Fixed, Variable or Battery SPR Power Negotiation” .....	480
Figure 8-6 “Rejected Fixed, Variable or Battery SPR Power Negotiation” .....	484
Figure 8-7 “Wait response to Fixed, Variable or Battery SPR Power Negotiation” .....	487
Figure 8-8 “Successful GotoMin operation” .....	490
Figure 8-9 “SPR PPS Keep Alive” .....	493
Figure 8-10 “SPR Sink Makes Request (Accept)” .....	497
Figure 8-11 “SPR Sink Makes Request (Reject)” .....	500
Figure 8-12 “SPR Sink Makes Request (Wait)” .....	503
Figure 8-13 “Entering EPR Mode (Success)” .....	506
Figure 8-14 “Entering EPR Mode (Failure due to non-EPR cable)” .....	509
Figure 8-15 “Entering EPR Mode (Failure of VCONN Swap)” .....	512
Figure 8-16 “Successful Fixed EPR Power Negotiation” .....	516
Figure 8-17 “Rejected Fixed EPR Power Negotiation” .....	520
Figure 8-18 “Wait response to Fixed EPR Power Negotiation” .....	523
Figure 8-19 “EPR Keep Alive” .....	526
Figure 8-20 “Exiting EPR Mode (Sink Initiated)” .....	529
Figure 8-21 “Exiting EPR Mode (Source Initiated)” .....	532
Figure 8-22 “EPR Sink Makes Request (Accept)” .....	535
Figure 8-23 “EPR Sink Makes Request (Reject)” .....	538
Figure 8-24 “EPR Sink Makes Request (Wait)” .....	541
Figure 8-25 “Unsupported message” .....	544
Figure 8-26 “Ping” .....	547
Figure 8-27 “Soft Reset” .....	549
Figure 8-28 “DFP Initiated Data Reset where the DFP is the VCONN Source” .....	552
Figure 8-29 “DFP Receives Data Reset where the DFP is the VCONN Source” .....	556
Figure 8-30 “DFP Initiated Data Reset where the UFP is the Vconn Source” .....	560
Figure 8-31 “DFP Receives a Data Reset where the UFP is the VCONN Source” .....	565
Figure 8-32 “Source initiated Hard Reset” .....	570
Figure 8-33 “Sink Initiated Hard Reset” .....	573
Figure 8-34 “Source initiated reset - Sink long reset” .....	576
Figure 8-35 “Successful Power Role Swap Sequence Initiated by the Source” .....	580
Figure 8-36 “Rejected Power Role Swap Sequence Initiated by the Source” .....	584
Figure 8-37 “Power Role Swap Sequence with wait Initiated by the Source” .....	587
Figure 8-38 “Successful Power Role Swap Sequence Initiated by the Sink” .....	591
Figure 8-39 “Rejected Power Role Swap Sequence Initiated by the Sink” .....	595
Figure 8-40 “Power Role Swap Sequence with wait Initiated by the Sink” .....	598
Figure 8-41 “Successful Fast Role Swap Sequence” .....	602
Figure 8-42 “Data Role Swap, UFP operating as Sink initiates” .....	606
Figure 8-43 “Rejected Data Role Swap, UFP operating as Sink initiates” .....	609
Figure 8-44 “Data Role Swap with Wait, UFP operating as Sink initiates” .....	612
Figure 8-45 “Data Role Swap, UFP operating as Source initiates” .....	615
Figure 8-46 “Rejected Data Role Swap, UFP operating as Source initiates” .....	618
Figure 8-47 “Data Role Swap with Wait, UFP operating as Source initiates” .....	621
Figure 8-48 “Data Role Swap, DFP operating as Source initiates” .....	624
Figure 8-49 “Rejected Data Role Swap, DFP operating as Source initiates” .....	627
Figure 8-50 “Data Role Swap with Wait, DFP operating as Source initiates” .....	630

Figure 8-51 “Data Role Swap, DFP operating as Sink initiates” .....633

Figure 8-52 “Rejected Data Role Swap, DFP operating as Sink initiates” .....636

Figure 8-53 “Data Role Swap with Wait, DFP operating as Sink initiates” .....639

Figure 8-54 “Successful VCONN Source Swap, initiated by VCONN Source” .....642

Figure 8-55 “Rejected VCONN Source Swap, initiated by VCONN Source” .....645

Figure 8-56 “VCONN Source Swap with Wait, initiated by VCONN Source” .....648

Figure 8-57 “VCONN Source Swap, initiated by non- VCONN Source” .....651

Figure 8-58 “Rejected VCONN Source Swap, initiated by non- VCONN Source” .....654

Figure 8-59 “VCONN Source Swap with Wait, initiated by non- VCONN Source” .....657

Figure 8-60 “Source Alert to Sink” .....660

Figure 8-61 “Sink Alert to Source” .....662

Figure 8-62 “Sink Gets Source Status” .....664

Figure 8-63 “Source Gets Sink Status” .....667

Figure 8-64 “VCONN Source Gets Cable Plug Status” .....670

Figure 8-65 “Sink Gets Source PPS Status” .....673

Figure 8-66 “Sink Gets Source’s Capabilities” .....676

Figure 8-67 “Dual-Role Source Gets Dual-Role Sink’s Capabilities as a Source” .....679

Figure 8-68 “Source Gets Sink’s Capabilities” .....682

Figure 8-69 “Dual-Role Sink Gets Dual-Role Source’s Capabilities as a Sink” .....685

Figure 8-70 “Sink Gets Source’s EPR Capabilities” .....688

Figure 8-71 “Dual-Role Source Gets Dual-Role Sink’s Capabilities as an EPR Source” .....691

Figure 8-72 “Source Gets Sink’s EPR Capabilities” .....694

Figure 8-73 “Dual-Role Sink Gets Dual-Role Source’s Capabilities as an EPR Sink” .....697

Figure 8-74 “Sink Gets Source’s Extended Capabilities” .....700

Figure 8-75 “Dual-Role Source Gets Dual-Role Sink’s Extended Capabilities” .....703

Figure 8-76 “Source Gets Sink’s Extended Capabilities” .....706

Figure 8-77 “Dual-Role Sink Gets Dual-Role Source’s Extended Capabilities” .....709

Figure 8-78 “Sink Gets Source’s Battery Capabilities” .....712

Figure 8-79 “Source Gets Sink’s Battery Capabilities” .....715

Figure 8-80 “Sink Gets Source’s Battery Status” .....718

Figure 8-81 “Source Gets Sink’s Battery Status” .....721

Figure 8-82 “Source Gets Sink’s Port Manufacturer Information” .....724

Figure 8-83 “Sink Gets Source’s Port Manufacturer Information” .....727

Figure 8-84 “Source Gets Sink’s Battery Manufacturer Information” .....730

Figure 8-85 “Sink Gets Source’s Battery Manufacturer Information” .....733

Figure 8-86 “VCONN Source Gets Cable Plug’s Manufacturer Information” .....736

Figure 8-87 “Source Gets Sink’s Country Codes” .....739

Figure 8-88 “Sink Gets Source’s Country Codes” .....742

Figure 8-89 “VCONN Source Gets Cable Plug’s Country Codes” .....745

Figure 8-90 “Source Gets Sink’s Country Information” .....748

Figure 8-91 “Sink Gets Source’s Country Information” .....751

Figure 8-92 “VCONN Source Gets Cable Plug’s Country Information” .....754

Figure 8-93 “Source Gets Sink’s Revision Information” .....757

Figure 8-94 “Sink Gets Source’s Revision Information” .....760

Figure 8-95 “VCONN Source Gets Cable Plug’s Revision Information” .....763

Figure 8-96 “Sink Gets Source’s Information” .....766

Figure 8-97 “Dual-Role Source Gets Dual-Role Sink’s Information as a Source” .....769

Figure 8-98 “Source requests security exchange with Sink” .....772

Figure 8-99 “Sink requests security exchange with Source” .....775

Figure 8-100 “VCONN Source requests security exchange with Cable Plug” .....778

Figure 8-101 “Source requests firmware update exchange with Sink” .....781

Figure 8-102 “Sink requests firmware update exchange with Source” .....	784
Figure 8-103 “VCONN Source requests firmware update exchange with Cable Plug” .....	787
Figure 8-104 “Initiator to Responder Discover Identity (ACK)” .....	790
Figure 8-105 “Initiator to Responder Discover Identity (NAK)” .....	793
Figure 8-106 “Initiator to Responder Discover Identity (BUSY)” .....	796
Figure 8-107 “Initiator to Responder Discover SVIDs (ACK)” .....	799
Figure 8-108 “Initiator to Responder Discover SVIDs (NAK)” .....	802
Figure 8-109 “Initiator to Responder Discover SVIDs (BUSY)” .....	805
Figure 8-110 “Initiator to Responder Discover Modes (ACK)” .....	808
Figure 8-111 “Initiator to Responder Discover Modes (NAK)” .....	811
Figure 8-112 “Initiator to Responder Discover Modes (BUSY)” .....	814
Figure 8-113 “DFP to UFP Enter Mode” .....	817
Figure 8-114 “DFP to UFP Exit Mode” .....	820
Figure 8-115 “DFP to Cable Plug Enter Mode” .....	823
Figure 8-116 “DFP to Cable Plug Exit Mode” .....	826
Figure 8-117 “Initiator to Responder Attention” .....	829
Figure 8-118 “BIST Carrier Mode Test” .....	831
Figure 8-119 “BIST Test Data Test” .....	834
Figure 8-120 “BIST Share Capacity Mode Test” .....	838
Figure 8-121 “UFP Entering USB4® Mode (Accept)” .....	841
Figure 8-122 “UFP Entering USB4® Mode (Reject)” .....	844
Figure 8-123 “UFP Entering USB4® Mode (Wait)” .....	847
Figure 8-124 “Cable Plug Entering USB4® Mode (Accept)” .....	850
Figure 8-125 “Cable Plug Entering USB4® Mode (Reject)” .....	853
Figure 8-126 “Cable Plug Entering USB4® Mode (Wait)” .....	856
Figure 8-127 “Unstructured VDM Message Sequence” .....	859
Figure 8-128 “VDEM Message Sequence” .....	862
Figure 8-129 “Outline of States” .....	865
Figure 8-130 “References to states” .....	866
Figure 8-131 “Example of state reference with conditions” .....	866
Figure 8-132 “Example of state reference with the same entry and exit” .....	866
Figure 8-133 “SenderResponseTimer Policy Engine State Diagram” .....	868
Figure 8-134 “Source Port State Diagram” .....	870
Figure 8-135 “Sink Port State Diagram” .....	878
Figure 8-136 “SOP Source Port Soft Reset and Protocol Error State Diagram” .....	884
Figure 8-137 “Sink Port Soft Reset and Protocol Error Diagram” .....	886
Figure 8-138 “DFP Data_Reset Message State Diagram” .....	888
Figure 8-139 “UFP Data_Reset Message State Diagram” .....	891
Figure 8-140 “Source Port Not Supported Message State Diagram” .....	894
Figure 8-141 “Sink Port Not Supported Message State Diagram” .....	896
Figure 8-142 “Source Port Ping State Diagram” .....	898
Figure 8-143 “Source Port Source Alert State Diagram” .....	899
Figure 8-144 “Sink Port Source Alert State Diagram” .....	901
Figure 8-145 “Sink Port Sink Alert State Diagram” .....	902
Figure 8-146 “Source Port Sink Alert State Diagram” .....	904
Figure 8-147 “Sink Port Get Source Capabilities Extended State Diagram” .....	905
Figure 8-148 “Source Give Source Capabilities Extended State Diagram” .....	906
Figure 8-149 “Source Port Get Sink Capabilities Extended State Diagram” .....	907
Figure 8-150 “Sink Give Sink Capabilities Extended State Diagram” .....	908
Figure 8-151 “Sink Port Get Source Information State Diagram” .....	909
Figure 8-152 “Source Give Source Information State Diagram” .....	910

Figure 8-153 “Get Status State Diagram” .....	911
Figure 8-154 “Give Status State Diagram” .....	912
Figure 8-155 “Sink Port Get Source PPS Status State Diagram” .....	913
Figure 8-156 “Source Give Source PPS Status State Diagram” .....	914
Figure 8-157 “Get Battery Capabilities State Diagram” .....	915
Figure 8-158 “Give Battery Capabilities State Diagram” .....	916
Figure 8-159 “Get Battery Status State Diagram” .....	917
Figure 8-160 “Give Battery Status State Diagram” .....	918
Figure 8-161 “Get Manufacturer Information State Diagram” .....	919
Figure 8-162 “Give Manufacturer Information State Diagram” .....	920
Figure 8-163 “Get Country Codes State Diagram” .....	921
Figure 8-164 “Give Country Codes State Diagram” .....	922
Figure 8-165 “Get Country Information State Diagram” .....	923
Figure 8-166 “Give Country Information State Diagram” .....	924
Figure 8-167 “Get Revision State Diagram” .....	925
Figure 8-168 “Give Revision State Diagram” .....	926
Figure 8-169 “DFP Enter_USB Message State Diagram” .....	927
Figure 8-170 “UFP Enter_USB Message State Diagram” .....	928
Figure 8-171 “Send security request State Diagram” .....	929
Figure 8-172 “Send security response State Diagram” .....	930
Figure 8-173 “Security response received State Diagram” .....	931
Figure 8-174 “Send firmware update request State Diagram” .....	932
Figure 8-175 “Send firmware update response State Diagram” .....	933
Figure 8-176 “Firmware update response received State Diagram” .....	934
Figure 8-177: “DFP to UFP Data Role Swap State Diagram” .....	935
Figure 8-178: “UFP to DFP Data Role Swap State Diagram” .....	938
Figure 8-179: “Dual-Role Port in Source to Sink Power Role Swap State Diagram” .....	941
Figure 8-180: “Dual-role Port in Sink to Source Power Role Swap State Diagram” .....	944
Figure 8-181: “Dual-Role Port in Source to Sink Fast Role Swap State Diagram” .....	947
Figure 8-182: “Dual-role Port in Sink to Source Fast Role Swap State Diagram” .....	950
Figure 8-183 “Dual-Role (Source) Get Source Capabilities diagram” .....	953
Figure 8-184 “Dual-Role (Source) Give Sink Capabilities diagram” .....	954
Figure 8-185 “Dual-Role (Sink) Get Sink Capabilities State Diagram” .....	955
Figure 8-186 “Dual-Role (Sink) Give Source Capabilities State Diagram” .....	956
Figure 8-187 “Dual-Role (Source) Get Source Capabilities Extended State Diagram” .....	956
Figure 8-188 “Dual-Role (Sink) Give Source Capabilities Extended diagram” .....	958
Figure 8-189 “Dual-Role (Sink) Get Sink Capabilities Extended State Diagram” .....	958
Figure 8-190 “Dual-Role (Source) Give Sink Capabilities Extended diagram” .....	959
Figure 8-191 “Dual-Role (Source) Get Source Information State Diagram” .....	960
Figure 8-192 “Dual-Role (Source) Give Source Information diagram” .....	961
Figure 8-193 “VCONN Swap State Diagram” .....	962
Figure 8-194 “Initiator to Port VDM Discover Identity State Diagram” .....	965
Figure 8-195 “Initiator VDM Discover SVIDs State Diagram” .....	967
Figure 8-196 “Initiator VDM Discover Modes State Diagram” .....	969
Figure 8-197 “Initiator VDM Attention State Diagram” .....	971
Figure 8-198 “Responder Structured VDM Discover Identity State Diagram” .....	972
Figure 8-199 “Responder Structured VDM Discover SVIDs State Diagram” .....	973
Figure 8-200 “Responder Structured VDM Discover Modes State Diagram” .....	974
Figure 8-201 “Receiving a Structured VDM Attention State Diagram” .....	975
Figure 8-202 “DFP VDM Mode Entry State Diagram” .....	976
Figure 8-203 “DFP VDM Mode Exit State Diagram” .....	978

Figure 8-204 “UFP Structured VDM Enter Mode State Diagram” .....	980
Figure 8-205 “UFP Structured VDM Exit Mode State Diagram” .....	982
Figure 8-206 “Cable Ready State Diagram” .....	984
Figure 8-207 “Cable Plug Soft Reset State Diagram” .....	985
Figure 8-208 “Cable Plug Hard Reset State Diagram” .....	986
Figure 8-209 “DFP/VCONN Source Soft Reset or Cable Reset of a Cable Plug or VPD State Diagram” .....	987
Figure 8-210 “UFP/VCONN Source Soft Reset of a Cable Plug or VPD State Diagram” .....	989
Figure 8-211 “Source Startup Structured VDM Discover Identity State Diagram” .....	991
Figure 8-212 “Cable Plug Structured VDM Enter Mode State Diagram” .....	993
Figure 8-213 “Cable Plug Structured VDM Exit Mode State Diagram” .....	995
Figure 8-214 “Source EPR Mode Entry State Diagram” .....	997
Figure 8-215 “Sink EPR Mode Entry State Diagram” .....	1000
Figure 8-216 “Source EPR Mode Exit State Diagram” .....	1002
Figure 8-217 “Sink EPR Mode Exit State Diagram” .....	1004
Figure 8-218 “BIST Carrier Mode State Diagram” .....	1006
Figure 8-219 “BIST Test Mode State Diagram” .....	1008
Figure 8-220 “BIST Shared Capacity Test Mode State Diagram” .....	1010
Figure 9-1 “Example PD Topology” .....	1022
Figure 9-2 “Mapping of PD Topology to USB” .....	1023
Figure 9-3 “USB Attached to USB Powered State Transition” .....	1024
Figure 9-4 “Any USB State to USB Attached State Transition (When operating as a Consumer)” .....	1025
Figure 9-5 “Any USB State to USB Attached State Transition (When operating as a Provider)” .....	1025
Figure 9-6 “Any USB State to USB Attached State Transition (After a USB Type-C® Data Role Swap)” .....	1026
Figure 9-7 “Software stack on a PD aware OS” .....	1026
Figure 9-8 “Enumeration of a PDUUSB Device” .....	1027
Figure 10-1 “SPR Source Power Rule Illustration for Fixed PDOs” .....	1044
Figure 10-2 “SPR Source Power Rule Example For Fixed PDOs” .....	1045
Figure 10-3 “Valid SPR AVS Operating Region for a Source advertising in the range of $27W < PDP \leq 45W$ ” .....	1048
Figure 10-4 “Valid SPR AVS Operating Region for a Source advertising in the range of $45W < PDP \leq 60W$ ” .....	1049
Figure 10-5 “Valid SPR AVS Operating Region for a Source advertising in the range of $60W < PDP \leq 100W$ ” .....	1049
Figure 10-6 “Valid EPR AVS Operating Region” .....	1058
Figure 10-7 “EPR Source Power Rule Illustration for Fixed PDOs” .....	1059
Figure B-1 “External Power supplied downstream” .....	1066
Figure B-2 External Power supplied upstream .....	1070
Figure B-3 “Giving Back Power” .....	1076
Figure D-1 “Circuit Block of BMC Finite Difference Receiver” .....	1101
Figure D-2 “BMC AC and DC noise from VBUS at Power Sink” .....	1102
Figure D-3 “Sample BMC Signals (a) without USB 2.0 SE0 Noise (b) with USB 2.0 SE0 Noise” .....	1102
Figure D-4 “Scaled BMC Signal Derivative with 50ns Sampling Rate” .....	1103
Figure D-5 “BMC Signal and Finite Difference Output with Various Time Steps” .....	1103
Figure D-6 “Output of Finite Difference in dash line and Edge Detector in solid line” .....	1104
Figure D-7 “Noise Zone and Detect Zone of BMC Receiver” .....	1104
Figure D-8 “Circuit Block of BMC Subtraction Receiver” .....	1105
Figure D-9 “(a) Output of LPF1 and LPF2 (b) Subtraction of LPF1 and LPF2 Output” .....	1105
Figure D-10 “Output of the BMC LPF1 in blue dash curve and the Subtractor in red solid curve” .....	1106
Figure E-1 “Example FRS Capable System” .....	1107
Figure E-2 “Slow $V_{BUS}$ Discharge” .....	1108
Figure E-3 “Fast $V_{BUS}$ Discharge” .....	1109
Figure E-4 “Sequence Diagram for slow $V_{BUS}$ discharge (it discharges after FR_Swap message is sent)” .....	1113
Figure E-5 Sequence for $V_{bus}$ discharges quickly (before FR_Swap message is sent) after adapter disconnected ...	1115

# 1. Introduction

USB has evolved from a data interface capable of supplying limited power to a primary provider of power with a data interface. Today many devices charge or get their power from USB ports contained in laptops, cars, aircraft or even wall sockets. USB has become a ubiquitous power socket for many small devices such as cell phones, MP3 players and other hand-held devices. Users need USB to fulfil their requirements not only in terms of data but also to provide power to, or charge, their devices simply, often without the need to load a driver, in order to carry out “traditional” USB functions.

There are, however, still many devices which either require an additional power connection to the wall, or exceed the USB rated current in order to operate. Increasingly, international regulations require better energy management due to ecological and practical concerns relating to the availability of power. Regulations limit the amount of power available from the wall which has led to a pressing need to optimize power usage. The USB Power Delivery Specification has the potential to minimize waste as it becomes a standard for charging devices that are not satisfied by [\[USBBC 1.2\]](#).

Wider usage of wireless solutions is an attempt to remove data cabling but the need for “tethered” charging remains. In addition, industrial design requirements drive wired connectivity to do much more over the same connector.

USB Power Delivery is designed to enable the maximum functionality of USB by providing more flexible power delivery along with data over a single cable. Its aim is to operate with and build on the existing USB ecosystem; increasing power levels from existing USB standards, for example Battery Charging, enabling new higher power use cases such as USB powered Hard Disk Drives (HDDs) and printers.

With USB Power Delivery the power direction is no longer fixed. This enables the product with the power (Host or Peripheral) to provide the power. For example, a display with a supply from the wall can power, or charge, a laptop. Alternatively, USB power bricks or chargers are able to supply power to laptops and other battery powered devices through their, traditionally power providing, USB ports.

USB Power Delivery enables hubs to become the means to optimize power management across multiple peripherals by allowing each device to take only the power it requires, and to get more power when required for a given application. For example, battery powered devices can get increased charging current and then give it back temporarily when the user’s HDD requires spinning up. **Optionally** the hubs can communicate with the PC to enable even more intelligent and flexible management of power either automatically or with some level of user intervention.

USB Power Delivery allows Low Power cases such as headsets to negotiate for only the power they require. This provides a simple solution that enables USB devices to operate at their optimal power levels.

The Power Delivery Specification, in addition to providing mechanisms to negotiate power also can be used as a side-band channel for standard and vendor defined messaging. Power Delivery enables alternative modes of operation by providing the mechanisms to discover, enter and exit Alternate Modes. The specification also enables discovery of cable capabilities such as supported speeds and current levels.

## 1.1 Overview

This specification defines how USB Devices can negotiate for more current and/or higher or lower Voltages over the USB cable (using the USB Type-C® CC wire as the communications channel) than are defined in the [\[USB 2.0\]](#), [\[USB 3.2\]](#), [\[USB4\]](#), [\[USB Type-C 2.3\]](#) or [\[USBBC 1.2\]](#) specifications. It allows Devices with greater power requirements than can be met with today’s specification to get the power they require to operate from  $V_{BUS}$  and negotiate with external power sources (e.g., Wall Warts). In addition, it allows a Source and Sink to swap power roles such that a Device could supply power to the Host. For example, a display could supply power to a notebook to charge its battery.

The USB Power Delivery Specification is guided by the following principles:

- Works seamlessly with legacy USB Devices
- Compatible with existing spec-compliant USB cables
- Minimizes potential damage from non-compliant cables (e.g., ‘Y’ cables etc.)
- Optimized for low-cost implementations.

This specification defines mechanisms to discover, enter and exit Modes defined either by a standard or by a particular vendor. These Modes can be supported either by the Port Partner or by a cable connecting the two Port Partners.

The specification defines mechanisms to discover the capabilities of cables which can communicate using Power Delivery.

This specification adds a mechanism to swap the data roles such that the upstream facing Port becomes the downstream facing Port and vice versa. It also enables a swap of the end supplying VCONN to a powered cable.

To facilitate optimum charging, the specification defines two mechanisms a USB Charger can Advertise for the Device to use:

- 1) A list of fixed Voltages each with a maximum current. The Device selects a Voltage and current from the list. This is the traditional model used by Devices that use internal electronics to manage the charging of their battery including modifying the Voltage and current actually supplied to the battery. The side-effect of this model is that the charging circuitry generates heat that can be problematic for small form factor devices.
- 2) A list of programmable Voltage ranges each with a maximum current (PPS). The Device requests a Voltage (in 20mV increments in SPR PPS Mode and in 100mV increments in EPR AVS Mode) that is within the Advertised range and a maximum current. The USB Charger delivers the requested Voltage until the maximum current is reached at which time the USB charger reduces its output Voltage so as not to supply more than the requested maximum current. During the high current portion of the charge cycle, the USB Charger can be directly connected (through an appropriate safety device) to the battery. This model is used by Devices that want to minimize the thermal impact of their internal charging circuitry.

## 1.2 Purpose

The USB Power Delivery specification defines a power delivery system covering all elements of a USB system including Hosts, Devices, Hubs, Chargers and cable assemblies. This specification describes the architecture, protocols, power supply behavior, connectors and cabling necessary for managing power delivery over USB at up to 100W. This specification is intended to be fully compatible and extend the existing USB infrastructure. It is intended that this specification will allow system OEMs, power supply and peripheral developers adequate flexibility for product versatility and market differentiation without losing backwards compatibility.

USB Power Delivery is designed to operate independently of the existing USB bus defined mechanisms used to negotiate power which are:

- [\[USB 2.0\]](#), [\[USB 3.2\]](#) in band requests for high power interfaces.
- [\[USBBC 1.2\]](#) mechanisms for supplying higher power (not mandated by this specification).
- [\[USB Type-C 2.3\]](#) mechanisms for supplying higher power.

Initial operating conditions remain the USB Default Operation as defined in [\[USB 2.0\]](#), [\[USB 3.2\]](#), [\[USB Type-C 2.3\]](#) or [\[USBBC 1.2\]](#).

- The DFP sources *vSafe5V* over  $V_{BUS}$ .
- The UFP consumes power from  $V_{BUS}$ .

## 1.2.1 Scope

This specification is intended as an extension to the existing [\[USB 2.0\]](#), [\[USB 3.2\]](#), [\[USB Type-C 2.3\]](#) and [\[USBBC 1.2\]](#) specifications. It addresses only the elements required to implement USB Power Delivery. It is targeted at power supply vendors, manufacturers of [\[USB 2.0\]](#), [\[USB 3.2\]](#), [\[USB Type-C 2.3\]](#) and [\[USBBC 1.2\]](#) Platforms, Devices and cable assemblies.

**Normative** information is provided to allow interoperability of components designed to this specification.

**Informative** information, when provided, illustrates possible design implementation.

## 1.3 Section Overview

This specification contains the following sections:

**Table 1.1 Section Overview**

Section	Description
<a href="#">Section 1 “Introduction”</a>	Introduction, conventions used in the document, list of terms and abbreviations, references, and details of parameter usage.
<a href="#">Section 2 “Overview”</a>	Overview of the document including a description of the operation of PD and the architecture.
<a href="#">Section 3 “USB Type-A and USB Type-B Cable Assemblies and Connectors”</a>	Mechanical and electrical characteristics of the cables and connectors used by PD. Section <b>Deprecated</b> . See <a href="#">[USBPD 2.0]</a> for legacy PD connector specification.
<a href="#">Section 4 “Electrical Requirements”</a>	Electrical requirements for Dead Battery operation and cable detection.
<a href="#">Section 5 “Physical Layer”</a>	Details of the PD PHY Layer requirements
<a href="#">Section 6 “Protocol Layer”</a>	Protocol Layer requirements including the Messages, timers, counters, and state operation.
<a href="#">Section 7 “Power Supply”</a>	Power supply requirements for both Providers and Consumers.
<a href="#">Section 8 “Device Policy”</a>	Device Policy Manager requirements. Policy Engine Message sequence diagrams and state diagrams
<a href="#">Section 9 “States and Status Reporting”</a>	USBPD Device requirements including mapping of $V_{BUS}$ to USB states. System Policy Manager requirements including descriptors, events, and requests.
<a href="#">Section 10 “Power Rules”</a>	Rated Output Power definitions for PD.
<a href="#">Appendix A “CRC calculation”</a>	Example CRC calculations.
<a href="#">Appendix B “PD Message Sequence Examples”</a>	Scenarios illustrating Device Policy Manager operation.
<a href="#">Appendix C “VDM Command Examples”</a>	Examples of Structured VDM usage.
<a href="#">Appendix D “BMC Receiver Design Examples”</a>	BMC Receiver Design Examples.
<a href="#">Appendix E “FRS System Level Example”</a>	FRS System Level Example.

## 1.4 Conventions

### 1.4.1 Precedence

If there is a conflict between text, figures, and tables, the precedence **Shall** be tables, figures, and then text.

In there is a conflict between a generic statement and a more specific statement, the more specific statement **Shall** apply.

### 1.4.2 Keywords

The following keywords differentiate between the levels of requirements and options.

#### 1.4.2.1 Conditional Normative

**Conditional Normative** is a keyword used to indicate a feature that is mandatory when another related feature has been implemented. Designers are mandated to implement all such requirements, when the dependent features have been implemented, to ensure interoperability with other compliant Devices.

#### 1.4.2.2 Deprecated

**Deprecated** is a keyword used to indicate a feature, supported in previous releases of the specification, which is no longer supported.

#### 1.4.2.3 Discarded

**Discard**, **Discards** and **Discarded** are equivalent keywords indicating that a Packet when received **Shall** be thrown away by the PHY Layer and not passed to the Protocol Layer for processing. No **GoodCRC** Message **Shall** be sent in response to the Packet.

#### 1.4.2.4 Ignored

**Ignore**, **Ignores** and **Ignored** are equivalent keywords indicating Messages or Message fields which, when received, **Shall** result in no special action by the receiver. An **Ignored** Message **Shall** only result in returning a **GoodCRC** Message to acknowledge Message receipt. A Message with an **Ignored** field **Shall** be processed normally except for any actions relating to the **Ignored** field.

#### 1.4.2.5 Informative

**Informative** is a keyword indicating text with no specific requirements, provided only to improve understanding.

#### 1.4.2.6 Invalid

**Invalid** is a keyword when used in relation to a Packet indicates that the Packet's usage or fields fall outside of the defined specification usage. When **Invalid** is used in relation to an Explicit Contract it indicates that a previously established Explicit Contract which can no longer be maintained by the Source. When **Invalid** is used in relation to individual K-codes or K-code sequences indicates that the received Signaling falls outside of the defined specification.

#### 1.4.2.7 May

**May** is a keyword that indicates a choice with no implied preference.

### 1.4.2.8 May Not

**May Not** is a keyword that is the inverse of **May**. Indicates a choice to not implement a given feature with no implied preference.

### 1.4.2.9 N/A

**N/A** is a keyword that indicates that a field or value is not applicable and has no defined value and **Shall Not** be checked or used by the recipient.

### 1.4.2.10 Optional/Optionally/Optional Normative

**Optional**, **Optionally** and **Optional Normative** are equivalent keywords that describe features not mandated by this specification. However, if an **Optional** feature is implemented, the feature **Shall** be implemented as defined by this specification.

#### 1.4.2.10.1 Reserved

**Reserved** is a keyword indicating **Reserved** bits, bytes, words, fields, and code values that are set-aside for future standardization. Their use and interpretation **May** be specified by future extensions to this specification and **Shall Not** be utilized or adapted by vendor implementation. A **Reserved** bit, byte, word, or field **Shall** be set to zero by the sender and **Shall** be **Ignored** by the receiver. **Reserved** field values **Shall Not** be sent by the sender and **Shall** be **Ignored** by the receiver.

#### 1.4.2.11 Shall/Normative

**Shall** and **Normative** are equivalent keywords indicating a mandatory requirement. Designers are mandated to implement all such requirements to ensure interoperability with other compliant Devices.

#### 1.4.2.12 Shall Not

**Shall Not** is a keyword that is the inverse of **Shall** indicating non-compliant operation.

#### 1.4.2.13 Should

**Should** is a keyword indicating flexibility of choice with a preferred alternative; equivalent to the phrase “it is recommended that...”.

#### 1.4.2.14 Should Not

**Should Not** is a keyword is the inverse of **Should**; equivalent to the phrase “it is recommended that implementations do not...”.

#### 1.4.2.15 Valid

**Valid** is a keyword that is the inverse of **Invalid** indicating either a Packet or Signaling that fall within the defined specification or an Explicit Contract that can be maintained by the Source.

## 1.4.3 Numbering

Numbers that are immediately followed by a lowercase "b" (e.g., 01b) are binary values. Numbers that are immediately followed by an uppercase "B" are byte values. Numbers that are immediately followed by a lowercase "h" (e.g., 3Ah) or are preceded by "0x" (e.g., 0xFF00) are hexadecimal values. Numbers not immediately followed by either a "b", "B", or "h" are decimal values.

## 1.5 Related Documents

Document references listed below are inclusive of all approved and published ECNs and Errata:

**Table 1.2 Document References**

Bookmark Reference	Title	Revision and date
[DPTC2.1]	DisplayPort™ Alt Mode on USB Type-C® Standard <a href="http://www.vesa.org">www.vesa.org</a> .	Version 2.1 2022-11
[IEC 60950-1]	IEC 60950-1:2005 Information technology equipment – Safety – Part 1: General requirements: Amendment 1:2009, Amendment 2:2013. <a href="http://www.iec.ch">www.iec.ch</a> .	2005, 2009, 2013
[IEC 60958-1]	IEC 60958-1:2021 Digital Audio Interface Part:1 General. <a href="http://www.iec.ch">www.iec.ch</a> .	2021-09-10
[IEC 62368-1]	IEC 62368-1:2018 Audio/Video, information, and communication technology equipment – Part 1: Safety requirements. <a href="http://www.iec.ch">www.iec.ch</a> .	2018-10-04
[IEC 62368-3]	IEC 62368-3:2017 Audio/video, information, and communication technology equipment - Part 3: Safety aspects for DC power transfer through communication cables and ports <a href="http://www.iec.ch">www.iec.ch</a> .	2017-12-07
[IEC 63002]	IEC 63002:2021 Interoperability specifications and communication method for external power supplies used with computing and consumer electronics devices <a href="http://www.iec.ch">www.iec.ch</a> .	2021-05-27
[ISO 3166]	ISO 3166 international Standard for country codes and codes for their subdivisions. <a href="http://www.iso.org/iso/home/standards/country_codes.htm">http://www.iso.org/iso/home/standards/country_codes.htm</a> .	
[TBT3]	see [USB4] Chapter 13 for Thunderbolt™ 3 device operation.	
[UCSI]	USB Type-C® Connector System Software Interface (UCSI) Specification <a href="https://www.usb.org/documents">https://www.usb.org/documents</a> .	2023-06-23
[USB 2.0]	Universal Serial Bus 2.0 Specification, , <a href="https://www.usb.org/documents">https://www.usb.org/documents</a> .	Revision 2.0
[USB 3.2]	Universal Serial Bus 3.2 Specification <a href="https://www.usb.org/documents">https://www.usb.org/documents</a> .	Revision 1.1 June 2022
[USB Type-C 2.3]	Universal Serial Bus Type-C® Cable and Connector Specification, <a href="https://www.usb.org/documents">https://www.usb.org/documents</a> .	Release 2.3 October 2023
[USB4]	Universal Serial Bus 4 Specification (USB4®), <a href="https://www.usb.org/documents">https://www.usb.org/documents</a> .	Version 2.0 October 2022
[USBBC 1.2]	Universal Serial Bus Battery Charging Specification plus Errata (referred to in this document as the Battery Charging specification). <a href="https://www.usb.org/documents">https://www.usb.org/documents</a> .	Revision 1.2
[USBPD 2.0]	Universal Serial Bus Power Delivery Specification, <a href="https://www.usb.org/documents">https://www.usb.org/documents</a> .	Revision 2 Version 1.2 March 25, 2016
[USBPDCompliance]	USB Power Delivery Compliance Test Specification, <a href="https://www.usb.org/documents">https://www.usb.org/documents</a> .	Revision Q2, 2023 OR April 2023

<i>[USBPDFirmwareUpdate 1.0]</i>	Universal Serial Bus Power Delivery Firmware Update Specification, <a href="https://www.usb.org/documents">https://www.usb.org/documents</a> .	Revision 1.0, September 15, 2016
<i>[USBTypeCAuthentication 1.0]</i>	Universal Serial Bus Type-C® Authentication Specification, <a href="https://www.usb.org/documents">https://www.usb.org/documents</a> .	Revision 1.0, March 25, 2016
<i>[USBTypeCBridge 1.1]</i>	Universal Serial Bus Type-C® Bridge Specification, <a href="https://www.usb.org/documents">https://www.usb.org/documents</a> .	Revision 1.1 September 2017