



American National Standard for

Rotodynamic (Centrifugal) Pumps

for Design and Application

ANSI/HI 1.3-2009



6 Campus Drive
First Floor North
Parsippany, New Jersey
07054-4406
www.Pumps.org

This page intentionally blank.

ANSI/HI 1.3-2009

American National Standard for
Rotodynamic (Centrifugal) Pumps
for Design and Application

Sponsor
Hydraulic Institute
www.Pumps.org

Approved April 6, 2009
American National Standards Institute, Inc.

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published By

Hydraulic Institute
6 Campus Drive, First Floor North
Parsippany, NJ 07054-4406

www.Pumps.org

Copyright © 2009 Hydraulic Institute
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN 978-1-880952-90-0



Recycled
paper

Contents

	Page
Foreword	ix
1.3 Design and application	1
1.3.1 Scope	1
1.3.2 Introduction to pump classifications	1
1.3.3 Casings	6
1.3.4 Impellers	11
1.3.5 Mechanical features	14
1.3.6 Performance, selection criteria	66
1.3.7 Noise levels	91
1.3.8 Baseplates – introduction	94
Appendix A Introduction to pump classifications, industry segments, and general applications	109
A.1.3.1 Pump classifications	109
A.1.3.2 Pump industry segments and general service applications	112
Appendix B Other configurations	125
B.1.3 Introduction to Appendix B	125
B.1.3.1 Regenerative turbine pumps	125
B.1.3.2 Pitot tube pumps	130
B.1.3.3 Sump pumps - introduction	136
Appendix C Drivers	153
C.1.3 Introduction to Appendix C	153
C.1.3.1 Electric motors	153
C.1.3.2 Engines	168
C.1.3.3 Steam turbine	175
C.1.3.4 Eddy current drives	176
C.1.3.5 Deceleration devices	176
C.1.3.6 Variable-speed drives and gears	176
Appendix D Bibliography	177
Appendix E Index	179
 Figures	
1.3.1 — Rotodynamic (centrifugal) pump types	2
1.3.3.1 — Single volute casing	7
1.3.3.2 — Double (dual) volute casing	7
1.3.3.3 — Diffuser casing	7
1.3.3.4 — Circular (concentric) casing	8

1.3.3.5.1 — Type BB3 between-bearings axial split multistage pump	8
1.3.3.5.2 — Type BB4 between-bearings radial split single case multistage pump	9
1.3.3.5.3 — Type BB5 between-bearings radial split double case multistage volute pump	9
1.3.5.5.4.1 — Type BB5 between-bearings radial split double case multistage pump with stacked in-line diffuser construction	10
1.3.3.5.4.2 — Type BB5 between-bearings radial split double case multistage pump with back-to-back diffuser construction	10
1.3.4.1 — General impeller types	11
1.3.4.2 — Single suction impeller	12
1.3.4.3 — Double suction impeller	12
1.3.4.5 — Enclosed impeller	13
1.3.4.6 — Semi-open impeller	13
1.3.4.7 — Open impeller	13
1.3.4.8 — Inducer	14
1.3.5.1a — Additional sketch to illustrate D_2 and b_2	15
1.3.5.1b — Single volute radial thrust distribution	15
1.3.5.1c — Single volute	16
1.3.5.1d — Radial thrust factor for single volute with various specific speeds	16
1.3.5.1e — Double volute	17
1.3.5.1f — Radial thrust factor for double volute with various specific speeds	17
1.3.5.1g — Circular (concentric) casing	18
1.3.5.1h — Radial thrust factor for circular (concentric) casing typical for specific speed 20 (1000)	18
1.3.5.2.1a — Pressure distribution on enclosed impeller	19
1.3.5.2.1b — Pressure distribution on enclosed impeller shrouds for various specific speeds	21
1.3.5.2.1c — Thrust calculation example (metric units) for enclosed impeller with plain back shroud	22
1.3.5.2.1d — Impeller with back ring	23
1.3.5.2.2a — Semi-open impeller with a full back shroud	27
1.3.5.2.2b — Semi-open impeller with a scalloped back shroud	27
1.3.5.2.2c — Cross section of semi-open impeller showing diameter locations	28
1.3.5.3.1 — Overhung impeller pump	30
1.3.5.3.2 — Impeller between bearings	31
1.3.5.3.2.1 — Pressure distribution on between-bearings double suction enclosed impeller	32
1.3.5.3.2.2 — Horizontal between-bearings axially split multistage pump	32
1.3.5.4.2.4a — Overhung impeller	34
1.3.5.4.2.4b — Between-bearings single stage pump - method of calculating shaft deflection neglecting coupling weight	38
1.3.5.5.2.2a — Sleeve bearings	44
1.3.5.5.2.2b — Type BB4 multistage radial split single casing pump with ball and roller bearings	45
1.3.5.8.1a — Stuffing box without lantern ring	59
1.3.5.8.1b — Stuffing box with lantern ring	59
1.3.5.8.2.1a — Mechanical seal classification by arrangement	61

1.3.5.8.2.1b — Mechanical seal classification by design	61
1.3.5.8.6.1 — Types of bearing housing shaft seals	64
1.3.5.8.6.3a — Lip seal	65
1.3.5.8.6.3b — Lip seal with secondary V-ring	65
1.3.5.8.6.8 — Bearing isolator	66
1.3.6.1.1a — Pump performance curve versus system curve	66
1.3.6.1.1b — Variable speed curve	67
1.3.6.1.2a — Impeller with straight outside diameter	68
1.3.6.1.2b — Impeller with angled outside diameter	68
1.3.6.1.2c — Trimming only the impeller vane	69
1.3.6.3.5a — NPSHR reduction for pumps handling hydrocarbon liquids and high-temperature water (metric units)	74
1.3.6.3.5b — NPSHR reduction for pumps handling hydrocarbon liquids and high-temperature water (US customary units)	75
1.3.6.5.1a — Pumps operating in series	76
1.3.6.5.1b — Pumps operating in parallel	76
1.3.6.14a — Torque curve	84
1.3.6.14b — Evaluation of pump torque versus speed (metric units)	85
1.3.6.14c — Evaluation of pump torque versus speed (US customary units)	86
1.3.6.14d — Plotting torque versus speed (metric units)	87
1.3.6.14e — Plotting pump torque versus speed (US customary units)	90
1.3.7.1a — Combining sound pressure	92
1.3.7.1b — dBA correction for impeller trim and percent BEP operation	93
1.3.8.2.1a — Grouted baseplate, fabricated steel	96
1.3.8.2.1b — Grouted baseplate, cast iron	97
1.3.8.2.2 — Nongrout baseplate	97
1.3.8.2.3 — Pregrouted baseplate	98
1.3.8.2.4 — Soleplate	99
1.3.8.2.5a — Freestanding baseplate	100
1.3.8.2.5b — Baseplate mounting springs with slide bearing	100
1.3.8.2.6.1 — ASME B73.1 pump and baseplate	100
1.3.8.2.6.2 — ISO pump and baseplate	101
1.3.8.2.7.1 — Formed polymer baseplate	102
1.3.8.2.7.2 — Polymer concrete base	103
1.3.8.2.7.3 — Pedestal baseplate	103
1.3.8.2.8 — Oil pipeline skid type baseplate	104
1.3.8.2.9 — Offshore skid type baseplate	105
1.3.8.2.10a — Three-point mount type baseplate	105
1.3.8.2.10b — Underside of the three-point mount baseplate (O, P, and Q show the mounting points)	106
A1.3.1.a — Overhung pump types and classifications	110
A1.3.1.b — Between-bearing pump types and classifications	111

A1.3.1.c — Vertically suspended pump types and classifications	111
A1.3.2.4a — Turbine characteristics	114
A1.3.2.4b — Turbine performance.	116
A1.3.2.5c — Dry pit pump — overhung foot mounted flexibly coupled horizontal end suction	117
A1.3.2.5a — Dry pit pump — overhung flexibly coupled vertical end suction	117
A1.3.2.5b — Dry pit pump — overhung close coupled vertical end suction	117
A1.3.2.6a — Self-priming pump — construction industry	119
A1.3.2.6b — Self-priming pump — chemical industry	120
A1.3.2.7a — Two-phase pumping applications	121
A1.3.2.7b — Helico-axial multiphase pump	122
A1.3.2.7c — Screw-type multiphase pump	123
A1.3.2.7d — Effect of gas on pump performance	124
A1.3.2.7e — Venting the eye of the impeller	124
A1.3.2.7f — Top suction impeller	124
B1.3.1 — Regenerative turbine pumps types and classifications	125
B1.3.1.1a — Regenerative turbine – impeller between bearings – two stage	126
B1.3.1.1b — Regenerative turbine flow path	127
B1.3.1.4.1 — Regenerative turbine pump performance	129
B1.3.2.1.2.6a — Cross section of pitot tube pump	131
B1.3.2.1.2.6b — Rotating assembly	132
B1.3.2.2.2 — Pitot tube pump performance.	134
B1.3.3.1 — Type VS4 line shaft design sump pump	138
B1.3.3.1.3.4 — Tailpipe and float control.	141
B1.3.3.1.3.3 — Rate of flow versus minimum submergence	142
B1.3.3.1.4.4 — Schematic showing vapor-proof/pressurized design.	144
B1.3.3.1.4.6 — Alarms and controls	145
B1.3.3.1.4.7 — Applied forces and moments	145
B1.3.3.2 — Type VS5 cantilever shaft design sump pump	147
B1.3.3.2.3.3 — Rate of flow versus minimum submergence	150
B1.3.3.2.4.5 — Applied forces and moments	151
C1.3.1.3.2a — Torque speed curves for NEMA Design AC motors	160
C1.3.1.3.2b — Design A, B, C, D for AC motors	161
C1.3.2.7 — Outline of an internal combustion engine	175
Tables	
1.3.2 — Principal symbols	5
1.3.5.5.2.1 — Rolling element bearing types	43
1.3.5.5.3.5 — Life adjustment factors	49
1.3.5.5.3.6 — Oil contamination factor η_c	51
1.3.5.7 — Shaft couplings - functions and parameters for selection	57

1.3.6.12a — Guidelines for minimum and maximum liquid temperature for gray iron, ductile iron, carbon steel, chrome steel, austenitic stainless and duplex stainless steel pumps (°C)	83
1.3.6.12b — Guidelines for minimum and maximum liquid temperature for gray iron, ductile iron, carbon steel, chrome steel, austenitic stainless and duplex stainless steel pumps (°F)	83
1.3.7.1 — Multistage pump sound pressure reductions.	92
1.3.8.1 — Functions of a baseplate and parameters for selection.	95
C1.3.1 — Drivers – functions and parameters for selection.	154
C1.3.1.2.1 — Common electric motor enclosure types	157
C1.3.1.2.2a — IP classification system	158
C1.3.1.2.2b — Definition of second numeral in IP classification system	158

This page intentionally blank.

Foreword (Not part of Standard)

Scope

The purpose and aims of the Institute are to promote the continued growth of pump knowledge for the interest of pump users and manufacturers and to further the interests of the public in such matters as are involved in manufacturing, engineering, distribution, safety, transportation and other problems of the industry, and to this end, among other things:

- a) To develop and publish standards for pumps;
- b) To collect and disseminate information of value to its members and to the public;
- c) To appear for its members before governmental departments and agencies and other bodies in regard to matters affecting the industry;
- d) To increase the amount and to improve the quality of pump service to the public;
- e) To support educational and research activities;
- f) To promote the business interests of its members but not to engage in business of the kind ordinarily carried on for profit or to perform particular services for its members or individual persons as distinguished from activities to improve the business conditions and lawful interests of all of its members.

Purpose of Standards

- 1) Hydraulic Institute Standards are adopted in the public interest and are designed to help eliminate misunderstandings between the manufacturer, the purchaser and/or the user and to assist the purchaser in selecting and obtaining the proper product for a particular need.
- 2) Use of Hydraulic Institute Standards is completely voluntary. Existence of Hydraulic Institute Standards does not in any respect preclude a member from manufacturing or selling products not conforming to the Standards.

Definition of a Standard of the Hydraulic Institute

Quoting from Article XV, Standards, of the By-Laws of the Institute, Section B:

"An Institute Standard defines the product, material, process or procedure with reference to one or more of the following: nomenclature, composition, construction, dimensions, tolerances, safety, operating characteristics, performance, quality, rating, testing and service for which designed."

Comments from users

Comments from users of this Standard will be appreciated to help the Hydraulic Institute prepare even more useful future editions. Questions arising from the content of this Standard may be sent to the Technical Director of the Hydraulic Institute. The inquiry will then be directed to the appropriate technical committee for provision of a suitable answer.

If a dispute arises regarding the content of an Institute standard or an answer provided by the Institute to a question such as indicated above, the point in question shall be sent in writing to the Technical Director of the Hydraulic Institute, who shall initiate the Appeals Process.

Revisions

The Standards of the Hydraulic Institute are subject to constant review, and revisions are undertaken whenever it is found necessary because of new developments and progress in the art. If no revisions are made for five years, the standards are reaffirmed using the ANSI canvass procedure.