



American National Standard for

Rotodynamic Centrifugal Pumps

for Design and Application

ANSI/HI 1.3-2013



6 Campus Drive
First Floor North
Parsippany, New Jersey
07054-4406
www.Pumps.org

This page intentionally blank.

ANSI/HI 1.3-2013

American National Standard for
Rotodynamic Centrifugal Pumps
for Design and Application

Sponsor
Hydraulic Institute
www.Pumps.org

Approved December 19, 2013
American National Standards Institute, Inc.

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published By

Hydraulic Institute
6 Campus Drive, First Floor North
Parsippany, NJ 07054-4406

www.Pumps.org

Copyright © 2013 Hydraulic Institute
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN 978-1-935762-16-4



Recycled
paper

Contents

| | Page |
|---|------|
| Foreword | ix |
| 1.3 Design and application | 1 |
| 1.3.1 Scope | 1 |
| 1.3.2 Introduction to pump classifications | 1 |
| 1.3.2.1 Introduction to pump industry segments and general applications | 3 |
| 1.3.2.2 Preferred units for pump applications | 4 |
| 1.3.3 Casings | 7 |
| 1.3.3.1 Single volute | 7 |
| 1.3.3.2 Double volute | 7 |
| 1.3.3.3 Diffuser | 8 |
| 1.3.3.4 Circular (concentric) casing | 8 |
| 1.3.3.5 Multistage arrangements | 8 |
| 1.3.3.6 Corrosion allowance for metallic rotodynamic pumps | 11 |
| 1.3.4 Impellers | 11 |
| 1.3.4.1 General impeller types | 11 |
| 1.3.4.2 Single suction | 12 |
| 1.3.4.3 Double suction | 13 |
| 1.3.4.4 Multistage pumps | 13 |
| 1.3.4.5 Enclosed | 13 |
| 1.3.4.6 Semi-open | 14 |
| 1.3.4.7 Open | 14 |
| 1.3.4.8 Special suction impeller (inducer) | 14 |
| 1.3.5 Mechanical features | 15 |
| 1.3.5.1 Calculation of radial thrust for volute pumps | 15 |
| 1.3.5.2 Calculation of axial thrust for impellers | 21 |
| 1.3.5.3 Types of bearing arrangements | 31 |
| 1.3.5.4 Shaft deflection | 35 |
| 1.3.5.5 Guidelines for bearings and lubrication methods | 43 |
| 1.3.5.6 Bearing lubrication | 53 |
| 1.3.5.7 Type of couplings | 57 |
| 1.3.5.8 Shaft seals | 60 |
| 1.3.6 Performance, selection criteria | 66 |
| 1.3.6.1 Determination of operating duty point | 66 |
| 1.3.6.2 Minimum flow | 72 |
| 1.3.6.3 Net positive suction head | 72 |
| 1.3.6.4 Suction performance considerations | 78 |
| 1.3.6.5 Liquid temperature rise in a rotodynamic pump | 78 |
| 1.3.6.6 Efficiency prediction method for rotodynamic pumps | 81 |
| 1.3.6.7 Effects of handling viscous liquids | 81 |
| 1.3.6.8 Startup and shutdown | 81 |
| 1.3.6.9 Reverse runaway speed | 82 |
| 1.3.6.10 Water hammer (hydraulic shock) | 82 |
| 1.3.6.11 Pump liquid temperature limits on end suction pumps | 83 |
| 1.3.6.12 Intake design | 83 |

| | | |
|----------------|---|-----|
| 1.3.6.13 | Pump and motor speed–torque curves | 83 |
| 1.3.7 | Noise levels | 92 |
| 1.3.7.1 | Estimation of sound pressure levels | 92 |
| 1.3.8 | Baseplates – introduction | 94 |
| 1.3.8.1 | Functional requirements | 95 |
| 1.3.8.2 | Baseplate types | 96 |
| 1.3.8.3 | Tolerancing | 107 |
| 1.3.8.4 | Stress and rigidity requirements | 107 |
| 1.3.8.5 | Coupling alignment | 107 |
| 1.3.8.6 | Shims and fasteners | 108 |
| 1.3.8.7 | Lifting requirements | 108 |
| 1.3.8.8 | Miscellaneous criteria | 108 |
| Appendix A | Introduction to pump classifications, industry segments, and general applications | 110 |
| A.1 | Pump classifications | 110 |
| A.2 | Pump industry segments and general service applications | 110 |
| A.2.1 | General service applications | 113 |
| A.2.2 | Transfer pumping | 113 |
| A.2.3 | Booster service | 114 |
| A.2.4 | Pumps used as hydraulic turbines | 114 |
| A.2.5 | Dry pit (nonclog) pumps | 117 |
| A.2.6 | Self-priming pump applications | 119 |
| A.2.7 | Two-phase pumping applications | 122 |
| Appendix B | Other configurations | 126 |
| B.1 | Introduction to Appendix B | 126 |
| B.1.1 | Regenerative turbine pumps | 126 |
| B.1.2 | Pitot tube pumps | 131 |
| B.1.3 | Sump pumps - introduction | 137 |
| Appendix C | Drivers | 153 |
| C.1 | Introduction to Appendix C | 153 |
| C.1.1 | Electric motors | 153 |
| C.1.2 | Engines | 168 |
| C.1.3 | Steam turbine | 175 |
| C.1.4 | Eddy current drives | 176 |
| C.1.5 | Deceleration devices | 176 |
| C.1.6 | Variable-speed drives and gears | 176 |
| Appendix D | Bibliography | 177 |
| Appendix E | Index | 180 |
| Figures | | |
| 1.3.1 | — Rotodynamic centrifugal pump types | 2 |
| 1.3.3.1 | — Single volute casing | 7 |
| 1.3.3.2 | — Double (dual) volute casing | 7 |
| 1.3.3.3 | — Diffuser casing | 8 |
| 1.3.3.4 | — Circular (concentric) casing | 8 |
| 1.3.3.5.1 | — Type BB3 between-bearings axial split multistage pump | 9 |
| 1.3.3.5.2 | — Type BB4 between-bearings radial split single case multistage pump | 9 |

| | |
|--|----|
| 1.3.3.5.3 — Type BB5 between-bearings radial split double case multistage volute pump | 10 |
| 1.3.5.5.4.1 — Type BB5 between-bearings radial split double case multistage pump with stacked in-line diffuser construction | 10 |
| 1.3.3.5.4.2 — Type BB5 between-bearings radial split double case multistage pump with back-to-back diffuser construction | 11 |
| 1.3.4.1 — General impeller types | 12 |
| 1.3.4.2 — Single suction impeller | 12 |
| 1.3.4.3 — Double suction impeller | 13 |
| 1.3.4.5 — Enclosed impeller | 13 |
| 1.3.4.6 — Semi-open impeller | 14 |
| 1.3.4.7 — Open impeller | 14 |
| 1.3.4.8 — Inducer | 14 |
| 1.3.5.1a — Additional sketch to illustrate D_2 and b_2 | 16 |
| 1.3.5.1b — Single volute radial thrust distribution | 16 |
| 1.3.5.1c — Single volute | 17 |
| 1.3.5.1d — Radial thrust factor for single volute with various specific speeds. | 17 |
| 1.3.5.1e — Double volute | 18 |
| 1.3.5.1f — Radial thrust factor for double volute with various specific speeds | 18 |
| 1.3.5.1g — Circular (concentric) casing. | 19 |
| 1.3.5.1h — Radial thrust factor for circular (concentric) casing typical for specific speed 20 (1000). | 19 |
| 1.3.5.2.1a — Pressure distribution on enclosed impeller. | 21 |
| 1.3.5.2.1b — Pressure distribution on enclosed impeller shrouds for various specific speeds | 22 |
| 1.3.5.2.1c — Thrust calculation example for enclosed impeller with plain back shroud | 23 |
| 1.3.5.2.1d — Impeller with back ring | 25 |
| 1.3.5.2.2a — Semi-open impeller with a full back shroud | 29 |
| 1.3.5.2.2b — Semi-open impeller with a scalloped back shroud | 29 |
| 1.3.5.2.2c — Cross section of semi-open impeller showing diameter locations | 30 |
| 1.3.5.3.1 — Overhung impeller pump | 32 |
| 1.3.5.3.2 — Impeller between bearings | 33 |
| 1.3.5.3.2.1 — Pressure distribution on between-bearings double suction enclosed impeller | 34 |
| 1.3.5.3.2.2 — Horizontal between-bearings axially split multistage pump. | 34 |
| 1.3.5.4.2.4a — Overhung impeller | 36 |
| 1.3.5.4.2.4b — Between-bearings, single-stage pump - method of calculating shaft deflection neglecting coupling weight | 39 |
| 1.3.5.5.2.2a — Sleeve bearings. | 45 |
| 1.3.5.5.2.2b — Type BB4 multistage radial split single casing pump with ball and roller bearings | 46 |
| 1.3.5.8.1a — Stuffing box without lantern ring | 60 |
| 1.3.5.8.1b — Stuffing box with lantern ring | 60 |
| 1.3.5.8.2.1a — Mechanical seal classification by arrangement | 62 |
| 1.3.5.8.2.1b — Mechanical seal classification by design. | 62 |
| 1.3.5.8.6.1 — Types of bearing housing shaft seals | 65 |
| 1.3.5.8.6.3a — Lip seal | 66 |
| 1.3.5.8.6.3b — Lip seal with secondary V-ring | 66 |
| 1.3.5.8.6.8 — Bearing isolator | 67 |
| 1.3.6.1.1a — Pump performance curve versus system curve | 67 |
| 1.3.6.1.1b — Variable speed curve | 68 |
| 1.3.6.1.2a — Pumps operating in series | 68 |
| 1.3.6.1.2b — Pumps operating in parallel | 69 |

| | |
|--|-----|
| 1.3.6.1.4a — Impeller with straight outside diameter | 70 |
| 1.3.6.1.4b — Impeller with angled outside diameter | 70 |
| 1.3.6.1.4c — Trimming only the impeller vane | 71 |
| 1.3.6.3.5a — NPSHR reduction for pumps handling hydrocarbon liquids and high-temperature water (metric units) | 76 |
| 1.3.6.3.5b — NPSHR reduction for pumps handling hydrocarbon liquids and high-temperature water (US customary units) | 77 |
| 1.3.6.13a — Torque curve | 85 |
| 1.3.6.13b — Evaluation of pump torque versus speed (metric units) | 86 |
| 1.3.6.13c — Evaluation of pump torque versus speed (US customary units) | 87 |
| 1.3.6.13d — Plotting torque versus speed (metric units) | 89 |
| 1.3.6.13e — Plotting pump torque versus speed (US customary units) | 91 |
| 1.3.7.1a — Combining sound pressure | 93 |
| 1.3.7.1b — dBA correction for impeller trim and percent BEP operation | 94 |
| 1.3.8.2.1a — Grouted baseplate, fabricated steel | 97 |
| 1.3.8.2.1b — Grouted baseplate, cast iron | 98 |
| 1.3.8.2.2 — Nongrout baseplate | 98 |
| 1.3.8.2.3 — PregROUTed baseplate | 99 |
| 1.3.8.2.4 — Soleplate | 100 |
| 1.3.8.2.5a — Freestanding baseplate | 100 |
| 1.3.8.2.5b — Baseplate mounting springs with slide bearing | 100 |
| 1.3.8.2.6.1 — ASME B73.1 pump and baseplate | 101 |
| 1.3.8.2.6.2 — ISO pump and baseplate | 102 |
| 1.3.8.2.7.1 — Formed polymer baseplate | 103 |
| 1.3.8.2.7.2 — Polymer concrete base | 103 |
| 1.3.8.2.7.3 — Pedestal baseplate | 104 |
| 1.3.8.2.8 — Oil pipeline skid type baseplate | 105 |
| 1.3.8.2.9 — Offshore skid type baseplate | 105 |
| 1.3.8.2.10a — Three-point mount type baseplate | 106 |
| 1.3.8.2.10b — Underside of the three-point mount baseplate (O, P, and Q show the mounting points) | 106 |
| A.1 — Overhung pump types and classifications | 111 |
| A.2 — Between-bearing pump types and classifications | 112 |
| A.3 — Vertically suspended pump types and classifications | 112 |
| A.4 — Turbine characteristics | 115 |
| A.5 — Turbine performance | 117 |
| A.6 — Dry pit pump — overhung flexibly coupled vertical end suction | 118 |
| A.7 — Dry pit pump — overhung close coupled vertical end suction | 118 |
| A.8 — Dry pit pump — overhung foot mounted flexibly coupled horizontal end suction | 118 |
| A.9 — Self-priming pump — construction industry | 120 |
| A.10 — Self-priming pump — chemical industry | 121 |
| A.11 — Two-phase pumping applications | 122 |
| A.12 — Helico-axial multiphase pump | 123 |
| A.13 — Screw-type multiphase pump | 124 |
| A.14 — Effect of gas on pump performance | 125 |
| A.15 — Venting the eye of the impeller | 125 |
| A.16 — Top suction impeller | 125 |
| B.1 — Regenerative turbine pumps types and classifications | 126 |
| B.2 — Regenerative turbine — impeller between bearings — two stage | 127 |

| | |
|---|-----|
| B.3 — Regenerative turbine flow path | 128 |
| B.4 — Regenerative turbine pump performance | 130 |
| B.5 — Cross section of Pitot tube pump | 132 |
| B.6 — Rotating assembly | 133 |
| B.7 — Pitot tube pump performance | 135 |
| B.8 — Type VS4 line-shaft design sump pump | 139 |
| B.9 — Tailpipe and float control | 142 |
| B.10 — Rate of flow versus minimum submergence | 143 |
| B.11 — Schematic showing vaporproof/pressurized design | 145 |
| B.12 — Alarms and controls | 146 |
| B.13 — Applied forces and moments | 146 |
| B.14 — Type VS5 cantilever shaft design sump pump | 148 |
| B.15 — Rate of flow versus minimum submergence | 151 |
| B.16 — Applied forces and moments | 152 |
| C.1 — Torque–speed curves for NEMA Design AC motors | 160 |
| C.2 — Design A, B, C, and D for AC motors | 161 |
| C.3 — Outline of an internal combustion engine | 175 |
| Tables | |
| 1.3.2.2 — Principal symbols | 5 |
| 1.3.5.5.2.1 — Rolling element bearing type | 44 |
| 1.3.5.5.3.5 — Life adjustment factors | 50 |
| 1.3.5.5.3.6 — Oil contamination factor η_c | 52 |
| 1.3.5.7 — Shaft couplings - functions and parameters for selection | 58 |
| 1.3.6.11a — Guidelines for minimum and maximum liquid temperature for gray iron, ductile iron, carbon steel, chrome steel, austenitic stainless and duplex stainless steel pumps (°C) | 84 |
| 1.3.6.11b — Guidelines for minimum and maximum liquid temperature for gray iron, ductile iron, carbon steel, chrome steel, austenitic stainless and duplex stainless steel pumps (°F). | 84 |
| 1.3.7.1 — Multistage pump sound pressure reductions. | 93 |
| 1.3.8.1 — Functions of a baseplate and parameters for selection. | 95 |
| C.1 — Drivers – functions and parameters for selection | 154 |
| C.2 — Common electric motor enclosure types. | 157 |
| C.3 — IP classification system. | 158 |
| C.4 — Definition of second numeral in IP classification system | 158 |

This page intentionally blank.

Foreword (Not part of Standard)

Scope

The purpose and aims of the Institute are to promote the continued growth of pump knowledge for the interest of pump users and manufacturers and to further the interests of the public in such matters as are involved in manufacturing, engineering, distribution, safety, transportation and other problems of the industry, and to this end, among other things:

- a) To develop and publish standards for pumps;
- b) To collect and disseminate information of value to its members and to the public;
- c) To appear for its members before governmental departments and agencies and other bodies in regard to matters affecting the industry;
- d) To increase the amount and to improve the quality of pump service to the public;
- e) To support educational and research activities;
- f) To promote the business interests of its members but not to engage in business of the kind ordinarily carried on for profit or to perform particular services for its members or individual persons as distinguished from activities to improve the business conditions and lawful interests of all of its members.

Purpose of Standards

- 1) Hydraulic Institute Standards are adopted in the public interest and are designed to help eliminate misunderstandings between the manufacturer, the purchaser and/or the user and to assist the purchaser in selecting and obtaining the proper product for a particular need.
- 2) Use of Hydraulic Institute Standards is completely voluntary. Existence of Hydraulic Institute Standards does not in any respect preclude a member from manufacturing or selling products not conforming to the Standards.

Definition of a Standard of the Hydraulic Institute

Quoting from Article XV, Standards, of the By-Laws of the Institute, Section B:

"An Institute Standard defines the product, material, process or procedure with reference to one or more of the following: nomenclature, composition, construction, dimensions, tolerances, safety, operating characteristics, performance, quality, rating, testing and service for which designed."

Comments from users

Comments from users of this standard will be appreciated to help the Hydraulic Institute prepare even more useful future editions. Questions arising from the content of this standard may be sent to the Technical Director of the Hydraulic Institute. The inquiry will then be directed to the appropriate technical committee for provision of a suitable answer.

If a dispute arises regarding the content of an Institute Standard or an answer provided by the Institute to a question such as indicated above, the point in question shall be sent in writing to the Technical Director of the Hydraulic Institute, who shall initiate the appeals process.

Revisions

The Standards of the Hydraulic Institute are subject to constant review, and revisions are undertaken whenever it is found necessary because of new developments and progress in the art. If no revisions are made for five years, the standards are reaffirmed using the ANSI canvass procedure.