



American National Standard for

Rotodynamic Pumps

for Vibration Measurements and
Allowable Values

ANSI/HI 9.6.4-2016



6 Campus Drive
First Floor North
Parsippany, New Jersey
07054-4406
www.Pumps.org

This is a preview of "ANSI/HI 9.6.4-2016". [Click here to purchase the full version from the ANSI store.](#)

This page intentionally blank.

ANSI/HI 9.6.4-2016

American National Standard for
Rotodynamic Pumps
for Vibration Measurements and
Allowable Values

Sponsor
Hydraulic Institute
www.Pumps.org

Approved November 7, 2016
American National Standards Institute, Inc.

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published By

Hydraulic Institute
6 Campus Drive, First Floor North
Parsippany, NJ 07054-4406

www.Pumps.org

Copyright © 2016 Hydraulic Institute
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN 978-1-935762-54-6



Recycled
paper

Contents

	Page
Foreword	v
9.6.4 Rotodynamic pumps for vibration measurements and allowable values.....	1
9.6.4.1 Introduction and scope	1
9.6.4.1.1 Introduction	1
9.6.4.1.2 Scope.....	1
9.6.4.2 Bearing housing vibration measurement.....	2
9.6.4.2.1 Measurement procedure and units	2
9.6.4.2.2 Vibration measurement instrumentation and transducers	3
9.6.4.2.3 Measurement locations and directions.....	4
9.6.4.2.4 Vibration acceptance tests.....	4
9.6.4.2.5 Allowable pump bearing housing vibration.....	7
Appendix A Test report (informative)	11
Appendix B Factors affecting vibration (informative)	13
B.1 Residual mechanical unbalance of rotating parts	13
B.2 Residual mechanical unbalance of rotating parts - abrasive fluids	17
B.3 Pump and driver natural frequency and resonance.....	17
B.4 Miscellaneous mechanical problems	17
B.5 Hydraulic disturbances.....	18
B.6 Hydraulic resonance in piping	18
B.7 Managing vibration of vertical structures	19
Appendix C Guideline for motor vibration for vertical pumps (informative).....	20
C.1 Introduction and recommendation	20
C.2 Background	21
Appendix D Vibration source identification chart (informative)	22
Appendix E Vibration transducer mounting and sensitivity (informative)	23
Appendix F Vibration transducer types (informative)	25
Appendix G Index	27
 Figures	
9.6.4.2.2.2 — Mounting methods for vibration transducers	4
9.6.4.2.3.1 — Measurement locations and directions	5
9.6.4.2.5.1a — Allowable pump vibration, pump types BB and OH.....	8
9.6.4.2.5.1b — Allowable pump vibration, pump types VS1, VS2, VS3, VS4, VS5, VS6, VS7, and VS8	8
9.6.4.2.5.1c — Allowable pump vibration, solids-handling pump types.....	9
9.6.4.2.5.1d — Allowable pump vibration, horizontal and vertical slurry pump types (excluding wet pit cantilever belt-driven pumps with overhung motors).....	9
B.1 — Center of gravity displacement or acceptable residual unbalance (balance grade G6.3) – metric units	14
B.2 — Center of gravity displacement or acceptable residual unbalance (balance grade G6.3) – US customary units	15

B.3 — Single suction impeller	16
B.4 — Double suction impeller	16
C.1 — Guidelines for acceptable vibration levels at the top of the motor	20
E.1 — Typical response of three mounting types	23
Tables	
9.6.4.2.5.2a — Additional acceptance criteria for pumps operating at 600 rpm and below	10
9.6.4.2.5.2b — Additive values to Table 9.6.4.2.5.2a	10

Foreword (Not part of Standard)

Purpose and aims of the Hydraulic Institute

The purpose and aims of the Hydraulic Institute are to promote the advancement of the pump manufacturing industry and further the interests of the public and to this end, among other things:

- a) Develop and publish standards.
- b) Address pump systems.
- c) Expand knowledge and resources.
- d) Educate the marketplace.
- e) Advocate for the industry.

Purpose of Standards and Guidelines

- a) Hydraulic Institute Standards and Guidelines are adopted in the public interest and are designed to help eliminate misunderstandings between the manufacturer, the purchaser, and/or the user and to assist the purchaser in selecting and obtaining the proper product for a particular need.
- b) Use of Hydraulic Institute Standards and Guidelines is completely voluntary. Existence of Hydraulic Institute Standards does not in any respect preclude a member from manufacturing or selling products not conforming to the standards.

Definition of a Standard of the Hydraulic Institute

Quoting from Article XV, Standards, of the By-Laws of the Institute, Section B:

“An Institute Standard defines the product, material, process or procedure with reference to one or more of the following: nomenclature, composition, construction, dimensions, tolerances, safety, operating characteristics, performance, quality, rating, testing and service for which designed.”

Definition of a Hydraulic Institute Guideline

A Hydraulic Institute Guideline is not normative. The guideline is tutorial in nature, to help the reader better understand the subject matter.

Comments from users

Comments from users of this standard will be appreciated, to help the Hydraulic Institute prepare even more useful future editions. Questions arising from the content of this standard may be directed to the Technical Director of the Hydraulic Institute. If appropriate, the inquiry will then be directed to the appropriate technical committee for provision of a suitable answer.

Revisions

American National Standards of the Hydraulic Institute are subject to constant review, and revisions are undertaken whenever it is found necessary because of new developments and progress in the art. If no revisions are made for five years, the standards are reaffirmed using the ANSI canvass procedure.

Disclaimer

This document was prepared by a committee of the Hydraulic Institute and approved by following ANSI essential requirements. Neither the Hydraulic Institute, Hydraulic Institute committees, nor any person acting on behalf of the Hydraulic Institute: 1) makes any warranty, expressed or implied, with respect to the use of any information, apparatus, method, or process disclosed in this document or guarantees that such may not infringe privately owned rights; 2) assumes any liabilities with respect to the use of, or for damages resulting from the use of, any information, apparatus, method, or process disclosed in this guideline. The Hydraulic Institute is in no way responsible for