



American National Standard for

Rotodynamic (Centrifugal and Vertical) Pumps

– Guideline for Condition Monitoring

ANSI/HI 9.6.5-2009



6 Campus Drive
First Floor North
Parsippany, New Jersey
07054-4406
www.Pumps.org

This is a preview of "ANSI/HI 9.6.5-2009". [Click here to purchase the full version from the ANSI store.](#)

This page intentionally blank.

ANSI/HI 9.6.5-2009

American National Standard for
**Rotodynamic (Centrifugal and
Vertical) Pumps —
Guideline for Condition Monitoring**

Sponsor
Hydraulic Institute
www.Pumps.org

Approved October 13, 2009
American National Standards Institute, Inc.

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published By

Hydraulic Institute
6 Campus Drive, First Floor North
Parsippany, NJ 07054-4406

www.Pumps.org

Copyright © 2009 Hydraulic Institute
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN 978-1-880952-89-4



Recycled
paper

Contents

	Page
Foreword	vii
9.6.5 Rotodynamic (Centrifugal and Vertical) Pumps for Condition Monitoring.....	1
9.6.5.0 Scope	1
9.6.5.0.1 Purpose.....	1
9.6.5.0.2 Use of this document	1
9.6.5.0.3 Monitoring frequency	2
9.6.5.0.4 Control limits	3
9.6.5.1 Power monitoring	4
9.6.5.1.1 Introduction	4
9.6.5.1.2 Means of power monitoring.....	4
9.6.5.1.3 Power monitoring frequency	5
9.6.5.1.4 Power control limits.....	5
9.6.5.2 Temperature monitoring	5
9.6.5.2.1 Introduction	5
9.6.5.2.2 Means of monitoring temperature.....	5
9.6.5.2.3 Specific applications of temperature monitoring	5
9.6.5.2.4 Sealless pump liquid temperature.....	6
9.6.5.2.5 Temperature monitoring frequency.....	7
9.6.5.2.6 Temperature control limits	7
9.6.5.3 Corrosion monitoring.....	7
9.6.5.3.1 Introduction	7
9.6.5.3.2 Means of corrosion monitoring	7
9.6.5.3.3 Corrosion monitoring frequency	8
9.6.5.3.4 Corrosion parameter control limits	8
9.6.5.4 Leakage monitoring	9
9.6.5.4.1 Introduction	9
9.6.5.4.2 Means of monitoring leakage	9
9.6.5.4.3 Leakage monitoring frequency	10
9.6.5.4.4 Leakage control limits.....	11
9.6.5.4.5 Leakage control limits for gas seal consumption	11
9.6.5.5 Pressure monitoring	11
9.6.5.5.1 Introduction	11
9.6.5.5.2 Means of pressure monitoring	11
9.6.5.5.3 Pressure monitoring frequency.....	11
9.6.5.5.4 Pressure control limits.....	11

9.6.5.6	Vibration monitoring	12
9.6.5.6.1	Introduction	12
9.6.5.6.2	Means of vibration monitoring	12
9.6.5.6.3	Vibration monitoring frequency	13
9.6.5.6.4	Vibration control limits	13
9.6.5.7	Periodic lubricant analysis	13
9.6.5.7.1	Introduction	13
9.6.5.7.2	Measuring metal particles from wear	13
9.6.5.7.3	Measuring contamination of lubricant	14
9.6.5.7.4	Measuring lubricant degradation	15
9.6.5.7.5	Lubricant sampling techniques	15
9.6.5.7.6	Lubricant monitoring frequency	15
9.6.5.7.7	Lubricant control limits	15
9.6.5.8	Shaft position monitoring	15
9.6.5.8.1	Introduction	15
9.6.5.8.2	How to monitor shaft position	16
9.6.5.8.3	Shaft monitoring frequency	16
9.6.5.8.4	Shaft control limits	16
9.6.5.9	Rate-of-flow monitoring	16
9.6.5.9.1	Introduction	16
9.6.5.9.2	Measuring rate of flow	16
9.6.5.9.3	Rate-of-flow monitoring frequency	16
9.6.5.9.4	Rate-of-flow control limits	16
9.6.5.10	Maintenance inspection	17
9.6.5.10.1	Introduction	17
9.6.5.10.2	Maintenance inspection practice	17
9.6.5.10.3	Maintenance inspection frequency	19
9.6.5.11	Speed (rpm) monitoring	19
9.6.5.11.1	Introduction	19
9.6.5.11.2	Speed measurement methods	19
9.6.5.11.3	Speed monitoring frequency	20
9.6.5.11.4	Speed control limits	20
9.6.5.12	Bearing wear monitoring of plain bearings in sealless pumps	20
9.6.5.12.1	Introduction	20
9.6.5.12.2	Means of detecting bearing wear	20
9.6.5.12.3	Bearing wear monitoring frequency	21
9.6.5.12.4	Bearing wear control limits	21

9.6.5.13	Preinstallation hydrostatic test	21
9.6.5.13.1	Introduction	21
9.6.5.13.2	Means of conducting a preinstallation hydrostatic test	22
9.6.5.13.3	Hydrostatic test monitoring frequency.	22
9.6.5.13.4	Hydrostatic test control limits	22
9.6.5.14	Design review	22
9.6.5.14.1	Introduction	22
9.6.5.14.2	Design review practice	22
9.6.5.14.3	Design review frequency.	24
Appendix A	Condition Monitoring, Failure Modes	25
Appendix B	Condition Monitoring Indicators	31
Appendix C	Definitions	36
Appendix D	Index	38
Tables		
9.6.5.0.3a	— Severity levels	2
9.6.5.0.3b	— Frequency of monitoring.	3
9.6.5.4.2.6	— Application guidelines for leakage monitoring systems' mechanical seals	10
A.1	— Condition monitoring failure modes	25
A.2	— Additional failure modes for sealless pumps and pumps with journal bearings	30
B.1	— Condition monitoring indicators.	31

This page intentionally blank.

Foreword (Not part of Standard)

Purpose and aims of the Hydraulic Institute

The purpose and aims of the Institute are to promote the continued growth and well-being of pump manufacturers and further the interests of the public in such matters as are involved in manufacturing, engineering, distribution, safety, transportation and other problems of the industry, and to this end, among other things:

- a) To develop and publish standards and guidelines for pumps;
- b) To collect and disseminate information of value to its members and to the public;
- c) To appear for its members before governmental departments and agencies and other bodies in regard to matters affecting the industry;
- d) To increase the amount and to improve the quality of pump service to the public;
- e) To support educational and research activities;
- f) To promote the business interests of its members but not to engage in business of the kind ordinarily carried on for profit or to perform particular services for its members or individual persons as distinguished from activities to improve the business conditions and lawful interests of all of its members.

Purpose of Standards and Guidelines

- 1) Hydraulic Institute Standards and Guidelines are adopted in the public interest and are designed to help eliminate misunderstandings between the manufacturer, the purchaser and/or the user and to assist the purchaser in selecting and obtaining the proper product for a particular need.
- 2) Use of Hydraulic Institute Standards and Guidelines is completely voluntary. Existence of Hydraulic Institute Standards does not in any respect preclude a member from manufacturing or selling products not conforming to the Standards.

Definition of a Hydraulic Institute Guideline

A Hydraulic Institute Guideline is not normative. The guideline is tutorial in nature, to help the reader better understand the subject matter.

Comments from users

Comments from users of this guideline will be appreciated, to help the Hydraulic Institute prepare even more useful future editions. Questions arising from the content of this guideline may be directed to the Hydraulic Institute. It will direct all such questions to the appropriate technical committee for provision of a suitable answer.

If a dispute arises regarding contents of an Institute publication or an answer provided by the Institute to a question such as indicated above, the point in question shall be sent in writing to the Technical Director of the Hydraulic Institute, who shall initiate the Appeals Process.

Revisions

The Standards and Guidelines of the Hydraulic Institute are subject to constant review, and revisions are undertaken whenever it is found necessary because of new developments and progress in the art. If no revisions are made for five years, the standards and guidelines are reaffirmed using the ANSI canvass procedure.

Units of measurement

Metric units of measurement are used and corresponding US customary units appear in brackets. Charts, graphs, and sample calculations are also shown in both metric and US customary units. Since values given in metric units are not exact equivalents to values given in US customary units, it is important that the selected units of measure to be applied be stated in reference to this guideline. If no such statement is provided, metric units shall govern.