



American National Standard for

Rotodynamic Pumps

for Pump Intake Design

ANSI/HI 9.8-2012



6 Campus Drive
First Floor North
Parsippany, New Jersey
07054-4406
www.Pumps.org

This page intentionally blank.

ANSI/HI 9.8-2012

American National Standard for
Rotodynamic Pumps
for Pump Intake Design

Sponsor
Hydraulic Institute
www.Pumps.org

Approved December 4, 2012
American National Standards Institute, Inc.

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published By

Hydraulic Institute
6 Campus Drive, First Floor North
Parsippany, NJ 07054-4406

www.Pumps.org

Copyright © 2012 Hydraulic Institute
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN 978-880952-70-2



Recycled
paper

Contents

	Page
Foreword	vii
9.8 Pump intake design	1
9.8.1 Design objectives	1
9.8.2 Intake structures for clear liquids	2
9.8.2.1 Rectangular intakes	2
9.8.2.2 Formed suction intakes	8
9.8.2.3 Circular pump stations (clear liquids)	9
9.8.2.4 Trench-type intakes (clear liquids)	13
9.8.2.5 Tanks - pump suction	15
9.8.2.6 Can vertical turbine pump intakes (clear liquids), including those with submersible motors (refer to Appendix G)	17
9.8.2.7 Unconfined intakes (Figure 9.8.2.7)	21
9.8.3 Intake structures for solids-bearing liquids	23
9.8.3.1 General	23
9.8.3.2 Trench-type wet wells for solids-bearing liquids	25
9.8.3.3 Circular plan wet pit for solids-bearing liquids	28
9.8.3.4 Rectangular wet wells for solids-bearing liquids	30
9.8.4 Physical model studies of intake structures and pump suction piping	32
9.8.4.1 Need for a physical model study	32
9.8.4.2 Physical model study objectives	33
9.8.4.3 Physical model similitude and scale selection	33
9.8.4.4 Physical model study scope	35
9.8.4.5 Instrumentation and measuring techniques	36
9.8.4.6 Test plan	38
9.8.4.7 Acceptance criteria	39
9.8.4.8 Report preparation	39
9.8.5 Inlet bell design diameter (D)	39
9.8.5.1 General	39
9.8.5.2 Objective	39
9.8.6 Required submergence for minimizing surface vortices	43
9.8.6.1 General	43
9.8.6.2 Controlling parameters	43
9.8.6.3 Application considerations	44
9.8.7 Use of computational fluid dynamics (CFD)	45
9.8.7.1 General	45
9.8.7.2 Simulation methods	48
9.8.7.3 Correlation of simulation and experimental results	48
9.8.7.4 Acceptable uses of computational fluid dynamics (CFD)	48

9.8.8	Glossary and nomenclature	48
9.8.8.1	Glossary	48
9.8.8.2	Nomenclature	54
Appendix A	Remedial measures for problem intakes	60
Appendix B	Sump volume	75
Appendix C	Intake basin entrance conditions, trench-type wet wells for solids-bearing liquids	79
Appendix D	Performance enhancements for trench-type wet wells	84
Appendix E	Aspects of design of rectangular wet wells for solids-bearing liquids	89
Appendix F	Suction bell design	95
Appendix G	Submersible pumps – well motor type	97
Appendix H	Modification of existing pumping systems	98
Appendix I	Alternate formed suction intake designs	99
Appendix J	Rectangular intakes for shallow liquid source	103
Appendix K	Influence of pump selection on intake design	107
Appendix L	References	110
Appendix M	Index	112

Figures

9.8.2.1.4a	— Rectangular intake structure layout	5
9.8.2.1.4b	— Filler wall details for proper bay width	6
9.8.2.2.2	— Formed suction intake	10
9.8.2.3.1a	— Wet-pit duplex sump with pumps offset	11
9.8.2.3.1b	— Wet-pit duplex sump with pumps on centerline	11
9.8.2.3.1c	— Dry-pit/wet-pit duplex sump	11
9.8.2.3.1d	— Wet-pit triplex sump, pumps in line	11
9.8.2.3.1e	— Wet-pit triplex sump, compact	11
9.8.2.3.1f	— Dry-pit/wet-pit triplex sump	11
9.8.2.4.1a	— Trench-type wet well	13
9.8.2.4.1b	— Trench-type wet well with formed suction inlet	14
9.8.2.5.4	— Datum for calculation of submergence	17
9.8.2.5.5	— Definitions of V and D for calculation of submergence	18
9.8.2.6.4	— Open bottom can intakes	20
9.8.2.6.5	— Closed bottom can	21
9.8.2.7	— Unconfined intakes	22
9.8.3.2.2	— Open trench-type wet well	26
9.8.3.3.1a	— Circular wet pit with sloping walls and minimized horizontal floor area (dry-pit pumps)	29
9.8.3.3.1b	— Circular wet pit with sloping walls and minimized horizontal floor area (submersible pumps shown for illustration)	29
9.8.3.3.1c	— Circular wet pit with sloping walls and minimized horizontal floor area (wet-pit pumps shown for illustration)	30

9.8.3.4.4 — Confined wet-well design	31
9.8.4.5a — Classification of free surface and subsurface vortices	37
9.8.4.5b — Typical swirl meter.	38
9.8.5.2a — Inlet bell design diameter (metric units).	41
9.8.5.2b — Inlet bell design diameter (US customary units)	42
9.8.6.3a — Minimum submergence to minimize free surface vortices (metric units).	46
9.8.6.3b — Minimum submergence to minimize free surface vortices (US customary units)	47
A.1 — Examples of approach flow conditions at intake structures and the resulting effect on velocity, all pumps operating.	62
A.2 — Examples of pump approach flow patterns for various combinations of operating pumps	63
A.3 — Comparison of flow patterns in open and partitioned sumps	64
A.4 — Effect of trash rack design and location on velocity distribution entering pump bay.	64
A.5 — Flow-guiding devices at entrance to individual pump bays.	65
A.6 — Concentrated influent configuration, with and without flow distribution devices	66
A.7 — Baffling to improve flow pattern downstream from dual flow screen.	67
A.8 — Typical flow pattern through a dual flow screen	67
A.9 — Improvements to approach flow without diverging sump walls.	68
A.10 — Elevation view of a curtain wall for minimizing surface vortices	69
A.11 — Methods to reduce subsurface vortices (examples i – ix)	70
A.12 — Combination of remedial corrections	71
A.13 — Tank antivortex devices	73
A.14 — Tank inflow and outflow configurations	74
B.1 — Graphical analysis for liquid-level controllers	76
B.2 — Graphical analysis for a “smart” controller	78
C.1 — Schematic diagram of approach pipe	80
D.1 — Open trench-type wet well hydraulic jump	85
D.2 — Open trench-type wet well with inlet baffle.	85
D.3 — Suction bell vanes.	85
D.4 — Floor cone with vanes for clear liquids	86
D.5 — Floor cone with vanes for solids-bearing liquids.	86
D.6 — Flow splitter in wet well	86
E.1 — Front – high-level entry	91
E.2 — Schematic, front – high-level entry	91
E.3 — Side – high-level entry	92
E.4 — Schematic, side – high-level entry	92
E.5 — Side – low-level entry	93
E.6 — Schematic, side – low-level entry	93
E.7 — Recommended sump dimensions.	94
F.1 — Bell intake shapes	96
G.1 — Submersible vertical turbine pump	97
I.1a — Stork-type FSI, plan view	100

I.1b — Stork-type FSI, elevation view	100
I.1c — Stork-type FSI, perspective view	100
I.2 — Shoe-box-type FSI, plan view	101
I.3 — Shoe-box-type FSI, Section B	101
I.4 — Shoe-box-type FSI, Section A	102
J.1 — Configuration for rectangular intakes withdrawing from shallow liquid source, maximum three pumps (refer to Figure J.2)	105
J.2 — Pump bay details near the pump bells for rectangular intakes with a shallow liquid source	106
K.1 — Simplified system curve	108
K.2 — Multiple system curves	108
K.3 — Multiple system curves, variable speed	109
Tables	
9.8.2.1.4a — Dimensions for Figures 9.8.2.1.4a and b	6
9.8.2.1.4b — Design sequence, rectangular intake structures	8
9.8.5.2a — Acceptable velocity ranges for inlet bell diameter D (metric units)	40
9.8.5.2b — Acceptable velocity ranges for inlet bell diameter D (US customary units)	40
9.8.8.2 — Nomenclature	54
C.1 — Maximum allowable flow rates in approach pipes (metric units)	81
C.2 — Maximum allowable flow rates in approach pipes (US customary units)	82

Foreword (Not part of Standard)

Purpose and aims of the Hydraulic Institute

The purpose and aims of the Institute are to promote the continued growth of pump knowledge for the interest of pump manufacturers and to further the interests of the public in such matters as are involved in manufacturing, engineering, distribution, safety, transportation and other problems of the industry, and to this end, among other things:

- a) To develop and publish standards for pumps;
- b) To collect and disseminate information of value to its members and to the public;
- c) To appear for its members before governmental departments and agencies and other bodies in regard to matters affecting the industry;
- d) To increase the amount and to improve the quality of pump service to the public;
- e) To support educational and research activities;
- f) To promote the business interests of its members but not to engage in business of the kind ordinarily carried on for profit or to perform particular services for its members or individual persons as distinguished from activities to improve the business conditions and lawful interests of all of its members.

Purpose of Standards

- 1) Hydraulic Institute Standards are adopted in the public interest and are designed to help eliminate misunderstandings between the manufacturer, the purchaser and/or the user and to assist the purchaser in selecting and obtaining the proper product for a particular need.
- 2) Use of Hydraulic Institute Standards is completely voluntary. Existence of Hydraulic Institute Standards does not in any respect preclude a member from manufacturing or selling products not conforming to the Standards.

Definition of a Standard of the Hydraulic Institute

Quoting from Article XV, Standards, of the By-Laws of the Institute, Section B:

"An Institute Standard defines the product, material, process or procedure with reference to one or more of the following: nomenclature, composition, construction, dimensions, tolerances, safety, operating characteristics, performance, quality, rating, testing and service for which designed."

Comments from users

Comments from users of this standard will be appreciated, to help the Hydraulic Institute prepare even more useful future editions. Questions arising from the content of this standard may be directed to the Technical Director of the Hydraulic Institute. The inquiry will then be directed to the appropriate technical committee for provision of a suitable answer.

If a dispute arises regarding contents of an Institute publication or an answer provided by the Institute to a question such as indicated above, then the point in question shall be sent in writing to the Technical Director of the Hydraulic Institute, who shall initiate the Appeals Process.

Revisions

The Standards of the Hydraulic Institute are subject to constant review, and revisions are undertaken whenever it is found necessary because of new developments and progress in the art. If no revisions are made for five years, the standards are reaffirmed using the ANSI canvass procedure.