



This is a preview of "IEC 60417-DB-3M Ed. ...". [Click here to purchase the full version from the ANSI store.](#)

The database on Graphical Symbols for Use on Equipment contains the complete set of graphical symbols included in IEC 60417 and ISO 7000. It therefore offers end-users a "one-stop" shop for all such graphical symbols. These International Standards are maintained respectively by IEC/TC 3, subcommittee SC 3C and ISO/TC 145, subcommittee SC 3.

Each graphical symbol is identified by a reference number and contains a title (in English and French), a graphical representation in GIF and vectorized PDF format, and some additional data as applicable. Various search and navigation facilities allow for easy retrieval of graphical symbols.

Subscriptions

Customers have the possibility to subscribe to the joint IEC and ISO collection of symbols or to each respective organization's symbols only.

[Joint IEC 60417 and ISO 7000 collection](#)

The most cost effective solution is the combined collection which offers the IEC 60417 and ISO 7000 collections in database format, with the possibility to download IEC 60417 snapshots or the ISO 7000 standard in PDF format. In order to subscribe please contact your local IEC National Committee/approved sales outlet or local ISO member, or visit the [IEC Webstore](#) or the [ISO Store](#).

[IEC 60417 collection only](#)

If you are only interested in those graphical symbols produced by the IEC, then this restricted collection offers you access to the IEC 60417 standard only, with PDF snapshots of the entire collection available for added value. In order to subscribe please contact your local IEC National Committee/approved sales outlet or visit the [IEC Webstore](#).

[ISO 7000 collection only](#)

If you are only interested in those graphical symbols produced by ISO, then this restricted collection offers you access to the ISO 7000 standard only, with a PDF version of ISO 7000 available for added value. In order to subscribe please contact your local ISO member or visit the [ISO Store](#).

Special access requests

IEC National Committees ([click here](#))

ISO members ([click here](#))

IEC TC/SC Officers ([click here](#))

ISO TC/SC Officers ([click here](#))

IEC National Committees and ISO Member Bodies should indicate the names of the staff members to be authorized and the username used for accessing documents on the IEC or ISO web site respectively.

TC/SC officers should indicate their position with respect to a given TC/SC (chair, secretary, convenor) and the username used for accessing documents on the IEC or ISO web site respectively.

Localized versions

In addition to the international standard IEC 60417 maintained by IEC/TC 3, subcommittee SC 3C, IEC also hosts localized versions of IEC 60417 maintained under the responsibility of the respective National Committee. The following localized version is currently available:

[Japanese](#)

Queries and comments

Please send any queries or comments to the [IEC Customer Service Centre](#) or to [ISO Customer Services](#).

This is a preview of "IEC 60417-DB-3M Ed. ...". [Click here to purchase the full version from the ANSI store.](#)

Graphical Symbols for Use on Equipment

[Home](#)
[Introduction](#)
[General description](#)
[Symbols by:](#)
[Symbol ID](#)
[Name \(IEC 60417\)](#)
[Name \(ISO 7000\)](#)
[Keywords](#)
[Shape](#)
[Function](#)
[Application](#)
[TC/SC](#)
[Publication](#)
[Status](#)
[Date of release](#)
[Advanced Search](#)
[Snapshots \(PDF\)](#)
[Print overview](#)
[Contact](#)
[Maintenance:](#)
[CR for action](#)
[CR by status](#)
[CR by number](#)
[Lists](#)
[Keywords](#)
[New symbol](#)
[New CR](#)
[New list item](#)
[Report: IEC CRs](#)
[Report: IEC Symbols](#)
[Report: ISO CRs](#)
[Report: ISO Symbols](#)

Introduction

The database is organized as a set of "data sheets" describing the graphical symbols and their attributes. Please click on "General description" on the left panel to see how the database is structured and how to use graphical symbols.

IEC 60417 is used as a reference by the following IEC member countries:

Austria, Belgium, Canada, Cyprus, Czech Republic, Denmark, Finland, France, Germany, Ireland, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Spain, Sweden, Switzerland, Ukraine, United Kingdom

Languages

The database is bilingual with all symbol data available in English and French (not always true for ISO 7000 graphical symbols). While viewing a symbol data sheet you can switch back and forth between the two languages.

Links

All items in blue represent links to other elements or to specific action.

Finding a symbol

The database provides two methods for finding a symbol:

1. Search function (top right of each page)

You can combine two search terms with a boolean "AND", "OR" or "NOT" operator.

2. Categorized views

Symbols are categorized by symbol ID, name, keyword, shape, function, application, TC/SC, publication and status. Some of the views are presently not available for ISO 7000 graphical symbols.

Snapshots

Snapshots of the database contents are made available for reference purposes in PDF format. Please click on "Snapshots" in the left panel for further information.

Submitting proposals for change requests

The maintenance process for any changes to this joint IEC 60417 and ISO 7000 database, either for the inclusion of a new graphical symbol or a change to existing graphical symbols should be initiated by a change request (CR). Details are defined in the ISO/IEC Directives (IEC specific procedures, Annex SL for IEC 60417 symbols, and ISO specific procedures, Annex ST for ISO 7000 symbols).

In drafting technical content that may be included in the CR, please refer to IEC 80416-1, *Basic principles for graphical symbols for use on equipment – Part 1: Creation of graphical symbols for registration* and ISO 80416-2: *Basic principles for graphical symbols for use on equipment – Part 2: Form and use of arrows*. The most recent guidance for the wording of the description for a symbol original can be found on both the [IEC TC 3/SC 3C](#) and [ISO TC 145/SC 3](#) website.

Proposers of such change requests can [click here](#) to send an e-mail to the secretaries of IEC SC 3C and ISO TC 145/SC 3 who are responsible for the maintenance of IEC 60417 and ISO 7000, respectively.

This is a preview of "IEC 60417-DB-3M Ed. ...". [Click here to purchase the full version from the ANSI store.](#)

Graphical Symbols for Use on Equipment

[Home](#)
[Introduction](#)
[General description](#)
[Symbols by:](#)
[Symbol ID](#)
[Name \(IEC 60417\)](#)
[Name \(ISO 7000\)](#)
[Keywords](#)
[Shape](#)
[Function](#)
[Application](#)
[TC/SC](#)
[Publication](#)
[Status](#)
[Date of release](#)
[Advanced Search](#)
[Snapshots \(PDF\)](#)
[Print overview](#)
[Contact](#)
[Maintenance:](#)
[CR for action](#)
[CR by status](#)
[CR by number](#)
[Lists](#)
[Keywords](#)
[New symbol](#)
[New CR](#)
[New list item](#)
[Report: IEC CRs](#)
[Report: IEC Symbols](#)
[Report: ISO CRs](#)
[Report: ISO Symbols](#)

General description

A graphical symbol is a visually perceptible figure used to transmit information independently of language. The graphical symbols for use on equipment are used for a wide range of purposes. For such graphical symbols, consistency in design of families of symbols used in one location or on similar equipment is an important issue, as is legibility when these symbols are reduced to small dimensions. Thus, there have been common provisions among areas covered by IEC and ISO on basic principles for graphical symbols for use on equipment to ensure visual clarity, to maintain consistency and thereby to improve recognition (see IEC 80416-1 and ISO 80416-2).

Scope

IEC 60417 graphical symbols are primarily intended to:

- identify the equipment or a part of the equipment (e.g. a control or display);
- indicate a functional state (e.g. on, off, alarm);
- designate connections (e.g. terminals, filling points for materials);
- provide information on packaging (e.g. identification of contents, instructions for handling);
- provide instruction for the operation of the equipment (e.g. limitations of use).

IEC 60417 does not apply to symbol originals for:

- safety signs;
- use on drawings and diagrams;
- use in technical documentation of products and in technical product documentation;
- use for public information.

IEC 60417 has the status of a horizontal standard in accordance with IEC Guide 108.

ISO 7000 provides a synopsis of those graphical symbols which are placed on equipment or parts of equipment of any kind in order to instruct the person(s) using the equipment as to its operation.

Structure of the database

Each graphical symbol carries a registration number (symbol ID) and a name in English and French, together with a graphical representation in GIF or PNG and in vectorized PDF format. There are also several optional fields. Below is a full listing of all the database fields. Some of them do not apply presently to ISO 7000 graphical symbols.

- Symbol ID
- Name
- Graphical representation in GIF or PNG format
- Graphical representation in vectorized PDF format
- Status
- Product area
- Description
- Notes
- Date of release
- Date of withdrawal
- Example of application class
- Function class
- Shape class
- Keywords
- Publication reference
- Relevant TCs and publications
- Replacing
- Replaced by
- Change requests

How to use released graphical symbols

The graphical symbols are intended for use on equipment; generally speaking any kind of equipment. The field "Example of application class" can be used to indicate more specifically for which type of equipment a graphical symbol is intended.

This is a preview of "IEC 60417-DB-3M Ed. ...". [Click here to purchase the full version from the ANSI store.](#)

(icons) are in ISO 80416-4.

This is a preview of "IEC 60417-DB-3M Ed. ...". Click here to purchase the full version from the ANSI store.


5001A Battery, general	Battery, general	Positioning of ear	AC/DC converter, rectifier; substitute power supply	variability	Pods, positive polarity	Pods, negative polarity	ON (power)
5008: "OFF" (power)	5009: Stand-by	5010: "ON"/"OFF" (push-push)	5011: "ON"/"OFF" (push button)	5012: Lamp; lighting; illumination	5013: Bell	5014: Horn, electrical / electromechanical	5015: Air impeller; blower; fan
5016: Fuse	5017: Earth; ground	5018: Functional earthing; functional grounding (US)	5019: Protective earth; protective ground	5020: Frame or chassis	5021: Equipotentiality	5022: Movement in one direction	5023: Movement in both directions
5024: Movement limited in both directions	5025: Effect or action away from a reference point	5026: Effect or action towards a reference point	5027: Effect or action in both directions away from a reference point	5028: Effect or action in both directions towards a reference point	5029: Non-simultaneous effect or action away from and towards a reference point	5030: Simultaneous effect or action away from and towards a reference point	5031: Direct current
5032: Alternating current	5032-1: Three-phase alternating current	5032-2: Three-phase alternating current with neutral conductor	5032-3: Two-phase alternating current	5032-4: Two-phase alternating current with neutral conductor	5032-5: Single-phase alternating current	5033: Both direct and alternating current	5034: Input current
5035: Output	5036: Dangerous voltage	5037: Treble control	5038: Bass control	5039: Aerial; antenna	5040: Dipole	5041: Caution, hot surface	5042: Frame aerial; loop antenna
5043: Tuner; radio receiver	5044: Signal strength attenuation, local/distant	5045: Tuning	5046: Automatic frequency control	5047: Muting; squelch	5048: Colour (qualifying symbol)	5049: Television; video; screen	5050: Colour television
5051: Television monitor	5052: Colour television monitor	5053: Television receiver	5054: Colour television receiver	5055: Focus	5056: Brightness; brilliance	5057: Contrast	5058: Colour saturation
5059: Crispener	5060: Hue	5061: Horizontal synchronization	5062: Vertical synchronization	5063: Horizontal picture shift	5064: Vertical picture shift	5065: Horizontal picture amplitude	5066: Vertical picture amplitude
5067: Picture size adjustment	5068: Horizontal linearity	5069: Vertical linearity	5070: Monophonic	5071: Stereophonic	5072: Balance	5073: Omnidirectional microphone	5074: Bi-directional microphone
5075: Unidirectional or cardioid microphone	5076: Earphone	5077: Headphones	5078: Stereophonic headphones	5079: Headset	5080: Loudspeaker	5081: Loudspeaker/microphone	5082: Microphone, general
5083: Stereophonic microphone	5084: Amplifier	5085: Music	5086: Pick-up for disk records	5087: Stereophonic pick-up for disk records	5088: Piezo-electric pick-up, crystal or ceramic	5089: Dynamic pick-up, electro- or magneto-dynamic	5090: Telephone; telephone adapter
5091:	5092:	5093:	5094:	5095:	5096:	5097:	5098:

IEC/ISO Graphical Symbols for Use on Equipment

High-pass filter Low-pass filter Tape recorder Magnetic tape stereo sound recorder Recording on tape Play-back or reading from tape Erasing from tape Monitoring at the input during recording on tape

This is a preview of "IEC 60417-DB-3M Ed. ...". Click here to purchase the full version from the ANSI store.

5099: Monitoring recording on tape	or reading from tape	recorders	recorders	5109: Not to be used in residential areas	5110A: Stop	5110B: Stop	5111A: Pause; interruption
5107A: Normal run; normal speed	5107B: Normal run; normal speed	5108A: Fast run; fast speed	5108B: Fast run; fast speed	5109: Not to be used in residential areas	5110A: Stop	5110B: Stop	5111A: Pause; interruption
5111B: Pause; interruption	5112: Transfer of signal	5113: Rejection	5114: Foot switch	5115: Signal lamp	5116: Television camera	5117: Colour television camera	5118: Videotape recorder
5119: Colour videotape recorder	5120: Video recording	5121: Colour video recording	5122: Video play-back	5123: Colour video play-back	5124A: Slow run; slow speed	5124B: Slow run; slow speed	5125A: Recapitulate
5125B: Recapitulate	5126: Loudspeaker in operation as a microphone	5127: Loudspeaker in operation as such	5128: Heading marker	5129: Aerial rotation; scanner rotation	5130: Pulse, general	5131: Long pulse	5132: Programmable start
5133: Bearing marker	5134: Electrostatic sensitive devices	5136: Ship's head-up presentation	5136-1: Ship's head-up presentation, heading line off	5137: North-up presentation	5138: Independent lighting auxiliary	5140: Non-ionizing electromagnetic radiation	5141: Anti sea-clutter, position of minimum
5142: Anti rain-clutter, position of minimum	5143: Range selector	5144: Range rings brilliance	5145: Variable range marker	5146: Adjustment to a minimum	5147: Adjustment to a maximum	5148: Pick-up for video disk record player	5149: Transmitted power monitor
5150: Transmit/receive monitor	5151: Hydrophone	5152: Radiation of laser apparatus	5153: Underwater sound projector	5154: Reversible transducer for underwater sound	5156: Transformer	5157: Band-pass filter	5158: Band-pass filter with variable centre frequency
5159: Band-pass filter with variable pass-band; selectivity control	5160: Band-stop filter	5161: Anti sea-clutter, position of maximum	5162: Anti rain-clutter, position of maximum	5163: Recording on an information carrier	5164: Reading or reproduction from an information carrier	5165: Erasing from an information carrier	5166: Monitoring input data during writing or recording on an information carrier
5167: Monitoring input data after writing or recording on an information carrier	5168: Monitoring output data during read-out or reproduction from an information carrier	5169: Recording lock	5170: Marker	5171: Tape cutting, general	5172: Class II equipment	5173: Signal low terminal	5177: Fast start
5178: Fast stop	5179: Test voltage	5179-1: Test voltage, impulse	5180: Class III equipment	5181: Variability in steps	5182: Sound; audio	5183: Variability, maximum step	5184: Clock; time switch; timer
5185: Rejection filter; wave trap	5186: Rectifier, general	5187: Teacher; supervisor	5188: Student; operator	5189: Group of students; group of operators	5190: All students; all operators	5191: Frame adjustment	5192: Graphical recorder
5193: Printer	5194: DC/AC-converter	5195: Variable band-stop filter	5196: Gyro indicator, general	5197: Gyro indicator, setting	5198: Gyro-compass true bearing	5199: Relative bearing	5200: Bearing ruler setting




This is a preview of "IEC 60417-DB-3M Ed. ...". Click here to purchase the full version from the ANSI store.

5220: Short-circuit-proof transformer	5221: Isolating transformer, general	5222: Safety isolating transformer, general	5223: Non-short-circuit-proof transformer	5225: Electric shaver outlet	5226: Pre-wash, textile washing machines	5227: Main wash, textile washing machines	5228: Rinsing
5229: Stop after last rinse	5230: Spinning	5231: Without spinning	5232: Special treatment	5234: High water level	5235: Low water level	5236: Draining	5237: Drying or warming operation
5244: Automatic gain control, large field	5245: Automatic gain control, small field	5249: Frequency of an alarm signal	5250: Conference	5251: Enter subscriber data into the local memory	5252: Parked call; held call	5253: (Call) transfer	5254: Link unit
5255: Travelling wave tube amplifier	5256: Signalling sender	5257: Signalling receiver	5258: Frequency of a test, identification or control signal	5259: Frequency of a synchronizing signal	5260: Demodulator	5260-1: Demodulator, primary group	5260-2: Demodulator, secondary group
5261: Modulator	5261-1: Modulator, primary group	5261-2: Modulator, secondary group	5262: Modem	5263: Principal control panel	5264: "ON" for a part of equipment	5265: "OFF" for a part of equipment	5266: Stand-by or preparatory state for a part of equipment
5267: Synchronizing function	5268: "IN" position of a bi-stable push control	5269: "OUT" position of a bi-stable push control	5270: Programmable stop; sleep timer	5271: Channel selector with logic control	5272: Harmonic generator	5273: Automatic change-over unit	5274: Manual change-over unit
5275: Overvoltage protection device	5276: Local	5276-1: Carrier, local	5276-2: Pilot, local	5276-3: Measure, local	5276-4: Signalling, local	5276-5: Alarm, local	5277: Remote
5277-1: Carrier, remote	5277-2: Pilot, remote	5277-3: Measure, remote	5277-4: Signalling, remote	5277-5: Alarm, remote	5278: Phase jitter	5279: Phase jitter filter	5280: Loop, transmission line
5281: Digital combiner	5282: Digital separator	5283: Regenerative repeater	5284: Converter with stabilized output voltage	5285: Adjustable device	5286: Distortion corrector	5286-1: Distortion corrector, amplitude/frequency	5286-2: Distortion corrector, phase/frequency
5286-3: Distortion corrector, delay/frequency	5287: Tracking	5288: Dubbing	5289: Application assistance	5290: Page hold	5291: Picture-in-picture mode	5292: Interchange	5293: Position switch having a break contact with positive opening operation
5294: Badly soiled items; cooking utensils	5295: Normally soiled items	5296: Lightly soiled items	5297: Delicate items	5298: Regenerating agent	5299: Final rinse agent	5300: Pre-wash, dish washers	5301: Main wash detergent
5302: Converter with stabilized output current	5303: Operational amplifier	5304: Equipment containing logic elements	5305: Sampling unit	5306: Comparator, general	5306-1: Comparator, voltage	5306-2: Comparator, current	5306-3: Comparator, frequency

This is a preview of "IEC 60417-DB-3M Ed. ...". Click here to purchase the full version from the ANSI store.

5307: Alarm	5315: Two-level signal	5316: Three-level signal	5317: Binary coded signal	5318: Strobe, general	5318-1: Strobe, video equipment	5319: Alarm inhibit	5320: Indirect lighting	5321: Low-intensity lighting
5322: Hand-held switch	5323: Iris diaphragm, open	5323-1: Iris diaphragm, centre-weighted	5323-2: Iris diaphragm, spot	5323-3: Iris diaphragm, average	5324: Iris diaphragm, closed	5325: Small focal spot	5326: Intermediate focal spot	5327: Large focal spot
5328: Radiographic control	5329: Indirect radiography	5330: Radioscopy	5331: Category AP equipment	5332: Category APG equipment	5333: Type BF applied part	5334: Defibrillation-proof type BF applied part	5335: Type CF applied part	5336: Defibrillation-proof type CF applied part
5337: X-ray tube	5338: X-ray source assembly	5339: X-ray source assembly, emitting	5340: Vertical radioscopic stand	5341: Vertical radiographic stand	5342: Horizontal radiographic table	5343: Photo-fluorographic stand	5344: Photo-fluorographic camera	5345: Equipment for tomography
5346: Tilting table with overtable X-ray source assembly	5347: Tilting table with undertable X-ray source assembly	5348: Radiodiagnostic compression device	5349: Radiodiagnostic compression device, movement	5350: Radiodiagnostic compression device, pressure applied	5351: Radiodiagnostic compression device, parked	5352: Anti-scatter grid	5353: Anti-scatter grid, movement	5354: Anti-scatter grid, not used
5355: Radiodiagnostic automatic control system	5356: Serial changer for single radiographic film	5359: Radiographic film selection, full format and orientation	5360: Radiographic film selection, division by two and orientation	5361: Radiographic film selection, division by four and orientation	5362: Film or cassette changer	5363: Film or cassette changers, bi-plane operation	5364: Radiodiagnostic simultaneous bi-plane operation	5365: Radiodiagnostic alternating bi-plane operation
5366: Floor mounted radiological equipment	5367: Ceiling suspended radiological equipment	5368: Radiodiagnostic urological table	5369: Surgical table	5370: Patient's chair, rotation about a vertical axis	5371: Patient's chair, tilt about a horizontal axis	5372: Craniographic equipment	5373: Radiodiagnostic C-arm	5374: Radiodiagnostic U-arm
5377: X-ray image intensifier with stabilized input	5378: Image intensifier, full input field	5379: Image intensifier, small input field	5380: X-ray image intensifier, getting	5381: Radiation filter or filtration	5382: Injection syringe	5383: Indication of radiation field centre by light	5384: Indication of radiation field by light	5385: Beam limiting device, open
5386: Beam limiting device, closed	5387: Beam limiting device with separate opening of the shutters	5388: Beam limiting device with separate closing of the shutters	5389: Patient, thin	5390: Patient, general; patient, normal	5391: Patient, obese	5392: Patient support, tilting	5393: Patient support, longitudinal movement	5394: Patient support, stepwise movement
5395: Patient support, orthogonal movement to its plane	5396: Patient support, movements in its plane	5397: Patient support, rotation about a longitudinal axis	5398: Patient cradle, rotation about its longitudinal axis	5399: Patient support, rotation about an orthogonal axis	5401: Tomographic movement without X radiation	5402: Tomographic movement	5403: Tomographic layer selection	5404: Anode rotation, normal speed
5405: Anode rotation, high	5406: Ionization chamber	5407: Electronic image, normal	5408: Electronic image, reversal	5409: Electronic image, inverted				

IEC/ISO Graphical Symbols for Use on Equipment



































































































This is a preview of "IEC 60417-DB-3M Ed. ...". [Click here to purchase the full version from the ANSI store.](#)

5410: Electromagnetic radiation, top-to-bottom, right-to-left	5419: Dust bag	5420: Scrambler	5421: Descrambler	5422: Interface device, general	5424-1: Interface device, 140 Mbit/s	5424-2: Interface device, binary	5424-3: Interface device, synchronization	5430: Priority
5431: Direct link	5432: Omnibus link	5433: Normal operation	5434: Reserve operation	5435: Brightness and contrast	5436: Sound muting	5438: Spatial sound effect	5439A: Automatic search tuning	
5439B: Automatic search tuning	5440: Programmable timer, general	5444: Remote control reception indicator	5446: Single or multi-digit selection	5447: Frequency band selection	5448: Input/output	5457: Auto reverse	5459: Eject	
5460: Storage/store mode finished	5463: Teletext mode	5464: Satellite reception mode, general	5464-1: Satellite reception mode, television	5467: Screen or video image, freeze	5470A: Run with visualization; cue	5470B: Run with visualization; cue	5471: Frame by frame, general	
5471-1: Frame by frame, video	5476: Main index page	5477: Image display, cancel	5478: Page enlargement	5480: TV and text mixed	5483: Page number down	5484: Page number up	5487: Video data	
5490: Enlargement of the cooking zone, concentric	5491: Enlargement of the cooking zone, eccentric	5492: Enlargement of the cooking zone, oval	5493: Enlargement of the cooking zone, bilateral	5495: Return to an initial state	5498: Short code dialling	5499: Basic diversion	5500: Three-party call	
5501: Call-back	5502: Incoming calls barred	5503: General cancel	5504: Repeat last call	5505: No-reply diversion	5506: Enquiry call	5507: Call waiting	5508: Call pick-up	
5509: Disconnection	5510: Additional information on screen	5511: Menu	5512: System status display	5513: Picture-in-picture, shift	5514: Picture-in-picture, freeze	5515: Picture-in-picture, swap	5516: Picture-in-picture, select	
5517A: Multi-picture display	5517B: Multi-picture display	5518: Video disc player	5519: Timed page cancel	5520: Subtitle	5521A: Video input/output	5521B: Video input/output	5522: Colour video input/output	
5522-1: Colour video input/output, analogue	5522-2: Colour video input/output, digital	5525A: Video input	5525B: Video input	5526: Colour video input	5526-1: Colour video input, analogue	5526-2: Colour video input, digital	5529A: Video output	
5529B: Video output	5530: Colour video output	5530-1: Colour video output, analogue	5530-2: Colour video output, digital	5533: Record review	5534: Power plug	5535: Loudness	5536: Moisture	
5537: Fader	5538: Close-up	5539: Wide-angle	5540: Tele(photo)	5541: Background light	5542: Plane of sensitized material; image plane	5543: Record player; phonograph	5544: Compact disc player	



5546: Battery

This is a preview of "IEC 60417-DB-3M Ed. ...". Click here to purchase the full version from the ANSI store.

							
5554: Still mode	5555: Tape running direction	5556: Manual reverse	5557: Auto reverse continuously	5558: White balance	5559: Two independent audio channels	5560: Cable television distribution	5561: Cassette
							
5562: Tape end	5569: Locking, general	5570: Unlocking	5572: Cable coiling	5573: Water tap, closed	5574: Water tap, open	5575: Filter cleaning / changing	5576: Bell cancel
							
5576-1: Bell, cancel acknowledged; acknowledged	5576-2: Bell, cancel temporary	5576-3: Bell, cancel temporary acknowledged; temporary acknowledged	5577: Zone focus, very short distance	5578: Zone focus, short distance	5579: Zone focus, middle distance	5580: Zone focus, long distance	5581: Save; economize
							
5582: Suitable for use in a bath or shower	5583: Short wash programme	5584: Laundry starch	5585: Gentle spin dry	5586: Half load	5587: Lightly soiled	5588: Medium soiled	5589: Heavily soiled
							
5594: Crease resisting	5595: Condensate collector, general	5596: Condensate collector, full	5597: Steam, low jet	5598: Steam, medium jet	5599: Steam, high jet	5600: Smooth floor or surface	5601: Carpet, general
							
5602: Carpet, long pile	5603: Upholstery	5604: Curtains	5605: Brush, extended	5606: Brush, retracted	5607: Oven, general	5608: Oven, rotisserie	5609: Oven, grill
							
5610: Oven, warm circulating air	5611: Oven, warm air grill	5612: Oven, lower heating	5613: Oven, upper heating	5614: Oven, lower and upper heating	5615: Oven, microwave	5616: Oven, microwave and turntable	5617: Oven, self-cleaning
							
5618: Oven, automatic	5619: Oven, lighting	5620: Oven, defrosting position	5621: Oven, thermometer	5622: Stove, plate indicator	5623: Door, closed	5624: Door, open	5625: Intermediate rinsing, dish washers
							
5627: Oven, warming	5628: Functional movement, stepwise mode	5630A: Run with visualization; review	5630B: Run with visualization; review	5631: Three component video input/output	5632: Three component video input/output, analogue	5632-1: Three component video input/output, analogue	5632-2: Three component video input/output, digital
							
5633: Three component video input	5633-1: Three component video input, analogue	5633-2: Three component video input, digital	5634: Three component video output	5634-1: Three component video output, analogue	5634-2: Three component video output, digital	5635: Two component video input/output	5635-1: Two component video input/output, analogue
							
5635-2: Two component video input/output, digital	5636: Two component video input	5636-1: Two component video input, analogue	5636-2: Two component video input, digital	5637: Two component video output	5637-1: Two component video output, analogue	5637-2: Two component video output, digital	5638: Emergency stop
							
5639: Rechargeable battery	5640: Main wash, dish washers	5641: Suitable for covering	5642: Image intensifier, medium input field	5643: Zero line shift	5645: Correction of a region of interest	5646: Definition of a region of interest	5647: Display in cascade

































































































5648:
Display









This is a preview of "IEC 60417-DB-3M Ed. ...". Click here to purchase the full version from the ANSI store.

5657: Mixing of substances	5658: Distance measurement	5659: Start, test run	5661: Ready for transport	5662: Date	5663: Next person	5664: Person identification	5665: Body weight
5666: Body height	5667: Baby	5668: Nurse	5669: Scintillation counter	5670: Scintillation counter with well	5671: Gamma camera	5672: Gamma camera, tilt	5673: Gamma camera, rotation
5674: Movement of a patient support at normal speed	5675: Movement of a patient support at high speed	5676: Equipment for tomography, movement to start position	5677: Floor standing X-ray source assembly with horizontal table	5678: Floor standing X-ray source assembly with tilting table	5679: Ceiling suspended X-ray source assembly with horizontal table	5680: Ceiling suspended X-ray source assembly with tilting table	5681: Equipment for tomography with tilting table
5683: X-ray intensifying screen, low sensitivity	5684: X-ray intensifying screen, medium sensitivity	5685: X-ray intensifying screen, high sensitivity	5686: Stereo focal spot	5687: Ultrasound image, general	5688: Ultrasound image, dual-image	5689: Ultrasound image, field selection	5690: Ultrasound image, magnification
5691: Ultrasound image, scan-line selection	5692: Ultrasound image, image selection	5693: Ultrasound image, M mode	5694: Ultrasound image, B and M modes	5695: Ultrasound image, M speed	5696: Ultrasound image, pulsed Doppler mode	5697: Ultrasound image, CW Doppler mode	5698: Ultrasound image, measuring volume increase
5699: Ultrasound image, measuring volume movement upwards	5700: Ultrasound image, measuring volume movement downwards	5701: Ultrasound image, measuring volume decrease	5702: Ultrasound image, positioning of the focus	5707: Pencil probe	5709: Probe for sector-shaped sound field	5710: Linear or curved array probe	5711: Probe for circular sound field
5712: Variation of ultrasound energy	5713: Variation of scan depth	5714: Variation of scan aperture	5715: Ultrasound receiver, overall gain	5716: Ultrasound receiver, near field gain	5717: Ultrasound receiver, start point depth compensation	5718: Ultrasound receiver, depth compensation	5719: Ultrasound receiver, far field gain
5720: Image line density	5721: Dynamic range	5722: Grey scale	5723: Edge enhancement	5725: Shockwave head	5726: Shockwave head, overtable position	5727: Shockwave head, undertable position	5728: Shockwave head, movement in the longitudinal direction
5729: Shockwave head, rotational movement	5730: Shockwave head, target position	5731: Shockwave head, park position	5732: Shockwave head, decouple	5733: Shockwave head, couple	5734: Shockwave head, therapy position left	5735: Shockwave head, therapy position right	5736: Impulse
5737: Respiratory triggering	5738: Alignment of the target position	5739: Driving to the target position	5740: Electrode replacement position	5741: Respiratory mask	5742: Tracheal tube	5743: Laryngoscope	5744: Ampule
5745: Hypodermic needle	5746: Resuscitator	5747: Infusion bottle	5748: Surgical instrument	5749: Electrical cautery device	5750: Radiation, infrared	5751: Radiation, ultraviolet	5752: Changing the line spacing
5753: Digital indicator	5754: Probe angulation	5755: Probe, longitudinal movement	5756: Probe in parking position	5757: Integral radiation measurement	5758: Energy selective radiation measurement, window	5759: Energy selective radiation measurement, window	5760: Energy selective radiation measurement, window

































































































This is a preview of "IEC 60417-DB-3M Ed. ...". Click here to purchase the full version from the ANSI store.

							
5761: Energy meas	width, symmetrical adjustment						
							
5769: Shockwave head, movement in lateral direction	5770: Keypad	5771: Electronic image, averaging	5772: Electronic image, rotation	5773: Television or video image, interlacing	5774: Film blackening	5777: Electrosurgery, electrode handle	5778: Electrosurgery, one-button electrode handle
							
5779: Electrosurgery, two-button electrode handle	5780: Electrosurgery, cutting mode	5781: Electrosurgery, blended cutting mode	5782: Electrosurgery, coagulation mode	5783: Electrosurgery, spray coagulation mode	5784: Electrosurgery, bipolar coagulation mode	5785: Suitable for use in the tropics	5786: Suitable for use in the subtropics
							
5788: Displayed image, enlarged	5789: Displayed image, reduced	5791: Panning function	5792: Enlargement of region of interest	5794: Image interchange	5795: ECG triggered display	5800: Split screen	5802: Screen selection
							
5810: Patient position, head/foot reversed	5811: Patient position, supine	5812: Patient position, prone	5814: Patient position, left side	5815: Next image series	5816: Previous image series	5817: Exposure with contrast injection	5818: Beam limiting device, general preset
							
5819: Beam limiting device, esophagus preset	5820: Beam limiting device, small field preset	5821: Selection of other bi-plane channel	5822: Manual movement	5823: Definition of start position of patient support movement	5824: Movement of patient support to start position	5825: Wedge, in / out movement	5826: Contour wedge, in / out movement
							
5827: Central wedge, in / out movement	5828: Wedge, rotation	5829: Central wedge, rotation	5830: X-ray source, rotation around a horizontal axis	5831: X-ray source and image intensifier, combined rotation	5832: X-ray source and image intensifier, combined movement	5833: X-ray source, rotation around its beam axis	5840: Type B applied part
							
5841: Defibrillation-proof type B applied part	5842: Multi-pulse	5843: Target position	5844: Body temperature	5845: Inner diameter	5846: Outer diameter	5847: Trend	5848: Probe rotation
							
5849: Setup	5850: Serial interface	5851: Printer connection; parallel interface	5852: X-ray filter	5853: Final rinsing, dish washers	5854: Fast freeze; superfrost	5855: Minimum supply capacity	5856: Pre-wash detergent
							
5857: Lamp test	5861: Next; to play next part	5862: Previous; to play previous part	5863: Tune, high key	5864: Tune, low key	5865: Tune, normal key	5866: Picture adjustment, tilt	5867: Picture adjustment, skew
							
5868: Picture adjustment, horizontal keystone	5869: Picture adjustment, vertical keystone	5870: Picture adjustment, horizontal pincushion	5871: Picture adjustment, vertical pincushion	5872: Picture adjustment, horizontal bow	5873: Picture adjustment, vertical bow	5874: Picture adjustment, rotation	5875: Optical focus
							
5876: Night portrait mode	5877: Low light mode	5879: Self-timer	5880: World time	5881: Summer time	5882: Sound and language selection	5883: Camera position selection	5884: Memory disk
							
5885:	5886:	5887:	5888:	5889:	5890:	5892:	5893:

IEC/ISO Graphical Symbols for Use on Equipment

Still camera 	Image display, basic setting 	Camera recorder 	Transfer marked images 	Marking of an image 	Store displayed image 	Transfer image 	Electronic shutters, close 
---	--	---	--	---	--	--	--

This is a preview of "IEC 60417-DB-3M Ed. ...". Click here to purchase the full version from the ANSI store.

5916: Pair of students 	5917: Single frame shot 	5918: Lighting with reflector 	5920: Position, centre front 	5921: Position, centre rear 	5922: Position, centre 	5923: Position, left front 	5924: Position, left rear 
5925: Position, left 	5926: Polarity of d.c. power connector 	5927: Fast shutter speed mode; sports mode 	5928: Wide-screen (16:9), normal mode 	5929: Wide-screen (16:9), selection of picture mode 	5930: Wide-screen (16:9), full picture mode 	5931: Wide-screen (16:9), horizontal zoom mode 	5932: Wide-screen (16:9), zoom mode 
5933: Wide-screen (16:9), zoom in/out 	5934: Wide-screen (16:9), picture enlarge mode 	5935: Motorized cleaning head for water suction cleaning 	5937: Cardiac pacemaker; implantable cardioverter defibrillator 	5938: Communication, infrared 	5939: Power supply type of electric device 	5941: Auto-transformer, general 	5942: Auto-transformer, non-short-circuit proof 
5943: Auto-transformer, short-circuit proof 	5944: Isolating transformer, non-short-circuit proof 	5945: Isolating transformer, short-circuit proof 	5946: Safety isolating transformer, non-short-circuit proof 	5947: Safety isolating transformer, short-circuit proof 	5948: Perturbation attenuation isolating transformer, general 	5949: Perturbation attenuation isolating transformer, short-circuit proof 	5950: Small reactor, general 
5951: Small reactor, non-overload proof 	5952: Small reactor, overload proof 	5953: Transformer for Class III handlamps, short-circuit proof 	5954: Colour temperature, fluorescent lamp 	5955: Colour temperature, cloudy/rainy 	5956: Colour temperature, sunrise/sunset 	5957: For indoor use only 	5958: Radiodiagnostic C-arm, angulation 
5959: X-ray source to image intensifier distance, increase 	5960: X-ray source to image intensifier distance, decrease 	5961: X-ray source to image intensifier, centering 	5962: Image intensifier, rotation around a horizontal axis 	5963: X-ray source, lateral movement 	5964: X-ray source, longitudinal movement 	5965: X-ray source, vertical movement 	5966: Patient support, patient transfer position 
5967: Gantry, tilt 	5968: Perturbation attenuation safety isolating transformer 	5969: Perturbation attenuation safety isolating transformer, short-circuit proof 	5970: Frequency converter 	5971: Transformer for Class III handlamps, non-short-circuit proof 	5972: Isolating transformer for the Mirror contact supply of medical locations, non-short-circuit proof 	5973: 	5974: Devices for connection of fixed luminaires; DCL 
5975: Electronic image, general 	5976: X-ray image receptor, radiographic 	5977: X-ray image receptor, radioscopic 	5978: X-ray image receptor, changer 	5979: X-ray cassette, freely positioned 	5980: Indirect radiography, digital 	5981: Radioscopy, pulsed 	5982: X-ray field, not limited by shutters 
5983: Radiodiagnostic compression device, no pressure applied 	5984: Radiodiagnostic automatic control system, field selection 	5985: Determination of radiography settings from radioscopy 	5986: Disc media; optical disc; compact disc (CD) 	5987: Hard disk 	5988: Computer network 	5989: Telephone line 	5990: Mouse 
5991: Keyboard 	5992: Locking, numerals; num-lock 	5993: Locking, capitals; caps-lock 	5994: Locking, scroll; scroll lock 	5995: Do not immerse in any liquid 	5997: Message, general 	5998: Message, confidential 	5999: Telephone, ringing 
6000: On-hook dialling 	6001: Internal call 	6002: External call 	6003: Stamping 	6004: Door-phone 	6005: Pulse background 	6006: Pulse peak 	6007: Hot start 
6008: 	6009: 	6010: 	6010-1: 	6010-2: 	6010-3: 	6010-4: 	6010-5: 

IEC/ISO Graphical Symbols for Use on Equipment

Slope, increasing Slope, decreasing Construction site, general Isolating transformer for construction sites, fail-safe Isolating transformer for construction sites, fail-safe, safety Isolating transformer for construction sites, fail-safe, mid-point or starpoint earthed Isolating transformer for construction sites, non-short-circuit proof Isolating transformer for construction sites, non-short-circuit proof, safety

This is a preview of "IEC 60417-DB-3M Ed. ...". Click here to purchase the full version from the ANSI store.

6010-6: Isolating transformer for construction sites, non-short-circuit proof, midpoint or star-point earthed	6010-7: Isolating transformer for construction sites, short-circuit proof	6010-8: Isolating transformer for construction sites, short-circuit proof, safety	6010-9: Isolating transformer for construction sites, short-circuit proof, mid-point or star-point earthed	6011: Constant voltage separating transformer, general	6012: Constant voltage isolating transformer, general	6013: Constant voltage safety isolating transformer, general	6014: Variable separating transformer, general
6015: Variable isolating transformer, general	6016: Variable safety isolating transformer, general	6017: Constant voltage auto-transformer, general	6018: Variable auto-transformer, general	6019: Vibration	6020: Variability, rotational adjustment with maximum step	6021: Electronic image, cancel	6022: Mouse, left click
6023: Electronic programme guide; EPG	6024: Inlet for liquid; input for liquid	6025: Outlet for liquid; output for liquid	6026: Inlet for gas; input for gas	6027: Outlet for gas; output for gas	6028: Display brilliance	6029: Scale panel illumination	6030: Self-shielded lamp, general
6031: Distance from water level	6032: Do not connect to protective earth; do not connect to protective ground	6033: Do not remove battery	6034: Rough service luminaires	6035A: Press and hold; long push	6035B: Press and hold; long push	6036: Control transformer, fail-safe	6037: Control transformer, non-short-circuit proof
6038: Control transformer, short-circuit proof	6039: Flames kept away	6040: Ultraviolet radiation, instructional safeguard	6041: Visible radiation, instructional safeguard	6042: Caution, risk of electric shock	6043: Caution, sharp edges	6044: Caution, avoid listening at high volume levels for long periods	6045: Rated power input, a.c.
6046: Rated power input, d.c.	6047: Rated power output, a.c.	6048: Rated power output, d.c.	6049: Country of manufacture	6050: Model number	6051A: Undo	6051B: Undo	6053: Built-in LED module
6054: Speech output	6055: Audio description	6056: Caution, moving fan blades	6057: Caution, moving parts	6058: Battery, removal	6059: Caution, possibility of tilting	6060: Anti-tip restraints	6061: Do not hose
6062: Do not expose to moisture	6063: Separating transformer, high insulation level, general	6064: Separating transformer, high insulation level, non-short-circuit-proof	6065: Separating transformer, high insulation level, short-circuit-proof	6066: Separating transformer, output voltages exceeding 1 kV, general	6067: Separating transformer, output voltages exceeding 1 kV, non-short-circuit-proof	6068: Separating transformer, output voltages exceeding 1 kV, short-circuit-proof	6069: Caution, very bright light
6070: Do not disconnect under load	6071: Caution, unprotected lamp	6072-1: Space, en	6072-10: Space, zero width	6072-11: Space, medium mathematical	6072-12: Space, narrow no-break	6072-13: Space, select	6072-2: Space, em
6072-3: Space, three-per-em	6072-4: Space, four-per-em	6072-5: Space, six-per-em	6072-6: Space, figure	6072-7: Space, punctuation	6072-8: Space, thin or narrow	6072-9: Space, hair	6073: Hyphen, soft
6074: Hyphen, non-breaking	6075: Non-stopping dot	6076-1: Separator, line	6076-2: Separator, paragraph	6077-1: Zero-width non-joiner	6077-2: Joiner, zero-width	6077-3: Joiner, word	6077-4: Joiner, combining grapheme
6078: Mark, left-to-right	6079-1: Applicator, horizontal stroke	6079-2: Applicator, diagonal slash	6079-3: Applicator, overlaid tilde	6079-4: Applicator, hook below	6079-5: Applicator, hook above	6079-6: Applicator, hook	6079-7: Applicator, superscript

<p>This is a preview of "IEC 60417-DB-3M Ed. ...". Click here to purchase the full version from the ANSI store.</p>							

IEC/ISO Graphical Symbols for Use on Equipment

Connection, protective conductor (PE) Electronic controlgear, audio-frequency impedance Live working, unsuitable for hand-manipulation Alternative position Transformer and power supply unit for saving energy Suitable for use under dust and moisture Not suitable for use under dust and moisture Not suitable for use under moisture

This is a preview of "IEC 60417-DB-3M Ed. ...". Click here to purchase the full version from the ANSI store.

6179: Not suitable for use under dust	6185-3: Own ship, minimised	6186: Optical filtre	6187: Continuous operation	6188: Air impeller, feeding	6189: Air impeller, suction	6190: Power supply unit, switch mode; switch mode power supply unit; SMPS	6191: RF coil, transmit	6192: RF coil, transmit and receive
6193: RF coil, receive	6194: Gas discharge tube, two-electrode; two-electrode GDT	6195: Gas discharge tube, three-electrode; three-electrode GDT	6196: Immediate stop, light source	6197: Immediate stop, laser light source	6198: Ignition transformer, inherently short circuit proof, one end of output winding connected to the earth	6199: Ignition transformer, inherently short circuit proof, midpoint of output winding connected to the earth	6200: Aiming beam	
6201: Aiming beam, blinking	6202: Packaging for ESD, general	6203: Water tank, periodical cleaning	6204: Caution, static magnetic field hazard	6205: Caution, alternating magnetic nearfield hazard	6206: Caution, electric field hazard	6207: Caution, touch current that can cause burns	6208: Caution, touch current or voltage	
6209: Power supply unit, general	6210: Power supply unit, linear	6211: Copying paper / material, general	6212: Copying paper / material, punch location	6213: Copying paper / material, staple location	6214: Copying paper / material, transparency	6215: Copying paper / material, manual feed	6216: Copying paper / material, automatic selection	
6217: Copying paper / material, roll	6218: Waste bin, toner	6219: Waste bin, paper/material	6220: Staple, jam	6221: Photoconductor unit	6222: Information, general; help, general	6223: Address book	6224: Area, rectangular	
6225: Area, polygonal	6226: Copying, margin	6227: Copying, reversal black-to-white	6228: Copying, overlay	6229: Scanned image, movement	6230: Scanned image, centring	6231: Copying, continuous scaling	6232: Copying, normalization	
6233: Scan mode	6234: Personal computer; PC	6235: Contrast, automatic adjustment	6236: Authentication	6238: Output tray selection	6239: Printing side, face up	6240: Printing side, face down	6241: Copying, facsimile	
6242: Originals, size mixed	6243: Copying, general	6244: Conformity	6245: TANGO-IN; TI	6246: TANGO-OUT; TO	6247: VIDEO-IN; VI	6248: VIDEO-OUT; VO	6249: AUDIO-IN; AI	
6250: AUDIO-OUT; AO	6251: CHEMO-IN; XI	6252: CHEMO-OUT; XO	6253: RADIO-IN; RI	6254: RADIO-OUT; RO	6255: CALOR-IN; CI	6256: CALOR-OUT; CO	6257: ELECTRO-IN; EI	
6258: ELECTRO-OUT; EO	6260: Vascular image recognition, general	6261: Vascular image recognition, hand	6262: Vascular image recognition, finger	6263: Collector position change	6264: Position of use, vertical	6265: Position of use, horizontal	6266: Position of use, inclined	
6267: Permanent-magnet moving-coil instrument	6268: Permanent-magnet ratiometer; permanent-magnet quotientmeter	6269: Moving-iron instrument, polarized	6270: Moving permanent-magnet instrument	6271: Moving permanent-magnet ratiometer; moving permanent-magnet quotientmeter	6272: Moving-iron instrument, general	6273: Moving-iron ratiometer; moving-iron quotientmeter	6274: Electrodynamic instrument, ironless	

This is a preview of "IEC 60417-DB-3M Ed. ...". Click here to purchase the full version from the ANSI store.

6275: Electromechanical instrument, iron-cored	6275: Electromechanical instrument, ironless	6275: Electromechanical instrument, iron-cored	6275: Electromechanical instrument, ironless	6275: Electromechanical instrument, iron-cored	6275: Electromechanical instrument, ironless	6275: Electromechanical instrument, iron-cored	6275: Electromechanical instrument, ironless
6283: Thermal converter, non-insulated thermocouple	6284: Thermal converter, insulated thermocouple	6285: Zero / span adjuster	6286: Overload protection device fitted	6287: Negation	6288: IC-CPD, general; in-cable control and protection device, general	6289: IC-CPD, switched protective conductor included	6290: IC-CPD, non-switched protective conductor included
6291: Residual current sensitive device (RCD), additional function integrated	6292: Cold environment	6293: Not for IT system	6294: AIS SAR aircraft	6295: Concentric circle	6296: LUM connection; luminaire connection	6297: Residual current sensitive device (RCD), type B symbol element	6298: Electrotechnical protection, general
6299: Hexagon	6300: Suitable for uninsulated hazardous live conductors	6301: Ultra-violet light source, exposure distance	6302: Welding time, continuous mode	6303: Welding time, intermittent mode	6304: Welding power source, engine	6305: Welding power output, submerged arc welding	6306: Welding power output, manual metal arc welding with covered electrodes
6307: Welding power output, tungsten inert-gas welding	6308: Welding power output, metal inert and active gas welding including the use of flux cored wire	6309: Welding power output, self-shielded flux cored arc welding	6310: Welding power output, plasma cutting	6311: Welding power output, plasma gouging	6312: Welding power output, plasma welding	6313: Electrode holder, air carbon arc gouging	6314: Air carbon arc gouging
6315: Air flow, general	6316: Air flow, narrowed; air pressure	6317: Air flow, filtered; air filter	6318: Arc striking, without contact	6319: Arc striking, with contact	6320: Distance, general; dimension, general	6321: Resistor, general; series device	6322: Shunt
6323: Electronic device in a measuring circuit	6324: Electronic device in an auxiliary circuit	6325: Skip	6326: Slide show	6327: Global positioning system; GPS	6328: Tulip; UMF	6330A-1: Wireless signal level, very strong signal	6330A-2: Wireless signal level, strong signal
6330A-3: Wireless signal level, weak signal	6330A-4: Wireless signal level, very weak signal	6330A-5: Wireless signal level, no signal	6330B-1: Wireless signal level, very strong signal	6330B-2: Wireless signal level, strong signal	6330B-3: Wireless signal level, weak signal	6330B-4: Wireless signal level, very weak signal	6330B-5: Wireless signal level, no signal
6331: Not suitable for outlet with normal water pressure	6332: Tropical climate	6333-1: Standing position, forward	6333-2: Standing position, backward	6333-3: Standing position, left	6333-4: Standing position, right	6334A: Selection; affirmative acknowledgement; success; ACK	6334B: Selection; affirmative acknowledgement; success; ACK
6335A: Negative acknowledgement; failure; NACK	6335B: Negative acknowledgement; failure; NACK	6336: Retry	6337: Human assistance	6338: Fingerprint application	6339-1: Finger/hand placement, index finger of right hand	6339-2: Finger/hand placement, four fingers of right hand	6339-3: Finger/hand placement, thumb of right hand
6340-1: Finger/hand placement, thumbs of left and right hands	6340-2: Finger/hand placement, index fingers of left and right hands	6341: Finger/hand quality feedback, press more or less	6342-1: Finger/hand quality feedback, increase pressure	6342-2: Finger/hand quality feedback, decrease pressure	6343: Maximum altitude $\leq 3000\text{m}$	6344-1: Finger/hand angle, raise	6344-2: Finger/hand angle, lower
6345: Rough surface IP-code	6346: Lamp control gear, class P thermally protected	6347: Lamp control gear, temperature declared thermally protected	6348: Overvoltage category I	6349: Overvoltage category II	6350: Overvoltage category III	6351: Overvoltage category IV	6352: Do not use power supply with damaged plug



This is a preview of "IEC 60417-DB-3M Ed. ...". Click here to purchase the full version from the ANSI store.

<p>6361: Facial recognition</p>	<p>6362: Non-ECE</p>	<p>6363: Not suitable for use on IT systems</p>	<p>6364: Not suitable for use on single-phase systems</p>	<p>6365: Direct opening action</p>	<p>6366: MWF vacuum cleaner</p>	<p>6367: Coin cell; coin battery</p>	<p>6368: Button cell; button battery</p>
<p>6369: Switch-disconnector, padlocked; on-load isolating switch, padlocked</p>	<p>6370: Normal-superconducting boundary</p>	<p>6371: Josephson junction</p>	<p>6372: Phacofragmentation</p>	<p>6373: Fragmentation, liquefaction</p>	<p>6374: Vitrectomy</p>	<p>6375: Connection to potable water supply</p>	<p>6377: Wire burnback control</p>
<p>6378: Foot control</p>	<p>6379: Panel; local</p>	<p>6380: Electrode holder, manual</p>	<p>6381: Arc welding torch, MIG/MAG</p>	<p>6382: Arc welding torch, self-shielded flux cored</p>	<p>6383: Arc welding torch, TIG</p>	<p>6384: Arc welding torch, plasma</p>	<p>6385: Motorised gun</p>
<p>6386: Motorised gun with filler wire supply</p>	<p>6387: Arc welding torch, submerged</p>	<p>6388: Arc force, increase</p>	<p>6389: Pulsed</p>	<p>6390: Inductance, variable</p>	<p>6391: Inductance, high</p>	<p>6392: Inductance, medium</p>	<p>6393: Inductance, low</p>
<p>6394: Variability with OFF position, rotary adjustment</p>	<p>6395: Welding power source, type S</p>	<p>6397: Enlargement of the cooking zone, multiple circular</p>	<p>6398: Residual current sensitive device (RCD), type B-2</p>	<p>6399: Residual current sensitive device (RCD), type F-2</p>	<p>6400: Photovoltaic array installation</p>	<p>6404: Earth referenced patient circuit</p>	<p>6405: Time synchronization, general</p>
<p>6406: Time synchronized type R security energizer</p>	<p>6407: Time synchronized type S security energizer</p>	<p>6408: VDIS, capacitive</p>	<p>6409: VDIS, resistive</p>	<p>6410: Control and protective switching device (CPS)</p>			