



# CONSOLIDATED VERSION



BASIC SAFETY PUBLICATION

---

## Effects of current on human beings and livestock – Part 1: General aspects

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

ICS 13.200; 29.020

ISBN 978-2-8322-0000-0

**Warning! Make sure that you obtained this publication from an authorized distributor.**



Edition 4.1 2016-07

# REDLINE VERSION



BASIC SAFETY PUBLICATION

## Effects of current on human beings and livestock – Part 1: General aspects

## CONTENTS

|                                                                                                                                                                  |    |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| FOREWORD.....                                                                                                                                                    | 6  |
| INTRODUCTION.....                                                                                                                                                | 9  |
| 1 Scope .....                                                                                                                                                    | 11 |
| 2 Normative references .....                                                                                                                                     | 11 |
| 3 Terms and definitions .....                                                                                                                                    | 12 |
| 3.1 General definitions .....                                                                                                                                    | 12 |
| 3.2 Effects of sinusoidal alternating current in the range 15 Hz to 100 Hz .....                                                                                 | 13 |
| 3.3 Effects of direct current.....                                                                                                                               | 13 |
| 4 Electrical impedance of the human body .....                                                                                                                   | 14 |
| 4.1 Internal impedance of the human body ( $Z_i$ ).....                                                                                                          | 14 |
| 4.2 Impedance of the skin ( $Z_s$ ).....                                                                                                                         | 14 |
| 4.3 Total impedance of the human body ( $Z_T$ ) .....                                                                                                            | 15 |
| 4.4 Factors affecting initial resistance of the human body ( $R_0$ ).....                                                                                        | 15 |
| 4.5 Values of the total impedance of the human body ( $Z_T$ ).....                                                                                               | 15 |
| 4.5.1 Sinusoidal alternating current 50/60 Hz for large surface areas of contact .....                                                                           | 15 |
| 4.5.2 Sinusoidal alternating current 50/60 Hz for medium and small surface areas of contact .....                                                                | 18 |
| 4.5.3 Sinusoidal alternating current with frequencies up to 20 kHz .....                                                                                         | 21 |
| 4.5.4 Direct current.....                                                                                                                                        | 22 |
| 4.6 Value of the initial resistance of the human body ( $R_0$ ).....                                                                                             | 23 |
| 5 Effects of sinusoidal alternating current in the range of 15 Hz to <del>100</del> 150 Hz.....                                                                  | 23 |
| 5.1 Threshold of perception .....                                                                                                                                | 23 |
| 5.2 Threshold of reaction .....                                                                                                                                  | 23 |
| 5.3 Immobilization .....                                                                                                                                         | 23 |
| 5.4 Threshold of let-go .....                                                                                                                                    | 23 |
| 5.5 Threshold of ventricular fibrillation .....                                                                                                                  | 24 |
| 5.6 Other effects related to electric shocks.....                                                                                                                | 24 |
| 5.7 Effects of current on the skin .....                                                                                                                         | 25 |
| 5.8 Description of time/current zones (see Figure 20).....                                                                                                       | 25 |
| 5.9 Application of heart-current factor ( $F$ ).....                                                                                                             | 26 |
| 6 Effects of direct current.....                                                                                                                                 | 26 |
| 6.1 Threshold of perception and threshold of reaction .....                                                                                                      | 26 |
| 6.2 Threshold of immobilization and threshold of let-go .....                                                                                                    | 27 |
| 6.3 Threshold of ventricular fibrillation .....                                                                                                                  | 27 |
| 6.4 Other effects of current.....                                                                                                                                | 27 |
| 6.5 Description of time/current zones (see Figure 22).....                                                                                                       | 28 |
| 6.6 Heart factor .....                                                                                                                                           | 28 |
| 6.7 Effects of anodic versus cathodic d.c. currents .....                                                                                                        | 46 |
| Annexes .....                                                                                                                                                    | 50 |
| Annex A (normative) Measurements of the total body impedances $Z_T$ made on living human beings and on corpses and the statistical analysis of the results ..... | 51 |
| Annex B (normative) Influence of frequency on the total body impedance ( $Z_T$ ) .....                                                                           | 54 |
| Annex C (normative) Total body resistance ( $R_T$ ) for direct current.....                                                                                      | 55 |
| Annex D (informative) Examples of calculations of $Z_T$ .....                                                                                                    | 56 |

|                                                                                                                                                                                                                                                                                                                                                                                                |    |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Annex E (informative) Theories of ventricular fibrillation.....                                                                                                                                                                                                                                                                                                                                | 60 |
| Annex F (informative) Quantities ULV and LLV .....                                                                                                                                                                                                                                                                                                                                             | 61 |
| Annex G (informative) Circuit simulation methods in electric shock evaluation.....                                                                                                                                                                                                                                                                                                             | 62 |
| Figure 1 – Impedances of the human body .....                                                                                                                                                                                                                                                                                                                                                  | 28 |
| Figure 2 – Internal partial impedances $Z_{ip}$ of the human body .....                                                                                                                                                                                                                                                                                                                        | 29 |
| Figure 3 – Simplified schematic diagram for the internal impedances of the human body.....                                                                                                                                                                                                                                                                                                     | 30 |
| Figure 4 – Total body impedances $Z_T$ (50 %) for a current path hand to hand, for large surface areas of contact in dry, water-wet and saltwater-wet conditions for a percentile rank of 50 % of the population for touch voltages $U_T = 25$ V to 700 V, a.c. 50/60 Hz .....                                                                                                                 | 31 |
| Figure 5 – Dependence of the total impedance $Z_T$ of one living person on the surface area of contact in dry condition and at touch voltage (50 Hz) .....                                                                                                                                                                                                                                     | 32 |
| Figure 6 – Dependence of the total body impedance $Z_T$ on the touch voltage $U_T$ for a current path from the tips of the right to the left forefinger compared with large surface areas of contact from the right to the left hand in dry conditions measured on one living person, touch voltage range $U_T = 25$ V to 200 V, a.c. 50 Hz, duration of current flow max. 25 ms.....          | 33 |
| Figure 7 – Dependence of the total body impedance $Z_T$ for the 50 <sup>th</sup> percentile rank of a population of living human beings for large, medium and small surface areas of contact (order of magnitude 10 000 mm <sup>2</sup> , 1 000 mm <sup>2</sup> and 100 mm <sup>2</sup> respectively) in dry conditions at touch voltages $U_T = 25$ V to 200 V a.c. 50/60 Hz.....             | 34 |
| Figure 8 – Dependence of the total body impedance $Z_T$ for the 50 <sup>th</sup> percentile rank of a population of living human beings for large, medium and small surface areas of contact (order of magnitude 10 000 mm <sup>2</sup> , 1 000 mm <sup>2</sup> and 100 mm <sup>2</sup> respectively) in water-wet conditions at touch voltages $U_T = 25$ V to 200 V, a.c. 50/60 Hz.....      | 35 |
| Figure 9 – Dependence of the total body impedance $Z_T$ for the 50 <sup>th</sup> percentile rank of a population of living human beings for large, medium and small surface areas of contact (order of magnitude 10 000 mm <sup>2</sup> , 1 000 mm <sup>2</sup> and 100 mm <sup>2</sup> respectively) in saltwater-wet conditions at touch voltages $U_T = 25$ V to 200 V, a.c. 50/60 Hz ..... | 36 |
| Figure 10 – Values for the total body impedance $Z_T$ measured on 10 living human beings with a current path hand to hand and large surface areas of contact in dry conditions at a touch voltage of 10 V and frequencies from 25 Hz to 20 kHz.....                                                                                                                                            | 37 |
| Figure 11 – Values for the total body impedance $Z_T$ measured on one living human being with a current path hand to hand and large surface areas of contact in dry conditions at a touch voltage of 25 V and frequencies from 25 Hz to 2 kHz .....                                                                                                                                            | 37 |
| Figure 12 – Frequency dependence of the total body impedance $Z_T$ of a population for a percentile rank of 50 % for touch voltages from 10 V to 1 000 V and a frequency range from 50 Hz to <del>2</del> 150 kHz for a current path hand to hand or hand to foot, large surface areas of contact in dry conditions .....                                                                      | 38 |
| Figure 13 – Statistical value of total body impedances $Z_T$ and body resistances $R_T$ for a percentile rank of 50 % of a population of living human beings for the current path hand to hand, large surface areas of contact, dry conditions, for touch voltages up to 700 V, for a.c. 50/60 Hz and d.c. ....                                                                                | 39 |
| Figure 14 – Dependence of the alteration of human skin condition on current density $i_T$ and duration of current flow (for detailed description of zones, see 5.7) .....                                                                                                                                                                                                                      | 40 |
| Figure 15 – Electrodes used for the measurement of the dependence of the impedance of the human body $Z_T$ on the surface area of contact .....                                                                                                                                                                                                                                                | 41 |
| Figure 16 – Oscillograms of touch voltages $U_T$ and touch currents $I_T$ for a.c., current path hand to hand, large surface areas of contact in dry conditions taken from measurements.....                                                                                                                                                                                                   | 42 |
| Figure 17 – Occurrence of the vulnerable period of ventricles during the cardiac cycle .....                                                                                                                                                                                                                                                                                                   | 43 |

|                                                                                                                                                                                                                                                                                           |    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Figure 18 – Triggering of ventricular fibrillation in the vulnerable period – Effects on electro-cardiogram (ECG) and blood pressure .....                                                                                                                                                | 43 |
| Figure 19 – Fibrillation data for dogs, pigs and sheep from experiments and for persons calculated from statistics of electrical accidents with transversal direction of current flow hand to hand and touch voltages $U_T = 220$ V and 380 V a.c. with body impedances $Z_T$ (5 %) ..... | 44 |
| Figure 20 – Conventional time/current zones of effects of a.c. currents (15 Hz to 100 Hz) on persons for a current path corresponding to left hand to feet (for explanation see Table 11) .....                                                                                           | 45 |
| Figure 21 – Oscillogram of touch voltages $U_T$ and touch current $I_T$ for d.c., current path hand to hand, large surface areas of contact in dry conditions.....                                                                                                                        | 45 |
| Figure 22 – Conventional time/current zones of effects of d.c. currents on persons for a longitudinal upward current path (for explanation see Table 13) .....                                                                                                                            | 46 |
| Figure 23 – Let-go currents for 60 Hz sinusoidal current .....                                                                                                                                                                                                                            | 46 |
| Figure 24 – Effects of anodic versus cathodic d.c. currents .....                                                                                                                                                                                                                         | 47 |
| Figure 25 – Pulsed d.c. stimulation of single heart cells .....                                                                                                                                                                                                                           | 48 |
| Figure G.1 – Electric shock in electrical model by Hart [33] including startle reaction effect.....                                                                                                                                                                                       | 63 |
| Bibliography .....                                                                                                                                                                                                                                                                        | 65 |
| Table 1 – Total body impedances $Z_T$ for a current path hand to hand a.c. 50/60 Hz, for large surface areas of contact in dry conditions .....                                                                                                                                           | 16 |
| Table 2 – Total body impedances $Z_T$ for a current path hand to hand a.c. 50/60 Hz, for large surface areas of contact in water-wet conditions .....                                                                                                                                     | 17 |
| Table 3 – Total body impedances $Z_T$ for a current path hand to hand a.c. 50/60 Hz, for large surface areas of contact in saltwater-wet conditions.....                                                                                                                                  | 18 |
| Table 4 –Total body impedances $Z_T$ for a current path hand to hand for medium surface areas of contact in dry conditions at touch voltages $U_T = 25$ V to 200 V a.c. 50/60 Hz (values rounded to 25 $\Omega$ ).....                                                                    | 19 |
| Table 5 – Total body impedances $Z_T$ for a current path hand to hand for medium surface areas of contact in water-wet conditions at touch voltages $U_T = 25$ V to 200 V a.c. 50/60 Hz (values rounded to 25 $\Omega$ ) .....                                                            | 20 |
| Table 6 – Total body impedances $Z_T$ for a current path hand to hand for medium surface areas of contact in saltwater-wet conditions at touch voltages $U_T = 25$ V to 200 V a.c. 50/60 Hz (values rounded to 5 $\Omega$ ) .....                                                         | 20 |
| Table 7 – Total body impedances $Z_T$ for a current path hand to hand for small surface areas of contact in dry conditions at touch voltages $U_T = 25$ V to 200 V a.c. 50/60 Hz (values rounded to 25 $\Omega$ ) .....                                                                   | 20 |
| Table 8 – Total body impedances $Z_T$ for a current path hand to hand for small surface areas of contact in water-wet conditions at touch voltages $U_T = 25$ V to 200 V a.c. 50/60 Hz (values rounded to 25 $\Omega$ ).....                                                              | 21 |
| Table 9 – Total body impedances $Z_T$ for a current path hand to hand for small surface areas of contact in saltwater-wet conditions at touch voltages $U_T = 25$ V to 200 V a.c. 50/60 Hz (values rounded to 5 $\Omega$ ).....                                                           | 21 |
| Table 10 – Total body resistances $R_T$ for a current path hand to hand, d.c., for large surface areas of contact in dry conditions.....                                                                                                                                                  | 22 |
| Table 11 – Time/current zones for a.c. 15 Hz to 100 Hz for hand to feet pathway – Summary of zones of Figure 20.....                                                                                                                                                                      | 25 |
| Table 12 – Heart-current factor $F$ for different current paths.....                                                                                                                                                                                                                      | 26 |
| Table 13 – Time/current zones for d.c. for hand to feet pathway – Summary of zones of Figure 22.....                                                                                                                                                                                      | 28 |

|                                                                                                                                                                                                                                                                      |    |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Table A.1 – Total body impedances $Z_T$ , electrodes type A for dry condition and deviation factors $F_D$ (5 % and 95 %) .....                                                                                                                                       | 51 |
| Table A.2 – Total body impedances $Z_T$ , electrodes type B for dry, water-wet and saltwater-wet conditions and deviation factors $F_D$ (5 % and 95 %) .....                                                                                                         | 51 |
| Table A.3 – Total body impedances $Z_T$ for dry, water-wet and saltwater-wet conditions and deviation factors $F_D$ (5 % and 95 %).....                                                                                                                              | 51 |
| Table A.4 – Deviation factors $F_D$ (5 %) and $F_D$ (95 %) for dry and water-wet conditions in the touch voltage range $U_T = 25$ V up to 400 V for large, medium and small surface areas of contact.....                                                            | 53 |
| Table D.1 – 50 <sup>th</sup> percentile values for the total body impedance for a current path hands-feet medium surface area of contact for hands, large for feet, reduction factor 0,8, dry conditions, touch currents $I_T$ and electrophysiological effects..... | 58 |
| Table G.1 – Body impedance examples (uncompensated).....                                                                                                                                                                                                             | 63 |

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

### EFFECTS OF CURRENT ON HUMAN BEINGS AND LIVESTOCK –

#### Part 1: General aspects

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

#### **DISCLAIMER**

**This Consolidated version is not an official IEC Standard and has been prepared for user convenience. Only the current versions of the standard and its amendment(s) are to be considered the official documents.**

**This Consolidated version of IEC TS 60479-1 bears the edition number 4.1. It consists of the fourth edition (2005-07) [documents 64/1427/DTS and 64/1463/RVC] and its amendment 1 (2016-07) [documents 64/2095/DTS and 64/2113/RVC]. The technical content is identical to the base edition and its amendment.**

**In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.**

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC 60479-1, which is a technical specification, has been prepared by IEC technical committee 64: Electrical installations and protection against electric shock.

This fourth edition cancels and replaces the third edition, published as a technical report in 1994, and constitutes a technical revision.

The main changes with respect to the previous edition are listed below:

- Dependence of the total body impedance  $Z_T$  for 50<sup>th</sup> percentile rank of a population of living human beings for large, average and small surface areas of a contact in dry, water-wet and saltwater-wet conditions at touch voltage  $U_T = 25 \text{ V to } 200 \text{ V a.c. } 50/60 \text{ Hz}$ .
- Oscillograms of touch voltages  $U_T$  and touch currents  $I_T$  for a.c., current path hand-to-hand, large surface areas of contact in dry condition taken from measurements given in Figure 16 with the relevant explanations in the main text.
- Fibrillation data for dogs, pigs and sheep obtained from experiments and for persons calculated from statistics of electrical accidents with transversal direction of current flow, hand-to-hand and touch voltages  $U_T = 220 \text{ V to } 380 \text{ V a.c.}$  with body impedances  $Z_T$  (5%) given in Figure 19 with the relevant explanations in the main text.
- Change of Curve B in Figure 20 from 10 mA to 5 mA: conventional time/current zones of effects of a.c. current (15 Hz to 100 Hz) on persons with the relevant explanations in the main text.
- Let-go currents for 60 Hz sinusoidal current given in Figure 23 with the relevant explanations in the main text.
- new structure to the body of the standard.
- Extension of the applicability of the total body impedance to a frequency range up to 150 kHz;
- Clarification of the difference in anodic versus cathodic d.c. pulses;
- Extension of the ventricular fibrillation threshold of single pulses down to 1  $\mu\text{s}$  pulse width;
- Addition of informative annexes:
  - Annex E: Theories of ventricular fibrillation;
  - Annex F: Quantities ULV and LLV;
  - Annex G: Circuit simulation methods in electric shock evaluation.

This technical specification has the status of a basic safety publication in accordance with IEC Guide 104.

The text of this technical specification is based on the following documents:

|               |                  |
|---------------|------------------|
| Enquiry draft | Report on voting |
| 64/1427/DTS   | 64/1463/RVC      |

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above Table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 60479 consists of the following parts under the general title *Effects of current on human beings and livestock*

Part 1: General aspects

Part 2: Special aspects:

Chapter 4: Effects of alternating current with frequencies above 100 Hz

Chapter 5: Effects of special waveforms of current

Chapter 6: Effects of unidirectional single impulse currents of short duration

Part 3: Effects of currents passing through the bodies of livestock

Part 4: Effects of lightning strokes on human beings and livestock

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

The contents of the corrigendum of October 2006 and June 2013 have been included in this copy.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## INTRODUCTION

This basic safety publication is primarily intended for use by technical committees in the preparation of standards in accordance with the principles laid down in IEC Guide 104 and ISO/IEC Guide 51. It is not intended for use by manufacturers or certification bodies.

One of the responsibilities of a technical committee is, wherever applicable, to make use of basic safety publications in the preparation of its publications.

This technical specification provides basic guidance on the effects of shock current on human beings and livestock, for use in the establishment of electrical safety requirements.

In order to avoid errors in the interpretation of this technical specification, it ~~must~~ should be emphasized that the data given herein is mainly based on experiments with animals as well as on information available from clinical observations. Only a few experiments with shock currents of short duration have been carried out on living human beings.

On the evidence available, mostly from animal research, the values are so conservative that ~~the standard~~ this document applies to persons of normal physiological conditions including children, irrespective of age and weight.

There are, however, other aspects to be taken into account, such as probability of faults, probability of contact with live or faulty parts, ratio between touch voltage and fault voltage, experience gained, technical feasibilities, and economics. These parameters ~~have to~~ should be considered carefully when fixing safety requirements, for example, operating characteristics of protective devices for electrical installations.

The form of the ~~specification~~ document as has been adopted summarizes results so far achieved which are being used by technical committee 64 as a basis for fixing requirements for protection against shock. These results are considered important enough to justify an IEC publication which may serve as a guide to other IEC committees and countries having need of such information.

This technical specification applies to the threshold of ventricular fibrillation which is the main cause of deaths by electric current. The analysis of results of recent research work on cardiac physiology and on the fibrillation threshold, taken together, has made it possible to better appreciate the influence of the main physical parameters and, especially, of the duration of the current flow.

IEC TS 60479-1 contains information about body impedance and body current thresholds for various physiological effects. This information can be combined to derive estimates of a.c. and d.c. touch voltage thresholds for certain body current pathways, contact moisture conditions, and skin contact areas. ~~Information about touch voltage thresholds for physiological effects is contained in the IEC 61201.~~

This technical specification refers specifically to the effects of electric current. When an assessment of the harmful effects of any event on human beings and livestock is being made, other non-electric phenomena, including falls, heat, fire, or others should be taken into account. These matters are beyond the scope of this technical specification, but may be extremely serious in their own right.

~~Recent research work has also been conducted on the other physical accident parameters, especially the waveform and frequency of the current and the impedance of the human body. This fourth revision of IEC 60479-1 should be viewed as the logical development and evolution of the third edition.~~

~~Clause 2 of IEC 60479-1 (third edition) on the impedance of the human body contained little information on the dependence of the impedance on the surface area of contact and then only for dry conditions.~~

~~Therefore measurements were carried out on 10 persons using medium and small surface areas of contact in dry, water wet and saltwater wet conditions, current path hand to hand, at a touch voltage of 25 V a.c. 50 Hz. The impedance values for a percentile rank of 5 %, 50 % and 95 % have been calculated from these measurements.~~

~~Due to unpleasant sensations and the possibility of inherent danger, measurements using large surface areas of contact (order of magnitude 10 000 mm<sup>2</sup>) in dry, water wet and saltwater wet conditions and with medium and small surface areas of contact (order of magnitude 1 000 mm<sup>2</sup> and 100 mm<sup>2</sup>) in dry condition at touch voltages from 25 V up to and including 200 V a.c. have only been carried out on one person. By the use of deviation factors it was nevertheless possible to derive values of the total body impedance  $Z_T$  for a percentile rank of 5 %, 50 % and 95 % of a population of persons. With the same one person measurements were also made with still smaller surface areas of contact (10 mm<sup>2</sup> and 1 mm<sup>2</sup>) and between fingertips.~~

~~For the calculation of total body impedance  $Z_T$  for a percentile rank of 5 %, 50 % and 95 % of a population of persons for large surface areas of contact for touch voltages above 200 V up to 700 V and higher up to the asymptotic values the method to adapt values of  $Z_T$  measured on corpses to those of persons used for the second edition of IEC 60479-1 was improved by taking account of the different temperature of the corpses during measurements and the temperature of 37 °C for persons.~~

~~The present state of knowledge of a.c. impedance  $Z_T$  of the human body for large, medium and small surface areas of contact in dry, water wet and salt water wet conditions and of the d.c. resistance  $R_T$  of the human body for large areas of contact in dry conditions are presented.~~

~~It should be mentioned that the thresholds as order of magnitude are valid for all persons (men, women and children) independent of their state of health. Often concerns are expressed in that respect but if the background of such objections is examined it is found that such objections represent just opinions without experimental evidence. Some measurements indicate that the thresholds of perception and let-go for women are lower than for men. This may also be the case for children.~~

~~Furthermore in Clause 5 a heart current factor  $F$  for the current path foot to foot has been introduced. This is important for electrical risks caused by step voltages.~~

Further experimental data are under consideration, such as recent ongoing experimental work on "current induced heart fibrillation by excitation with discrete Fourier spectra" which is intended to contribute to frequency factor data.

## EFFECTS OF CURRENT ON HUMAN BEINGS AND LIVESTOCK –

### Part 1: General aspects

#### 1 Scope

For a given current path through the human body, the danger to persons depends mainly on the magnitude and duration of the current flow. However, the time/current zones specified in the following clauses are, in many cases, not directly applicable in practice for designing measures of protection against electrical shock. The necessary criterion is the admissible limit of touch voltage (i.e. the product of the current through the body called touch current and the body impedance) as a function of time. The relationship between current and voltage is not linear because the impedance of the human body varies with the touch voltage, and data on this relationship is therefore required. The different parts of the human body (such as the skin, blood, muscles, other tissues and joints) present to the electric current a certain impedance composed of resistive and capacitive components.

The values of body impedance depend on a number of factors and, in particular, on current path, on touch voltage, duration of current flow, frequency, degree of moisture of the skin, surface area of contact, pressure exerted and temperature.

The impedance values indicated in this technical specification result from a close examination of the experimental results available from measurements carried out principally on corpses and on some living persons.

Knowledge of the effects of alternating current is primarily based on the findings related to the effects of current at frequencies of 50 Hz or 60 Hz which are the most common in electrical installations. The values given are, however, deemed applicable over the frequency range from 15 Hz to 100 Hz, threshold values at the limits of this range being higher than those at 50 Hz or 60 Hz. Principally the risk of ventricular fibrillation is considered to be the main mechanism of death of fatal electrical accidents.

Accidents with direct current are much less frequent than would be expected from the number of d.c. applications, and fatal electrical accidents occur only under very unfavourable conditions, for example, in mines. This is partly due to the fact that with direct current, the let-go of parts gripped is less difficult and that for shock durations longer than the period of the cardiac cycle, the threshold of ventricular fibrillation is considerably higher than for alternating current.

**NOTE** The IEC 60479 series contains information about body impedance and body current thresholds for various physiological effects. This information can be combined to derive estimates of a.c. and d.c. touch voltage thresholds for certain body current pathways, contact moisture conditions, and skin contact areas. Information about touch voltage thresholds for physiological effects is contained in IEC 61201.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61201:1992, *Extra-low voltage (ELV) – Limit values*

Guide 104:1997, *The preparation of safety publications and the use of basic safety publications and group safety publications*



Edition 4.1 2016-07

# FINAL VERSION

BASIC SAFETY PUBLICATION

## Effects of current on human beings and livestock – Part 1: General aspects

## CONTENTS

|                                                                                                                                                                  |    |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| FOREWORD.....                                                                                                                                                    | 6  |
| INTRODUCTION.....                                                                                                                                                | 9  |
| 1 Scope .....                                                                                                                                                    | 10 |
| 2 Normative references .....                                                                                                                                     | 10 |
| 3 Terms and definitions .....                                                                                                                                    | 11 |
| 3.1 General definitions .....                                                                                                                                    | 11 |
| 3.2 Effects of sinusoidal alternating current in the range 15 Hz to 100 Hz .....                                                                                 | 12 |
| 3.3 Effects of direct current.....                                                                                                                               | 12 |
| 4 Electrical impedance of the human body .....                                                                                                                   | 13 |
| 4.1 Internal impedance of the human body ( $Z_i$ ).....                                                                                                          | 13 |
| 4.2 Impedance of the skin ( $Z_s$ ).....                                                                                                                         | 13 |
| 4.3 Total impedance of the human body ( $Z_T$ ) .....                                                                                                            | 14 |
| 4.4 Factors affecting initial resistance of the human body ( $R_0$ ).....                                                                                        | 14 |
| 4.5 Values of the total impedance of the human body ( $Z_T$ ).....                                                                                               | 14 |
| 4.5.1 Sinusoidal alternating current 50/60 Hz for large surface areas of contact .....                                                                           | 14 |
| 4.5.2 Sinusoidal alternating current 50/60 Hz for medium and small surface areas of contact .....                                                                | 17 |
| 4.5.3 Sinusoidal alternating current with frequencies up to 20 kHz .....                                                                                         | 20 |
| 4.5.4 Direct current.....                                                                                                                                        | 21 |
| 4.6 Value of the initial resistance of the human body ( $R_0$ ).....                                                                                             | 22 |
| 5 Effects of sinusoidal alternating current in the range of 15 Hz to 150 Hz .....                                                                                | 22 |
| 5.1 Threshold of perception .....                                                                                                                                | 22 |
| 5.2 Threshold of reaction .....                                                                                                                                  | 22 |
| 5.3 Immobilization .....                                                                                                                                         | 22 |
| 5.4 Threshold of let-go .....                                                                                                                                    | 22 |
| 5.5 Threshold of ventricular fibrillation .....                                                                                                                  | 23 |
| 5.6 Other effects related to electric shocks.....                                                                                                                | 23 |
| 5.7 Effects of current on the skin .....                                                                                                                         | 24 |
| 5.8 Description of time/current zones (see Figure 20).....                                                                                                       | 24 |
| 5.9 Application of heart-current factor ( $F$ ).....                                                                                                             | 25 |
| 6 Effects of direct current.....                                                                                                                                 | 25 |
| 6.1 Threshold of perception and threshold of reaction .....                                                                                                      | 25 |
| 6.2 Threshold of immobilization and threshold of let-go .....                                                                                                    | 26 |
| 6.3 Threshold of ventricular fibrillation .....                                                                                                                  | 26 |
| 6.4 Other effects of current.....                                                                                                                                | 26 |
| 6.5 Description of time/current zones (see Figure 22).....                                                                                                       | 27 |
| 6.6 Heart factor .....                                                                                                                                           | 27 |
| 6.7 Effects of anodic versus cathodic d.c. currents .....                                                                                                        | 44 |
| Annexes .....                                                                                                                                                    | 48 |
| Annex A (normative) Measurements of the total body impedances $Z_T$ made on living human beings and on corpses and the statistical analysis of the results ..... | 49 |
| Annex B (normative) Influence of frequency on the total body impedance ( $Z_T$ ) .....                                                                           | 52 |
| Annex C (normative) Total body resistance ( $R_T$ ) for direct current.....                                                                                      | 53 |
| Annex D (informative) Examples of calculations of $Z_T$ .....                                                                                                    | 54 |

|                                                                                                                                                                                                                                                                                                                                                                                                |    |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Annex E (informative) Theories of ventricular fibrillation.....                                                                                                                                                                                                                                                                                                                                | 58 |
| Annex F (informative) Quantities ULV and LLV .....                                                                                                                                                                                                                                                                                                                                             | 59 |
| Annex G (informative) Circuit simulation methods in electric shock evaluation.....                                                                                                                                                                                                                                                                                                             | 60 |
| Figure 1 – Impedances of the human body .....                                                                                                                                                                                                                                                                                                                                                  | 27 |
| Figure 2 – Internal partial impedances $Z_{ip}$ of the human body .....                                                                                                                                                                                                                                                                                                                        | 28 |
| Figure 3 – Simplified schematic diagram for the internal impedances of the human body.....                                                                                                                                                                                                                                                                                                     | 29 |
| Figure 4 – Total body impedances $Z_T$ (50 %) for a current path hand to hand, for large surface areas of contact in dry, water-wet and saltwater-wet conditions for a percentile rank of 50 % of the population for touch voltages $U_T = 25$ V to 700 V, a.c. 50/60 Hz .....                                                                                                                 | 30 |
| Figure 5 – Dependence of the total impedance $Z_T$ of one living person on the surface area of contact in dry condition and at touch voltage (50 Hz) .....                                                                                                                                                                                                                                     | 31 |
| Figure 6 – Dependence of the total body impedance $Z_T$ on the touch voltage $U_T$ for a current path from the tips of the right to the left forefinger compared with large surface areas of contact from the right to the left hand in dry conditions measured on one living person, touch voltage range $U_T = 25$ V to 200 V, a.c. 50 Hz, duration of current flow max. 25 ms.....          | 32 |
| Figure 7 – Dependence of the total body impedance $Z_T$ for the 50 <sup>th</sup> percentile rank of a population of living human beings for large, medium and small surface areas of contact (order of magnitude 10 000 mm <sup>2</sup> , 1 000 mm <sup>2</sup> and 100 mm <sup>2</sup> respectively) in dry conditions at touch voltages $U_T = 25$ V to 200 V a.c. 50/60 Hz.....             | 33 |
| Figure 8 – Dependence of the total body impedance $Z_T$ for the 50 <sup>th</sup> percentile rank of a population of living human beings for large, medium and small surface areas of contact (order of magnitude 10 000 mm <sup>2</sup> , 1 000 mm <sup>2</sup> and 100 mm <sup>2</sup> respectively) in water-wet conditions at touch voltages $U_T = 25$ V to 200 V, a.c. 50/60 Hz.....      | 34 |
| Figure 9 – Dependence of the total body impedance $Z_T$ for the 50 <sup>th</sup> percentile rank of a population of living human beings for large, medium and small surface areas of contact (order of magnitude 10 000 mm <sup>2</sup> , 1 000 mm <sup>2</sup> and 100 mm <sup>2</sup> respectively) in saltwater-wet conditions at touch voltages $U_T = 25$ V to 200 V, a.c. 50/60 Hz ..... | 35 |
| Figure 10 – Values for the total body impedance $Z_T$ measured on 10 living human beings with a current path hand to hand and large surface areas of contact in dry conditions at a touch voltage of 10 V and frequencies from 25 Hz to 20 kHz.....                                                                                                                                            | 36 |
| Figure 11 – Values for the total body impedance $Z_T$ measured on one living human being with a current path hand to hand and large surface areas of contact in dry conditions at a touch voltage of 25 V and frequencies from 25 Hz to 2 kHz .....                                                                                                                                            | 36 |
| Figure 12 – Frequency dependence of the total body impedance $Z_T$ of a population for a percentile rank of 50 % for touch voltages from 10 V to 1 000 V and a frequency range from 50 Hz to 150 kHz for a current path hand to hand or hand to foot, large surface areas of contact in dry conditions.....                                                                                    | 37 |
| Figure 13 – Statistical value of total body impedances $Z_T$ and body resistances $R_T$ for a percentile rank of 50 % of a population of living human beings for the current path hand to hand, large surface areas of contact, dry conditions, for touch voltages up to 700 V, for a.c. 50/60 Hz and d.c. ....                                                                                | 37 |
| Figure 14 – Dependence of the alteration of human skin condition on current density $i_T$ and duration of current flow (for detailed description of zones, see 5.7) .....                                                                                                                                                                                                                      | 38 |
| Figure 15 – Electrodes used for the measurement of the dependence of the impedance of the human body $Z_T$ on the surface area of contact .....                                                                                                                                                                                                                                                | 39 |
| Figure 16 – Oscillograms of touch voltages $U_T$ and touch currents $I_T$ for a.c., current path hand to hand, large surface areas of contact in dry conditions taken from measurements.....                                                                                                                                                                                                   | 40 |
| Figure 17 – Occurrence of the vulnerable period of ventricles during the cardiac cycle .....                                                                                                                                                                                                                                                                                                   | 41 |

|                                                                                                                                                                                                                                                                                           |    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Figure 18 – Triggering of ventricular fibrillation in the vulnerable period – Effects on electro-cardiogram (ECG) and blood pressure .....                                                                                                                                                | 41 |
| Figure 19 – Fibrillation data for dogs, pigs and sheep from experiments and for persons calculated from statistics of electrical accidents with transversal direction of current flow hand to hand and touch voltages $U_T = 220$ V and 380 V a.c. with body impedances $Z_T$ (5 %) ..... | 42 |
| Figure 20 – Conventional time/current zones of effects of a.c. currents (15 Hz to 100 Hz) on persons for a current path corresponding to left hand to feet (for explanation see Table 11) .....                                                                                           | 43 |
| Figure 21 – Oscillogram of touch voltages $U_T$ and touch current $I_T$ for d.c., current path hand to hand, large surface areas of contact in dry conditions.....                                                                                                                        | 43 |
| Figure 22 – Conventional time/current zones of effects of d.c. currents on persons for a longitudinal upward current path (for explanation see Table 13) .....                                                                                                                            | 44 |
| Figure 23 – Let-go currents for 60 Hz sinusoidal current .....                                                                                                                                                                                                                            | 44 |
| Figure 24 – Effects of anodic versus cathodic d.c. currents .....                                                                                                                                                                                                                         | 45 |
| Figure 25 – Pulsed d.c. stimulation of single heart cells .....                                                                                                                                                                                                                           | 46 |
| Figure G.1 – Electric shock in electrical model by Hart [33] including startle reaction effect.....                                                                                                                                                                                       | 61 |
| Bibliography .....                                                                                                                                                                                                                                                                        | 63 |
| <br>Table 1 – Total body impedances $Z_T$ for a current path hand to hand a.c. 50/60 Hz, for large surface areas of contact in dry conditions .....                                                                                                                                       | 15 |
| Table 2 – Total body impedances $Z_T$ for a current path hand to hand a.c. 50/60 Hz, for large surface areas of contact in water-wet conditions .....                                                                                                                                     | 16 |
| Table 3 – Total body impedances $Z_T$ for a current path hand to hand a.c. 50/60 Hz, for large surface areas of contact in saltwater-wet conditions.....                                                                                                                                  | 17 |
| Table 4 –Total body impedances $Z_T$ for a current path hand to hand for medium surface areas of contact in dry conditions at touch voltages $U_T = 25$ V to 200 V a.c. 50/60 Hz (values rounded to 25 $\Omega$ ).....                                                                    | 18 |
| Table 5 – Total body impedances $Z_T$ for a current path hand to hand for medium surface areas of contact in water-wet conditions at touch voltages $U_T = 25$ V to 200 V a.c. 50/60 Hz (values rounded to 25 $\Omega$ ) .....                                                            | 19 |
| Table 6 – Total body impedances $Z_T$ for a current path hand to hand for medium surface areas of contact in saltwater-wet conditions at touch voltages $U_T = 25$ V to 200 V a.c. 50/60 Hz (values rounded to 5 $\Omega$ ) .....                                                         | 19 |
| Table 7 – Total body impedances $Z_T$ for a current path hand to hand for small surface areas of contact in dry conditions at touch voltages $U_T = 25$ V to 200 V a.c. 50/60 Hz (values rounded to 25 $\Omega$ ) .....                                                                   | 19 |
| Table 8 – Total body impedances $Z_T$ for a current path hand to hand for small surface areas of contact in water-wet conditions at touch voltages $U_T = 25$ V to 200 V a.c. 50/60 Hz (values rounded to 25 $\Omega$ ).....                                                              | 20 |
| Table 9 – Total body impedances $Z_T$ for a current path hand to hand for small surface areas of contact in saltwater-wet conditions at touch voltages $U_T = 25$ V to 200 V a.c. 50/60 Hz (values rounded to 5 $\Omega$ ).....                                                           | 20 |
| Table 10 – Total body resistances $R_T$ for a current path hand to hand, d.c., for large surface areas of contact in dry conditions.....                                                                                                                                                  | 21 |
| Table 11 – Time/current zones for a.c. 15 Hz to 100 Hz for hand to feet pathway – Summary of zones of Figure 20.....                                                                                                                                                                      | 24 |
| Table 12 – Heart-current factor $F$ for different current paths.....                                                                                                                                                                                                                      | 25 |
| Table 13 – Time/current zones for d.c. for hand to feet pathway – Summary of zones of Figure 22.....                                                                                                                                                                                      | 27 |

|                                                                                                                                                                                                                                                                      |    |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Table A.1 – Total body impedances $Z_T$ , electrodes type A for dry condition and deviation factors $F_D$ (5 % and 95 %) .....                                                                                                                                       | 49 |
| Table A.2 – Total body impedances $Z_T$ , electrodes type B for dry, water-wet and saltwater-wet conditions and deviation factors $F_D$ (5 % and 95 %) .....                                                                                                         | 49 |
| Table A.3 – Total body impedances $Z_T$ for dry, water-wet and saltwater-wet conditions and deviation factors $F_D$ (5 % and 95 %).....                                                                                                                              | 49 |
| Table A.4 – Deviation factors $F_D$ (5 %) and $F_D$ (95 %) for dry and water-wet conditions in the touch voltage range $U_T = 25$ V up to 400 V for large, medium and small surface areas of contact.....                                                            | 51 |
| Table D.1 – 50 <sup>th</sup> percentile values for the total body impedance for a current path hands-feet medium surface area of contact for hands, large for feet, reduction factor 0,8, dry conditions, touch currents $I_T$ and electrophysiological effects..... | 56 |
| Table G.1 – Body impedance examples (uncompensated).....                                                                                                                                                                                                             | 61 |

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

### EFFECTS OF CURRENT ON HUMAN BEINGS AND LIVESTOCK –

#### Part 1: General aspects

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

#### **DISCLAIMER**

**This Consolidated version is not an official IEC Standard and has been prepared for user convenience. Only the current versions of the standard and its amendment(s) are to be considered the official documents.**

**This Consolidated version of IEC TS 60479-1 bears the edition number 4.1. It consists of the fourth edition (2005-07) [documents 64/1427/DTS and 64/1463/RVC] and its amendment 1 (2016-07) [documents 64/2095/DTS and 64/2113/RVC]. The technical content is identical to the base edition and its amendment.**

**This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.**

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC 60479-1, which is a technical specification, has been prepared by IEC technical committee 64: Electrical installations and protection against electric shock.

This fourth edition cancels and replaces the third edition, published as a technical report in 1994, and constitutes a technical revision.

The main changes with respect to the previous edition are listed below:

- Dependence of the total body impedance  $Z_T$  for 50<sup>th</sup> percentile rank of a population of living human beings for large, average and small surface areas of a contact in dry, water-wet and saltwater-wet conditions at touch voltage  $U_T = 25$  V to 200 V a.c. 50/60 Hz.
- Oscillograms of touch voltages  $U_T$  and touch currents  $I_T$  for a.c., current path hand-to-hand, large surface areas of contact in dry condition taken from measurements given in Figure 16 with the relevant explanations in the main text.
- Fibrillation data for dogs, pigs and sheep obtained from experiments and for persons calculated from statistics of electrical accidents with transversal direction of current flow, hand-to-hand and touch voltages  $U_T = 220$  V to 380 V a.c. with body impedances  $Z_T$  (5%) given in Figure 19 with the relevant explanations in the main text.
- Change of Curve B in Figure 20 from 10 mA to 5 mA: conventional time/current zones of effects of a.c. current (15 Hz to 100 Hz) on persons with the relevant explanations in the main text.
- Let-go currents for 60 Hz sinusoidal current given in Figure 23 with the relevant explanations in the main text.
- new structure to the body of the standard.
- Extension of the applicability of the total body impedance to a frequency range up to 150 kHz;
- Clarification of the difference in anodic versus cathodic d.c. pulses;
- Extension of the ventricular fibrillation threshold of single pulses down to 1  $\mu$ s pulse width;
- Addition of informative annexes:
  - Annex E: Theories of ventricular fibrillation;
  - Annex F: Quantities ULV and LLV;
  - Annex G: Circuit simulation methods in electric shock evaluation.

This technical specification has the status of a basic safety publication in accordance with IEC Guide 104.

The text of this technical specification is based on the following documents:

|               |                  |
|---------------|------------------|
| Enquiry draft | Report on voting |
| 64/1427/DTS   | 64/1463/RVC      |

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above Table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 60479 consists of the following parts under the general title *Effects of current on human beings and livestock*

Part 1: General aspects

Part 2: Special aspects:

Chapter 4: Effects of alternating current with frequencies above 100 Hz

Chapter 5: Effects of special waveforms of current

Chapter 6: Effects of unidirectional single impulse currents of short duration

Part 3: Effects of currents passing through the bodies of livestock

Part 4: Effects of lightning strokes on human beings and livestock

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

The contents of the corrigendum of October 2006 and June 2013 have been included in this copy.

## INTRODUCTION

This basic safety publication is primarily intended for use by technical committees in the preparation of standards in accordance with the principles laid down in IEC Guide 104 and ISO/IEC Guide 51. It is not intended for use by manufacturers or certification bodies.

One of the responsibilities of a technical committee is, wherever applicable, to make use of basic safety publications in the preparation of its publications.

This technical specification provides basic guidance on the effects of shock current on human beings and livestock, for use in the establishment of electrical safety requirements.

In order to avoid errors in the interpretation of this technical specification, it should be emphasized that the data given herein is mainly based on experiments with animals as well as on information available from clinical observations. Only a few experiments with shock currents of short duration have been carried out on living human beings.

On the evidence available, mostly from animal research, the values are so conservative that this document applies to persons of normal physiological conditions including children, irrespective of age and weight.

There are, however, other aspects to be taken into account, such as probability of faults, probability of contact with live or faulty parts, ratio between touch voltage and fault voltage, experience gained, technical feasibilities, and economics. These parameters should be considered carefully when fixing safety requirements, for example, operating characteristics of protective devices for electrical installations.

The form of the document as has been adopted summarizes results so far achieved which are being used by technical committee 64 as a basis for fixing requirements for protection against shock. These results are considered important enough to justify an IEC publication which may serve as a guide to other IEC committees and countries having need of such information.

This technical specification applies to the threshold of ventricular fibrillation which is the main cause of deaths by electric current. The analysis of results of recent research work on cardiac physiology and on the fibrillation threshold, taken together, has made it possible to better appreciate the influence of the main physical parameters and, especially, of the duration of the current flow.

IEC TS 60479-1 contains information about body impedance and body current thresholds for various physiological effects. This information can be combined to derive estimates of a.c. and d.c. touch voltage thresholds for certain body current pathways, contact moisture conditions, and skin contact areas.

This technical specification refers specifically to the effects of electric current. When an assessment of the harmful effects of any event on human beings and livestock is being made, other non-electric phenomena, including falls, heat, fire, or others should be taken into account. These matters are beyond the scope of this technical specification, but may be extremely serious in their own right.

Further experimental data are under consideration, such as recent ongoing experimental work on "current induced heart fibrillation by excitation with discrete Fourier spectra" which is intended to contribute to frequency factor data.

## EFFECTS OF CURRENT ON HUMAN BEINGS AND LIVESTOCK –

### Part 1: General aspects

#### 1 Scope

For a given current path through the human body, the danger to persons depends mainly on the magnitude and duration of the current flow. However, the time/current zones specified in the following clauses are, in many cases, not directly applicable in practice for designing measures of protection against electrical shock. The necessary criterion is the admissible limit of touch voltage (i.e. the product of the current through the body called touch current and the body impedance) as a function of time. The relationship between current and voltage is not linear because the impedance of the human body varies with the touch voltage, and data on this relationship is therefore required. The different parts of the human body (such as the skin, blood, muscles, other tissues and joints) present to the electric current a certain impedance composed of resistive and capacitive components.

The values of body impedance depend on a number of factors and, in particular, on current path, on touch voltage, duration of current flow, frequency, degree of moisture of the skin, surface area of contact, pressure exerted and temperature.

The impedance values indicated in this technical specification result from a close examination of the experimental results available from measurements carried out principally on corpses and on some living persons.

Knowledge of the effects of alternating current is primarily based on the findings related to the effects of current at frequencies of 50 Hz or 60 Hz which are the most common in electrical installations. The values given are, however, deemed applicable over the frequency range from 15 Hz to 100 Hz, threshold values at the limits of this range being higher than those at 50 Hz or 60 Hz. Principally the risk of ventricular fibrillation is considered to be the main mechanism of death of fatal electrical accidents.

Accidents with direct current are much less frequent than would be expected from the number of d.c. applications, and fatal electrical accidents occur only under very unfavourable conditions, for example, in mines. This is partly due to the fact that with direct current, the let-go of parts gripped is less difficult and that for shock durations longer than the period of the cardiac cycle, the threshold of ventricular fibrillation is considerably higher than for alternating current.

**NOTE** The IEC 60479 series contains information about body impedance and body current thresholds for various physiological effects. This information can be combined to derive estimates of a.c. and d.c. touch voltage thresholds for certain body current pathways, contact moisture conditions, and skin contact areas. Information about touch voltage thresholds for physiological effects is contained in IEC 61201.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61201:1992, *Extra-low voltage (ELV) – Limit values*

Guide 104:1997, *The preparation of safety publications and the use of basic safety publications and group safety publications*