INTERNATIONAL STANDARD

IEC 61131-2

Third edition 2007-07

Programmable controllers -

Part 2:

Equipment requirements and tests



CONTENTS

FOREWORD				10
IN٦	ROD	UCTION	1	12
1	Gen	eral		13
	1.1	Scope	and object	13
	1.2	Compl	iance with this standard	14
	1.3	-	ative references	
2	Турє	e tests		17
	2.1	Equipr	ment to be tested (equipment under test/EUT)	17
	2.2	Specia	al features for immunity and EMC tests	18
	2.3	Withst	and test conditions	19
	2.4	Verific	ation procedure	19
	2.5		rements for test programmes and proper functioning verification dures (PFVPs) to be provided by the manufacturer	19
	2.6	Gener	al conditions for tests	20
3	Term	ns and c	lefinitions	20
4	Norn	nal serv	ice conditions and requirements	28
	4.1	Climat	ic conditions and requirements	28
		4.1.1	Operating ambient air temperature	28
		4.1.2	Relative humidity	28
		4.1.3	Altitude	28
		4.1.4	Pollution degree	29
	4.2	Mecha	nical service conditions and requirements	
		4.2.1	Vibrations	29
		4.2.2	Shock	
		4.2.3	Free falls (portable and hand-held equipment)	
	4.3		port and storage conditions and requirements	
		4.3.1	Temperature	
		4.3.2	Relative humidity	
		4.3.3	Altitude	
		4.3.4	Free falls (PLC units in manufacturer's original packaging)	
		4.3.5	Other conditions	
	4.4		cal service conditions and requirements	
		4.4.1 4.4.2	AC and d.c. equipment power supply	
		4.4.2	Overvoltage category, control of transient overvoltages	
	4.5		Non-periodic overvoltagesal conditions and requirements	
5		-	equirements	
5	5.1		onal power supply and memory back-up requirements	
	5.1	5.1.1	AC and d.c. power supply	
		5.1.1	Memory back-up	
	5.2		I/Os	
	J.Z	5.2.1	Digital inputs (current sinking)	
		5.2.2	Digital outputs for alternating currents (current sourcing)	
		5.2.3	Digital outputs for direct current (current sourcing)	
			0 (

	5.3	Analog	ue I/Os	41
		5.3.1	Analogue inputs	41
		5.3.2	Analogue outputs	41
	5.4	Comm	unication interface requirements	42
	5.5	Main processing unit(s) and memory(ies) of the PLC-system requirements		
	5.6		e input/output stations (RIOSs) requirements	
	5.7	Peripherals (PADTs, TEs, HMIs) requirements		
	5.8	PLC-system self-tests and diagnostics requirements		
	5.9	Function	onal earthing	43
	5.10	Mounti	ng requirements	43
	5.11	Genera	al marking requirements	44
		5.11.1	Functional identifications	44
		5.11.2	Module location and module identifications	44
		5.11.3	Functional earth terminals markings	44
	5.12	Requir	ements for normal service and functional type tests and verifications	44
			ements for information on normal service and function	
6	Norm	al servi	ce and functional type tests and verifications	44
	6.1	Climati	ic tests	44
	6.2		at and cold withstand tests	
		6.2.1	Variation of temperature	
		6.2.2	Cyclic damp heat withstand test	
	6.3		nical tests	
		6.3.1	Vibration (type test associated with normal service conditions)	
		6.3.2	Shock (type test associated with normal service conditions)	
		6.3.3	Free fall (type test associated with normal service conditions)	
		6.3.4	Free fall (type test associated with transport and storage conditions)	
		6.3.5	Plugging/unplugging of removable units	
	6.4	Verifica	ation of special functional requirements for power ports and memory	
		back-u	p – Special immunity limits for power ports	
		6.4.1	Verification of functional equipment power input port (a.c. or d.c.)	50
		6.4.2	External energy supply variation tests (immunity tests)	51
		6.4.3	Improper equipment power supply connection tests	54
		6.4.4	Verification of memory back-up requirements	55
	6.5	Verifica	ation of input/output requirements	55
		6.5.1	General	55
		6.5.2	Verification of digital inputs	56
		6.5.3	Verification of digital outputs	56
		6.5.4	Verification of analogue I/Os	57
	6.6	Verifica	ation of communication interface requirements	58
	6.7	Verification of MPU requirements		58
	6.8	Verifica	ation of remote I/O stations	59
		6.8.1	Response time test	59
		6.8.2	Loss of communication test	59
		6.8.3	Verification of other requirements	59
	6.9	Verifica	ation of peripheral (PADTs, TEs, HMIs) requirements	59
	6.10	S.10 Verification of PLC-system self-tests and diagnostics		59
	6.11	Verifica	ation of markings and manufacturer's documentation	59
7	Gene	ral info	rmation to be provided by the manufacturer	60
	7 1	Inform	ation on type and content of documentation	60

		7.1.1 Information on catalogues and datasheets6	60
		7.1.2 Information on user's manuals	
		7.1.3 Information on technical documentation6	
	7.2	Information on compliance with this standard $oldsymbol{\epsilon}$	
	7.3	Information on reliability6	61
	7.4	Information on other conditions6	61
	7.5	Information on shipping and storage6	
	7.6	Information on a.c. and d.c. power supply6	61
	7.7	Information on digital inputs (current sinking)6	61
	7.8	Information on digital outputs for alternating currents (current sourcing)	62
	7.9	Information on digital outputs for direct current (current sourcing) $oldsymbol{arphi}$	63
	7.10	Information on analogue inputs $oldsymbol{\epsilon}$	63
		7.10.1 Information on analogue input static characteristics	63
		7.10.2 Information on analogue input dynamic characteristics	63
		7.10.3 Information on analogue input general characteristics	64
		7.10.4 Information on analogue input miscellaneous characteristics	64
	7.11	Information on analogue outputs6	64
		7.11.1 Information on analogue output static characteristics	64
		7.11.2 Information on analogue output dynamic characteristics	64
		7.11.3 Information on analogue output general characteristics	65
		7.11.4 Information on analogue output miscellaneous characteristics6	65
	7.12	Information on communication interfaces6	65
	7.13	Information on main processing unit(s) and memory(ies) of the PLC-system6	65
	7.14	Information on remote input/output stations (RIOSs)	66
	7.15	Information on peripherals (PADTs, TEs, HMIs)6	67
	7.16	Information on self-tests and diagnostics6	67
8	Elect	omagnetic compatibility (EMC) requirements	67
	8.1	General6	67
	8.2	Emission requirements	68
		8.2.1 General requirements for emission6	68
		8.2.2 Emission limits in the low-frequency range	68
		8.2.3 Emission limits in the high-frequency range6	68
	8.3	EMC immunity requirements	
		8.3.1 General	
		8.3.2 Performance criteria	70
		8.3.3 Immunity levels	71
		8.3.4 Voltage dips and interruptions power ports	73
	8.4	Requirements for EMC tests and verifications	
	8.5	Requirements for information on EMC	74
9	Elect	omagnetic compatibility (EMC) type tests and verifications	
	9.1	Electromagnetic compatibility-related tests	
	9.2	Test environment	
	9.3	Measurement of radiated interference	
	9.4	Measurement of conducted interference	
	9.5	Electrostatic discharge	
	9.6	Radiofrequency electromagnetic field – Amplitude modulated	
	9.7	Power-frequency magnetic fields	
	9.8	Fast transient bursts	
	9.9	High-energy surges	
	J.J	riigir chorgy durged	, 0

	9.10	Condu	cted radiofrequency interference	78
	9.11	Dampe	ed oscillatory wave (for zone C only)	79
	9.12	Voltage	e dips and interruptions	79
10	Elect	romagn	etic compatibility (EMC) information to be provided by the manufacturer.	80
11	Safet	v requir	rements	80
			nent types and protection	
			Open PLC-system equipment	
			Enclosed PLC-system equipment	
	11 2		tion against electrical shock	
	11.2		Permissible limits for accessible parts	
			Dielectric strength	
			Ports requiring protection	
			Protection in normal condition	
			Protection in single-fault condition	
	44.0		Secondary circuits which do not pose a risk of electrical shock	
	11.3		tion against the spread of fire	
			Limited power circuits	
	11.4		nce and creepage distances requirements	
			Clearances relating to overvoltage category II	89
		11.4.2	Clearances for micro-environment where voltages are known and controlled	90
		11.4.3	Creepage distances for basic and supplementary insulation	91
		11.4.4	Creepage distances for double/reinforced insulation	94
		11.4.5	Creepage for field-wiring terminals	94
	11.5	Flame-	retardant requirements for non-metallic materials	94
		11.5.1	Non-metallic enclosure material	94
		11.5.2	Non-metallic material supporting live parts	94
		11.5.3	Non-metallic parts	95
		11.5.4	Decorative and labelling materials	95
		11.5.5	Internal wiring or interconnection cables	95
	11.6	Tempe	rature limits	95
	11.7	Enclos	ures	95
		11.7.1	Open equipment	96
			Enclosed equipment	
	11.8		or-accessible hazardous live field-wiring terminal constructional	
			ments	96
	11.9	Provisi	ons for protective earthing	96
		11.9.1	Protective earthing requirements for enclosed equipment	97
		11.9.2	Protective earthing requirements for open equipment	97
	11.10) Wirin	g	98
		11.10.	1 Internal wiring	98
		11.10.2	2 Interconnection wiring	98
			B Equipment power input cord	
	11.11		ching devices	
	11.12		ponents related to safety requirements	
	11.13		ry requirements	
	11.14		mum voltage and minimum voltage	
	11.15		ings and identification	
			1 External wiring terminals identification	100

	11.15.2 Live parts	100
	11.15.3 Protective earth terminals markings	100
	11.15.4 Enclosed Class II equipment	100
	11.15.5 Equipment supplied by SELV/PELV	101
	11.15.6 Rating information	101
	11.16 Requirements for safety type tests and verifications	
	11.17 Requirements for safety routine tests and verifications	101
	11.17.1 Requirement for dielectric strength verification	101
	11.17.2 Requirement for protective earthing verification	101
	11.18 Requirements for information on safety	101
12	Safety type tests and verifications	102
	12.1 Safety-related mechanical tests and verifications	102
	12.1.1 Impact withstand test	
	12.1.2 Operator accessibility tests	
	12.1.3 General examination of openings	
	12.1.4 Wire flexing test	
	12.1.5 Temperature test	
	12.1.6 Protective coating test	
	12.1.7 Rigidity test	
	12.1.8 Clearance and creepage verification	
	12.1.9 Field-wiring terminals constructional verification	
	12.2 Safety-related electrical tests	
	12.2.1 Dielectric withstand verification test	
	12.2.2 Protective earthing continuity test	
	12.2.3 Stored energy injury risk test	
	12.2.4 Overload test	
	12.2.5 Endurance test	
	12.3 Single-fault condition tests	109
	12.3.1 Single-fault condition – General	
	12.3.2 Single-fault condition – Breakdown of components test	
	12.3.3 Single-fault condition – Protective impedance test	
	12.3.4 Single-fault condition – isolation transformers test	
	12.4 Limited power circuits test	
13	Safety routine tests	
	13.1 Dielectric withstand test	
	13.2 Dielectric withstand verification test	
	13.3 Protective earthing test	
14	Safety information to be provided by the manufacturer	
•	14.1 Information on evaluation of enclosures for open equipment (power	
	dissipation)dissipation on evaluation of enclosures for open equipment (power	112
	14.2 Information on mechanical terminal connection	
Δnr	nex A (informative) Illustration of PLC-system hardware definitions	113
	nex B (informative) Digital input standard operating range equations	
	nex C (normative) Test tools	
	nex D (informative) Zone C – EMC immunity levels	
Anr	nex E (informative) Overvoltage example	120
Rih	liography	122

Figure 1 – EUT configurations	18
Figure 2 – Typical interface/port diagram of a PLC-system	32
Figure 3 – I/O Parameters	35
Figure 4 – U-I operation regions of current-sinking inputs	36
Figure 5 – Temporary overload waveform for digital a.c. outputs	38
Figure 6 – Temporary overload waveform for digital d.c. outputs	40
Figure 7 – Third harmonic immunity test	51
Figure 8 – Gradual shut-down/start-up test	52
Figure 9 – Fast supply voltage variation test	53
Figure 10 – Slow supply voltage variation test	54
Figure 11 – EMC immunity zones	69
Figure 12 – Impact withstand test procedure	102
Figure 13 – Dielectric withstand test procedures	107
Figure A.1 – Programmable controller system (PLC-system)	113
Figure C.1 – Jointed test finger	115
Figure C.2 – 15 mm × 3 mm test pin	116
Figure C.3 – 100 mm × 4 mm test pin	116
Figure C.4 – 100 mm × 3 mm test pin	117
Figure E.1 – Creepage distances of circuits where recurring peak voltages are generated	120
Table 1 – General conditions for tests	20
Table 2 – Operating ambient air temperature of PLC-systems	28
Table 3 – Sinusoidal vibrations service conditions for PLC-systems	29
Table 4 – Free fall on concrete floor for portable and hand-held equipment	30
Table 5 – Free fall on concrete floor in manufacturer's original packaging	31
Table 6 – Rated values and operating ranges of incoming power supply	33
Table 7– Voltage interruptions (functional requirements)	34
Table 8 – Standard operating ranges for digital inputs (current sinking)	37
Table 9 – Rated values and operating ranges for current sourcing digital a.c. outputs	38
Table 10 – Rated values and operating ranges (d.c.) for current-sourcing digital d.c.	
outputs	
Table 11 – Rated values and impedance limits for analogue inputs	
Table 12 – Rated values and impedance limits for analogue outputs	
Table 13 – Dry-heat and cold withstand tests	
Table 14 – Change of temperature, withstand and immunity tests	
Table 15 – Cyclic (12 + 12) damp-heat test	
Table 16 – Immunity vibration test	
Table 17 – Immunity shock test	
Table 18 – Free-fall immunity/withstand tests (portable and hand-held equipment)	
Table 19 – Free-fall withstand test (units within manufacturer's original packaging)	
Table 20 – Insertion/withdrawal of removable units	
Table 21 – Voltage ripple and frequency range immunity test	50

Table 22 – Third harmonic immunity test	50
Table 23 – Gradual shut-down/start-up test	52
Table 24 – Supply voltage variation tests	53
Table 25 – Voltage interruptions immunity test (Functional tests)	54
Table 26 – Back-up duration withstand test	55
Table 27 – Change of energy source test	55
Table 28 – Overload and short-circuit tests for digital outputs	57
Table 29 – Emission limits	68
Table 30 – EMC immunity zones, example regarding surge	70
Table 31 – Criteria to prove the performance of a PLC-system against EMC disturbances	70
Table 32 – Enclosure port tests, Zones A and B	71
Table 33 – Conducted immunity tests, Zone B	72
Table 34 – Conducted immunity tests, zone A	73
Table 35 – Voltage dips and interruptions (EMC requirements)	74
Table 36 – Radiated emission measurement	75
Table 37 – Conducted emission measurement	75
Table 38 – Electrostatic discharge immunity test	76
Table 39 – Radiated electromagnetic field immunity test	76
Table 40 – Power-frequency magnetic field immunity test	77
Table 41 – Fast transient burst immunity test	77
Table 42 – High-energy surge immunity test	78
Table 43 – Conducted r.f. immunity test	78
Table 44 – Damped oscillatory wave immunity test	79
Table 45 – Voltage dips and interruptions immunity test (EMC tests)	79
Table 46 – Shock protection requirements for open and enclosed equipment	84
Table 47 – Limits of output current and output power for inherently limited power	
sources	88
Table 48 – Limits of output current, output power and ratings for over-current protective devices for non-inherently limited power sources	88
Table 49 – Minimum clearances in air corresponding to overvoltage category II conditions (except for field wiring terminals) for basic/supplementary insulation	89
Table 50 – Minimum clearances in air corresponding to overvoltage category II conditions (except for field wiring terminals) for double /reinforced insulation	
Table 51 – Minimum clearances in air at field-wiring terminals	90
Table 52 – Minimum clearances in air for micro-environment where the voltages are known and controlled	91
Table 53 – Classification of material group according to comparative tracking index (CTI)	91
Table 54 - Minimum creepage distances for other than printed circuit boards (1)	92
Table 55 – Minimum creepage distances for printed circuit boards (1), (6), (9) (basic and supplementary insulation)	93
Table 56 – Minimum creepage distances related to recurring peak voltages on printed wiring boards without protective coating (1) (pollution degrees 1 and 2)	94
Table 57 – Temperature limits	
Table 58 – Impact withstand test (1)	102

Table 59 – Operator accessibility tests (1)	103
Table 60 – Dielectric withstand voltages for impulse a.c. power-frequency and d.c. tests for basic/supplementary insulation (5)	106
Table 61 – Dielectric withstand voltages for impulse a.c. power frequency and d.c. tests for double/reinforced insulation (5)	107
Table 62 – Overload test circuit values	108
Table 63 – Endurance test circuit values	109
Table 64 – Routine dielectric withstand test (5)	111
Table D.1 – Enclosure port tests, Zone C	118
Table D.2 – Conducted immunity tests. Zone C	119

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PROGRAMMABLE CONTROLLERS -

Part 2: Equipment requirements and tests

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international
 consensus of opinion on the relevant subjects since each technical committee has representation from all
 interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61131-2 has been prepared by subcommittee 65B: Devices, of IEC technical committee 65: Industrial-process measurement and control.

This third edition of IEC 61131-2 cancels and replaces the second edition published in 2003 and constitutes a technical revision.

This third edition includes the following significant technical changes with respect to the previous edition.

- a) DC power port requirements have been moved from Clause 8 to Clause 5.
- b) Correction of the following tests of Clause 6:
 - · voltage range test;
 - fast supply voltage variation test;
 - slow supply voltage variation test;
 - gradual shut-down/start-up test.
- c) Change of EMC requirements in Clause 8:

- requirements for radiofrequency interference in Table 33 changed from 3 V to 10 V for Zone B equipment;
- reference to EMC basic standards with the last version;
- reference to generic standards 61000-6-x;
- · cable length aligned to generic standards.
- d) Correction of the following tests in Clause 9:
 - voltage dips and interruptions power port type tests and verifications.
- e) New organization of Clause 11:
 - equipment types and protection;
 - open PLC-system equipment;
 - enclosed PLC-system equipment:
 - Class I equipment;
 - Class II equipment;
 - Class III equipment;
 - protection against electric shock;
 - definition of secondary circuits which do not pose a risk of electric shock:
 - Class 2 circuit;
 - limited voltage/current circuit;
 - limited voltage circuit;
 - limited energy circuit ≤30 V a.c. or 42,2 V peak;
 - limited impedance circuit;
 - protection against the spread of fire within limited power circuits;
 - potective earthing requirements for enclosed equipment;
 - minor improvements in different subclauses;
 - impulse test only for verification of clearances.

The text of this standard is based on the following documents:

FDIS	Report on voting
65B/623/FDIS	65B/636/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all parts of the IEC 61131 series, under the general title *Programmable controllers*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- · amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

IEC 61131-2 is part of a series of standards on programmable controllers and the associated peripherals and should be read in conjunction with the other parts of the series.

Where a conflict exists between this and other IEC standards (except basic safety standards), the provisions of this standard should be considered to govern in the area of programmable controllers and their associated peripherals.

Compliance with IEC 61131-2 cannot be claimed unless the requirements of 7.2 are met.

Service and physical environment requirements are specified in Clause 4. Functional requirements are specified in Clause 5. Electromagnetic compatibility requirements are specified in Clause 8. Safety requirements are specified in Clause 11.

Terms of general use are defined in IEC 61131-1. More specific terms are defined in each part.

PROGRAMMABLE CONTROLLERS -

Part 2: Equipment requirements and tests

1 General

1.1 Scope and object

This part of IEC 61131 specifies requirements and related tests for programmable controllers (PLCs) and their associated peripherals (for example, programming and debugging tools (PADTs), human-machine interfaces (HMIs), etc.) which have as their intended use the control and command of machines and industrial processes.

PLCs and their associated peripherals are intended to be used in an industrial environment and may be provided as open or enclosed equipment. If a PLC or its associated peripherals are intended for use in other environments (light industrial, commercial, residential), then the specific requirements, standards and installation practices for those other environments should be additionally applied to the PLC and its associated peripherals.

This standard also applies to any products performing the function of PLCs and/or their associated peripherals.

Equipment covered in this standard is intended for use in overvoltage category II (IEC 60664-1) in low-voltage installations, where the rated equipment supply voltage does not exceed a.c. 1 000 V r.m.s. (50/60 Hz), or d.c. 1 500 V. (If PLCs or their associated peripherals are applied in overvoltage category III installations, then additional analysis will be required to determine the suitability of the equipment for those applications.)

This standard does not deal with the functional safety or other aspects of the overall automated system. PLCs, their application programme and their associated peripherals are considered as components of a control system.

Since PLCs are component devices, safety considerations for the overall automated system including installation and application are beyond the scope of this standard. Refer to IEC 60364-1 or applicable national/local regulations for electrical installation and guidelines.

However, PLC safety as related to electric shock and fire hazards, electrical interference immunity and error detecting of the PLC-system operation (such as the use of parity checking, self-testing diagnostics, etc.), are addressed.

The object of this standard is

- to establish the definitions and identify the principal characteristics relevant to the selection and application of PLCs and their associated peripherals;
- to specify the minimum requirements for functional, electrical, mechanical, environmental and construction characteristics, service conditions, safety, EMC, user programming and tests applicable to PLCs and the associated peripherals.

This standard also specifies

- a) service, storage and transportation requirements for PLCs and their associated peripherals (Clause 4);
- b) functional requirements for PLCs and their associated peripherals (Clause 5);
- c) EMC requirements for PLCs and their associated peripherals (Clause 8);

- d) safety requirements for PLCs and their associated peripherals (Clause 11);
- e) information that the manufacturer is required to supply (Clauses 7, 10 and 14);
- f) test methods and procedures that are to be used for the verification of compliance of PLCs and their associated peripherals with the requirements (Clauses 6, 9 and 12).
- g) safety routine tests for PLCs and their peripherals (Clause 13).

The tests are type tests or production routine tests, and not tests related to the ways PLC systems are applied.

1.2 Compliance with this standard

When compliance with this standard is indicated without qualification, compliance with all clauses, including all tests and verifications required in this standard, should be verified. Moreover, the manufacturer's obligations expressed in this standard are not waived if no type test is required, or if the test conditions are restricted for practical reasons.

When compliance with some portion of this standard is indicated, it is only necessary to verify compliance with those clauses against which the compliance claim is made. The manufacturer's obligations as indicated above are still applicable. The smallest unit of this standard for compliance purposes should be a clause, such as Clauses 5, 8 or 11.

Compliance with a portion of this standard is provided to facilitate efforts with respect to particular conformity assessment requirements (for example, Clause 8, 9 and 10 as the compliance requirements for the EU electromagnetic compatibility directive or Clause 11, 12, 13 and 14 as the compliance requirements for the EU low-voltage directive).

Compliance with constructional requirements and with requirements for information to be provided by the manufacturer should be verified by suitable examination, visual inspection and/or measurement.

All requirements not tested according to the clauses on tests and verifications should be verifiable under a procedure to be agreed to by the manufacturer and the user.

The manufacturer shall provide, on request, compliance verification information for all requirements referenced in the claims of compliance with all or a portion of this standard.

It is the manufacturer's responsibility to ensure that delivered PLC equipment and associated peripherals are equivalent to the sample(s) which have been type-tested according to this standard and therefore that they comply with all requirements of this standard.

Significant modifications shall be indicated through the use of suitable revision level indexes and markings (see 5.11 and 11.15) and shall comply with this standard.

NOTE A new type test may be required to confirm compliance.

Where the manufacturer is allowed to select among several options, he shall clearly specify in his catalogues and/or datasheets those to which any portion of the PLC-system equipment complies. This applies to severity classes of voltage dips (i.e. PS1 or PS2) and types of digital inputs (i.e. Type 1 or Type 3).

1.3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60060-1:1992, High-voltage test techniques – Part 1: General definitions and test requirements

IEC 60068-2-1:2007, Environmental testing - Part 2-1: Tests - Test A: Cold

IEC 60068-2-2:1974, Environmental testing – Part 2: Tests – Tests B: Dry heat

IEC 60068-2-6:1995, Environmental testing – Part 2: Tests – Test Fc: Vibration (sinusoidal)

IEC 60068-2-14:1984, Environmental testing – Part 2: Tests – Test N: Change of temperature

IEC 60068-2-27:1987, Environmental testing – Part 2: Tests – Test Ea and guidance: Shock

IEC 60068-2-30:2005, Environmental testing – Part 2: Tests – Test Db: Damp heat, cyclic (12 h + 12-hour cycle)

IEC 60068-2-31:1969, Environmental testing – Part 2: Tests – Test Ec: Drop and topple, primarily for equipment-type specimens

IEC 60068-2-32:1975, Environmental testing - Part 2: Tests - Test Ed: Free fall

IEC 60364-1:2005, Low-voltage electrical installations – Part 1: Fundamental principles, assessment of general characteristics, definitions

IEC 60364-4-41:2005, Low-voltage electrical installations – Part 4-41: Protection for safety – Protection against electric shock

IEC 60417, Graphical symbols for use on equipment

IEC 60529:2001, Degrees of protection provided by enclosures (IP Code)¹ Amendment 1 (1999)

IEC 60664-1:1992, Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests²

Amendment 1 (2000) Amendment 2 (2002)

IEC 60664-3:2003, Insulation coordination for equipment within low-voltage systems – Part 3: Use of coating, potting or moulding for protection against pollution

IEC 60695-2-11:2000, Fire hazard testing – Part 2-11: Glowing/hot-wire based test methods – Glow-wire flammability test method for end-products

IEC 60695-11-10:1999, Fire hazard testing – Part 11-10: Test flames – 50 W horizontal and vertical flame test methods

IEC 60947-5-1:2003, Low-voltage switchgear and controlgear – Part 5-1: Control circuit devices and switching elements – Electromechanical control circuit devices

IEC 60947-5-2:2004, Low-voltage switchgear and controlgear – Part 5-2: Control circuit devices and switching elements – Proximity switches

IEC 60947-7-1:2002, Low-voltage switchgear and controlgear – Part 7-1: Ancillary equipment – Terminal blocks for copper conductors

IEC 60950-1:2001, Information technology equipment – Safety – Part 1: General requirements

¹ There exists a consolidated edition 2.1 that includes edition 2.0 (2001) and its amendment.

² There exists a consolidated edition 1.2 that includes edition 1.0 (1992) and its amendments.

IEC 61000-4-2:1995, Electromagnetic compatibility (EMC) – Part 4-2: Testing and measurement techniques – Electrostatic discharge immunity test

IEC 61000-4-3:2006, Electromagnetic compatibility (EMC) – Part 4-3: Testing and measurement techniques – Radiated radio-frequency electromagnetic field immunity test

IEC 61000-4-4:2004, Electromagnetic compatibility (EMC) – Part 4: Testing and measurement techniques – Section 4: Electrical fast transient/burst immunity test

IEC 61000-4-5:2005, Electromagnetic compatibility (EMC) – Part 4-5: Testing and measurement techniques – Surge immunity test

IEC 61000-4-6:2003, Electromagnetic compatibility (EMC) – Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances induced by radio-frequency fields

IEC 61000-4-8:1993, Electromagnetic compatibility (EMC) – Part 4-8: Testing and measurement techniques – Power frequency magnetic field immunity test

IEC 61000-4-11:2004, Electromagnetic compatibility (EMC) – Part 4-11: Testing and measurement techniques – Voltage dips, short interruptions and voltage variations immunity test

IEC 61000-4-18:2006, Electromagnetic compatibility (EMC) – Part 4-18: Testing and measurement techniques – Damped oscillatory waves immunity test

IEC 61000-4-29:2000, Electromagnetic compatibility (EMC) – Part 4-29: Testing and measurement techniques – Voltage dips, short interruptions and voltage variations on d.c. input power port immunity test

IEC 61000-6-1:2005, Electromagnetic compatibility (EMC) – Part 6-1: Generic standards – Immunity for residential, commercial and light-industrial environments

IEC 61000-6-2:2005, Electromagnetic compatibility (EMC) – Part 6-2: Generic standards – Immunity for industrial environments

IEC 61000-6-4:2006, Electromagnetic compatibility (EMC) – Part 6-4: Generic standards – Emission standard for industrial environments

IEC 61010-1:2001, Safety requirements for electrical equipment for measurement, control, and laboratory use – Part 1: General requirements

IEC 61131-1:2003, Programmable controllers – Part 1: General information

IEC 61131-3:2003, Programmable controllers - Part 3: Programming languages

IEC 61131-4:2004, Programmable controllers – Part 4: User guidelines

CISPR 14-1:2005, Electromagnetic compatibility – Requirements for household appliances, electric tools and similar apparatus – Part 1: Emission

CISPR 16-1-2:2003, Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-2: Radio disturbance and immunity measuring apparatus – Ancillary equipment – Conducted disturbances

CISPR 16-1-4:2004, Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-4: Radio disturbance and immunity measuring apparatus – Ancillary equipment – Radiated disturbances

CISPR 16-2-1:2005, Specification for radio disturbance and immunity measuring apparatus and methods – Part 2-1: Methods of measurement of disturbances and immunity – Conducted disturbance measurements

CISPR 16-2-3:2006, Specification for radio disturbance and immunity measuring apparatus and methods – Part 2-3: Methods of measurement of disturbances and immunity – Radiated disturbance measurements

2 Type tests

The object of this clause is to define how to verify compliance of the PLC and the associated peripherals with the requirements set forth in this standard. This compliance verification includes

- verification by type tests given in Clauses 6, 9 and 12;
- verification by suitable examination, visual inspection or/and measurement.

These tests are qualification tests and not tests related to the ways PLCs are employed. According to the scope of this standard, the above compliance verification may not cover the verification of the ability of the PLC-system to satisfy the intended automated system requirements. Where needed, special tests, not covered by this standard, shall be agreed to by the manufacturer and the user.

In addition, routine tests are specified in Clause 13.

NOTE Peripherals, used in the same environment as the PLC-system, should meet the same requirements as the PLC-system.

2.1 Equipment to be tested (equipment under test/EUT)

PLC-systems span the range from stand-alone products to modular designs; this leads to an infinite variety of user-built actual PLC-system configurations. For obvious practical reasons, in most cases type tests cannot be conducted on EUT identical to user-built PLC-systems, and engineering judgement is necessary. Therefore, the manufacturer is required to define the EUTs and document the corresponding test plan and test programmes to meet the following principles.

Combination of tests/EUTs/test programmes shall be such that one may reasonably think that any configuration built by the user according to the manufacturer's specifications and installation instructions would pass satisfactorily the same tests, and will properly function in normal operation, which these tests are intended to reflect.

Unless otherwise specified in this standard, the manufacturer may elect to use various EUTs to achieve the objectives of a given type test.

If an EUT representing a basic PLC or a remote I/Os (RIOS) is of modular structure, it shall fulfil the following minimum requirement.

All types of modules shall be represented in one (1) or several EUT configurations in which any mix of modules is permissible.

All types of modules shall be configured in the EUTs and tested at least once.

NOTE It may be appropriate to consider statistical criteria based on samples for a large number of I/Os (for example, >100).

If there are too many families to be included into a single EUT, the manufacturer will define several EUTs as follows.