



Edition 1.0 2018-04

INTERNATIONAL STANDARD

Electric vehicle conductive charging system -

Part 21-2: Electric vehicle requirements for conductive connection to an AC/DC supply – EMC requirements for off-board electric vehicle charging systems

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.100.10; 43.120

ISBN 978-2-8322-5123-2

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FC	DREWC	RD	5		
1	Scop	e	7		
2	Norm	native references	7		
3	Term	s and definitions	9		
4					
	4.1	General	11		
	4.2	Configuration of EUT			
	4.3	Termination of the EUT during testing	12		
	4.4	Operating and test conditions	12		
	4.4.1	General	12		
	4.4.2	Immunity	12		
	4.4.3	Emissions	12		
	4.4.4	Environmental conditions/limitations	13		
5	Immu	unity requirements	13		
	5.1	General	13		
	5.2	Performance criteria	22		
	5.2.1	General	22		
	5.2.2	Performance criteria A	22		
	5.2.3				
	5.2.4				
6	Emis	sion requirements	23		
	6.1	General			
	6.2	Limits and test conditions for disturbances in the low frequency (LF) range			
	6.2.1				
	6.2.2				
	6.2.3	5			
6.3 Limits and test conditions for disturbances in the radio frequency (RF) range					
	6.3.1				
	6.3.2				
	6.3.3				
	6.3.4				
7	6.3.5				
7		results and test report			
Annex A (normative) Example test setups					
Ar	nex B (informative) Radiated disturbance test for keyless entry	35		
	B.1	General			
	B.2	Test setup			
	B.3	Test method			
	B.4	Limits for radiated disturbances keyless entry (2 kHz to 185 kHz)			
Annex C (normative) Termination of ports					
	C.1	General	37		
	C.2	Termination of communication lines – Impedance stabilization networks	27		
	<u> </u>	(ISN)			
	C.2.1	General	31		

C.2.2	Symmetric communication lines (e.g. CAN)	.37
C.2.3	Coupling devices for PLC on power lines	. 39
C.2.4	PLC (technology) on control pilot	.40
	pling and termination devices for other communication and signalling	.41
	native) Voltage transient disturbances from DC charging equipment	
Annex E (norm	native) Voltage surge test setup for DC charging EUT	.44
Annex F (infor	mative) Transient immunity test for DC charging EUT	.46
Bibliography		.47
-	mples of ports of off- board charging equipment	.10
	xample test setup for floor standing equipment for radiated and ssion and immunity	. 33
	xample test setup for table top and wall mounted equipment for emission	. 34
	xample of a test setup for measurement of radiated disturbances to layout and spacing for the loop sensor)	. 36
	xample of an impedance stabilization network for symmetric	. 38
Figure C.2 – E	xample of a circuit for emission tests of PLC on AC or DC power lines	.39
Figure C.3 – E	xample of a circuit for immunity tests of PLC on AC or DC power lines	.39
Figure C.4 – E	xample of a circuit for emission tests of PLC on control pilot line	.40
Figure C.5 – E	xample of a circuit for immunity tests of PLC on control pilot line	.41
Figure C.6 – E	xample of a termination circuit for testing of system A	.41
Figure D.1 – V	oltage transient of DC charging EUT	.42
Figure D.2 – V	oltage transient measurement equipment	.43
Figure E.1 – E	xample of transient test setup	.45
Table 1 – AC o	charging immunity requirements – Environments other than residential	.14
Table 2 – AC o	charging immunity requirements – Residential environments	.16
Table 3 – DC o	charging immunity requirements – Environments other than residential	.18
Table 4 – DC o	charging immunity requirements – Residential environments	.20
Table 5 – Refe	erences for evaluation of low frequency (LF) phenomena	.23
	rences for evaluation of disturbances appearing in the radio frequency	. 24
Table 7 – Dist	urbance voltage limits for class A equipment for AC power input port	.25
Table 8 – Dist	urbance voltage limits for class B equipment for AC power input port	.25
Table 9 – Dist	urbance voltage limits for DC power input port	.26
Table 10 - Dis	turbance voltage limits for class A equipment for AC CPT port	.26
Table 11 – Dis	turbance voltage limits for class B equipment for AC CPT port	.26
Table 12 – Dis	turbance voltage limits for DC CPT port	.27
	quirements for asymmetric mode conducted emissions from Class A	. 28
	quirements for asymmetric mode conducted emissions from Class B	00
Table 15 – Re	quired highest frequency for radiated measurement	.29

Table 16 – Requirements for radiated emissions at frequencies up to 1 GHz for ClassA equipment	30
Table 17 – Requirements for radiated emissions at frequencies above 1 GHz for ClassA equipment	30
Table 18 – Requirements for radiated emissions at frequencies up to 1 GHz for Class B equipment	31
Table 19 – Requirements for radiated emissions at frequencies above 1 GHz for Class B equipment	31
Table B.1 – Limit values of radiated disturbances (2 kHz to 185 kHz)	36
Table C.1 – Termination of ports	37
Table D.1 – Voltage transient limit of EUT	42
Table E.1 – Maximum voltage to be measured on the CPT	44

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRIC VEHICLE CONDUCTIVE CHARGING SYSTEM –

Part 21-2: Electric vehicle requirements for conductive connection to an AC/DC supply – EMC requirements for off-board electric vehicle charging systems

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61851-21-2 has been prepared by IEC technical committee 69: Electric road vehicles and electric industrial trucks.

This first edition, together with IEC 61851-21-1, cancels and replaces IEC 61851-21:2001. It constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 61851-21:2001:

- a) this document addresses now only EMC related tests instead of other electrical tests;
- b) Clauses 2 and 3 have been updated;
- c) the port definition, the test-setups and their corresponding limits as well as the operation modes are defined more precisely;

d) Annexes A to F have been added.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
69/531/FDIS	69/545/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61851 series, published under the general title *Electric vehicle conductive charging system*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

ELECTRIC VEHICLE CONDUCTIVE CHARGING SYSTEM -

Part 21-2: Electric vehicle requirements for conductive connection to an AC/DC supply – EMC requirements for off-board electric vehicle charging systems

1 Scope

This part of IEC 61851 defines the EMC requirements for any off-board components or equipment of such systems used to supply or charge electric vehicles with electric power by conductive power transfer (CPT), with a rated input voltage, according to IEC 60038:2009, up to 1 000 V AC or 1 500 V DC and an output voltage up to 1 000 V AC or 1 500 V DC.

This document covers off-board charging equipment for mode 1, mode 2, mode 3 and mode 4 charging as defined in IEC 61851-1:2017.

Cables where there is no electronics or no electric/electronic switching are considered as passive (benign) and are deemed to comply with the emission and immunity requirements of this document without any need for testing.

This document does not apply to any on-board components or equipment of charging or power supply systems being part of the vehicles. The EMC requirements for such equipment are covered by IEC 61851-21-1: 2017.

Compliance with the emission and immunity requirements of this document is verified where it can be demonstrated that the equipment under test (EUT) meets the respective limits, during type tests in the measuring arrangement of this document.

Requirements for electric vehicle wireless power transfer (WPT) systems are covered in IEC 61980 (all parts).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61851-1:2017, Electric vehicle conductive charging system – Part 1: General requirements

IEC 61851-23:2014, *Electric vehicle conductive charging system – Part 23: DC electric vehicle charging station*

IEC 60038:2009, IEC standard voltages

IEC 62053-21:2003, *Electricity metering equipment (a.c.) – Particular requirements – Part 21:* Static meters for active energy (classes 1 and 2)

IEC 61000-3-2:2014, Electromagnetic compatibility (EMC) – Part 3-2: Limits – Limits for harmonic current emissions (equipment input current \leq 16 A per phase)

IEC 61000-3-3:2013, Electromagnetic compatibility (EMC) – Part 3-3: Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current \leq 16 A per phase and not subject to conditional connexion

IEC 61000-3-11:2017, Electromagnetic compatibility (EMC) – Part 3-11 – Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems – Equipment with rated current \leq 75 A and subject to conditional connection

IEC 61000-3-12:2011, Electromagnetic compatibility (EMC) – Part 3-12 – Limits – Limits for harmonic currents produced by equipment connected to public low-voltage systems with input current > 16 A and \leq 75 A per phase

IEC 61000-4-2:2008, Electromagnetic compatibility (EMC) – Part 4-2: Testing and measurement techniques – Electrostatic discharge immunity test

IEC 61000-4-3:2006, *Electromagnetic compatibility (EMC) – Part 4-3: Testing and measurement techniques – Radiated, radio-frequency, electromagnetic field immunity test* IEC 61000-4-3:2006/AMD1:2007 IEC 61000-4-3:2006/AMD2:2010

IEC 61000-4-4:2012, Electromagnetic compatibility (EMC) – Part 4-4: Testing and measurement techniques – Electrical fast transient/burst immunity test

IEC 61000-4-5:2014, Electromagnetic compatibility (EMC) – Part 4-5: Testing and measurement techniques – Surge immunity test IEC 61000-4-5:2014/AMD1:2017

IEC 61000-4-6:2013, Electromagnetic compatibility (EMC) – Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields

IEC 61000-4-8:2009, Electromagnetic compatibility (EMC) – Part 4-8: Testing and measurement techniques – Power frequency magnetic field immunity test

IEC 61000-4-11:2004, Electromagnetic compatibility (EMC) – Part 4-11: Testing and measurement techniques – Voltage dips, short interruptions and voltage variations immunity tests

IEC 61000-4-11:2004/AMD1:2017

IEC 61000-4-34:2005, Electromagnetic compatibility (EMC) – Part 4-34: Testing and measurement techniques – Voltage dips, short interruptions and voltage variations immunity tests for equipment with input current more than 16 A per phase IEC 61000-4-34:2005/AMD1:2009

IEC 61000-6-1:2016, Electromagnetic compatibility (EMC) – Part 6-1: Generic standards – Immunity standard for residential, commercial and light-industrial environments

IEC 61000-6-2:2016, Electromagnetic compatibility (EMC) – Part 6-2: Generic standards – Immunity standard for industrial environments

IEC 61000-6-3:2006, *Electromagnetic compatibility (EMC) – Part 6-3: Generic standards – Emission standard for residential, commercial and light-industrial environments* IEC 61000-6-3:2006/AMD1:2010

IEC 61000-6-4:2006, *Electromagnetic compatibility (EMC) – Part 6-4: Generic standards – Emission standard for industrial environments* IEC 61000-6-4:2006/AMD1:2010 IEC 61851-21-2:2018 © IEC 2018 - 9 -

CISPR 16-1-2:2014, Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-2: Radio disturbance and immunity measuring apparatus – Coupling devices for conducted disturbance measurements

CISPR 16-1-4:2010, Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-4: Radio disturbance and immunity measuring apparatus – Antennas and test sites for radiated disturbance measurements CISPR 16-1-4:2010/AMD1:2012 CISPR 16-1-4:2010/AMD2:2017

CISPR 25:2008, Vehicles, boats and internal combustion engines – Radio disturbance characteristics – Limits and methods of measurement for the protection of on-board receivers ^1 $\,$

CISPR 32:2015, *Electromagnetic compatibility of multimedia equipment – Emission requirements*

MIL-STD-461F:2007, Department of Defense interface standard requirements for the control of electromagnetic interference characteristics of subsystems and equipment

^{1 3&}lt;sup>rd</sup> edition (2008). This 3rd edition has been replaced in 2016 by a 4th edition CISPR 25:2016, Vehicles, boats and internal combustion engines - Radio disturbance characteristics - Limits and methods of measurement for the protection of on-board receivers.