

Edition 2.0 2015-12

INTERNATIONAL STANDARD



Metallic communication cable test methods -

Part 4-7: Electromagnetic compatibility (EMC) – Test method for measuring of transfer impedance Z_T and screening attenuation a_s or coupling attenuation a_c of connectors and assemblies up to and above 3 GHz – Triaxial tube in tube method

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.100; 33.120.10 ISBN 978-2-8322-3054-1

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FC	REWO	RD	5
IN	TRODU	CTION	7
1	Scop	e	8
2	Norm	ative references	8
3	Term	s and definitions	8
4	Phys	ical background	10
5	•	iple of the test methods	
	5.1	General	
	5.2	Transfer impedance	
	5.3	Screening attenuation	
	5.4	Coupling attenuation	12
6	Test	procedure	13
	6.1	General	13
	6.2	Tube in tube procedure	13
	6.3	Test equipment	14
	6.4	Calibration procedure	
	6.5	Connection between extension tube and device under test	
	6.6	Dynamic range respectively noise floor	
	6.7	Impedance matching	
_	6.8	Influence of Adapters	
7		ple preparation	
	7.1	Coaxial connector or device	
	7.2	Balanced or multiconductor device	
8	7.3	Cable assemblysurement of transfer impedance	
		General	
	8.1 8.2		
	8.3	Principle block diagram of transfer impedance	
	8.4	Measuring	
	8.5	Evaluation of test results	
	8.6	Test report	
9	Scree	ening attenuation	
	9.1	General	
	9.2	Impedance matching	
	9.2.1	General	
	9.2.2	Evaluation of test results with matched conditions	22
	9.2.3	Measuring with mismatch	22
	9.2.4	Evaluation of test results	22
	9.3	Test report	23
10	Coup	ling attenuation	23
	10.1	Procedure	23
	10.2	Expression of results	
	10.3	Test report	
	10.4	Balunless procedure	
An	nex A (normative) Determination of the impedance of the inner circuit	26

Annex B (informative) Example of a self-made impedance matching adapter	27
Annex C (informative) Measurements of the screening effectiveness of connectors and cable assemblies	29
C.1 General	29
C.2 Physical basics	29
C.2.1 General coupling equation	29
C.2.2 Coupling transfer function	31
C.3 Triaxial test set-up	33
C.3.1 General	
C.3.2 Measurement of cable assemblies	
C.3.3 Measurement of connectors	
C.4 Conclusion	
Bibliography	41
Figure 1 – Definition of Z _T	9
Figure 2 – Principle of the test set-up to measure transfer impedance and screening or coupling attenuation of connectors with tube in tube	11
Figure 3 – Principle of the test set-up to measure transfer impedance and screening attenuation of a cable assembly	14
Figure 4 – Principle set-up for verification test	16
Figure 5 – Preparation of balanced or multiconductor connectors	18
Figure 6 – Test set-up (principle) for transfer impedance measurement according to test method B of IEC 62153-4-3	19
Figure 7 – Measuring the screening attenuation with tube in tube with impedance matching device	21
Figure 8 – Measuring the coupling attenuation with tube in tube and balun	24
Figure 9 – Typical measurement of a connector of 0,04 m length with 1 m extension tube	
Figure 10 – Measuring the coupling attenuation with multiport VNA (balunless procedure is under consideration)	25
Figure B.1 – Attenuation and return loss of a 50 Ω to 5 Ω impedance matching adapter, log scale	27
Figure B.2 – Attenuation and return loss of a 50 Ω to 5 Ω impedance matching adapter, lin scale	
Figure C.1 – Equivalent circuit of coupled transmission lines	30
Figure C.2 – Summing function S	
Figure C.3 – Calculated coupling transfer function ($l = 1 \text{ m}$; $e_{r1} = 2.3$; $e_{r2} = 1$; $Z_F = 0$)	
Figure C.4 – Triaxial set-up for the measurement of the screening attenuation a_S and the transfer impedance Z_T	
Figure C.5 – Simulation of a cable assembly (logarithmic scale)	
Figure C.6 – Simulation of a cable assembly (linear scale)	
Figure C.7 – Triaxial set-up with extension tube for short cable assemblies	
Figure C.8 – Triaxial set-up with extension tube for connectors	
Figure C.9 – Simulation, logarithmic frequency scale	
Figure C.10 – Measurement, logarithmic frequency scale	
Figure C.11 – Simulation, linear frequency scale	37

This is a preview of "IEC 62153-4-7 Ed. 2....". Click here to purchase the full version from the ANSI store.

Figure C.12 – Measurement, linear frequency scale	37
Figure C.13 – Simulation, logarithmic frequency scale	38
Figure C.14 – simulation, linear frequency scale	38
Figure D.1 – Contact resistances of the test set-up	39
Figure D.2 – Equivalent circuit of the test set-up	39
Table 1 – IEC 62153, Metallic communication cable test methods – Test procedures with triaxial test set-up	11

INTERNATIONAL ELECTROTECHNICAL COMMISSION

METALLIC COMMUNICATION CABLE TEST METHODS -

Part 4-7: Electromagnetic compatibility (EMC) – Test method for measuring of transfer impedance Z_T and screening attenuation a_s or coupling attenuation a_c of connectors and assemblies up to and above 3 GHz – Triaxial tube in tube method

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62153-4-7 has been prepared by IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

This second edition cancels and replaces the first edition published in 2006. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

The document is revised and updated. The changes of the revised IEC 62153-4-3:2013, and IEC 62153-4-4:2015, are included.

This is a preview of "IEC 62153-4-7 Ed. 2....". Click here to purchase the full version from the ANSI store.

Measurements can be achieved now with mismatch at the generator site, impedance matching devices are not necessary.

The text of this standard is based on the following documents:

FDIS	Report on voting
46/572/FDIS	46/585/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 62153 series, under the general title: *Metallic communication cable test methods*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed.
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

This is a preview of "IEC 62153-4-7 Ed. 2....". Click here to purchase the full version from the ANSI store.

INTRODUCTION

The shielded screening attenuation test set-up according to IEC 62153-4-3 and IEC 62153-4-4 have been extended to take into account the particularities of electrically short elements like connectors and cable assemblies. Due to the concentric outer tube of the triaxial set-up, measurements are independent of irregularities on the circumference and outer electromagnetic fields.

With the use of an additional resonator tube (inner tube respectively tube in tube), a system is created where the screening effectiveness of an electrically short device is measured in realistic and controlled conditions. Also a lower cut off frequency for the transition between electrically short (transfer impedance $Z_{\rm T}$) and electrically long (screening attenuation $a_{\rm S}$) can be achieved.

A wide dynamic and frequency range can be applied to test even super screened connectors and assemblies with normal instrumentation from low frequencies up to the limit of defined transversal waves in the outer circuit at approximately 4 GHz.

METALLIC COMMUNICATION CABLE TEST METHODS -

Part 4-7: Electromagnetic compatibility (EMC) – Test method for measuring of transfer impedance Z_T and screening attenuation a_s or coupling attenuation a_c of connectors and assemblies up to and above 3 GHz – Triaxial tube in tube method

1 Scope

This triaxial method is suitable to determine the surface transfer impedance and/or screening attenuation and coupling attenuation of mated screened connectors (including the connection between cable and connector) and cable assemblies. This method could also be extended to determine the transfer impedance, coupling or screening attenuation of balanced or multipin connectors and multicore cable assemblies. For the measurement of transfer impedance and screening- or coupling attenuation, only one test set-up is needed.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC TS 62153-4-1, Metallic communication cable test methods – Part 4-1: Electromagnetic compatibility (EMC) – Introduction to electromagnetic screening measurements

IEC 62153-4-3, Metallic communication cable test methods – Part 4-3: Electromagnetic Compatibility (EMC) – Surface transfer impedance – Triaxial method

IEC 62153-4-4, Metallic communication cable test methods – Part 4-4: Electromagnetic compatibility (EMC) – Shielded screening attenuation, test method for measuring of the screening attenuation as up to and above 3 GHz

IEC 62153-4-15, Metallic communication cable test methods – Part 4-15: Electromagnetic compatibility (EMC) – Test method for measuring transfer impedance and screening attenuation – or coupling attenuation with Triaxial Cell