

Edition 2.0 2010-12

INTERNATIONAL STANDARD



Protection against lightning – Part 2: Risk management

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.020; 91.120.40 ISBN 978-2-88912-281-3

CONTENTS

FO	REWO	RD		6	
INT	RODU	JCTION		8	
1	Scop	e		. 10	
2	Norm	ormative references			
3	Terms, definitions, symbols and abbreviations				
	3.1	Terms	and definitions	. 10	
	3.2	Symbo	Is and abbreviations	. 16	
4	Expla	anation o	of terms	. 19	
	4.1	Damag	e and loss	. 19	
		4.1.1	Source of damage	. 19	
		4.1.2	Types of damage	. 19	
		4.1.3	Types of loss	. 19	
	4.2	Risk ar	nd risk components	. 20	
		4.2.1	Risk	. 20	
		4.2.2	Risk components for a structure due to flashes to the structure		
		4.2.3	Risk component for a structure due to flashes near the structure	. 21	
		4.2.4	Risk components for a structure due to flashes to a line connected to the structure	21	
		4.2.5	Risk component for a structure due to flashes near a line connected		
			to the structure	. 21	
	4.3	Compo	sition of risk components	. 22	
5	Risk	manage	ment	. 23	
	5.1	Basic p	procedure	. 23	
	5.2	Structu	re to be considered for risk assessment	. 23	
	5.3	Tolerab	ole risk R _T	. 24	
	5.4	Specifi	c procedure to evaluate the need of protection	. 24	
	5.5	Proced	ure to evaluate the cost effectiveness of protection	. 25	
	5.6	Protect	tion measures	. 28	
	5.7	Selecti	on of protection measures	. 28	
6	Assessment of risk components				
	6.1	Basic e	equationequation	. 28	
	6.2	Assess	ment of risk components due to flashes to the structure (S1)	. 29	
	6.3	Assess	ment of the risk component due to flashes near the structure (S2)	. 29	
	6.4	Assessment of risk components due to flashes to a line connected to the structure (S3)		. 29	
	6.5		ment of risk component due to flashes near a line connected to the re (S4)	. 30	
	6.6		ary of risk components		
	6.7		ning of a structure in zones Z _S		
	6.8	Partitio	ning of a line into sections S _L	. 32	
	6.9	Assess	ment of risk components in a structure with zones Z _S	. 32	
		6.9.1	General criteria	. 32	
		6.9.2	Single zone structure	. 32	
		6.9.3	Multi-zone structure		
	6.10	Cost-b	enefit analysis for economic loss (L4)	. 33	
Ann	nex A	(informa	ative) Assessment of annual number N of dangerous events	. 34	
Ann	nex B	(informa	ative) Assessment of probability P_{X} of damage	. 42	

Annex C (informative)	Assessment of amount of loss L_{χ}	50
Annex D (informative)	Evaluation of costs of loss	57
Annex E (informative)	Case study	58
Bibliography		84
	for deciding the need of protection and for selecting protection	26
Figure 2 – Procedure f	for evaluating the cost-effectiveness of protection measures	27
Figure A.1 – Collection	n area A _D of an isolated structure	35
Figure A.2 – Complex	shaped structure	36
Figure A.3 – Different	methods to determine the collection area for the given structure	37
Figure A.4 – Structure	to be considered for evaluation of collection area A_D	38
Figure A.5 – Collection	n areas (A _{D,} A _M , A _I , A _L)	41
Figure E.1 – Country h	nouse	58
Figure E.2 – Office bui	ilding	63
Figure E.3 – Hospital .		69
Figure E.4 – Apartmen	nt block	80
Table 1 – Sources of c	damage, types of damage and types of loss according to the	20
Table 2 – Risk compor	nents to be considered for each type of loss in a structure	22
Table 3 – Factors influ	encing the risk components	23
Table 4 - Typical value	es of tolerable risk R _T	24
Table 5 – Parameters	relevant to the assessment of risk components	30
Table 6 – Risk compor	nents for different types of damage and source of damage	31
Table A.1 – Structure I	location factor C _D	39
Table A.2 – Line instal	llation factor C _I	40
Table A.3 – Line type t	factor C _T	40
Table A.4 – Line envir	onmental factor C _E	40
Table B.1 – Values of living beings due to da	probability P_{TA} that a flash to a structure will cause shock to angerous touch and step voltages	42
Table B.2 – Values of physical damage	probability P_{B} depending on the protection measures to reduce	43
Table B.3 – Value of the designed	he probability P_{SPD} as a function of LPL for which SPDs are	44
Table B.4 – Values of isolation conditions	factors C_{LD} and C_{LI} depending on shielding, grounding and	44
Table B.5 – Value of fa	actor $K_{f S3}$ depending on internal wiring	46
	probability P_{TU} that a flash to an entering line will cause shock dangerous touch voltages	47
Table B.7 – Value of the designed	he probability $P_{\sf EB}$ as a function of LPL for which SPDs are	47
	the probability $P_{\rm LD}$ depending on the resistance $R_{\rm S}$ of the cable e withstand voltage $U_{\rm W}$ of the equipment	47
Table B.9 – Values of	the probability P_{LI} depending on the line type and the impulse of the equipment	<i>1</i> C

Table C.1 – Type of loss L1: Loss values for each zone	51
Table C.2 – Type of loss L1: Typical mean values of L_T , L_F and L_O	51
Table C.3 – Reduction factor r_t as a function of the type of surface of soil or floor	52
Table C.4 – Reduction factor r_p as a function of provisions taken to reduce the	
consequences of fire	
Table C.5 – Reduction factor r_f as a function of risk of fire or explosion of structure	53
Table C.6 – Factor h _Z increasing the relative amount of loss in presence of a special hazard	53
Table C.7 – Type of loss L2: Loss values for each zone	
Table C.8 – Type of loss L2: Typical mean values of $L_{\rm F}$ and $L_{\rm O}$	
Table C.9 – Type of loss L3: Loss values for each zone	
Table C.10 – Type of loss L3: Typical mean value of L _F	
Table C.11 – Type of loss L4: Loss values for each zone	
Table C.12 – Type of loss L4: Typical mean values of L_T , L_F and L_O	
Table E.1 – Country house: Environment and structure characteristics	
Table E.2 – Country house: Power line	
Table E.3 – Country house: Telecom line (TLC)	
Table E.4 – Country house: Factors valid for zone Z ₂ (inside the building)	
Table E.5 – Country house: Collection areas of structure and lines	
Table E.6 – Country house: Expected annual number of dangerous events	
Table E.7 – Country house: Risk R_1 for the unprotected structure (values \times 10 ⁻⁵)	
Table E.8 – Country house: Risk components relevant to risk R_1 for protected structure	
Table E.9 – Office building: Environment and structure characteristics	
Table E.10 – Office building: Power line	
Table E.11 – Office building: Telecom line	
Table E.12 – Office building: Distribution of persons into zones	
Table E.13 – Office building: Factors valid for zone Z_1 (entrance area outside)	
Table E.14 – Office building: Factors valid for zone Z_2 (garden outside)	
Table E.15 – Office building: Factors valid for zone Z_2 (garden outside)	
Table E.16 – Office building: Factors valid for zone Z_4 (offices)	
Table E.17 – Office building: Factors valid for zone Z ₅ (computer centre)	
Table E.18 – Office building: Collection areas of structure and lines	
Table E.19 – Office building: Expected annual number of dangerous events	
Table E.20 – Office building: Risk R_1 for the unprotected structure (values \times 10 ⁻⁵)	
Table E.21 – Office building: Risk R_1 for the protected structure (values × 10 ⁻⁵)	
Table E.22 – Hospital: Environment and global structure characteristics	
Table E.23 – Hospital: Power line	
Table E.24 – Hospital: Telecom line	
Table E.25 – Hospital: Distribution of persons and of economic values into zones	
Table E.26 – Hospital: Factors valid for zone Z ₁ (outside the building)	
Table E.27 – Hospital: Factors valid for zone Z ₂ (rooms block)	
Table E.28 – Hospital: Factors valid for zone Z ₃ (operating block)	
Table E.29 – Hospital: Factors valid for zone Z ₄ (intensive care unit)	
Table E.30 – Hospital: Collection areas of structure and lines	

Table E.31 – Hospital: Expected annual number of dangerous events	75
Table E.32 – Hospital: Risk R_1 – Values of probability P for the unprotected structure	75
Table E.33 – Hospital: Risk R_1 for the unprotected structure (values \times 10 ⁻⁵)	75
Table E.34 – Hospital: Risk R_1 for the protected structure according to solution a) (values \times 10 ⁻⁵)	77
Table E.35 – Hospital: Risk R_1 for the protected structure according to solution b) (values \times 10 ⁻⁵)	77
Table E.36 – Hospital: Risk R_1 for the protected structure according to solution c) (values \times 10 ⁻⁵)	78
Table E.37 – Hospital: Cost of loss C_L (unprotected) and C_{RL} (protected)	78
Table E.38 – Hospital: Rates relevant to the protection measures	79
Table E.39 – Hospital: Cost $C_{\rm P}$ and $C_{\rm PM}$ of protection measures (values in \$)	79
Table E.40 – Hospital: Annual saving of money (values in \$)	79
Table E.41 – Apartment block: Environment and global structure characteristics	80
Table E.42 – Apartment block: Power line	80
Table E.43 – Apartment block: Telecom line	81
Table E.44 – Apartment block: Factors valid for zone Z ₂ (inside the building)	82
Table E.45 – Apartment block: Risk R_1 for the apartment block depending on protection measures	83

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PROTECTION AGAINST LIGHTNING -

Part 2: Risk management

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62305-2 has been prepared by IEC technical committee 81: Lightning protection.

This second edition cancels and replaces the first edition, published in 2006, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- 1) Risk assessment for services connected to structures is excluded from the scope.
- 2) Injuries of living beings caused by electric shock inside the structure are considered.
- 3) Tolerable risk of loss of cultural heritage is lowered from 10^{-3} to 10^{-4} . The value of tolerable risk of loss of economic value ($R_{\rm T}$ = 10^{-3}) is introduced, to be used when data for cost/benefit analysis are not available.
- 4) Extended damage to surroundings structures or to the environment is considered.
- 5) Improved equations are provided for evaluation of

- collection areas relevant to flashes nearby a structure,
- collection areas relevant to flashes to and nearby a line,
- probabilities that a flash can cause damage,
- loss factors even in structures with risk of explosion,
- risk relevant to a zone of a structure,
- cost of loss.
- 6) Tables are provided to select the relative amount of loss in all cases.
- 7) Impulse withstand voltage level of equipments was extended down to 1 kV.

The text of this standard is based on the following documents:

FDIS	Report on voting
81/371/FDIS	81/381/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 62305 series, under the general title *Protection against lightning*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- · reconfirmed.
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Lightning flashes to earth may be hazardous to structures and to lines.

The hazard to a structure can result in

- damage to the structure and to its contents,
- failure of associated electrical and electronic systems,
- injury to living beings in or close to the structure.

Consequential effects of the damage and failures may be extended to the surroundings of the structure or may involve its environment.

To reduce the loss due to lightning, protection measures may be required. Whether they are needed, and to what extent, should be determined by risk assessment.

The risk, defined in this part of IEC 62305 as the probable average annual loss in a structure due to lightning flashes, depends on:

- the annual number of lightning flashes influencing the structure;
- the probability of damage by one of the influencing lightning flashes;
- the mean amount of consequential loss.

Lightning flashes influencing the structure may be divided into

- flashes terminating on the structure,
- flashes terminating near the structure, direct to connected lines (power, telecommunication lines,) or near the lines.

Flashes to the structure or a connected line may cause physical damage and life hazards. Flashes near the structure or line as well as flashes to the structure or line may cause failure of electrical and electronic systems due to overvoltages resulting from resistive and inductive coupling of these systems with the lightning current.

Moreover, failures caused by lightning overvoltages in users' installations and in power supply lines may also generate switching type overvoltages in the installations.

NOTE Malfunctioning of electrical and electronic systems is not covered by the IEC 62305 series. Reference should be made to IEC 61000-4-5 [1]1.

The number of lightning flashes influencing the structure depends on the dimensions and the characteristics of the structure and of the connected lines, on the environmental characteristics of the structure and the lines, as well as on lightning ground flash density in the region where the structure and the lines are located.

The probability of lightning damage depends on the structure, the connected lines, and the lightning current characteristics, as well as on the type and efficiency of applied protection measures.

The annual mean amount of the consequential loss depends on the extent of damage and the consequential effects which may occur as result of a lightning flash.

The effect of protection measures results from the features of each protection measure and may reduce the damage probabilities or the amount of consequential loss.

¹ Figures in square brackets refer to the bibliography.

The decision to provide lightning protection may be taken regardless of the outcome of risk assessment where there is a desire that there be no avoidable risk.

PROTECTION AGAINST LIGHTNING -

Part 2: Risk management

1 Scope

This part of IEC 62305 is applicable to risk assessment for a structure due to lightning flashes to earth.

Its purpose is to provide a procedure for the evaluation of such a risk. Once an upper tolerable limit for the risk has been selected, this procedure allows the selection of appropriate protection measures to be adopted to reduce the risk to or below the tolerable limit.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62305-1:2010, Protection against lightning – Part 1: General principles

IEC 62305-3:2010, Protection against lightning – Part 3: Physical damage to structures and life hazard

IEC 62305-4:2010, Protection against lightning – Part 4: Electrical and electronic systems within structures