

This is a preview of "IEC 62680-1-3 Ed. 2...". Click here to purchase the full version from the ANSI store.



Edition 2.0 2017-09

INTERNATIONAL STANDARD



Universal serial bus interfaces for data and power – Part 1-3: Common components – USB Type-C™ Cable and Connector Specification

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.120.20; 33.120.30; 35.200

ISBN 978-2-8322-4842-3

Warning! Make sure that you obtained this publication from an authorized distributor.

INTERNATIONAL ELECTROTECHNICAL COMMISSION

UNIVERSAL SERIAL BUS INTERFACES FOR DATA AND POWER –

Part 1-3: Common components – USB Type-C™ Cable and Connector Specification

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62680-1-3 has been prepared by technical area 14: Interfaces and methods of measurement for personal computing equipment, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This second edition cancels and replaces the first edition published in 2016 and constitutes a technical revision.

The text of this standard was prepared by the USB Implementers Forum (USB-IF). The structure and editorial rules used in this publication reflect the practice of the organization which submitted it.

The text of this standard is based on the following documents:

CDV	Report on voting
100/2853/CDV	100/2958/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The IEC 62680 series is based on a series of specifications that were originally developed by the USB Implementers Forum (USB-IF). These specifications were submitted to the IEC under the auspices of a special agreement between the IEC and the USB-IF.

This standard is the USB-IF publication USB Type-C™ Cable and Connector Specification Revision 1.2 as of March 25, 2016.

The USB Implementers Forum, Inc.(USB-IF) is a non-profit corporation founded by the group of companies that developed the Universal Serial Bus specification. The USB-IF was formed to provide a support organization and forum for the advancement and adoption of Universal Serial Bus technology. The Forum facilitates the development of high-quality compatible USB peripherals (devices), and promotes the benefits of USB and the quality of products that have passed compliance testing.

ANY USB SPECIFICATIONS ARE PROVIDED TO YOU "AS IS, "WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE USB IMPLEMENTERS FORUM AND THE AUTHORS OF ANY USB SPECIFICATIONS DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OR INFORMATION IN THIS SPECIFICATION.

THE PROVISION OF ANY USB SPECIFICATIONS TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS.

Entering into USB Adopters Agreements may, however, allow a signing company to participate in a reciprocal, RAND-Z licensing arrangement for compliant products. For more information, please see:

<http://www.usb.org/developers/docs/>

http://www.usb.org/developers/devclass_docs#approved

IEC DOES NOT TAKE ANY POSITION AS TO WHETHER IT IS ADVISABLE FOR YOU TO ENTER INTO ANY USB ADOPTERS AGREEMENTS OR TO PARTICIPATE IN THE USB IMPLEMENTERS FORUM.”

Universal Serial Bus Type-C Cable and Connector Specification

**Revision 1.2
March 25, 2016**

**Copyright © 2014-2016, USB 3.0 Promoter Group:
Hewlett-Packard Company, Intel Corporation, Microsoft Corporation,
Renesas, STMicroelectronics, and Texas Instruments
All rights reserved.**

NOTE: Adopters may only use the USB Type-C™ cable and connector to implement USB or third party functionality as expressly described in this Specification; all other uses are prohibited.

LIMITED COPYRIGHT LICENSE: The USB 3.0 Promoters grant a conditional copyright license under the copyrights embodied in the USB Type-C Cable and Connector Specification to use and reproduce the Specification for the sole purpose of, and solely to the extent necessary for, evaluating whether to implement the Specification in products that would comply with the specification. Without limiting the foregoing, use of the Specification for the purpose of filing or modifying any patent application to target the Specification or USB compliant products is not authorized. Except for this express copyright license, no other rights or licenses are granted, including without limitation any patent licenses. In order to obtain any additional intellectual property licenses or licensing commitments associated with the Specification a party must execute the USB 3.0 Adopters Agreement. NOTE: By using the Specification, you accept these license terms on your own behalf and, in the case where you are doing this as an employee, on behalf of your employer.

INTELLECTUAL PROPERTY DISCLAIMER

THIS SPECIFICATION IS PROVIDED TO YOU "AS IS" WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE AUTHORS OF THIS SPECIFICATION DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OF INFORMATION IN THIS SPECIFICATION. THE PROVISION OF THIS SPECIFICATION TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS.

All implementation examples and reference designs contained within this Specification are included as part of the limited patent license for those companies that execute the USB 3.0 Adopters Agreement.

USB Type-C™ and USB-C™ are trademarks of the Universal Serial Bus Implementers Forum (USB-IF). All product names are trademarks, registered trademarks, or service marks of their respective owners.

CONTENTS

Specification Work Group Chairs / Specification Editors.....	16
Specification Work Group Contributors	16
Pre-Release Draft Industry Reviewing Companies That Provided Feedback	18
Revision History.....	18
1 Introduction	19
1.1 Purpose	19
1.2 Scope	19
1.3 Related Documents.....	19
1.4 Conventions.....	20
1.4.1 Precedence	20
1.4.2 Keywords	20
1.4.3 Numbering.....	21
1.5 Terms and Abbreviations	21
2 Overview	23
2.1 Introduction.....	23
2.2 USB Type-C Receptacles, Plugs and Cables	25
2.3 Configuration Process.....	26
2.3.1 Source-to-Sink Attach/Detach Detection	26
2.3.2 Plug Orientation/Cable Twist Detection.....	27
2.3.3 Initial Power (Source-to-Sink) Detection and Establishing the Data (Host-to-Device) Relationship.....	27
2.3.4 USB Type-C VBUS Current Detection and Usage	28
2.3.5 USB PD Communication	28
2.3.6 Functional Extensions.....	28
2.4 VBUS	28
2.5 VCONN.....	29
2.6 Hubs.....	29
3 Mechanical	30
3.1 Overview	30
3.1.1 Compliant Connectors	30
3.1.2 Compliant Cable Assemblies	30
3.1.3 Compliant USB Type-C to Legacy Cable Assemblies	30
3.1.4 Compliant USB Type-C to Legacy Adapter Assemblies	31
3.2 USB Type-C Connector Mating Interfaces	31
3.2.1 Interface Definition	31
3.2.2 Reference Designs	51
3.2.3 Pin Assignments and Descriptions	58
3.3 Cable Construction and Wire Assignments.....	59
3.3.1 Cable Construction (Informative)	60
3.3.2 Wire Assignments.....	61
3.3.3 Wire Gauges and Cable Diameters (Informative)	62
3.4 Standard USB Type-C Cable Assemblies.....	64
3.4.1 USB Full-Featured Type-C Cable Assembly.....	64

3.4.2	USB 2.0 Type-C Cable Assembly	65
3.4.3	USB Type-C Captive Cable Assemblies	66
3.5	Legacy Cable Assemblies	66
3.5.1	USB Type-C to <i>USB 3.1</i> Standard-A Cable Assembly	67
3.5.2	USB Type-C to <i>USB 2.0</i> Standard-A Cable Assembly	68
3.5.3	USB Type-C to <i>USB 3.1</i> Standard-B Cable Assembly	69
3.5.4	USB Type-C to <i>USB 2.0</i> Standard-B Cable Assembly	70
3.5.5	USB Type-C to <i>USB 2.0</i> Mini-B Cable Assembly	71
3.5.6	USB Type-C to <i>USB 3.1</i> Micro-B Cable Assembly	72
3.5.7	USB Type-C to <i>USB 2.0</i> Micro-B Cable Assembly	74
3.6	Legacy Adapter Assemblies	74
3.6.1	USB Type-C to <i>USB 3.1</i> Standard-A Receptacle Adapter Assembly	75
3.6.2	USB Type-C to <i>USB 2.0</i> Micro-B Receptacle Adapter Assembly	76
3.7	Electrical Characteristics	78
3.7.1	Raw Cable (Informative)	78
3.7.2	USB Type-C to Type-C Passive Cable Assemblies (Normative)	79
3.7.3	Mated Connector (Informative)	91
3.7.4	USB Type-C to Legacy Cable Assemblies (Normative)	95
3.7.5	USB Type-C to USB Legacy Adapter Assemblies (Normative)	99
3.7.6	Shielding Effectiveness Requirements (Normative)	101
3.7.7	DC Electrical Requirements (Normative)	103
3.8	Mechanical and Environmental Requirements (Normative)	105
3.8.1	Mechanical Requirements	105
3.8.2	Environmental Requirements	111
3.9	Docking Applications (Informative)	112
3.10	Implementation Notes and Design Guides	113
3.10.1	EMC Management (Informative)	113
3.10.2	Stacked and Side-by-Side Connector Physical Spacing (Informative)	115
3.10.3	Cable Mating Considerations (Informative)	116
4	Functional	117
4.1	Signal Summary	117
4.2	Signal Pin Descriptions	117
4.2.1	SuperSpeed USB Pins	117
4.2.2	USB 2.0 Pins	117
4.2.3	Auxiliary Signal Pins	118
4.2.4	Power and Ground Pins	118
4.2.5	Configuration Pins	118
4.3	Sideband Use (SBU)	118
4.4	Power and Ground	118
4.4.1	IR Drop	118
4.4.2	V _{BUS}	119
4.4.3	V _{CONN}	120
4.5	Configuration Channel (CC)	121
4.5.1	Architectural Overview	121
4.5.2	CC Functional and Behavioral Requirements	134

4.5.3	USB Port Interoperability Behavior	155
4.6	Power	165
4.6.1	Power Requirements during USB Suspend	166
4.6.2	VBUS Power Provided Over a USB Type-C Cable.....	167
4.7	USB Hubs	169
4.8	Chargers.....	170
4.8.1	DFP as a Power Source.....	170
4.8.2	Non-USB Charging Methods	172
4.8.3	Sinking Host	172
4.8.4	Sourcing Device	173
4.8.5	Charging a System with a Dead Battery.....	173
4.9	Electronically Marked Cables	173
4.10	VCONN-Powered Accessories	174
4.11	Parameter Values	175
4.11.1	Termination Parameters	175
4.11.2	Timing Parameters	177
4.11.3	Voltage Parameters	179
5	Functional Extensions	180
5.1	Alternate Modes.....	180
5.1.1	Alternate Mode Architecture	181
5.1.2	Alternate Mode Requirements.....	181
5.1.3	Parameter Values	185
5.1.4	Example Alternate Mode – USB DisplayPort™ Dock.....	185
5.2	Managed Active Cables	188
5.2.1	Requirements for Managed Active Cables that respond to SOP' and SOP" ..	188
5.2.2	Cable Message Structure	189
5.2.3	Modal Cable Management	190
A	Audio Adapter Accessory Mode	190
A.1.	Overview	190
A.2.	Detail	190
A.3.	Electrical Requirements	191
A.4.	Example Implementations	193
A.4.1.	Passive 3.5 mm to USB Type-C Adapter – Single Pole Detection Switch	193
A.4.2.	3.5 mm to USB Type-C Adapter Supporting 500 mA Charge-Through.....	193
B	Debug Accessory Mode	194
B.1.	Overview	194
B.2.	Functional.....	194
B.2.1.	Signal Summary	196
B.2.2.	Port Interoperability	196
B.2.3.	Debug Accessory Mode Entry	196
B.2.4.	Connection State Diagrams	197
B.2.5.	DTS Port Interoperability Behavior.....	206
B.2.6.	Orientation Detection.....	215
B.3.	Security/Privacy Requirements:	215
C	USB Type-C Digital Audio.....	216

FIGURES

Figure 2-1 USB Type-C Receptacle Interface (Front View).....	24
Figure 2-2 USB Full-Featured Type-C Plug Interface (Front View)	25
Figure 3-1 USB Type-C Receptacle Interface Dimensions.....	33
Figure 3-2 Reference Design USB Type-C Plug External EMC Spring Contact Zones	37
Figure 3-3 USB Full-Featured Type-C Plug Interface Dimensions	38
Figure 3-4 Reference Footprint for a USB Type-C Vertical Mount Receptacle (Informative)	41
Figure 3-5 Reference Footprint for a USB Type-C Dual-Row SMT Right Angle Receptacle (Informative)	42
Figure 3-6 Reference Footprint for a USB Type-C Hybrid Right-Angle Receptacle (Informative)	43
Figure 3-7 Reference Footprint for a USB Type-C Mid-Mount Dual-Row SMT Receptacle (Informative)	44
Figure 3-8 Reference Footprint for a USB Type-C Mid-Mount Hybrid Receptacle (Informative)	45
Figure 3-9 <i>USB 2.0</i> Type-C Plug Interface Dimensions	47
Figure 3-10 USB Type-C Plug EMC Shielding Spring Tip Requirements	50
Figure 3-11 Reference Design of Receptacle Mid-Plate	51
Figure 3-12 Reference Design of the Retention Latch	52
Figure 3-13 Illustration of the Latch Soldered to the Paddle Card Ground	52
Figure 3-14 Reference Design of the USB Full-Featured Type-C Plug Internal EMC Spring.....	53
Figure 3-15 Reference Design of the <i>USB 2.0</i> Type-C Plug Internal EMC Spring	54
Figure 3-16 Reference Design of Internal EMC Pad	55
Figure 3-17 Reference Design of a USB Type-C Receptacle with External EMC Springs	56
Figure 3-18 Reference Design for a USB Full-Featured Type-C Plug Paddle Card	57
Figure 3-19 Illustration of a USB Full-Featured Type-C Cable Cross Section, a Coaxial Wire Example with VCONN.....	60
Figure 3-20 Illustration of a USB Full-Featured Type-C Cable Cross Section, a Coaxial Wire Example without VCONN	60
Figure 3-21 USB Full-Featured Type-C Standard Cable Assembly	64
Figure 3-22 USB Type-C to USB 3.1 Standard-A Cable Assembly	67
Figure 3-23 USB Type-C to <i>USB 2.0</i> Standard-A Cable Assembly	68
Figure 3-24 USB Type-C to <i>USB 3.1</i> Standard-B Cable Assembly	69
Figure 3-25 USB Type-C to <i>USB 2.0</i> Standard-B Cable Assembly	70
Figure 3-26 USB Type-C to <i>USB 2.0</i> Mini-B Cable Assembly	71
Figure 3-27 USB Type-C to <i>USB 3.1</i> Micro-B Cable Assembly	72
Figure 3-28 USB Type-C to <i>USB 2.0</i> Micro-B Cable Assembly	74
Figure 3-29 USB Type-C to <i>USB 3.1</i> Standard-A Receptacle Adapter Assembly	75
Figure 3-30 USB Type-C to <i>USB 2.0</i> Micro-B Receptacle Adapter Assembly.....	76

Figure 3-31 Illustration of Test Points for a Mated Cable Assembly.....	79
Figure 3-32 Recommended Differential Insertion Loss Requirement	79
Figure 3-33 Recommended Differential Return Loss Requirement	80
Figure 3-34 Recommended Differential Crosstalk Requirement.....	80
Figure 3-35 Recommended Differential Near-End and Far-End Crosstalk Requirement between USB D+/D- Pair and USB SuperSpeed Pair.....	81
Figure 3-36 Illustration of Insertion Loss Fit at Nyquist Frequency	82
Figure 3-37 Input Pulse Spectrum.....	83
Figure 3-38 IMR Limit as Function of ILfitatNq	83
Figure 3-39 IRL Limit as Function of ILfitatNq	85
Figure 3-40 Differential-to-Common-Mode Conversion Requirement	85
Figure 3-41 Requirement for Differential Coupling between CC and D+/D-	87
Figure 3-42 Requirement for Single-Ended Coupling between CC and D- in USB 2.0 Type-C Cables.....	87
Figure 3-43 Requirement for Single-Ended Coupling between CC and D- in USB Full- Featured Type-C Cables.....	88
Figure 3-44 Requirement for Differential Coupling between VBUS and D+/D-	88
Figure 3-45 Requirement for Single-Ended Coupling between SBU_A and SBU_B	89
Figure 3-46 Requirement for Single-Ended Coupling between SBU_A/SBU_B and CC	89
Figure 3-47 Requirement for Coupling between SBU_A and differential D+/D-, and SBU_B and differential D+/D-	90
Figure 3-48 Illustration of USB Type-C Mated Connector	91
Figure 3-49 Recommended Impedance Limits of a USB Type-C Mated Connector	92
Figure 3-50 Recommended Ground Void Dimensions for USB Type-C Receptacle.....	93
Figure 3-51 Recommended Differential Near-End and Far-End Crosstalk Limits between D+/D- Pair and SuperSpeed Pairs.....	95
Figure 3-52 Recommended Limits for Differential-to-Common-Mode Conversion	95
Figure 3-53 IMR Limit as Function of ILfitatNq for USB Type-C to Legacy Cable Assembly.....	98
Figure 3-54 IRL Limit as Function of ILfitatNq for USB Type-C to Legacy Cable Assembly...	98
Figure 3-55 Cable Assembly Shielding Effectiveness Testing	102
Figure 3-56 Shielding Effectiveness Pass/Fail Criteria	102
Figure 3-57 LLCR Measurement Diagram	103
Figure 3-58 Temperature Measurement Point	104
Figure 3-59 Example Current Rating Test Fixture Trace Configuration.....	105
Figure 3-60 Example of 4-Axis Continuity Test Fixture	107
Figure 3-61 Example Wrenching Strength Test Fixture for Plugs without Overmold.....	109
Figure 3-62 Reference Wrenching Strength Continuity Test Fixture	110
Figure 3-63 Example of Wrenching Strength Test Mechanical Failure Point	110
Figure 3-64 Wrenching Strength Test with Cable in Fixture.....	111
Figure 3-65 USB Type-C Cable Receptacle Flange Example	113
Figure 3-66 EMC Guidelines for Side Latch and Mid-plate	114

Figure 3-67 EMC Finger Connections to Plug Shell.....	114
Figure 3-68 EMC Pad Connections to Receptacle Shell	115
Figure 3-69 Examples of Connector Apertures	115
Figure 3-70 Recommended Minimum Spacing between Connectors.....	116
Figure 3-71 Recommended Minimum Plug Overmold Clearance	116
Figure 3-72 Cable Plug Overmold and an Angled Surface.....	116
Figure 4-1 Cable IR Drop.....	119
Figure 4-2 Cable IR Drop for powered cables	119
Figure 4-3 Logical Model for Data Bus Routing across USB Type-C-based Ports.....	122
Figure 4-4 Logical Model for USB Type-C-based Ports for the Direct Connect Device.....	123
Figure 4-5 Pull-Up/Pull-Down CC Model	125
Figure 4-6 Current Source/Pull-Down CC Model	125
Figure 4-7 Source Functional Model for CC1 and CC2.....	128
Figure 4-8 Source Functional Model Supporting USB PD PR_Swap.....	129
Figure 4-9 Sink Functional Model for CC1 and CC2	129
Figure 4-10 UFP Functional Model Supporting USB PD PR_Swap and VCONN_Swap	130
Figure 4-11 DRP Functional Model for CC1 and CC2.....	131
Figure 4-12 Connection State Diagram: Source	135
Figure 4-13 Connection State Diagram: Sink.....	136
Figure 4-14 Connection State Diagram: Sink with Accessory Support	137
Figure 4-15 Connection State Diagram: DRP	138
Figure 4-16 Connection State Diagram: DRP with Accessory and Try.SRC Support.....	139
Figure 4-17 Connection State Diagram: DRP with Accessory and Try.SNK Support	140
Figure 4-18 Sink Power Sub-States	152
Figure 4-19 Source to Sink Functional Model.....	155
Figure 4-20 Source to DRP Functional Model	156
Figure 4-21 DRP to Sink Functional Model.....	157
Figure 4-22 DRP to DRP Functional Model – CASE 1	158
Figure 4-23 DRP to DRP Functional Model – CASE 2 & 3.....	159
Figure 4-24 Source to Source Functional Model.....	161
Figure 4-25 Sink to Sink Functional Model	162
Figure 4-26 Source to Legacy Device Port Functional Model	162
Figure 4-27 Legacy Host Port to Sink Functional Model	163
Figure 4-28 DRP to Legacy Device Port Functional Model	164
Figure 4-29 Legacy Host Port to DRP Functional Model.....	165
Figure 4-30 Sink Monitoring for Current in Pull-Up/Pull-Down CC Model.....	168
Figure 4-31 Sink Monitoring for Current in Current Source/Pull-Down CC Model.....	168
Figure 4-32 USB PD over CC Pins.....	169
Figure 4-33 USB PD BMC Signaling over CC.....	169

Figure 4-34 USB Type-C Cable's Output as a Function of Load for Non-PD-based USB Type-C Charging	171
Figure 4-35 0 – 3 A USB PD-based Charger USB Type-C Cable's Output as a Function of Load	171
Figure 4-36 3 – 5 A USB PD-based Charger USB Type-C Cable's Output as a Function of Load	172
Figure 4-37 Electronically Marked Cable with VCONN connected through the cable	174
Figure 4-38 Electronically Marked Cable with SOP' at both ends	174
Figure 4-39 DRP Timing	178
Figure 5-1 Pins Available for Reconfiguration over the Full-Featured Cable	182
Figure 5-2 Pins Available for Reconfiguration for Direct Connect Applications	182
Figure 5-3 Alternate Mode Implementation using a USB Type-C to USB Type-C Cable.....	183
Figure 5-4 Alternate Mode Implementation using a USB Type-C to Alternate Mode Cable or Device	184
Figure 5-5 USB DisplayPort Dock Example	186
Figure 5-6 Managed Active Cable Plug SOP' and SOP" Assignment	188
Figure 5-7 Managed Active Cable	189
Figure A-1 Example Passive 3.5 mm to USB Type-C Adapter	193
Figure A-2 Example 3.5 mm to USB Type-C Adapter Supporting 500 mA Charge-Through	194
Figure B-1 USB Type-C Debug Accessory Layered Behavior	195
Figure B-2 DTS Plug Interface	196
Figure B-3 Connection State Diagram: DTS Source	197
Figure B-4 Connection State Diagram: DTS Sink	198
Figure B-5 Connection State Diagram: DTS DRP	199
Figure B-6 TS Sink Power Sub-States	204

TABLES

Table 2-1 Summary of power supply options	29
Table 3-1 USB Type-C Standard Cable Assemblies	30
Table 3-2 USB Type-C Legacy Cable Assemblies	31
Table 3-3 USB Type-C Legacy Adapter Assemblies	31
Table 3-4 USB Type-C Receptacle Interface Pin Assignments	58
Table 3-5 USB Type-C Receptacle Interface Pin Assignments for USB 2.0-only Support	59
Table 3-6 USB Type-C Standard Cable Wire Assignments	61
Table 3-7 USB Type-C Cable Wire Assignments for Legacy Cables/Adapters	62
Table 3-8 Reference Wire Gauges for standard USB Type-C Cable Assemblies	63
Table 3-9 Reference Wire Gauges for USB Type-C to Legacy Cable Assemblies	63
Table 3-10 USB Full-Featured Type-C Standard Cable Assembly Wiring	65
Table 3-11 <i>USB 2.0</i> Type-C Standard Cable Assembly Wiring	66
Table 3-12 USB Type-C to <i>USB 3.1</i> Standard-A Cable Assembly Wiring	67
Table 3-13 USB Type-C to <i>USB 2.0</i> Standard-A Cable Assembly Wiring	68

Table 3-14	USB Type-C to <i>USB 3.1</i> Standard-B Cable Assembly Wiring.....	69
Table 3-15	USB Type-C to <i>USB 2.0</i> Standard-B Cable Assembly Wiring.....	70
Table 3-16	USB Type-C to <i>USB 2.0</i> Mini-B Cable Assembly Wiring	71
Table 3-17	USB Type-C to <i>USB 3.1</i> Micro-B Cable Assembly Wiring	73
Table 3-18	USB Type-C to <i>USB 2.0</i> Micro-B Cable Assembly Wiring	74
Table 3-19	USB Type-C to <i>USB 3.1</i> Standard-A Receptacle Adapter Assembly Wiring	76
Table 3-20	USB Type-C to <i>USB 2.0</i> Micro-B Receptacle Adapter Assembly Wiring.....	77
Table 3-21	Differential Insertion Loss Examples for USB SuperSpeed with Twisted Pair Construction	78
Table 3-22	Differential Insertion Loss Examples for USB SuperSpeed with Coaxial Construction	79
Table 3-23	Electrical Requirements for CC and SBU wires	86
Table 3-24	Coupling Matrix for Low Speed Signals	86
Table 3-25	USB D+/D- Signal Integrity Requirements for USB Type-C to USB Type-C Passive Cable Assemblies	91
Table 3-26	USB Type-C Mated Connector Recommended Signal Integrity Characteristics (Informative)	93
Table 3-27	USB D+/D- Signal Integrity Requirements for USB Type-C to Legacy USB Cable Assemblies	96
Table 3-28	Design Targets for USB Type-C to <i>USB 3.1</i> Gen 2 Legacy Cable Assemblies (Informative)	97
Table 3-29	USB Type-C to <i>USB 3.1</i> Gen 2 Legacy Cable Assembly Signal Integrity Requirements (Normative)	97
Table 3-30	USB D+/D- Signal Integrity Requirements for USB Type-C to Legacy USB Adapter Assemblies (Normative).....	99
Table 3-31	Design Targets for USB Type-C to <i>USB 3.1</i> Standard-A Adapter Assemblies (Informative)	100
Table 3-32	USB Type-C to <i>USB 3.1</i> Standard-A Receptacle Adapter Assembly Signal Integrity Requirements (Normative).....	101
Table 3-33	Current Rating Test PCB.....	105
Table 3-34	Force and Moment Requirements.....	108
Table 3-35	Environmental Test Conditions	111
Table 3-36	Reference Materials	112
Table 4-1	USB Type-C List of Signals	117
Table 4-2	VBUS Source Characteristics	120
Table 4-3	USB Type-C Source Port's VCONN Requirements Summary	120
Table 4-4	VCONN Source Characteristics.....	121
Table 4-5	VCONN Sink Characteristics.....	121
Table 4-6	USB Type-C-based Port Interoperability.....	124
Table 4-7	Source Perspective	126
Table 4-8	Source (Host) and Sink (Device) Behaviors by State	127
Table 4-9	USB PD Swapping Port Behavior Summary	132
Table 4-10	Power Role Behavioral Model Summary.....	133

Table 4-11 Source Port CC Pin State.....	141
Table 4-12 Sink Port CC Pin State.....	141
Table 4-13 Mandatory and Optional States.....	154
Table 4-14 Precedence of power source usage.....	166
Table 4-15 Source CC Termination (Rp) Requirements.....	175
Table 4-16 Sink CC Termination (Rd) Requirements.....	176
Table 4-17 Powered Cable Termination Requirements.....	176
Table 4-18 Sink CC Termination Requirements.....	176
Table 4-19 SBU Termination Requirements.....	176
Table 4-20 VBUS and VCONN Timing Parameters.....	177
Table 4-21 DRP Timing Parameters.....	178
Table 4-22 CC Timing.....	179
Table 4-23 CC Voltages on Source Side – Default USB.....	179
Table 4-24 CC Voltages on Source Side – 1.5 A @ 5 V.....	179
Table 4-25 CC Voltages on Source Side – 3.0 A @ 5 V.....	180
Table 4-26 Voltage on Sink CC Pins (Default USB Type-C Current only).....	180
Table 4-27 Voltage on Sink CC pins (Multiple Source Current Advertisements).....	180
Table 5-1 USB Safe State Electrical Requirements.....	184
Table 5-2 USB Billboard Device Class Availability Following Alternate Mode Entry Failure.....	185
Table 5-3 Alternate Mode Signal Noise Ingression Requirements.....	185
Table 5-4 SOP' and SOP" Timing.....	189
Table A-1 USB Type-C Analog Audio Pin Assignments.....	191
Table A-2 USB Type-C Analog Audio Pin Electrical Parameter Ratings.....	192
Table B-1 DTS to TS Port Interoperability.....	196
Table B-2 Rp/Rp Charging Current Values for a DTS Source.....	204
Table B-3 Mandatory and Optional States.....	206

Note: All Engineering Change Notice's (ECN) and Errata documents as of December 06, 2016 that pertain to this core specification follow the last page of the specification starting on page 217.

Specification Work Group Chairs / Specification Editors

Intel Corporation (USB 3.0 Promoter company)	Yun Ling – Mechanical WG co-chair, Mechanical Chapter Co-editor Bob Dunstan – Functional WG co-chair, Specification Co-author Brad Saunders – Plenary/Functional WG chair, Specification Co-author
Seagate	Alvin Cox, Mechanical WG co-chair, Mechanical Chapter Co-editor

Specification Work Group Contributors

Advanced-Connectek, Inc. (ACON)	Glen Chandler Jeff Chien Lee (Dick Lee) Ching Conrad Choy	Vicky Chuang Aven Kao Danny Liao Alan MacDougall	Alan Tsai Stephen Yang
Advanced Micro Devices	Steve Capezza	Walter Fry	Will Harris
Agilent Technologies, Inc.	James Choate		
Analogix Semiconductor, Inc.	Mehran Badii	Greg Stewart	
Apple	Mahmoud Amini Sree Anantharaman Paul Baker Jason Chung David Conroy Bill Cornelius William Ferry	Zheng Gao Girault Jones Keong Kam Min Kim Chris Ligtenberg Nathan Ng James Orr	Keith Porthouse Sascha Tietz Jennifer Tsai Colin Whitby- Stevens Dennis Yarak
Cypress Semiconductor	Mark Fu Rushil Kadakia	Anup Nayak Jagadeesan Raj	Sanjay Sancheti Subu Sankaran
Dell	Mohammed Hijazi David Meyers	Sean O'Neal Ernesto Ramirez	Thomas Voor
DisplayLink (UK) Ltd.	Pete Burgers	Richard Petrie	
Electronics Testing Center, Taiwan	Sophia Liu		
Foxconn	Asroc Chen Allen Cheng Jason Chou Edmond Choy Bob Hall	Chien-Ping Kao Ji Li Ann Liu Terry Little Steve Sedio	Pei Tsao AJ Yang Yuan Zhang Jessica Zheng Andy Yao
Foxlink/Cheng Uei Precision Industry Co., Ltd.	Robert Chen Sunny Chou Carrie Chuang Wen-Chuan Hsu Alex Hsue	Armando Lee Dennis Lee Justin Lin Tse Wu Ting	Steve Tsai Wen Yang Wiley Yang Junjie Yu
Google	Joshua Boilard Alec Berg Todd Broch Jim Guerin Jeffrey Hayashida	Mark Hayter Nithya Jagannathan Lawrence Lam Ingrid Lin Richard Palatin	Adam Rodriguez David Schneider Ken Wu
Granite River Labs	Mike Engbretson	Johnson Tan	
Hewlett Packard (USB 3.0 Promoter company)	Alan Berkema Robin Castell	Michael Krause Jim Mann	Linden McClure Mike Pescetto

Hirose Electric Co., Ltd.	Jeremy Buan William MacKillop	Gourgen Oganessyan	Sid Tono
Intel Corporation (USB 3.0 Promoter company)	Dave Ackelson Mike Bell Kuan-Yu Chen Hengju Cheng Bob Dunstan Paul Durley Howard Heck Hao-Han Hsu Abdul (Rahman) Ismail	James Jaussi Luke Johnson Jerzy Kolinski Rolf Kuhnig Christine Krause Henrik Leegaard Yun Ling Xiang Li Guobin Liu Steve McGowan	Sankaran Menon Chee Lim Nge Sridharan Ranganathan Brad Saunders Amit Srivastava Ron Swartz Karthi Vadivelu Rafal Wielicki
Japan Aviation Electronics Industry Ltd. (JAE)	Kenji Hagiwara Masaki Kimura Toshio Masumoto Joe Motojima Ron Muir Tadashi Okubo Kazuhiro Saito	Kimiaki Saito Yuichi Saito Mark Saubert Toshio Shimoyama Tatsuya Shioda Atsuo Tago Masaaki Takaku	Jussi Takaneva Tomohiko Tamada Kentaro Toda Kouhei Ueda Takakazu Usami Masahide Watanabe Youhei Yokoyama
JPC/Main Super Inc.	Sam Tseng	Ray Yang	
LeCroy Corporation	Daniel H. Jacobs		
Lenovo	Rob Bowser Tomoki Harada	Wei Liu	Howard Locker
Lotes Co., Ltd.	Ariel Delos Reyes Ernest Han Mark Ho	Regina Liu-Hwang Max Lo Charles Kaun	JinYi Tu Jason Yang
LSI Corporation	Dave Thompson		
Luxshare-ICT	Josue Castillo Daniel Chen Lisen Chen	CY Hsu Alan Kinningham John Lin	Stone Lin Pat Young
MegaChips Corporation	Alan Kobayashi		
Microchip (SMSC)	Josh Averyt Mark Bohm	Donald Perkins	Mohammed Rahman
Microsoft Corporation (USB 3.0 Promoter company)	Randy Aull Fred Bhesania Anthony Chen Marty Evans Vivek Gupta Robbie Harris	Robert Hollyer Kai Inha Jayson Kastens Andrea Keating Eric Lee	Ivan McCracken Toby Nixon Gene Obie Srivatsan Ravindran David Voth
MQP Electronics Ltd.	Sten Carlsen	Pat Crowe	
Nokia Corporation	Daniel Gratiot Pekka Leinonen	Samuli Makinen Pekka Talmola	Timo Toivola Panu Ylihaavisto
NXP Semiconductors	Vijendra Kuroodi	Guru Prasad	
Renesas Electronics Corp. (USB 3.0 Promoter company)	Nobuo Furuya	Philip Leung	Kiichi Muto
Rohm Co., Ltd.	Mark Aaldering Kris Bahar Yusuke Kondo	Arun Kumar Chris Lin	Takashi Sato Hiroshi Yoshimura

Samsung Electronics Co., Ltd.	Soondo Kim Woonki Kim	Jagoun Koo Cheolho Lee	Jun Bum Lee
Seagate	Alvin Cox Tony Priborsky	Tom Skaar	Dan Smith
STMicroelectronics (USB 3.0 Promoter company)	Nathalie Ballot Nicolas Florenchie Joel Huloux	Christophe Lorin Patrizia Milazzo	Federico Musarra Pascal Legrand
Tektronics, Inc.	Randy White		
Texas Instruments (USB 3.0 Promoter company)	Jawaid Ahmad Richard Hubbard Scott Jackson Yoon Lee Grant Ley	Win Maung Lauren Moore Martin Patoka Brian Quach Wes Ray	Anwar Sadat Sue Vining Deric Waters
Tyco Electronics Corp. (TE Connectivity Ltd.)	Max Chao Robert E. Cid Kengo Ijiri Eiji Ikematsu Joan Leu Clark Li Mike Lockyer	Jim McGrath Takeshi Nakashima Luis A. Navarro Masako Saito Yoshiaki Sakuma Gavin Shih Hiroshi Shirai	Scott Shuey Hidenori Taguchi Bernard Vetten Ryan Yu Sjoerd Zwartkruis
VIA Technologies Inc.	Terrance Shih	Jay Tseng	Fong-Jim Wang

Pre-Release Draft Industry Reviewing Companies That Provided Feedback

Aces	Joinsoon Electronics Mfg. Co. Ltd.	Parade Technology
Allion Labs, Inc.	JST Mfg. Co., Ltd.	Pericom
BizLink International Corp.	Korea Electric Terminal	Qualcomm
Corning Optical Communications LLC	Marvell Semiconductor	Semtech Corporation
Cypress Semiconductor	Motorola Mobility LLC	Shenzhen Deren Electronic Co., Ltd.
Etron Technology Inc.	NEC	Silicon Image
Fairchild Semiconductor	Newnex Technology Corp.	Simula Technology Corp.
Fujitsu Ltd.	NXP Semiconductors	SMK Corporation
Industrial Technology Research Institute (ITRI)	PalCONN/PalNova (Palpilot International Corp.)	Sony Corporation
		Sumitomo Electric Industries
		Toshiba Corporation

Revision History

Revision	Date	Description
1.0	August 11, 2014	Initial Release
1.1	April 3, 2015	Reprint release including incorporation of all approved ECNs as of the revision date plus editorial clean-up.
1.2	March 25, 2016	Reprint release including incorporation of all approved ECNs as of the revision date plus editorial clean-up.

1 Introduction

With the continued success of the USB interface, there exists a need to adapt USB technology to serve newer computing platforms and devices as they trend toward smaller, thinner and lighter form-factors. Many of these newer platforms and devices are reaching a point where existing USB receptacles and plugs are inhibiting innovation, especially given the relatively large size and internal volume constraints of the Standard-A and Standard-B versions of USB connectors. Additionally, as platform usage models have evolved, usability and robustness requirements have advanced and the existing set of USB connectors were not originally designed for some of these newer requirements. This specification is to establish a new USB connector ecosystem that addresses the evolving needs of platforms and devices while retaining all of the functional benefits of USB that form the basis for this most popular of computing device interconnects.

1.1 Purpose

This specification defines the USB Type-C™ receptacles, plug and cables.

The USB Type-C Cable and Connector Specification is guided by the following principles:

- Enable new and exciting host and device form-factors where size, industrial design and style are important parameters
- Work seamlessly with existing USB host and device silicon solutions
- Enhance ease of use for connecting USB devices with a focus on minimizing user confusion for plug and cable orientation

The USB Type-C Cable and Connector Specification defines a new receptacle, plug, cable and detection mechanisms that are compatible with existing USB interface electrical and functional specifications. This specification covers the following aspects that are needed to produce and use this new USB cable/connector solution in newer platforms and devices, and that interoperate with existing platforms and devices:

- USB Type-C receptacles, including electro-mechanical definition and performance requirements
- USB Type-C plugs and cable assemblies, including electro-mechanical definition and performance requirements
- USB Type-C to legacy cable assemblies and adapters
- USB Type-C-based device detection and interface configuration, including support for legacy connections
- USB Power Delivery optimized for the USB Type-C connector

The USB Type-C Cable and Connector Specification defines a standardized mechanism that supports Alternate Modes, such as repurposing the connector for docking-specific applications.

1.2 Scope

This specification is intended as a supplement to the existing *USB 2.0*, *USB 3.1* and *USB Power Delivery* specifications. It addresses only the elements required to implement and support the USB Type-C receptacles, plugs and cables.

Normative information is provided to allow interoperability of components designed to this specification. Informative information, when provided, may illustrate possible design implementations.