

Reaffirmed as
INCITS 452-2009 (R2019)

American National Standard

INCITS 452-2009

*for Information Technology –
AT Attachment 8 - ATA/ATAPI
Command Set (ATA8-ACS)*

Developed by



Where IT all begins



This is a preview of "INCITS 452-2009 (R20...". Click here to purchase the full version from the ANSI store.

INCITS 452-2009

American National Standard
for Information Technology –

AT Attachment 8 - ATA/ATAPI Command Set (ATA8-ACS)

Secretariat

Information Technology Industry Council

Approved September 29, 2009

American National Standards Institute, Inc.

Abstract

This standard specifies the AT Attachment command set used to communicate between host systems and storage devices. This provides a common command set for systems manufacturers, system integrators, software suppliers, and suppliers of storage devices. The AT Attachment command set includes the PACKET feature set implemented by devices commonly known as ATAPI devices. This standard maintains a high degree of compatibility with the AT Attachment Interface with Packet Interface - 7 (ATA/ATAPI-7) volume 1 (see ANSI INCITS 397-2004).

American National Standard

Approval of an American National Standard requires review by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made towards their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

CAUTION: The developers of this standard have requested that holders of patents that may be required for the implementation of the standard disclose such patents to the publisher. However, neither the developers nor the publisher have undertaken a patent search in order to identify which, if any, patents may apply to this standard. As of the date of publication of this standard, following calls for the identification of patents that may be required for the implementation of the standard, notice of one or more such claims has been received. By publication of this standard, no position is taken with respect to the validity of this claim or of any rights in connection therewith. The known patent holder(s) has (have), however, filed a statement of willingness to grant a license under these rights on reasonable and nondiscriminatory terms and conditions to applicants desiring to obtain such a license. Details may be obtained from the publisher. No further patent search is conducted by the developer or publisher in respect to any standard it processes. No representation is made or implied that this is the only license that may be required to avoid infringement in the use of this standard.

Published by

**American National Standards Institute, Inc.
25 West 43rd Street, New York, NY 10036**

Copyright © 2009 by Information Technology Industry Council (ITI)
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of ITI, 1101 K Street NW, Suite 610 Washington, DC 20005.

Printed in the United States of America

Contents

	Page
Foreword	xvii
Introduction	xx
1 Scope	1
2 Normative references	2
2.1 General	2
2.2 Approved references	2
2.3 References under development	3
2.4 Other references	3
3 Definitions, abbreviations, and conventions	4
3.1 Definitions and abbreviations	4
3.2 Conventions	7
3.2.1 Overview	7
3.2.2 Precedence	7
3.2.3 Lists	7
3.2.4 Keywords	8
3.2.5 Numbering	9
3.2.6 Bit conventions	9
3.2.7 State diagram conventions	10
3.2.8 Byte, word, DWord, and QWord Relationships	11
3.2.9 ATA string convention	13
4 Feature set definitions	14
4.1 Overview	14
4.2 General feature set	14
4.3 The PACKET feature set	15
4.3.1 Overview	15
4.3.2 Identification of PACKET feature set devices	16
4.3.3 Signature for ATAPI devices	16
4.3.4 The PACKET command	16
4.4 48-bit Address feature set	16
4.5 Advanced Power Management (APM) feature set	17
4.6 Automatic Acoustic Management (AAM) feature set	17
4.7 CompactFlash Association (CFA) feature set	17
4.8 Device Configuration Overlay (DCO) feature set	18
4.9 Free-fall Control feature set	20
4.10 General Purpose Logging (GPL) feature set	20
4.11 Host Protected Area (HPA) feature set	21
4.11.1 HPA overview	21
4.11.2 HPA security extensions	21
4.11.3 28-bit and 48-bit HPA commands interactions	21

	Page
4.11.4 IDENTIFY DEVICE data	23
4.11.5 Determination of SET MAX security extension status	23
4.11.6 HPA State Transition Diagrams	23
4.12 Long Logical Sector (LLS) feature set	39
4.13 Long Physical Sector (LPS) feature set	40
4.14 Media Card Pass Through Command feature set	42
4.15 Native Command Queuing (NCQ) feature set	42
4.15.1 Overview	42
4.15.2 Command Phases	43
4.16 NV Cache feature set	43
4.17 NV Cache Power Management feature set	45
4.18 Power Management feature set	45
4.18.1 Overview	45
4.18.2 Power management commands	46
4.18.3 Standby timer	46
4.18.4 Power modes	47
4.19 Power-Up In Standby (PUIS) feature set	48
4.20 Security feature set	49
4.20.1 Overview	49
4.20.2 Passwords	49
4.20.3 Master Password Capability	49
4.20.4 Frozen Mode	50
4.20.5 Commands	50
4.20.6 IDENTIFY DEVICE data	50
4.20.7 Security initial setting	50
4.20.8 Password Rules	50
4.20.9 Password attempt counter	50
4.20.10 Security states	52
4.20.11 Master Password Identifier feature	62
4.21 Self-Monitoring, Analysis, and Reporting Technology (SMART) feature set	63
4.21.1 Overview	63
4.21.2 Device SMART data structure	63
4.21.3 Background data collection	63
4.21.4 Off-line/Captive mode data collection	63
4.21.5 Threshold exceeded condition	63
4.21.6 SMART feature set commands	63
4.21.7 SMART operation with power management modes	63
4.21.8 SMART device error log reporting	64
4.22 Software Settings Preservation (SSP) feature set	64
4.23 Streaming feature set	64
4.23.1 Streaming feature set overview	64
4.23.2 Streaming commands	65

	Page
4.24	Tagged Command Queuing (TCQ) feature set 66
4.24.1	Overview 66
4.24.2	Queueing 67
4.25	Trusted Computing feature set 67
4.26	Write-Read-Verify feature set 67
5	ATA protocols 69
6	Normal and Error Output field descriptions 70
6.1	Overview 70
6.2	Status field 70
6.2.1	Overview 70
6.2.2	Busy bit 70
6.2.3	Check Condition bit 70
6.2.4	Data Request bit 70
6.2.5	Deferred Write Error bit 70
6.2.6	Device Fault bit 71
6.2.7	Device Ready bit 71
6.2.8	Error bit 71
6.2.9	Service bit 71
6.2.10	Stream Error bit 71
6.2.11	Transport Dependent (TD) 71
6.3	Error field 72
6.3.1	Overview 72
6.3.2	Abort bit 72
6.3.3	Attempted Partial Range Removal bit 72
6.3.4	Command Completion Time Out bit 72
6.3.5	End of Media bit 72
6.3.6	ID Not Found bit 72
6.3.7	Illegal Length Indicator bit 72
6.3.8	Insufficient LBA Range Entries Remaining bit 73
6.3.9	Insufficient NV Cache Space bit 73
6.3.10	Interface CRC bit 73
6.3.11	Media Error bit 73
6.3.12	Sense Key field 73
6.3.13	Uncorrectable Error bit 73
6.4	Interrupt Reason field 73
6.4.1	Overview 73
6.4.2	Command/Data bit 73
6.4.3	Input/Output (I/O) bit 73
6.4.4	Release bit 73
6.4.5	Tag field 73
6.5	Count field 74
6.5.1	Overview 74
6.5.2	NCQ Tag field 74
6.6	SActive field 74
6.7	SATA Status 74

	Page
7	Command descriptions 75
7.1	Command descripton introduction 75
7.1.1	Overview 75
7.1.2	Command Name - Command Code [/Subcommand Code], Command Protocol 75
7.1.3	Feature Set 75
7.1.4	Inputs 76
7.1.5	Normal Outputs 76
7.1.6	Error Outputs 77
7.1.7	Input from the Device to the Host Data Structure 77
7.1.8	Output from the Host to the Device Data Structure 78
7.1.9	Unsupported Commands 78
7.2	CFA ERASE SECTORS - C0h, Non-Data 79
7.3	CFA REQUEST EXTENDED ERROR CODE - 03h, Non-Data 80
7.4	CFA TRANSLATE SECTOR - 87h, PIO Data-In 82
7.5	CFA WRITE MULTIPLE WITHOUT ERASE - CDh, PIO Data-Out .. 84
7.6	CFA WRITE SECTORS WITHOUT ERASE - 38h, PIO Data-Out 85
7.7	CHECK MEDIA CARD TYPE - D1h, Non-Data 86
7.8	CHECK POWER MODE - E5h, Non-Data 87
7.9	CONFIGURE STREAM - 51h, Non-Data 88
7.10	Device Configuration Overlay (DCO) 90
7.10.1	DCO Overview 90
7.10.2	DEVICE CONFIGURATION FREEZE LOCK - B1h/C1h, Non-Data.. 91
7.10.3	DEVICE CONFIGURATION IDENTIFY - B1h/C2h, PIO Data-In..... 92
7.10.4	DEVICE CONFIGURATION RESTORE - B1h/C0h, Non-Data 96
7.10.5	DEVICE CONFIGURATION SET - B1h/C3h, PIO Data-Out 97
7.11	DEVICE RESET - 08h, Device Reset 106
7.12	DOWNLOAD MICROCODE - 92h, PIO Data-Out/Non-Data 107
7.13	EXECUTE DEVICE DIAGNOSTIC - 90h, Execute Device Diagnostic 110
7.14	FLUSH CACHE - E7h, Non-Data 112
7.15	FLUSH CACHE EXT - EAh, Non-Data 113
7.16	IDENTIFY DEVICE - ECh, PIO Data-In 114
7.17	IDENTIFY PACKET DEVICE - A1h, PIO Data-In 153
7.18	IDLE - E3h, Non-Data 171
7.19	IDLE IMMEDIATE - E1h, Non-Data 172
7.20	Non-Volatile Cache 174
7.20.1	NV Cache Overview 174
7.20.2	NV Cache Power Management Overview 174
7.20.3	ADD LBA(S) TO NV CACHE PINNED SET - B6h/10h, DMA..... 176
7.20.4	FLUSH NV CACHE - B6h/14h, Non-Data 178
7.20.5	NV CACHE DISABLE- B6h/16h, Non-Data 179

	Page	
7.20.6	NV CACHE ENABLE - B6h/15h, Non-Data	180
7.20.7	QUERY NV CACHE MISSES - B6h/13h, DMA.....	181
7.20.8	QUERY NV CACHE PINNED SET - B6h/12h, DMA.....	183
7.20.9	REMOVE LBA(S) FROM NV CACHE PINNED SET - B6h/11h, DMA/Non-Data	184
7.20.10	RETURN FROM NV CACHE POWER MODE - B6h/01h, Non-Data	186
7.20.11	SET NV CACHE POWER MODE - B6h/00h, Non-Data	187
7.21	NOP - 00h, Non-Data	188
7.22	PACKET - A0h, Packet	189
7.23	READ BUFFER - E4h, PIO Data-In	192
7.24	READ DMA - C8h, DMA	193
7.25	READ DMA EXT - 25h, DMA	194
7.26	READ DMA QUEUED - C7h, DMA Queued	195
7.27	READ DMA QUEUED EXT- 26h, DMA Queued	197
7.28	READ FPDMA QUEUED - 60h, DMA Queued	199
7.29	READ LOG EXT - 2Fh, PIO Data-In	200
7.30	READ LOG DMA EXT - 47h, DMA	202
7.31	READ MULTIPLE - C4h, PIO Data-In	203
7.32	READ MULTIPLE EXT - 29h, PIO Data-In	204
7.33	READ NATIVE MAX ADDRESS - F8h, Non-Data	205
7.34	READ NATIVE MAX ADDRESS EXT - 27h, Non-Data	206
7.35	READ SECTOR(S) - 20h, PIO Data-In	207
7.36	READ SECTOR(S) EXT - 24h, PIO Data-In	208
7.37	READ STREAM DMA EXT - 2Ah, DMA	209
7.38	READ STREAM EXT - 2Bh, PIO Data-In	212
7.39	READ VERIFY SECTOR(S) - 40h, Non-Data	213
7.40	READ VERIFY SECTOR(S) EXT - 42h, Non-Data	214
7.41	SECURITY DISABLE PASSWORD - F6h, PIO Data-Out	215
7.42	SECURITY ERASE PREPARE - F3h, Non-Data	217
7.43	SECURITY ERASE UNIT - F4h, PIO Data-Out	218
7.44	SECURITY FREEZE LOCK - F5h, Non-Data	220
7.45	SECURITY SET PASSWORD - F1h, PIO Data-Out	221
7.46	SECURITY UNLOCK - F2h, PIO Data-Out	223
7.47	SERVICE - A2h, DMA Queued	225
7.48	SET FEATURES - EFh, Non-Data	226
7.48.1	Feature Set	226
7.48.2	Description	226

	Page
7.48.3 Enable/disable 8-bit PIO data transfer	228
7.48.4 Enable/disable volatile write cache	228
7.48.5 Set transfer mode	228
7.48.6 Enable/disable the APM feature set	229
7.48.7 Enable/disable the PUIS feature set	230
7.48.8 PUIS feature set device spin-up	230
7.48.9 Enable/disable CFA power mode 1	230
7.48.10 Enable/Disable Write-Read-Verify feature set	230
7.48.11 Enable/disable the AAM feature set	231
7.48.12 Set Maximum Host Interface Sector Times	232
7.48.13 Enable/disable read look-ahead	232
7.48.14 Enable/disable release interrupt	232
7.48.15 Enable/disable SERVICE interrupt	232
7.48.16 Enable/disable reverting to defaults	232
7.48.17 Enable/Disable the Free-fall Control feature set	233
7.48.18 Enable/Disable SATA feature	233
 7.49 SET MAX	 235
7.49.1 SET MAX Overview	235
7.49.2 SET MAX ADDRESS - F9h, Non-Data	236
7.49.3 SET MAX FREEZE LOCK – F9h/04h, Non-Data	238
7.49.4 SET MAX LOCK - F9h/02h, Non-Data	239
7.49.5 SET MAX SET PASSWORD - F9h/01h, PIO Data-Out	240
7.49.6 SET MAX UNLOCK - F9h/03h, PIO Data-Out	241
 7.50 SET MAX ADDRESS EXT - 37h, Non-Data	 242
7.51 SET MULTIPLE MODE - C6h, Non-Data	244
7.52 SLEEP - E6h, Non-Data	246
 7.53 SMART	 247
7.53.1 Overview	247
7.53.2 SMART DISABLE OPERATIONS - B0h/D9h, Non-Data	248
7.53.3 SMART ENABLE/DISABLE ATTRIBUTE AUTOSAVE - B0h/D2h, Non-Data	249
7.53.4 SMART ENABLE OPERATIONS - B0h/D8h, Non-Data	251
7.53.5 SMART EXECUTE OFF-LINE IMMEDIATE - B0h/D4h, Non-Data	252
7.53.6 SMART READ DATA - B0h/D0h, PIO Data-In	256
7.53.7 SMART READ LOG - B0h/D5h, PIO Data-In	261
7.53.8 SMART RETURN STATUS - B0h/DAh, Non-Data	262
7.53.9 SMART WRITE LOG - B0h/D6h, PIO Data-Out	263
 7.54 STANDBY - E2h, Non-Data	 264
7.55 STANDBY IMMEDIATE - E0h, Non-Data	265
7.56 TRUSTED NON-DATA - 5Bh, Non-Data	266
7.57 TRUSTED RECEIVE - 5Ch, PIO Data-In	267
7.58 TRUSTED RECEIVE DMA - 5Dh, DMA	272
7.59 TRUSTED SEND - 5Eh, PIO Data-Out	273
7.60 TRUSTED SEND DMA - 5Fh, DMA	276
7.61 WRITE BUFFER - E8h, PIO Data-Out	277

	Page	
7.62	WRITE DMA - CAh, DMA	278
7.63	WRITE DMA EXT - 35h, DMA	279
7.64	WRITE DMA FUA EXT - 3Dh, DMA	280
7.65	WRITE DMA QUEUED - CCh, DMA Queued	281
7.66	WRITE DMA QUEUED EXT - 36h, DMA Queued	283
7.67	WRITE DMA QUEUED FUA EXT - 3Eh, DMA Queued	285
7.68	WRITE FPDMA QUEUED - 61h, DMA Queued	286
7.69	WRITE LOG EXT - 3Fh, PIO Data-Out	287
7.70	WRITE LOG DMA EXT - 57h, DMA	289
7.71	WRITE MULTIPLE - C5h, PIO Data-Out	290
7.72	WRITE MULTIPLE EXT - 39h, PIO Data-Out	291
7.73	WRITE MULTIPLE FUA EXT - CEh, PIO Data-Out	292
7.74	WRITE SECTOR(S) - 30h, PIO Data-Out	293
7.75	WRITE SECTOR(S) EXT - 34h, PIO Data-Out	294
7.76	WRITE STREAM DMA EXT - 3Ah, DMA	295
7.77	WRITE STREAM EXT - 3Bh, PIO Data-Out	298
7.78	WRITE UNCORRECTABLE EXT - 45h, Non-Data	299
8	SCT Command Transport	301
8.1	Introduction	301
8.1.1	Overview	301
8.1.2	SCT command nesting and interspersing with standard commands	301
8.1.3	Resets	301
8.2	Processing SCT commands	302
8.2.1	Processing SCT commands overview	302
8.2.2	SCT capability identification	302
8.2.3	SCT command transfer	302
8.2.4	SCT data transfer	306
8.2.5	SCT status	308
8.3	SCT Command Set	312
8.3.1	Overview	312
8.3.2	SCT Read/Write Long command	313
8.3.3	SCT Write Same command	316
8.3.4	SCT Error Recovery Control command	319
8.3.5	SCT Feature Control command	321
8.3.6	SCT Data Table command.....	324
9	Normal and Error Outputs	328
9.1	Overview	328
9.2	Normal Outputs	328
9.3	Error Outputs	348

	Page
Tables	
1 Approved ANSI References.....	2
2 References Under Development	3
3 ATA string byte swapping	13
4 ATA firmware revision example	13
5 Feature Set Summary.....	14
6 Block Size By Command	39
7 Media Card type references	42
8 Summary of Security States and Characteristics	52
9 Security Command Actions	53
10 IDENTIFY settings for Security state SEC1.....	58
11 IDENTIFY settings for Security state SEC2.....	59
12 IDENTIFY settings for Security state SEC4.....	60
13 IDENTIFY settings for Security state SEC5.....	61
14 IDENTIFY settings for Security state SEC6.....	62
15 Preserved Feature Sets and Settings.....	64
16 Status field	70
17 Error field	72
18 Interrupt Reason Field	73
19 Count field.....	74
20 Example Normal Output	76
21 Example Error Output	77
22 Extended error codes	80
23 CFA TRANSLATE SECTOR data	82
24 Device Configuration Overlay Feature field values.....	90
25 Device Configuration Identify data structure	93
26 Device Configuration Overlay (DCO) data structure.....	99
27 Count field output for DOWNLOAD MICROCODE requesting the offset transfer method	108
28 Diagnostic codes	111
29 IDENTIFY DEVICE data	115
30 Specific Configuration.....	133
31 Minor version number	139
32 Normal Erase Mode Time.....	145
33 Enhanced Erase Mode Time	145

	Page
34 IDENTIFY DEVICE data World Wide Name field (word-based view).....	148
35 IDENTIFY DEVICE data World Wide Name field (byte-based view).....	148
36 Device Nominal Form Factor	150
37 Nominal Media Rotation Rate	151
38 Transport minor version number	152
39 IDENTIFY PACKET DEVICE data	154
40 Standby timer periods	171
41 NV Cache Commands	174
42 NV Cache Power Management Commands	175
43 Request Pin Data	177
44 Cache Miss Data.....	182
45 Pin Set Data	183
46 Remove Pin Data	185
47 NOP Subcommand Code.....	188
48 SECURITY DISABLE PASSWORD data content	216
49 SECURITY ERASE UNIT data content.....	219
50 SECURITY SET PASSWORD data content	222
51 SECURITY UNLOCK data content	224
52 SET FEATURES Feature field definitions	226
53 Transfer modes	229
54 APM levels	229
55 Write-Read-Verify Modes.....	231
56 AAM levels	231
57 SATA Features.....	233
58 SET MAX Feature field values	235
59 SET MAX SET PASSWORD data content.....	240
60 SMART Feature field values	247
61 SMART EXECUTE OFF-LINE IMMEDIATE Subcommands	252
62 Device SMART data structure.....	257
63 Off-line data collection status byte values.....	258
64 Self-test execution status values.....	258
65 Off-line Data Collection Capabilities.....	259
66 TRUSTED RECEIVE Security Protocol field description	268

	Page	
67	Security Protocol 00h - SP Specific field descriptions for Protocol 00h	269
68	TRUSTED RECEIVE parameter data for SP Specific=0000h	270
69	TRUSTED RECEIVE parameter data for SP Specific=0001h	270
70	TRUSTED SEND - Security Protocol field description	274
71	Fields to issue an SCT command using SMART WRITE LOG	302
72	Fields to issue an SCT command using WRITE LOG (DMA) EXT..	303
73	Successful SCT command response.....	304
74	SCT command error response	305
75	Extended Status codes.....	306
76	SCT data transfer using SMART READ LOG or SMART WRITE LOG	307
77	SCT data transfer using the GPL feature set.....	308
78	SCT status request using SMART READ LOG	309
79	SCT status request using the GPL feature set	310
80	Format of SCT status response.....	310
81	SCT command format.....	312
82	SCT Action Codes	312
83	SCT Read/Write Long command.....	313
84	SCT Read/Write Long command status response	314
85	SCT Read/Write Long command Format	315
86	SCT Write Same command	317
87	SCT Write Same command status response.....	318
88	SCT Error Recovery Control command	319
89	SCT Error Recovery Control command status response.....	320
90	SCT Feature Control command.....	321
91	Feature Code List	322
92	SCT Feature Control command status response	323
93	SCT Data Table command	324
94	SCT Data Tables (by Table Identifier)	324
95	Absolute HDA Temperature.....	325
96	SCT Data Table command status response.....	327
97	Error Bit Defined For Normal Output	328
98	Extended Error Code for Normal Output	329
99	Generic Normal Output (No LBA Return Value) for Normal Output	330

	Page	
100	CFA Normal Output.....	331
101	Media Card Type Normal Output	332
102	Check Power Mode Normal Output	333
103	Stream Normal Output	334
104	Device Signatures for Normal Output	335
105	IDLE Unload Normal Output	336
106	ATAPI Normal Output	337
107	Queued Normal Output	338
108	HPA Normal Output	339
109	SMART Off-Line Immediate Normal Output.....	340
110	SMART Return Status Normal Output	341
111	Generic Extended Normal Output	342
112	SETMAX Extended Normal Output.....	343
113	Queued Extended Normal Output.....	344
114	NV Cache Normal Output	345
115	NV Cache Flush Normal Output.....	346
116	NCQ Command Acceptance Normal Output	347
117	NCQ Normal Outputs	347
118	Unsupported Command Error	348
119	CFA Erase Error.....	349
120	CFA Write Error.....	350
121	CFA & Check Power Mode Abort Error.....	351
122	Generic Abort wo/ICRC Error.....	352
123	Generic Abort Error	353
124	Trusted Abort Error	354
125	Generic SET MAX Error.....	355
126	SET MAX Unlock Error	356
127	Configure Stream Error	357
128	Flush Cache Error	358
129	Flush Cache Ext Error.....	359
130	Read DMA Error.....	360
131	Read DMA Ext Error	361
132	Read Log Ext Error	362
133	Read PIO Error	363
134	Read Stream Error.....	364

	Page	
135	HPA Error	365
136	Write Log Error	366
137	Write Log Ext Error	367
138	SMART Error	368
139	Write Extended Error	369
140	Write Stream Error.....	370
141	DCO Set Error	371
142	NOP Error	372
143	PACKET command Error.....	373
144	Read DMA Queued Error	374
145	Read DMA Queued Extended Error	375
146	SMART Read Log/SMART Read Data Error.....	376
147	Read PIO Extended Error.....	377
148	Read Native Max Extended Error	378
149	SETMAX Extended Error.....	379
150	Write Error	380
151	Write DMA Error	381
152	Write DMA Queued Error.....	382
153	NV Cache Add Abort Error	383
154	NV Cache Remove Abort Error	384
155	NV Cache Abort Error.....	385
156	NV Cache Abort with Data Transfer Error	386
157	NCQ Command Acceptance Error	387
158	NCQ Write Command Aborted Error	388
159	NCQ Read Command Aborted Error.....	389
A.1	Example Log Structure	391
A.2	Log address definition.....	392
A.3	General Purpose Log Directory	393
A.4	SMART Log Directory.....	393
A.5	Comprehensive error log	394
A.6	General Statistics.....	395
A.7	Extended Comprehensive SMART error log	396
A.8	Extended Error log data structure	397
A.9	Command data structure	398
A.10	Error data structure.....	399

	Page
A.11	State field values.....
A.12	Extended Self-test log data structure
A.13	Extended Self-test log descriptor entry
A.14	NCQ Command Error Log.....
A.15	Read Stream Error Log
A.16	Stream Error Log Entry
A.17	SATA Phy Event Counters Format
A.18	Selective self-test log
A.19	Selective self-test feature flags
A.20	Self-test log data structure
A.21	Self-test log descriptor entry
A.22	Summary SMART Error log
A.23	Error log data structure
A.24	Command data structure.....
A.25	Error data structure
A.26	State field values.....
A.27	Write Stream Error Log
B.1	Command Matrix.....
B.2	Command codes (sorted by command code)
B.3	Command codes (sorted by command name)
B.4	Historical Command Assignments
B.5	Historical SET FEATURE Code Assignments
D.1	SCT command using SMART WRITE LOG command.....
D.2	SCT command using WRITE LOG EXT command.....
Figures	
1	ATA document relationships
2	State diagram convention
3	Byte, word, DWord and QWord relationships
4	Device Configuration Overlay state diagram.....
5	HPA Not Set.....
6	HPA Set (28)
7	HPA Set (48)
8	HPA Locked (28).....
9	HPA Locked (48).....
10	LLS and LPS Example

	Page
11 Alignment 0.....	41
12 Alignment 1	41
13 Alignment 3.....	42
14 Power management state diagram.....	47
15 Security state diagram.....	57
16 Selective self-test span example	254
C.1 Unaligned Write Example	442
D.1 Example flowchart for SCT commands	444
D.2 Example sequence for foreground write same with a repeating pattern	445
D.3 Example sequence for foreground write same with a repeating sector.....	445
D.4 Example sequence for writing data using an SCT command with no background activity.....	446
D.5 Example sequence for reading data using an SCT command with no background activity.....	446
D.6 Example Sequence for a Non-Data SCT command with no background activity.....	447
D.7 Example sequence for writing data using an SCT command with background activity.....	448
D.8 Example sequence for a Non-Data SCT command with background activity	449
E.1 System Dependency Chain	453
E.2 Mapping Proposals	454
E.3 Logical to Physical Mapping	454
E.4 Uncorrectable Error Handling	456
E.5 Typical HDD Layout Using A Master Boot Record	457
Annexes	
A Log Definitions	391
A.1 Overview	391
A.2 General Purpose Log Directory (GPL Log Address 00h)	393
A.3 SMART Log Directory (SMART Logging Log Address 00h)	393
A.4 Comprehensive SMART Error Log (Log Address 02h)	393
A.5 Device Statistics (Log Address 04h)	395
A.6 Device Vendor Specific Logs (Log Addresses A0h-DFh)	396
A.7 Extended Comprehensive SMART Error log (Log Address 03h) ...	396
A.8 Extended SMART Self-Test Log (Log Address 07h)	400

	Page
A.9	Host Vendor Specific Logs (Log Addresses 80h-9Fh) 401
A.10	NCQ Command Error (Log Address 10h) 402
A.11	Read Stream Error Log (Log Address 22h) 403
A.12	SATA Phy Event Counters (Log Address 11h) 404
A.13	Selective Self-Test Log (Log Address 09h) 406
A.14	SMART Self-Test Log (Log Address 06h) 408
A.15	Summary SMART Error Log (Log Address 01h) 409
A.16	Write Stream Error Log (Log Address 21h) 412
B	(Command Set summary 415
C	Design and programming considerations for large physical sector devices 441
C.1	Introduction 441
C.2	Physical sectors 441
C.3	Unaligned write 441
C.4	SET MAX 442
C.5	Software compatibility 442
D	How to use SCT commands 443
D.1	How to use SCT commands overview 443
D.2	Examples of Log page command sequences 445
D.3	Issuing an SCT command to a device 449
D.3.1	Step 1 - Build a Key Page 449
D.3.2	Step 2 - Issue the SCT command 450
D.3.3	Step 3 - Transfer Data if Required 451
D.3.4	Step 4 - Final Status/SCT Command Completion 452
E	Implementation Guidelines for 1,024/4,096 Byte Sector Sizes 453
E.1	Introduction 453
E.2	Scope 453
E.3	Overview 453
E.4	Implementation 455
E.4.1	1,024 Byte Sector Size Implementation 455
E.4.2	4,096 Byte Sector Size Implementation 455
E.4.3	Reporting Alignment (512 Byte LBA Only) 455
E.4.4	Read-Modify-Write (RMW) (512-Byte LBA Only) 456
E.5	Implementation Issues (512-Byte LBA Only) 456
E.5.1	Overview 456

	Page
E.5.2	Drive Partitioning
E.5.3	File System Formatting
E.5.4	Virtual Memory accessing
E.5.5	Booting

Foreword

(This foreword is not part of American National Standard INCITS 452-2009.)

This AT Attachment 8 - ATA/ATAPI Command Set (ATA8-ACS) standard is designed to maintain a high degree of compatibility with the AT Attachment with Packet Interface - 7 (ATA/ATAPI-7) standard.

This standard contains five annexes. Annex A is normative and is considered part of the standard. Annexes B through E are informative and are not considered part of the standard.

Requests for interpretation, suggestions for improvement and addenda, or defect reports are welcome. They should be sent to the INCITS Secretariat, ITI, 1101 K Street, NW, Suite 610, Washington, DC 20005.

This standard was processed and approved for submittal to ANSI by InterNational Committee for Information Technology Standards (INCITS). Committee approval of this standard does not necessarily imply that all committee members voted for its approval. At the time it approved this standard, INCITS had the following members:

Don Wright, Chair
Jennifer Garner, Secretary

<i>Organization Represented</i>	<i>Name of Representative</i>
Adobe Systems, Inc.....	Scott Foshee Steve Zilles (Alt.)
AIM Global, Inc.	Dan Mullen Charles Biss (Alt.)
Apple Computer, Inc.	Kwok Lau Helene Workman (Alt.) David Singer (Alt.)
Distributed Management Task Force	Tony DiCenzo Jeff Hilland (Alt.) Winston Bumpus (Alt.)
Electronic Industries Alliance.....	Edward Mikoski, Jr.
EMC Corporation.....	Gary Robinson
Farance, Inc.....	Frank Farance Timothy Schoechle (Alt.)
Google.....	Zaheda Bhorat Robert Tai (Alt.)
GS1 US	Ray Delnicki Frank Sharkey (Alt.) James Chronowski (Alt.) Mary Wilson (Alt.)
Hewlett-Packard Company.....	Karen Higginbottom Paul Jeran (Alt.)
IBM Corporation	Ronald F. Silletti Robert Weir (Alt.)
IEEE	Judith Gorman Terry DeCourcelle (Alt.) Bill Ash (Alt.)
Intel.....	Jodie Haasz (Alt.) Bob Labelle (Alt.) Susan Tatiner (Alt.) Philip Wennblom Dave Thewlis (Alt.) Grace Wei (Alt.) Steven Balogh (Alt.)
Lexmark International	Don Wright Dwight Lewis (Alt.) Paul Menard (Alt.)
Microsoft Corporation	Jim Hughes Dave Welsh (Alt.) Mark Ryland (Alt.)

<i>Organization Represented</i>	<i>Name of Representative</i>
National Institute of Standards & Technology	Michael Hogan Elaine Barker (Alt.) Dan Benigni (Alt.) Fernando Podio (Alt.) Teresa Schwarzhoff (Alt.) Wo Chang (Alt.)
Oracle Corporation	Donald R. Deutsch Jim Melton (Alt.)] Michael Kavanaugh (Alt.) Peter Lord (Alt.) Toshihiro Suzuki (Alt.) Jeff Mischkinsky (Alt.)
Purdue University	Stephen Elliott
Storage Networking Industry Association (SNIA)	Gary Phillips Rick Bauer (Alt.) Arnold Jones (Alt.) Dave Thiel (Alt.)
US Department of Defense	Jerry Smith Dennis Devera (Alt.) Dave Brown (Alt.) Leonard Levine (Alt.)
US Department of Homeland Security	Peter Shebell Gregg Piermarini (Alt.)

Technical Committee T13 on ATA Interfaces, that reviewed this standard, had the following members and additional participants:

Dan Colegrove, Chair
Jim Hatfield, Vice-Chair
Mark Overby, Secretary

<i>Orgnaization Represented</i>	<i>Name of Representative</i>
AMD.....	Joe Scanlon
Apple Computer.....	Larry Barras Randy Sharp (Alt.) Sergio Henriques (Alt.)
Broadcom	Hale Landis Edward Dageforde (Alt.)
CPR Tools	Tony Alvarez Candy Alvarez (Alt.) Wally Bretzer (Alt.)
Dell	Marty Stevens
Emulex.....	Kenneth Hirata Bob Nixon (Alt.) Bill Martin (Alt.)
Finisar.....	Michael Lawson Eric Lanning (Alt.) Sumit Puri (Alt.)
Fujitsu.....	Mike Fitzpatrick
Hewlett Packard	Wayne Bellamy Jeff Wolford (Alt.)
Hitachi GST	Frank Chu
IBM	Takashi Sugawara Steve Livaccari (Alt.)
IBM	Henry Pesulima
Intel.....	Steven Wells Robert Strong (Alt.) Knut Grimsrud (Alt.)
Kionix.....	Ken Foust Izudin Cemer (Alt.)

<i>Organization Represented</i>	<i>Name of Representative</i>
Lexar Media	John Geldman
LSI Logic	Tim Thompson Brian Day (Alt.) Joshua Johnson (Alt.) George Penokie (Alt.) Dan Meyer (Alt.) Robert Sheffield (Alt.)
Marvell.....	Kevin TonThat Peter Dinh (Alt.)
Microsoft.....	Nathan Obr Frank Shu (Alt.) Ruston Panabaker (Alt.) Bob Griswold (Alt.)
nVidia	Mark Overby Scott Pritchett (Alt.) Andrew Currid (Alt.)
Phoenix Technologies.....	Karen Zelenko Chandra Buddhavaram (Alt.) Timothy Markey (Alt.) Andrew Currid (Alt.)
Qlogic	Greg Elkins Arie Krantz (Alt.)
Samsung	Joesph Chen John Schadegg (Alt.) Wonju Lee (Alt.) Samuel Oh (Alt.) D. Y. Lee (Alt.)
SanDisk Corporation	Yoni Shternhell Avraham Shimor (Alt.) Dave Landsman (Alt.)
Seagate.....	Jim Hatfield Marc Noblitt (Alt.)
Silicon Image.....	Diepvu Le
ST Microelectronics.....	Randy Hines
Toshiba	Kirk Arakawa Patrick Hery (Alt.) Tom McGoldrick (Alt.) Mark Quinn (Alt.) Scott Wright (Alt.) Mark Evans
Western Digital.....	Mladen Luksic (Alt.) John Masiewicz (Alt.) Curtis Stevens (Alt.) Duncan Penman (Alt.) Glenn Lott (Alt.) Aaron Wilson (Alt.) Wayne Thorsted (Alt.) Mark Evans (Alt.)

Introduction

This standard encompasses the following:

Clause 1 describes the scope.

Clause 2 provides normative references for the entire standard.

Clause 3 provides definitions, abbreviations, and conventions used within the entire standard.

Clause 4 describes the general operating requirements of the command layer.

Clause 5 describes the ATA protocols used by the commands in this standard.

Clause 6 describes Normal and Error Output fields.

Clause 7 describes commands.

Clause 8 describes the SCT Command Transport.

Clause 9 describes command normal and error outputs.

Annex A describes logs.

Annex B provides command summaries.

Annex C describes considerations for using devices with non-512 byte sectors.

Annex D provides a tutorial on how to use SCT.

Annex E provides implementation guidelines for 1,024/4,096 byte sectors.

Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries.

American National Standard
for Information Technology –

AT Attachment 8 - ATA/ATAPI Command Set (ATA8-ACS)

1 Scope

The set of AT Attachment standards consists of this standard and the ATA implementation standards described in AT Attachment - 8 ATA/ATAPI Architecture Model (ATA8-AAM). The AT Attachment ATA Command Set (ATA8-ACS) specifies the command set host systems use to access storage devices. It provides a common command set for systems manufacturers, system integrators, software suppliers, and suppliers of intelligent storage devices. Figure 1 shows the relationship of this standard to the other standards and related projects in the ATA and SCSI families of standards and specifications.




Figure 1 — ATA document relationships

ATA8-ACS maintains compatibility with the AT Attachment with Packet Interface - 7 standard (ATA/ATAPI-7), INCITS 397-2005 volume 1, while providing additional functions.