

INCITS 547-2020

American National Standard

*for Information Technology –
Fibre Channel –
Switch Fabric - 7 (FC-SW-7)*

Developed by



Where IT all begins



This is a preview of "INCITS 547-2020". [Click here to purchase the full version from the ANSI store.](#)

INCITS 547-2020

American National Standard
for Information Technology –

**Fibre Channel –
Switch Fabric - 7 (FC-SW-7)**

Secretariat

Information Technology Industry Council

Approved February 24, 2020

American National Standards Institute, Inc.

Abstract

This standard describes the requirements for an interconnecting Fabric consisting of multiple Fibre Channel Fabric Switch elements.

American National Standard

Approval of an American National Standard requires review by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made towards their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

CAUTION: The developers of this standard have requested that holders of patents that may be required for the implementation of the standard disclose such patents to the publisher. However, neither the developers nor the publisher have undertaken a patent search in order to identify which, if any, patents may apply to this standard. As of the date of publication of this standard, following calls for the identification of patents that may be required for the implementation of the standard, notice of one or more such claims has been received. By publication of this standard, no position is taken with respect to the validity of this claim or of any rights in connection therewith. The known patent holder(s) has (have), however, filed a statement of willingness to grant a license under these rights on reasonable and nondiscriminatory terms and conditions to applicants desiring to obtain such a license. Details may be obtained from the publisher. No further patent search is conducted by the developer or publisher in respect to any standard it processes. No representation is made or implied that this is the only license that may be required to avoid infringement in the use of this standard.

Published by

**American National Standards Institute, Inc.
25 West 43rd Street, New York, NY 10036**

Copyright © 2020 by Information Technology Industry Council (ITI)
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of ITI, 700 K Street NW, Suite 600, Washington, DC 20001.

Printed in the United States of America

Contents	Page
1 Scope	1
2 Normative references	1
2.1 Overview	1
2.2 Approved references	2
2.3 References under development	2
2.4 IETF references	3
3 Definitions, conventions, abbreviations, acronyms, and symbols	4
3.1 Definitions	4
3.2 Editorial conventions	11
3.3 State machine notation	12
3.4 Abbreviations, acronyms, and symbols	13
3.5 Definition of compliance terms	13
3.6 Keywords	14
3.7 T10 Vendor ID fields	14
3.8 Left-aligned ASCII data	15
4 Structure and concepts	16
4.1 Overview	16
4.2 E_Port operation	16
4.3 Fabric operation	16
4.4 Fabric definition	17
4.5 Switch	17
4.6 Switching characteristics	20
4.7 Distributed Switch and A_Port operations	20
4.7.1 Overview	20
4.7.2 A_Port operation	20
4.7.3 Controlling Switch functional model	21
4.7.4 FCDF functional model	22
4.8 Switch ports and Bridge ports	23
4.8.1 General characteristics	23
4.8.2 F_Port	24
4.8.3 FL_Port	24
4.8.4 E_Port	24
4.8.5 B_Port	24
4.8.6 A_Port	25
4.8.7 G_Ports and GL_Ports	25
4.8.8 PF_Port	25
4.8.9 VF_Port	25
4.8.10 PE_Port	25
4.8.11 VE_Port	25
4.8.12 PA_Port	25
4.8.13 VA_Port	25
4.9 Fabric addressing	25
4.10 Class F service	28
5 Switch ports and Bridge ports	29
5.1 Overview	29
5.2 Model elements	29
5.2.1 FC Transports	29
5.2.2 Switch Transport	29
5.2.3 Control Facilities	29
5.2.4 Link Services	29

5.3 F_Port operation	30
5.4 FL_Port operation	31
5.5 E_Port operation	33
5.6 B_Port operation	34
5.7 A_Port operation	35
5.8 Inter-Switch Link behavior	36
5.9 Class F service	38
5.9.1 Class F function	38
5.9.2 Class F rules	38
5.9.3 Class F frame format	39
5.9.4 Class F flow control	39
6 Internal Link Services	41
6.1 Switch Fabric Internal Link Services (SW_ILS)	41
6.2 Fabric SW_ILSs	43
6.2.1 Overview	43
6.2.2 Switch Fabric Internal Link Service Accept (SW_ACC)	43
6.2.3 Switch Fabric Internal Link Service Reject (SW_RJT)	43
6.2.4 Exchange Link Parameters (ELP)	47
6.2.4.1 ELP request	47
6.2.4.2 R_RDY flow control	52
6.2.4.3 VC_RDY flow control	53
6.2.4.4 ELP reply	54
6.2.5 Exchange Fabric Parameters (EFP)	55
6.2.6 Domain Identifier Assigned (DIA)	59
6.2.7 Request Domain_ID (RDI)	60
6.2.8 Hello (HLO)	63
6.2.8.1 HLO Overview	63
6.2.8.2 FSPF Header format	64
6.2.9 Link State Update (LSU)	65
6.2.9.1 LSU overview	65
6.2.9.2 Link State Record (LSR) format	66
6.2.9.3 Link State Header format	67
6.2.9.4 Link Descriptor format	69
6.2.10 Link State Acknowledgement (LSA)	69
6.2.11 Build Fabric (BF)	70
6.2.12 Reconfigure Fabric (RCF)	71
6.2.13 Inter-Switch Registered State Change Notification (SW_RSCN)	72
6.2.14 Distribute Registered Link Incident Records (DRLIR)	75
6.2.15 Merge Request (MR)	76
6.2.15.1 Merge Request payload	77
6.2.15.1.1 Merge Request payload in Basic Zoning	77
6.2.15.1.2 Merge Request payload in Enhanced Zoning	78
6.2.15.2 Merge Request reply	79
6.2.16 Acquire Change Authorization Request (ACA)	80
6.2.17 Release Change Authorization (RCA) request	82
6.2.18 Stage Fabric Configuration (SFC) request	83
6.2.18.1 SFC in Basic Zoning	85
6.2.18.2 SFC in Enhanced Zoning	85
6.2.18.2.1 Operation Request 'Activate Zone Set Enhanced'	86
6.2.18.2.2 Operation Request 'Deactivate Zone Set Enhanced'	86
6.2.18.2.3 Operation Request 'Distribute Zone Set Database'	87
6.2.18.2.4 Operation Request 'Activate Zone Set by Name'	87
6.2.18.2.5 Operation Request 'Set Zoning Policies'	88
6.2.19 Update Fabric Configuration (UFC) request	88

6.2.20 Check E_Port Connectivity (CEC)	89
6.2.21 Exchange Switch Capabilities	91
6.2.22 Exchange Switch Support (ESS)	94
6.2.22.1 ESS request payload	95
6.2.22.2 Interconnect Element Information Object	95
6.2.22.3 Capability Object	96
6.2.22.4 Service Specific Capability formats	96
6.2.22.4.1 Directory Server Capability	96
6.2.22.4.2 Fabric Controller Capability	97
6.2.22.4.3 ESS Fabric Configuration Server Capability Object	97
6.2.22.4.4 ESS Enhanced Zone Server Capability Object	98
6.2.22.4.5 Security Policy Server Capability Object	99
6.2.22.4.6 ESS Vendor Specific Capability Object	100
6.2.22.4.7 Domain Controller Capability Object	101
6.2.22.4.8 Event Server Capability Object	102
6.2.22.4.9 Switch Support Capability Object	102
6.2.22.4.10 Application Server Capability Object	102
6.2.22.4.11 Enhanced Fabric Configuration Server Capability Object	103
6.2.22.4.12 VE Identification Server Capability Object	104
6.2.22.5 ESS accept payload	104
6.2.23 Merge Request Resource Allocation (MRRRA)	105
6.2.24 Switch Trace Route (STR)	106
6.2.24.1 Basic function	106
6.2.25 Exchange Virtual Fabrics Parameters (EVFP)	111
6.2.25.1 Basic function	111
6.2.25.2 EVFP_SYNC Message Payload	114
6.2.25.2.1 Overview	114
6.2.25.2.2 Tagging Administrative Status descriptor	116
6.2.25.2.3 Port VF_ID descriptor	117
6.2.25.2.4 Locally-Enabled VF_ID List descriptor	117
6.2.25.2.5 Vendor Specific descriptor	118
6.2.25.3 EVFP_COMMIT Message Payload	118
6.2.26 Enhanced Acquire Change Authorization request (EACA)	118
6.2.26.1 Commit Exchange Preamble	119
6.2.26.1.1 Transaction Identifier	119
6.2.26.1.2 Number of Switch Identifiers	120
6.2.26.1.3 Flags	120
6.2.26.1.4 ECS Switch List	120
6.2.27 Enhanced Stage Fabric Configuration (ESFC) request	122
6.2.28 Enhanced Update Fabric Configuration (EUFC) request	123
6.2.29 Enhanced Release Change Authorization (ERCA) request	123
6.2.30 Transfer Commit Ownership (TCO) request	124
6.3 Distributed Switch VA_Port SW_ILSs	125
6.3.1 Overview	125
6.3.2 VA_Port SW_ILS descriptors	127
6.3.2.1 Descriptor format	127
6.3.2.2 VN_Port Reachability descriptor	128
6.3.2.3 FLOGI/NPIV FDISC Parameters descriptor	128
6.3.2.4 VN_Port Unreachability descriptor	128
6.3.2.5 FCDF Reachability descriptor	129
6.3.2.6 Sequence Number descriptor	129
6.3.2.7 Controlling Switch Reachability descriptor	130
6.3.2.8 N_Port_IDs Reachability descriptor	130
6.3.2.9 Domain_IDs Reachability descriptor	132

6.3.2.10 Allocation Status descriptor	133
6.3.2.11 Peering Status descriptor	134
6.3.2.12 Membership Set descriptor	135
6.3.2.13 Integrity descriptor	136
6.3.2.14 FCDF Identification descriptor	136
6.3.2.15 SW_ILS Request Information descriptor	137
6.3.2.16 ELS Payload descriptor	137
6.3.3 VA_Port SW_ILSs	138
6.3.3.1 VN_Port Reachability Notification (VNRN)	138
6.3.3.2 VN_Port Unreachability Notification (VNUN)	139
6.3.3.3 FCDF Reachability Notification (FCRN)	140
6.3.3.4 FCDF Unreachability Notification (FCUN)	141
6.3.3.5 N_Port_ID Route Distribution (NPRD)	143
6.3.3.6 N_Port_ID and Zoning ACL Distribution (NPZD)	144
6.3.3.7 Active Zoning ACL Distribution (AZAD)	146
6.3.3.8 Distributed Switch Membership Distribution (DSMD)	148
6.3.3.9 Distributed ELS (DELS)	149
6.3.4 VA_Port SW_ILS timeouts	151
6.4 Controlling Switch redundancy protocol SW_ILSs	151
6.4.1 Overview	151
6.4.2 Controlling Switch redundancy protocol descriptors	151
6.4.2.1 Descriptor format	151
6.4.2.2 Controlling Switch State descriptor	152
6.4.2.3 FCDF Topology descriptor	152
6.4.2.4 FCDF N_Port_IDs descriptor	154
6.4.2.5 RHello Interval descriptor	155
6.4.2.6 Controlling Switch Parameters descriptor	155
6.4.3 Controlling Switch redundancy protocol SW_ILSs	156
6.4.3.1 Exchange Redundancy Parameters (ERP)	156
6.4.3.2 Get FCDF Topology State (GFTS)	157
6.4.3.3 Get FCDF N_Port_IDs State (GFNS)	158
6.4.3.4 Secondary Synchronization Achieved (SSA)	159
6.4.3.5 Redundancy Hello (RHello)	160
6.4.3.6 Select Primary Controlling Switch (SPCS)	160
6.4.3.7 Exchange Controlling Switch Parameters (ECSP)	161
6.4.4 Controlling Switch redundancy protocol timeouts	163
7 Fabric Configuration	164
7.1 Fabric Configuration summary	164
7.2 Switch port initialization	165
7.2.1 Basic operation	165
7.2.2 Switch_Name usage	174
7.2.3 Exchange Switch Capabilities processing	174
7.2.4 B_Port impact on ESC processing	175
7.2.5 Extensions to support Virtual Fabrics	176
7.3 Principal Switch Selection	176
7.4 Address Distribution	182
7.4.1 Address Distribution overview	182
7.4.2 Domain_ID distribution by the Principal Switch	184
7.4.3 Domain_ID requests by the Switches	186
7.5 Principal ISL Recovery	189
7.5.1 Overview	189
7.5.2 Downstream Principal ISL discovery	189
7.5.3 Upstream Principal ISL Recovery	189

7.6 E_Port and Fabric isolation	189
7.7 B_Port operation	190
7.7.1 Differences between E_Ports and B_Ports	190
7.7.2 B_Port Internal Link Services	191
7.7.3 B_Port initialization	192
7.7.4 Example B_Port configuration	192
8 Fabric Shortest Path First (FSPF)	193
8.1 Overview	193
8.1.1 Basic components	193
8.1.2 Fabric connectivity	193
8.1.3 Addressing	193
8.1.4 Path selection and routing	193
8.1.5 FSPF path selection summary	194
8.2 FSPF message processing	194
8.2.1 Message transmission	194
8.2.2 Message reception and tests	194
8.3 Hello protocol	195
8.3.1 Basic functions	195
8.3.2 Hello message transmission	195
8.3.3 Hello message parameters	195
8.3.4 Hello message reception	196
8.4 The Link State Database	196
8.5 Usage of LSR fields	197
8.5.1 LSR Flags	197
8.5.2 LSR Age	197
8.5.3 LSR incarnation number	198
8.5.4 LSR instance rules	198
8.5.5 LSR checksum	199
8.5.6 Link Cost	201
8.6 Link State Database synchronization	202
8.6.1 Synchronization overview	202
8.6.2 Neighborhood and Adjacency	202
8.6.3 Continuous Link State Database synchronization	203
8.6.4 Reliable flooding	204
8.6.4.1 Basic operation	204
8.6.4.2 The flooding procedure	204
8.6.4.3 Generating a new LSR	205
8.6.4.4 Transmitting an LSR	205
8.6.4.5 Receiving an LSR	205
8.7 Neighbor finite state machine (FSM)	206
9 Distributed Services	211
9.1 Basic model	211
9.2 Distributed Services framework	211
9.2.1 Goals and characteristics of the Distributed Services framework	211
9.2.2 Distributed Service transport	211
9.2.2.1 Required FC-2 parameters	211
9.2.2.2 FC-CT Header usage	212
9.2.2.3 Frame distribution	212
9.2.2.4 Domain Controller Service Parameters	212
9.2.3 Common characteristics	212
9.2.4 Zoning considerations	213
9.2.5 Work categories	213

9.2.6	Frame formats	214
9.2.7	FC-CT command restrictions	214
9.3	Distributed Name Server	214
9.3.1	General behavior	214
9.3.2	FC-CT for distributed Name Servers	215
9.3.2.1	dNS command codes	215
9.3.2.2	FC-CT Header usage for dNS	219
9.3.3	Name Server Objects	220
9.3.4	FC-CT requests for dNS	222
9.3.4.1	Get Entry based on Port Identifier	222
9.3.4.2	Get Entry based on Port_Name	222
9.3.4.3	Get Entries based on Node_Name	223
9.3.4.4	Get Entries based on FC-4 TYPEs	224
9.3.4.5	Get Entries based on Port Type	224
9.3.4.6	Get Entries based on Zone Member	225
9.3.4.7	Get Entries based on Zone Name	226
9.3.4.8	Get Entries based on FC-4 Features	227
9.3.4.9	Get Entries based on Fabric Port_Name	228
9.4	Distributed Management Servers	228
9.4.1	General behavior	228
9.4.2	FC-CT Header	229
9.4.2.1	FC-CT Header parameters	229
9.4.2.2	FC-CT Header rule for Fabric internal requests	230
9.4.3	Fabric Configuration Service	230
9.4.4	Unzoned Name Service	233
9.4.5	Fabric Zone Service	233
9.4.6	Fabric-Device Management Service	233
9.4.6.1	Operational characteristics of the FDMI Server	233
9.4.6.2	Registration scenarios	234
9.4.6.2.1	HBA attached to a single Switch	234
9.4.6.2.2	HBA attached to multiple Switches	234
9.4.6.2.3	Resolution of the principal HBA manager	234
9.4.6.3	FDMI Inter-Switch messages	235
9.4.6.3.1	General format	235
9.4.6.3.2	FC-CT Header	235
9.4.6.3.3	FDMI Header	235
9.4.6.3.4	Payload	236
9.4.6.4	FDMI Inter-Switch requests	236
9.4.6.5	FDMI Inter-Switch responses	237
9.4.6.5.1	Reject response	237
9.4.6.5.2	Accept response	237
9.4.6.6	FDMI Inter-Switch operations	237
9.4.6.6.1	Registration Notification (FRN) operation	237
9.4.6.6.2	De-Register Notification (FDRN) operation	238
9.4.6.6.3	Update Notification (FUN) operation	238
9.4.6.6.4	Update Forward (FUF) operation	238
9.4.6.6.5	De-Register Forward (FDRF) operation	238
9.4.6.6.6	Fetch	238
9.4.6.7	GS client initiated FDMI requests	239
9.4.7	Other Fabric internal services	240
9.4.7.1	Fabric internal requests	240
9.4.7.2	Get Management Server Capabilities (GCAP) request	241
9.4.7.2.1	Overview	241
9.4.7.2.2	Capability Entry	241

9.4.7.2.3 Subtype Capability Bit Masks	242
9.4.8 Security Information Server	242
9.4.9 Application Server	243
9.4.10 Enhanced Fabric Configuration Service	244
9.5 Distributed Event Server	245
9.5.1 General behavior	245
9.5.2 FC-CT for distributed Event Server	245
9.5.2.1 FC-CT Header parameters	245
9.5.2.2 dES command codes	245
9.6 Distributed VE Identification Server	245
9.6.1 General behavior	245
9.6.2 FC-CT for distributed VE Identification Server	246
9.6.3 FC-CT Requests for dVEIS	246
9.6.3.1 Get VE Mappings - Domain_ID (G_VEM_D)	246
9.6.3.2 Update VE Mappings (U_VE_M)	248
10 Switch Zone exchange & merge	250
10.1 Overview	250
10.2 Joining Switches	250
10.3 Enhanced Zoning support determination	250
10.4 Zoning framework and data structures	251
10.4.1 Basic Zoning framework	251
10.4.2 Basic Zoning data structures	254
10.4.2.1 Zoning Object List	254
10.4.2.2 Zoning Object format	255
10.4.2.3 General name format	256
10.4.2.4 Zone Member format	256
10.4.3 Enhanced Zoning framework	257
10.4.3.1 Introduction	257
10.4.3.2 Zone Set Database	257
10.4.3.3 Active Zone Set	260
10.4.4 Enhanced Zoning data structures	261
10.4.4.1 Zoning Object List	261
10.4.4.2 Zoning Object Types	261
10.4.4.3 Zone Set Object	262
10.4.4.3.1 Zone Set Object in the Zone Set Database	262
10.4.4.3.2 Zone Set Object in the Active Zone Set	263
10.4.4.4 Zone Reference Object	263
10.4.4.5 Zone Object in the Zone Set Database	264
10.4.4.6 Zone Object in the Active Zone Set	265
10.4.4.6.1 Zone Member format	266
10.4.4.7 Zone Alias Object	268
10.4.4.8 Zone Attribute Object	269
10.4.4.8.1 Zone Attribute Entry format	270
10.5 Merge Zone	273
10.5.1 Example merge operation	273
10.5.2 Merge Zone rules	276
10.5.2.1 Merge rules in Basic Zoning	276
10.5.2.2 Merge rules in Enhanced Zoning	276
10.6 Fabric Management Session protocol	277
10.6.1 Fabric Management Session protocol overview	277
10.6.2 Reserving Fabric Change Authorization	278
10.6.3 Staging the Fabric Configuration	278
10.6.4 Updating the Fabric Configuration	279

10.6.5 Releasing Fabric Change Authorization	279
10.6.6 Mapping of a Server session to a Fabric Management Session	279
10.6.7 Fabric behavior to handle the CT SFEZ request	281
10.6.8 Fabric behavior to handle the CT AAPZ and RAPZ requests	281
10.7 Switch behaviors during merge	281
11 Distributed broadcast	282
11.1 Overview	282
11.2 Spanning tree	282
11.2.1 Spanning tree example	282
12 Virtual Fabrics Switch support	284
12.1 Overview	284
12.2 VF Capable Switch functional model	285
12.3 Switch_Names usage	286
12.4 Configuration information	286
12.5 Enabling VFT tagging on Switch ports	286
12.6 Exchange Virtual Fabrics parameters processing	291
12.6.1 Overview	291
12.6.2 Changing the VFT tagging mode	293
12.6.3 Adding or removing Virtual Fabrics	294
12.6.4 Changing the port VF_ID	294
13 Enhanced Commit Service	295
13.1 Overview	295
13.2 Assisted mode protocol operations	295
13.3 Autonomous mode protocol operations	296
13.3.1 Protocol phases	296
13.3.1.1 Overview	296
13.3.1.2 Phase one	296
13.3.1.3 Phase two	296
13.3.1.4 Phase three	296
13.3.1.5 Phase four	296
13.3.2 Handling Fabric changes	297
13.3.3 Error recovery	297
13.3.3.1 Overview	297
13.3.3.2 Managing Switch not functional	297
13.3.3.2.1 Dead Man timer	297
13.3.3.2.2 Basic procedure	297
13.3.3.3 Resolution of multiple Managing Switches	298
13.3.3.3.1 Two Managing Switches - same commit phase	298
13.3.3.3.2 Two Managing Switches - different commit phases	298
13.3.4 Ladder diagrams	299
13.3.4.1 Normal case	299
13.3.4.2 Unsuccessful case	300
13.3.4.3 Transfer ownership case - recovery processing enabled	301
13.3.5 State machines	301
13.3.5.1 Overview	301
13.3.5.2 States and transitions for the Managing Switch	301
13.3.5.3 States and transitions for the managed Switch	304
13.3.5.4 States and transitions for transfer commit ownership	306
14 Virtual Channels for Switched Fabric	308
14.1 Overview	308
14.2 Assignment of Virtual Channels	308

14.2.1 Overview of assignment	308
14.2.2 Simple	308
14.2.3 Fixed	308
14.2.4 Variable	309
14.3 VC parameter negotiation	310
14.3.1 Agreement of assignment schemes	310
14.3.2 Negotiation of number of VCs	310
14.4 Credit management	311
14.4.1 Overview	311
14.4.2 VC_RDY Primitive Signals	311
15 Inter-Fabric Routing support	312
15.1 F_RJT and F_BSY processing for Class 2/F	312
15.1.1 Overview	312
15.1.2 Encapsulated Class 2 F_RJT or Class 2 F_BSY frame format	312
15.1.2.1 Overview	312
15.1.2.2 Encapsulated Enc_Header field values	313
15.1.2.3 Encapsulated IFR_Header field values	314
15.1.2.4 Encapsulated Frame_Header field values	314
16 Timers and constants	315
16.1 General timers and constants	315
16.2 SW_ILS timeout values	316
17 Distributed Switch	317
17.1 Overview	317
17.2 FCDF handling of well-known addresses	323
17.3 A_Port to A_Port links (ASLs)	326
17.4 Distributed Switch operations	327
17.4.1 Overview	327
17.4.2 FCDF routing	328
17.4.3 N_Port_ID handling	329
17.4.4 Distribution tree	331
17.5 Controlling Switch redundancy protocol	331
17.5.1 Controlling Switch redundancy protocol overview	331
17.5.2 Controlling Switch redundancy protocol state machine	331
18 Leaf Switch	339
18.1 Overview	339
Annex A	340
A.1 Introduction	340
A.2 Example 1: two E/F/FL_Port-capable Switch ports	340
A.3 Example 2: two E/F/FL_Port-capable Switch ports and one PN_Port	341
A.4 Example 3: one E/F/FL_Port-capable Port and one E/F_Port-capable Port	342
Annex B	343
B.1 Introduction	343
B.2 ELP exchange protocol	343
B.2.1 ELP exchange without parameter negotiation	343
B.2.2 ELP exchange with parameter negotiation	345
Annex C	347
C.1 Introduction	347

C.2 Sample flows	347
C.2.1 HBA registration - single Switch	347
C.2.2 HBA registration - multiple Switches - caches updated	348
C.2.3 HBA registration - multiple Switches - caches not updated	348
C.2.4 HBA de-registration - primary HBA manager	349
C.2.5 HBA de-registration - non-primary HBA manager	350
Annex D	352
D.1 Overview	352
D.2 Background	352
D.3 Definitions	352
D.4 Characteristics of Avionics Fabrics	353
D.4.1 Overview	353
D.4.2 AE Switch port mode initialization	354
D.4.2.1 Overview	354
D.4.2.2 Switch port mode initialization state machine modifications	354
D.4.3 ELP payload requirements	358
D.4.4 AE Principal Switch	359
D.4.4.1 AE Principal Switch initialization process	359
D.4.4.2 Map update process	360
D.4.4.3 AE Principal Switch update process	360
D.4.5 FFI Domain Topology Map distribution	361
D.4.5.1 Overview	361
D.4.5.2 FFI Domain Topology Map distribution state machine diagram	361
D.4.5.3 FFI Domain Topology Map distribution state machine text	362
D.4.6 Fast Fabric Initialization (FFI) SW_ILS definition	369
D.4.6.1 Overview	369
D.4.6.2 Fast Fabric Initialization Link State Record (FFI LSR) format	374
D.4.6.3 Fast Fabric Initialization Link Descriptor format	375
D.5 FFI Domain Topology Map Distribution (Informative)	376
D.5.1 Sample configuration	376
D.5.2 Initialization procedure example	377
D.5.3 AE Principal Switch update example	379

Figure	Page
Figure 1 – Sample state machine	12
Figure 2 – Basic Switch model	17
Figure 3 – Enhanced Switch functional model	18
Figure 4 – Multiple Switch Fabric example	19
Figure 5 – Controlling Switch functional model	21
Figure 6 – FCDF functional model	22
Figure 7 – FCDF Switching Element	23
Figure 8 – Domain, Area, and Port address partitioning	25
Figure 9 – F_Port model	30
Figure 10 – FL_Port model	32
Figure 11 – E_Port model	33
Figure 12 – B_Port model	34
Figure 13 – A_Port model	36
Figure 14 – Principal Inter-Switch Links	37
Figure 15 – VA_Port SW_ILS relay example	126
Figure 16 – Switch port mode initialization state machine	166
Figure 17 – Switch port mode initialization state machine - continued	167
Figure 18 – Simultaneous ELP processing- parameters acceptable to both Switches	171
Figure 19 – ESC processing	175
Figure 20 – Principal Switch selection state machine	177
Figure 21 – Example Propagation of BF and RCF SW_ILS requests	179
Figure 22 – Address Distribution state machines	183
Figure 23 – RDI request processing by Principal Switch	185
Figure 24 – RDI request Processing by non-Principal Switch	188
Figure 25 – Example B_Port configuration - Virtual ISL	192
Figure 26 – Neighbor finite state machine	210
Figure 27 – Basic Zoning framework	252
Figure 28 – Basic Zoning hierarchy	253
Figure 29 – Basic Zoning Object structure	254
Figure 30 – Logical structure of the Zone Set Database	259
Figure 31 – Logical structure of the Active Zone Set	260
Figure 32 – Merge operation between two Switches	274
Figure 33 – Merge operation among several Switches	275
Figure 34 – Broadcast path selection example	283
Figure 35 – Virtual Fabrics	284
Figure 36 – Functional model of a VF capable Switch	285
Figure 37 – Switch port mode initialization state machine - Virtual Fabric support	288
Figure 38 – A generic EVFP transaction	291
Figure 39 – Normal commit ladder diagram	299
Figure 40 – Unsuccessful commit ladder diagram	300
Figure 41 – Transfer ownership ladder diagram	301
Figure 42 – ECS Managing Switch state machine	302
Figure 43 – ECS managed Switch state machine	304
Figure 44 – ECS transfer commit ownership (TCO) state machine	306
Figure 45 – VC_RDY Primitive Signal format	311
Figure 46 – Encapsulated Class 2/F F_RJT and Class 2/F F_BSY frame format	312
Figure 47 – Distributed Switch example - one Controlling Switch and two FCDFs	317
Figure 48 – FSPF Topology of figure 47	318
Figure 49 – Distributed Switch example - two Controlling Switches - two FCDFs	319
Figure 50 – Distributed Switch example - two Controlling Switches - four cascaded FCDFs	320
Figure 51 – FSPF topology of figure 49 and figure 50	321
Figure 52 – Distributed Switch example - three Controlling Switches - two FCDFs	322

Figure 53 – FSPF topology of figure 52	323
Figure 54 – FCDF with no link to Primary Controlling Switch WKA frame processing example	325
Figure 55 – Redundant Distributed Switch example	331
Figure 56 – Controlling Switch redundancy protocol state machine	333
Figure 57 – Leaf Switch example	339
Figure A.1 – Initialization example 1	340
Figure A.2 – Initialization example 2	341
Figure A.3 – Initialization example 3	342
Figure B.1 – Reference ELP configuration	343
Figure B.2 – A successful and complete ELP exchange	344
Figure B.3 – An unsuccessful but complete ELP exchange	344
Figure B.4 – A successful ELP exchange protocol parameter negotiation	345
Figure B.5 – An unsuccessful ELP exchange protocol parameter negotiation	346
Figure C.1 – Registration of HBA information - single Switch	347
Figure C.2 – Registration of HBA information - multiple Switches caches updated	348
Figure C.3 – Registration of HBA Information - multiple Switches caches not updated	349
Figure C.4 – HBA de-registration - primary HBA manager	350
Figure C.5 – HBA de-registration - non-primary HBA manager	351
Figure D.1 – Modifications to Switch port mode initialization	355
Figure D.2 – FFI Domain Topology Map distribution state machine, non-principal AE Switches	361
Figure D.3 – FFI Domain Topology Map distribution state machine, AE Principal Switch	362
Figure D.4 – Example Avionics Fabric	377

Table	Page
Table 1 – Address identifier values	27
Table 2 – SW_ILS command codes	41
Table 3 – SW_RJT payload	44
Table 4 – SW_RJT reason codes	44
Table 5 – SW_RJT reason code explanations	45
Table 6 – ELP request payload	48
Table 7 – Fabric Controller Class F Service Parameters	50
Table 8 – Class 2 Interconnect_Port Parameters	51
Table 9 – Class 3 Interconnect_Port Parameters	51
Table 10 – ISL Flow Control Mode values	52
Table 11 – Flow Control Parameters.	52
Table 12 – VC_RDY flow control parameters	53
Table 13 – Assignment schemes	53
Table 15 – VC values - Fixed	54
Table 16 – VC Values - Variable	54
Table 14 – VC values - Simple	54
Table 17 – ELP accept payload	55
Table 18 – EFP request payload	56
Table 19 – Switch_Priority field values	57
Table 20 – Domain_ID_List record format	57
Table 21 – Record_Type field values	58
Table 22 – EFP accept payload	58
Table 23 – DIA request payload	59
Table 24 – DIA accept payload	60
Table 25 – RDI request payload	61
Table 26 – RDI accept payload	62
Table 27 – HLO request payload	63
Table 28 – FSPF Header	64
Table 29 – FSPF command codes	64
Table 30 – LSU request payload	65
Table 31 – Flags field bit map	66
Table 32 – Link State Record - Link Descriptor format	66
Table 33 – Link State Header format	67
Table 34 – Link State Record Type field values	67
Table 35 – LSR Flags field bit descriptions	68
Table 36 – Link Descriptor format	69
Table 37 – Link Type values	69
Table 38 – LSA request payload	70
Table 39 – BF request payload	71
Table 40 – BF accept payload	71
Table 41 – RCF request payload	72
Table 42 – RCF accept payload	72
Table 43 – SW_RSCN request payload	73
Table 44 – Device Entry format	74
Table 45 – SW_RSCN accept payload	75
Table 46 – DRLIR request payload	75
Table 47 – DRLIR accept payload	76
Table 48 – Merge Request request payload	77
Table 49 – Protocol Version values	77
Table 50 – Basic Zoning payload	77
Table 51 – Enhanced Zoning payload	78
Table 52 – Merge Request accept payload	80

Table 53 – ACA request payload	81
Table 54 – Acquire Change Authorization accept payload	82
Table 55 – RCA request payload	82
Table 56 – Release Change Authorization accept payload	83
Table 57 – SFC request payload	83
Table 58 – Operation Request values	84
Table 59 – Stage Fabric Configuration accept payload	85
Table 60 – Payload for Operation Request values 03 and 04	85
Table 61 – Payload for Operation Request ‘Activate Zone Set Enhanced’	86
Table 62 – Payload for Operation Request ‘Deactivate Zone Set Enhanced’	86
Table 63 – Payload for Operation Request ‘Distribute Zone Set Database’	87
Table 64 – Payload for Operation Request ‘Activate Zone Set by Name’	87
Table 65 – Payload for Operation Request ‘Set Zoning Policies’	88
Table 66 – Update Fabric Configuration request payload	88
Table 67 – Update Fabric Configuration accept payload	89
Table 68 – CEC request payload	90
Table 69 – CEC accept payload	91
Table 70 – ESC request payload	92
Table 71 – Protocol Descriptor format	92
Table 72 – Protocol ID values	93
Table 73 – ESC accept payload	93
Table 74 – ESS request payload	95
Table 75 – Capability Object format	96
Table 76 – Name Server Capability Flags	96
Table 77 – Fabric Controller Capability Flags	97
Table 78 – Fabric Configuration Server Capability Flags	98
Table 79 – Enhanced Zone Server Capability Flags	98
Table 80 – Vendor Specific Capability Object	100
Table 81 – Domain Controller Capability Object	101
Table 82 – Event Server Capability Object	102
Table 83 – Switch Support Capability Object	102
Table 84 – Application Server Capability Object	103
Table 85 – Enhanced Fabric Configuration Server Capability Object	103
Table 86 – VE Identification Server Capability Flags	104
Table 87 – ESS accept payload	104
Table 88 – MRRA request payload	105
Table 89 – Vendor Specific field	105
Table 90 – MRRA response payload	106
Table 91 – MRRA Response values	106
Table 92 – STR request payload	107
Table 93 – Nx_Port Tags	108
Table 94 – Flags field values	109
Table 95 – STR Reject Reason Code values	109
Table 96 – Path Information	110
Table 97 – STR accept payload	111
Table 98 – EVFP request payload	112
Table 99 – EVFP Message Codes	112
Table 100 – EVFP accept payload	113
Table 101 – SW_RJT reason codes	114
Table 102 – EVFP_SYNC Message Payload format	114
Table 103 – Descriptor format	115
Table 104 – Descriptor Control codes	115
Table 105 – Descriptor Types	115
Table 106 – Tagging Administrative Status descriptor	116

Table 107 – Administrative Tagging Modes	116
Table 108 – Tagging Mode negotiation	116
Table 109 – Port VF_ID descriptor	117
Table 110 – Locally-Enabled VF_ID List descriptor	117
Table 111 – Vendor Specific descriptor	118
Table 112 – EACA request payload	118
Table 113 – Commit Exchange Preamble	119
Table 114 – Transaction Identifier	119
Table 115 – Application ID values	120
Table 116 – ECS Switch List	121
Table 117 – Switch Identifier format	121
Table 118 – ESFC request payload	122
Table 119 – EUFC request payload	123
Table 120 – ERCA request payload	124
Table 121 – TCO request payload	125
Table 122 – VA_Port SW_ILSs command codes	126
Table 123 – Descriptor format	127
Table 124 – Descriptor tags	127
Table 125 – VN_Port Reachability descriptor format	128
Table 126 – FLOGI/NPIV FDISC Parameters descriptor format	128
Table 127 – VN_Port Unreachability descriptor format	128
Table 128 – FCDF Reachability descriptor format	129
Table 129 – Sequence Number descriptor format	129
Table 130 – Controlling Switch Reachability descriptor format	130
Table 131 – N_Port_IDs Reachability descriptor format	130
Table 132 – N_Port_ID Reachability Entry format	131
Table 133 – Domain_IDs Reachability descriptor format	132
Table 134 – Reachable Domain_ID Entry format	132
Table 135 – Allocation Status descriptor format	133
Table 136 – Allocation / Deallocation Entry format	133
Table 137 – Peering Status descriptor format	134
Table 138 – Peering Entry format	134
Table 139 – Membership Set descriptor format	135
Table 140 – Integrity descriptor format	136
Table 141 – Integrity Type field values	136
Table 142 – FCDF Identification descriptor format	136
Table 143 – SW_ILS Request Information descriptor format	137
Table 144 – ELS Payload descriptor format	137
Table 145 – VNRN request payload	138
Table 146 – VNRN SW_ACC payload	139
Table 147 – VNUN request payload	139
Table 148 – VNUN SW_ACC payload	140
Table 149 – FCRN request payload	141
Table 150 – FCRN SW_ACC payload	141
Table 151 – FCUN request payload	142
Table 152 – FCUN SW_ACC payload	142
Table 153 – NPRD request payload	143
Table 154 – NPRD SW_ACC payload	144
Table 155 – NPZD request payload	145
Table 156 – NPZD SW_ACC payload	146
Table 157 – AZAD request payload	147
Table 158 – AZAD SW_ACC payload	147
Table 159 – DSMD request payload	148
Table 160 – DSMD SW_ACC payload	149

Table 161 – DELS request payload	149
Table 162 – DELS SW_ACC payload	150
Table 163 – VA_Port SW_ILSs timeouts	151
Table 164 – Controlling Switch redundancy protocol SW_ILSs command codes	151
Table 165 – Controlling Switch State descriptor format	152
Table 166 – FCDF Topology descriptor format	152
Table 167 – FCDF Connectivity Record format	153
Table 168 – ASL Record format	153
Table 169 – FCDF N_Port_IDs descriptor format	154
Table 170 – FCDF Allocation Record format	154
Table 171 – RHello Interval descriptor format	155
Table 172 – Controlling Switch Parameters descriptor format	155
Table 173 – Controlling Switch Priority Switch_Name Record format	155
Table 174 – ERP request payload	156
Table 175 – ERP SW_ACC payload	157
Table 176 – GFTS request payload	157
Table 177 – GFTS SW_ACC payload	158
Table 178 – GFNS request payload	158
Table 179 – GFNS SW_ACC payload	159
Table 180 – SSA request payload	159
Table 181 – SSA SW_ACC payload	160
Table 182 – RHello request payload	160
Table 183 – SPCS request payload	161
Table 184 – SPCS SW_ACC payload	161
Table 185 – ECSP request payload	162
Table 186 – ECSP SW_ACC payload	162
Table 187 – Controlling Switch redundancy protocol SW_ILSs timeouts	163
Table 188 – Fabric Configuration summary	164
Table 189 – Responses to ELP request for originating Interconnect_Port	169
Table 190 – Recommended BF and RCF usage summary	176
Table 191 – B_Port ILS support	191
Table 192 – B_Port initialization summary	192
Table 193 – Path selection (FSPF) operation summary	194
Table 194 – Checksum byte order calculation	200
Table 195 – DEFAULT_COST values	201
Table 196 – Neighbor finite state machine	207
Table 197 – Default Domain Controller Service Parameter values	212
Table 198 – FC-CT command codes for dNS	216
Table 199 – Name Server Entry Object	220
Table 200 – Entry Object Format Indicator	221
Table 201 – Name Server Entry Object description	221
Table 202 – GE_ID request payload	222
Table 203 – GE_ID accept payload	222
Table 204 – GE_PN request payload	222
Table 205 – GE_PN accept payload	223
Table 206 – GE_NN request payload	223
Table 207 – GE_NN accept payload	223
Table 208 – GE_FT request payload	224
Table 209 – GE_FT accept payload	224
Table 210 – GE_PT request payload	224
Table 211 – GE_PT accept payload	225
Table 212 – GE_ZM request payload	225
Table 213 – GE_ZM accept payload	226
Table 214 – GE_ZN request payload	226

Table 215 – GE_ZN accept payload	226
Table 216 – GE_FF request payload	227
Table 217 – GE_FF accept payload	227
Table 218 – GE_FPN request payload	228
Table 219 – GE_FPN accept payload	228
Table 220 – Zoning effect on Servers of the distributed Management Service	229
Table 221 – dMS FC-CT Header parameters	229
Table 222 – Fabric Configuration Service command codes for dMS	230
Table 223 – FDMI Inter-Switch message format	235
Table 224 – FC-CT Header parameters	235
Table 225 – FDMI Header format	235
Table 226 – Vendor Specified field format	236
Table 227 – FDMI Fabric Internal command codes	236
Table 228 – Reason code explanation	237
Table 229 – Registered HBA/Port list format	238
Table 230 – HBA Entry format	239
Table 231 – Port Entry format	239
Table 232 – FDMI CT commands for the dMS	240
Table 233 – Fabric internal Management Server requests	240
Table 234 – GCAP request payload format	241
Table 235 – GCAP CT_ACC payload format	241
Table 236 – Capability Entry format	241
Table 237 – Fabric Configuration Server (CT_Subtype 01h)	242
Table 238 – Unzoned Name Server (CT_Subtype 02h)	242
Table 239 – Security Information Server command codes for dMS	242
Table 240 – Application Server command codes for dMS	243
Table 241 – Enhanced Fabric Configuration Service command codes for dMS	244
Table 242 – dES FC-CT Header parameters	245
Table 243 – FC-CT command codes for dES	245
Table 244 – dVEIS FC-CT Header parameters	246
Table 245 – FC-CT Command Codes for dVEIS	246
Table 246 – G_VEM_D Request payload	246
Table 247 – G_VEM_D Accept payload	247
Table 248 – VEM Mapping entry format	247
Table 249 – VE Mapping record format	247
Table 250 – Fabric VE ID format	248
Table 251 – U_VE_M Request Payload	248
Table 252 – VE Mapping entry format	249
Table 253 – U_VE_M Accept payload	249
Table 254 – Zoning Object List format	254
Table 255 – Zoning Object	255
Table 256 – Zoning Object Type values	255
Table 257 – Protocol Format values	256
Table 258 – Zone Member format	256
Table 259 – Zone Member Type and Identifier formats	257
Table 260 – Zoning Object List format	261
Table 261 – Zoning Object Type values	261
Table 262 – Zone Set Object format in the Zone Set Database	262
Table 263 – Zone Set Object format in the Active Zone Set	263
Table 264 – Zone Reference Object format	263
Table 265 – Zone Object format in the Zone Set Database	264
Table 266 – Zone Object format in the Active Zone Set	265
Table 267 – Zone Member format	266
Table 268 – Zone Member Type and Identifier formats	266

Table 269 – Wildcard Zone Member Identifier format	267
Table 270 – Vendor Specified Zone Member Identifier format	268
Table 271 – Zone Alias Object format	268
Table 272 – Zone Attribute Object format	269
Table 273 – Zone Attribute Block format	269
Table 274 – Zone Attribute Entry format	270
Table 275 – Zone Attribute Type values	270
Table 276 – Protocol Attribute Value format	271
Table 277 – Peer Zone Attribute Value format	273
Table 278 – Vendor Specific Attribute Value format	273
Table 279 – Basic Zoning merge rules	276
Table 280 – Enhanced Zoning merge rules	277
Table 281 – EACA phase - events and actions	304
Table 282 – ESFC phase - events and actions	305
Table 283 – EUFC phase - events and actions	305
Table 284 – Simple assignment scheme	308
Table 285 – Fixed assignment scheme	308
Table 286 – VC assignments - Fixed	309
Table 287 – Variable assignment scheme	309
Table 288 – VC assignments - Variable	310
Table 289 – VC_ID values for VC_RDY Primitive Signals	311
Table 290 – Encapsulated Class 2/F F_RJT/F_BSY Enc_Header field values	313
Table 291 – Encapsulated Class 2/F F_RJT/F_BSY IFR_Header field values	314
Table 292 – FC-SW-7 timers and constants	315
Table 293 – SW_ILS timeout values	316
Table 294 – Forwarded Domain Controller and well-known address identifiers	324
Table 295 – VA_Port ELP Flag bits	326
Table 296 – Controlling Switch priority values	332
Table D.1 – Responses to ELP request for originating Interconnect_Port	356
Table D.2 – ELP required payload values for AE_Ports	358
Table D.3 – Actions taken by non-Principal AE Switch for an FFI request Sequence	364
Table D.4 – Action taken by AE Principal Switch for an FFI request Sequence	368
Table D.5 – FFI request payload	370
Table D.6 – FFI Type Flags definition	371
Table D.7 – FFI Problem Detected Reason Codes	372
Table D.8 – FFI accept payload	373
Table D.9 – FFI Link State Record - Link Descriptor format	374
Table D.10 – FFI LSR Flags definition	374
Table D.11 – FFI Link Descriptor format	375
Table D.12 – FFI Link Descriptor Flags definition	375

Foreword (This foreword is not part of American National Standard INCITS 547-2020.)

This standard describes the requirements for an interconnecting Fabric consisting of multiple Fibre Channel Fabric Switch elements.

This standard was developed by Technical Committee T11 of Accredited Standards Committee INCITS during 2015-2019. The standards approval process started in 2019. This document includes annexes that are informative and are not considered part of the standard.

Requests for interpretation, suggestions for improvements or addenda, or defect reports are welcome. They should be sent to the INCITS Secretariat, Information Technology Industry Council, 700 K Street NW, Suite 600, Washington, DC 20001.

This standard was processed and approved for submittal to ANSI by the International Committee for Information Technology Standards (INCITS). Committee approval of the standard does not necessarily imply that all committee members voted for its approval. At the time it approved this standard, INCITS had the following members:

Laura Lindsay, Chair
 Donald Deutsch, Vice-Chair
 Jennifer Garner, Secretary

<i>Organization Represented</i>	<i>Name of Representative</i>
Adobe Systems, Inc.....	Scott Foshee
AIM Global, Inc.	Steve Halliday
	Mary Lou Bosco (Alt.)
	Chuck Evanhoe (Alt.)
Amazon Web Services, Inc.	Oliver Bell
	Sean Estrada (Alt.)
Apple	Helene Workman
	David Singer (Alt.)
	Anna Weinberg (Alt.)
CA Technologies	Ron Doyle
Department of Commerce - NIST	Michael Hogan
	Lisa Carnahan (Alt.)
	Wo Chang (Alt.)
	Sal Francomacaro (Alt.)
	Suzanne Radell (Alt.)
Farance, Inc.....	Frank Farance
	Timothy Schoechle (Alt.)
Futurewei Technologies, Inc.....	Wael Diab
	Wilbert Adams (Alt.)
	Timothy Jeffries (Alt.)
Google	Catherine Nelson
	Tommy Ward (Alt.)
GS1GO.....	Steven Keddie
	Edward Merrill (Alt.)
	Dan Mullen (Alt.)
HP, Inc.....	Karen Higginbottom
	Will Allen (Alt.)
	Paul Jeran (Alt.)
	Lonnie Mandigo (Alt.)
IBM Corporation	Steve Holbrook
	Alexander Tarpinian (Alt.)
Intel Corporation	Philip Wennblom
	Grace Wei (Alt.)
Microsoft Corporation	Laura Lindsay
	John Calhoon (Alt.)

<i>Organization Represented</i>	<i>Name of Representative</i>
Oracle	Donald Deutsch Anish Karmarkar (Alt.) Michael Kavanaugh (Alt.) Jim Melton (Alt.) Jan-Eike Michels (Alt.) Elaine Newton (Alt.)
Qualcomm, Inc.	Michael Atlass Mazen Chmaytelli (Alt.) Marta Karczewicz (Alt.) Farrokh Khatibi (Alt.)
Telecommunications Industry Association (TIA)	Florence Otieno
United States Dept. of Defense - Joint Artificial Intelligence Center	Steven Harrison Alka Paterl (Alt.)
VMware, Inc.....	Stephen Diamond Salim AbiEzzi (Alt.) Lawrence Lamers (Alt.)

Technical Committee T11 on Fibre Channel Interfaces, which reviewed this standard had the following members:

Steven Wilson, Chair
Craig Carlson, Vice-Chair
Patty Driever, Secretary

<i>Organization Represented</i>	<i>Name of Representative</i>
Amphenol Corporation.....	Gregory McSorley Brad Brubaker (Alt.) Daniel Dillow (Alt.) Chris Lyon (Alt.) Alex Persaud (Alt.) Hu Silver (Alt.) Michael Wingard (Alt.)
Anritsu Corporation.....	Tadanori Nishikobara
Broadcom, Inc.	Steven Wilson David Baldwin (Alt.) Evan Beauprez (Alt.) Ben Chu (Alt.) Adam Healey (Alt.) Howard Johnson (Alt.) Mark Jones (Alt.) Scott Kipp (Alt.) Anil Mehta (Alt.) David Peterson (Alt.) Rob Peterson (Alt.) James Smart (Alt.)
CIENA.....	Stephen Shew Sebastien Gareau (Alt.)
Cisco Systems, Inc.	Mike Blair Mark Allen (Alt.) Harsha Bharadwaj (Alt.) Rajesh LG (Alt.) Fabio Maino (Alt.) J. Metz (Alt.) Joe Pelissier (Alt.) Xiaohong Wu (Alt.)
CommScope	Sunny Xu Gary Gibbs (Alt.) Paul Kolesar (Alt.)
Corning, Inc.	Doug Coleman Steven Swanson (Alt.)
Data Center Systems	Todd Wheeler Steve Eisele (Alt.)

<i>Organization Represented</i>	<i>Name of Representative</i>
Dell, Inc.	Alan Rajapa David Black (Alt.) David Brown (Alt.) Gaurav Chawla (Alt.) Erik Smith (Alt.) Joseph White (Alt.) Jeff Young (Alt.)
Finisar Corporation.....	Vipul Bhatt Vera Koleva (Alt.) Lance Thompson (Alt.)
Foxconn Interconnect Technology, Ltd. (FIT)	John Petrilla Fred Fons (Alt.) Glenn Moore (Alt.) William Peters (Alt.)
Fujitsu America, Inc.....	Mark Malcolm Kun Katsumata (Alt.) Osamu Kimura (Alt.) Gene Owens (Alt.)
Futurewei Technologies, Inc.	Lei Wang Timothy Jeffries (Alt.)
GlobalFoundries US2 LLC	Adrian Butter John Ewen (Alt.) Jon Garlett (Alt.)
Hewlett-Packard Enterprise	Barry Maskas Curtis Ballard (Alt.) Rupin Mohan (Alt.) Krishna Babu Puttagunta (Alt.)
Hitachi Vantara.....	Eric Hibbard Vincent Franceschini (Alt.) Akinobu Shimada (Alt.) Erwin van Londen (Alt.) Ken Wood (Alt.)
IBM Corporation	Roger Hathorn Patty Driever (Alt.) Stephen Guendert (Alt.)
Keysight Technologies, Inc.	Stephen Didde Steve Sekel (Alt.) Joachim Vobis (Alt.)
Lumentum Operations.....	David Lewis
Macom	Thomas Palkert
Marvell Semiconductor, Inc.	Craig Carlson Anshul Agarwal (Alt.) Sanjaya Anand (Alt.) Girish Basrur (Alt.) Kathy Caballero (Alt.) Mike Dudek (Alt.) Arun Easi (Alt.) Robert Friend (Alt.) Duane Grigsby (Alt.) Rick Hicksted, Jr. (Alt.) Ali Khwaja (Alt.) Stephen Lam (Alt.) Ray Leung (Alt.) Akinori Maeda (Alt.) Praveen Midha (Alt.) Trinh Nguyen (Alt.) Raul Oteyza (Alt.) Eddy Soetjahja (Alt.) Alan Spalding (Alt.) Gourangadoss Sundar (Alt.) Darren Trapp (Alt.) Andrew Vasquez (Alt.) Dean Wallace (Alt.)
MediaTek USA, Inc.	Tamer Ali Mau-Lin Wu (Alt.)

<i>Organization Represented</i>	<i>Name of Representative</i>
Microsoft Corporation	Lee Prewitt Steve Olsson (Alt.)
Molex, Inc.	Alexandra Haser Jay Neer (Alt.) Tom Palkert (Alt.) Scott Sommers (Alt.)
NetApp, Inc.....	Frederick Knight John Meneghini (Alt.) Urmi Misra (Alt.) Vijay Rao (Alt.)
OFS Fitel LLC.....	Roman Shubochkin Mabud Choudhury (Alt.)
Panduit Corporation.....	Jose Castro Bulent Kose (Alt.) Robert Reid (Alt.) Steve Skiest (Alt.)
TE Connectivity	Nathan Tracy Jeff Mason (Alt.)
Teledyne LeCroy Corporation	David Rodgers Douglas Lee (Alt.) Henry Poelstra (Alt.)
Unisys Corporation	Jeffrey Dremann Phil Shelton (Alt.)
Viavi Solutions, Inc.	Jason Rusch Scott Baxter (Alt.) George Bullis (Alt.) Paul Gentieu (Alt.)
VMware, Inc.....	Neil MacLean Wenchao Cui (Alt.) Wenhua Liu (Alt.) Murali Rajagopal (Alt.) Ahmad Tawil (Alt.)

Members Emeritus

James Coomes
William Ham
Robert Kembel
Robert Nixon
Schelto Van Doorn

Introduction

FC-SW-7 is one of the Fibre Channel family of standards. This family includes INCITS FC-FS-6 and INCITS FC-PI-7/FC-PI-7P. INCITS FC-GS-8, is a document related to Generic Fabric Services and is closely tied to FC-SW-7. INCITS FC-BB-6 describes how Fabrics are extended over transports complementary to Fibre Channel. INCITS FC-MI-3 and INCITS FC-DA-2 describe interoperability profiles that assists in the interoperability of Switches. INCITS 332-1999, FC-AL-2, specifies the arbitrated loop topology. INCITS FC-SP-2 describes the Security requirements and protocols associated with Fibre Channel networks. INCITS FC-IFR describes the requirements and protocols associated with Inter-Fabric Routing.

FC-SW-7 describes how Switches communicate and interact with one another to form a Fabric of Switches. Included are Fabric initialization and configuration, routing, Server communication, event distribution and repository exchanges (e.g., Zoning information).

American National Standard
for Information Technology --

Fibre Channel --
Switch Fabric - 7 (FC-SW-7)

1 Scope

This American National Standard for FC-SW-7 describes the operation and interaction of Fibre Channel Switches.

This standard includes:

- a) E_Port operation and Fabric Configuration;
- b) Path selection (FSPF);
- c) Bridge port (B_Port) operation;
- d) Distributed Server interaction and communication;
- e) Exchange of information between Switches to support Zoning;
- f) Distribution of Event Notifications between Switches;
- g) Virtual Fabrics Switch Support;
- h) Enhanced Commit Service;
- i) Virtual Channels;
- j) Inter-Fabric Routing;
- k) Distributed Switch; and
- l) Leaf Switch.

2 Normative references

2.1 Overview

The following standards contain provisions that, through reference in the text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of the standards listed below.

For electronic copies of ANSI, INCITS, and International standards, visit ANSI's Electronic Standards Store (ESS) at <http://www.ansi.org>.