

This is a preview of "INCITS/ISO/IEC 15041...". Click here to purchase the full version from the ANSI store.

STANDARD

15041

First edition  
1997-04-15

Stabilized as  
INCITS/ISO/IEC 15041:1997[S2012]

---

---

## Information technology — Data interchange on 90 mm optical disk cartridges — Capacity: 640 Mbytes per cartridge

*Technologies de l'information — Échange de données sur cartouches de  
disque optique de 90 mm — Capacité: 640 Mbytes par cartouche*

**Adopted by INCITS (InterNational Committee for Information Technology Standards) as an American National Standard.**

Date of ANSI Approval: 9/25/97

Published by American National Standards Institute,  
25 West 43rd Street, New York, New York 10036

Copyright 2002 by Information Technology Industry Council (ITI).  
All rights reserved.

These materials are subject to copyright claims of International Standardization Organization (ISO), International Electrotechnical Commission (IEC), American National Standards Institute (ANSI), and Information Technology Industry Council (ITI). Not for resale. No part of this publication may be reproduced in any form, including an electronic retrieval system, without the prior written permission of ITI. All requests pertaining to this standard should be submitted to ITI, 1250 Eye Street NW, Washington, DC 20005.

Printed in the United States of America



Reference number  
ISO/IEC 15041:1997(E)

This is a preview of "INCITS/ISO/IEC 15041...". [Click here to purchase the full version from the ANSI store.](#)

## Contents

	<b>Page</b>
<b>Section 1 - General</b>	<b>1</b>
1 Scope	1
2 Conformance	2
2.1 Optical disk cartridge (ODC)	2
2.2 Generating system	2
2.3 Receiving system	2
2.4 Compatibility statement	2
3 Normative reference	2
4 Definitions	2
4.1 band	2
4.2 case	2
4.3 Channel bit	2
4.4 clamping zone	2
4.5 control track	2
4.6 Cyclic Redundancy Check (CRC)	2
4.7 defect management	2
4.8 DOW disk	2
4.9 disk reference plane	2
4.10 embossed mark	2
4.11 entrance surface	2
4.12 Error Correction Code (ECC)	2
4.13 field	2
4.14 format	2
4.15 fully embossed disk	3
4.16 fully rewritable disk	3
4.17 groove	3
4.18 hub	3
4.19 interleaving	3
4.20 Kerr rotation	3
4.21 land and groove	3
4.22 logical track	3
4.23 logical ZCAV	3
4.24 mark	3

©ISO/IEC 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office · Case Postale 56 · CH-1211 Genève 20 · Switzerland

Printed in Switzerland

This is a preview of "INCITS/ISO/IEC 15041...". Click here to purchase the full version from the ANSI store.

STANDARD

15041

First edition  
1997-04-15

---

---

**Information technology — Data  
interchange on 90 mm optical disk  
cartridges — Capacity: 640 Mbytes per  
cartridge**

*Technologies de l'information — Échange de données sur cartouches de  
disque optique de 90 mm — Capacité: 640 Mbytes par cartouche*



Reference number  
ISO/IEC 15041:1997(E)

This is a preview of "INCITS/ISO/IEC 15041...". Click here to purchase the full version from the ANSI store.

## Contents

	<b>Page</b>
<b>Section 1 - General</b>	<b>1</b>
1 Scope	1
2 Conformance	2
2.1 Optical disk cartridge (ODC)	2
2.2 Generating system	2
2.3 Receiving system	2
2.4 Compatibility statement	2
3 Normative reference	2
4 Definitions	2
4.1 band	2
4.2 case	2
4.3 Channel bit	2
4.4 clamping zone	2
4.5 control track	2
4.6 Cyclic Redundancy Check (CRC)	2
4.7 defect management	2
4.8 DOW disk	2
4.9 disk reference plane	2
4.10 embossed mark	2
4.11 entrance surface	2
4.12 Error Correction Code (ECC)	2
4.13 field	2
4.14 format	2
4.15 fully embossed disk	3
4.16 fully rewritable disk	3
4.17 groove	3
4.18 hub	3
4.19 interleaving	3
4.20 Kerr rotation	3
4.21 land and groove	3
4.22 logical track	3
4.23 logical ZCAV	3
4.24 mark	3

©ISO/IEC 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office · Case Postale 56 · CH-1211 Genève 20 · Switzerland

Printed in Switzerland

This is a preview of "INCITS/ISO/IEC 15041...". Click here to purchase the full version from the ANSI store.

4.25 optical disk	3
4.26 optical disk cartridge (ODC)	3
4.27 partially embossed disk	3
4.28 physical track	3
4.29 physical track group	3
4.30 pitch	3
4.31 polarization	3
4.32 read power	3
4.33 recording layer	3
4.34 Reed-Solomon code	3
4.35 sector	3
4.36 space	4
4.37 spindle	4
4.38 substrate	4
4.39 zone	4
5 Conventions and notations	4
5.1 Representation of numbers	4
5.2 Names	4
6 List of acronyms	4
7 General description of the optical disk cartridge	5
8 General requirements	5
8.1 Environments	5
8.1.1 Testing environment	5
8.1.2 Operating environment	5
8.1.3 Storage environment	6
8.1.4 Transportation	6
8.2 Temperature shock	6
8.3 Safety requirements	6
8.4 Flammability	6
9 Reference Drive	6
9.1 Optical system	6
9.2 Optical beam	8
9.3 Read channels	8
9.4 Tracking	8
9.5 Rotation of the disk	9
<b>Section 2 - Mechanical and physical characteristics</b>	<b>9</b>
10 Dimensional and physical characteristics of the case	9
10.1 General description of the case	9
10.2 Reference planes of the case	9
10.3 Dimensions of the case	9
10.3.1 Overall dimensions	9
10.3.2 Location hole	10
10.3.3 Alignment hole	10
10.3.4 Reference surfaces	10
10.3.5 Detents	11
10.3.6 Functional Areas	11
10.3.7 Spindle and head windows	12

This is a preview of "INCITS/ISO/IEC 15041...". Click [here](#) to purchase the full version from the ANSI store.

<b>10.3.8</b>	<b>Shutter</b>	<b>13</b>
<b>10.3.9</b>	<b>Path for shutter opener and shutter sensor notch</b>	<b>13</b>
<b>10.3.10</b>	<b>Mis-insert protections</b>	<b>14</b>
<b>10.3.11</b>	<b>Gripper slots</b>	<b>14</b>
<b>10.3.12</b>	<b>Label area</b>	<b>15</b>
<b>10.4</b>	<b>Mechanical characteristics</b>	<b>15</b>
<b>10.4.1</b>	<b>Material</b>	<b>15</b>
<b>10.4.2</b>	<b>Mass</b>	<b>15</b>
<b>10.4.3</b>	<b>Edge distortion</b>	<b>15</b>
<b>10.4.4</b>	<b>Compliance</b>	<b>15</b>
<b>10.4.5</b>	<b>Shutter opening force</b>	<b>15</b>
<b>11</b>	<b>Dimensional, mechanical and physical characteristics of the disk</b>	<b>27</b>
<b>11.1</b>	<b>General description of the disk</b>	<b>27</b>
<b>11.2</b>	<b>Reference axis and plane of the disk</b>	<b>27</b>
<b>11.3</b>	<b>Dimensions of the disk</b>	<b>27</b>
<b>11.3.1</b>	<b>Hub dimensions</b>	<b>27</b>
<b>11.3.2</b>	<b>Clamping zone</b>	<b>28</b>
<b>11.4</b>	<b>Mechanical characteristics</b>	<b>28</b>
<b>11.4.1</b>	<b>Material</b>	<b>28</b>
<b>11.4.2</b>	<b>Mass</b>	<b>29</b>
<b>11.4.3</b>	<b>Moment of inertia</b>	<b>29</b>
<b>11.4.4</b>	<b>Imbalance</b>	<b>29</b>
<b>11.4.5</b>	<b>Axial deflection</b>	<b>29</b>
<b>11.4.6</b>	<b>Axial acceleration</b>	<b>30</b>
<b>11.4.7</b>	<b>Radial runout</b>	<b>30</b>
<b>11.4.8</b>	<b>Radial acceleration</b>	<b>30</b>
<b>11.4.9</b>	<b>Tilt</b>	<b>30</b>
<b>11.5</b>	<b>Optical Characteristics</b>	<b>31</b>
<b>11.5.1</b>	<b>Index of refraction</b>	<b>31</b>
<b>11.5.2</b>	<b>Thickness of the substrate</b>	<b>31</b>
<b>11.5.3</b>	<b>Birefringence</b>	<b>31</b>
<b>11.5.4</b>	<b>Vertical Birefringence</b>	<b>31</b>
<b>11.5.5</b>	<b>Reflectance</b>	<b>31</b>
<b>12</b>	<b>Interface between cartridge and drive</b>	<b>32</b>
<b>12.1</b>	<b>Clamping method</b>	<b>32</b>
<b>12.2</b>	<b>Clamping force</b>	<b>32</b>
<b>12.3</b>	<b>Capture cylinder</b>	<b>32</b>
<b>12.4</b>	<b>Disk position in operating condition</b>	<b>32</b>
<b>Section 3</b>	<b>Format of information</b>	<b>34</b>
<b>13</b>	<b>Geometry of physical tracks</b>	<b>34</b>
<b>13.1</b>	<b>Physical track shape</b>	<b>34</b>
<b>13.2</b>	<b>Direction of track spiral</b>	<b>34</b>
<b>13.3</b>	<b>Physical track pitch</b>	<b>34</b>
<b>14</b>	<b>Track format</b>	<b>34</b>
<b>14.1</b>	<b>Logical Track number</b>	<b>34</b>
<b>14.2</b>	<b>Logical Track layout</b>	<b>34</b>
<b>14.3</b>	<b>Clock frequencies and periods</b>	<b>34</b>
<b>14.4</b>	<b>Radial alignment</b>	<b>35</b>

This is a preview of "INCITS/ISO/IEC 15041...". [Click here to purchase the full version from the ANSI store.](#)

<b>14.5 Sector number</b>	<b>35</b>
<b>15 Sector format</b>	<b>35</b>
<b>15.1 Sector layout</b>	<b>35</b>
<b>15.2 Sector Mark (SM)</b>	<b>36</b>
<b>15.3 VFO fields</b>	<b>38</b>
<b>15.4 Address Mark (AM)</b>	<b>38</b>
<b>15.5 ID fields</b>	<b>39</b>
<b>15.6 Postambles (PA)</b>	<b>39</b>
<b>15.7 Gap</b>	<b>39</b>
<b>15.8 Sync</b>	<b>40</b>
<b>15.9 Data field</b>	<b>40</b>
<b>15.9.1 User data bytes</b>	<b>40</b>
<b>15.9.2 CRC and ECC bytes</b>	<b>40</b>
<b>15.9.3 Resync bytes</b>	<b>40</b>
<b>15.10 Buffer field</b>	<b>40</b>
<b>16 Recording code</b>	<b>41</b>
<b>17 Format of the Information Zone</b>	<b>42</b>
<b>17.1 General description of the Information Zone</b>	<b>42</b>
<b>17.2 Division of the Information Zone</b>	<b>42</b>
<b>17.2.1 Initial Zone</b>	<b>42</b>
<b>17.2.2 Acquire Zone</b>	<b>42</b>
<b>17.2.3 Test Zones</b>	<b>42</b>
<b>17.2.4 Control Zone</b>	<b>44</b>
<b>17.2.5 Data Zone</b>	<b>44</b>
<b>17.2.6 Buffer Zones</b>	<b>45</b>
<b>18 Format of the Data Zone</b>	<b>45</b>
<b>18.1 Buffer tracks and Test tracks in the Data Zone</b>	<b>46</b>
<b>18.2 Defect Management Areas (DMAs)</b>	<b>46</b>
<b>18.3 Disk Definition Structure (DDS)</b>	<b>47</b>
<b>18.3.1 Fully rewritable disks</b>	<b>49</b>
<b>18.3.2 Fully embossed disks</b>	<b>49</b>
<b>18.3.3 Partially embossed disks</b>	<b>50</b>
<b>18.4 Partitioning</b>	<b>50</b>
<b>18.4.1 Fully rewritable disks</b>	<b>50</b>
<b>18.4.2 Partially embossed disks</b>	<b>50</b>
<b>18.4.3 Fully embossed disks</b>	<b>50</b>
<b>19 Defect management</b>	<b>52</b>
<b>19.1 Rewritable groups: Spare sectors</b>	<b>52</b>
<b>19.1.1 Initialization of the disk</b>	<b>52</b>
<b>19.1.2 Certification</b>	<b>52</b>
<b>19.1.3 Disks not certified</b>	<b>52</b>
<b>19.1.4 Write procedure</b>	<b>53</b>
<b>19.1.5 Primary Defect List (PDL)</b>	<b>53</b>
<b>19.1.6 Secondary Defect List (SDL)</b>	<b>53</b>
<b>19.2 Embossed groups: Parity sectors</b>	<b>54</b>

This is a preview of "INCITS/ISO/IEC 15041...". Click here to purchase the full version from the ANSI store.

<b>Section 4 - Characteristics of embossed information</b>	<b>56</b>
20 Method of testing	56
20.1 Environment	56
20.2 Use of the Reference Drive	56
20.2.1 Optics and mechanics	56
20.2.2 Read power	56
20.2.3 Read channels	56
20.2.4 Tracking	56
20.3 Definition of signals	56
21 Signals from grooves	58
21.1 Cross-track signal	58
21.2 Cross-Track minimum signal	58
21.3 Push-pull signal	58
21.4 Divided push-pull signal	59
21.5 Phase depth	59
21.6 Track location	59
22 Signals from Headers	60
22.1 Sector Mark	60
22.2 VFO1 and VFO2	60
22.3 Address Mark, ID field and Postamble	60
22.4 Timing jitter	60
23 Signals from embossed Recording fields	60
23.1 Signal amplitude	60
23.2 Modulation method offset	61
23.3 Timing jitter	61
<b>Section 5 - Characteristics of the recording layer</b>	<b>62</b>
24 Method of testing	62
24.1 Environment	62
24.2 Reference Drive	62
24.2.1 Optics and mechanics	62
24.2.2 Read power	62
24.2.3 Read channel	62
24.2.4 Tracking	62
24.2.5 Signal detection for testing purposes	62
24.3 Write conditions	62
24.3.1 Write pulse and power	62
24.3.2 Write magnetic field	65
24.3.3 2 T and 4 T pulse power determination	65
24.3.4 Media power sensitivity	65
24.4 Erase conditions	65
24.4.1 Erase power	66
24.4.2 Erase magnetic field	66
24.5 Definition of signals	66
25 Magneto-optical characteristics	66
25.1 Figure of merit	66
25.2 Imbalance of the magneto-optical signal	66



This is a preview of "INCITS/ISO/IEC 15041...". [Click here to purchase the full version from the ANSI store.](#)

<b>26</b>	<b>Write characteristics</b>	<b>67</b>
<b>26.1</b>	<b>Resolution</b>	<b>67</b>
<b>26.2</b>	<b>Narrow-band signal-to-noise ratio</b>	<b>67</b>
<b>26.3</b>	<b>Cross-talk ratio</b>	<b>68</b>
<b>26.3.1</b>	<b>Rewritable track test method</b>	<b>68</b>
<b>26.4</b>	<b>Timing Jitter</b>	<b>68</b>
<b>26.5</b>	<b>Media thermal interaction</b>	<b>68</b>
<b>27</b>	<b>Erase power determination</b>	<b>69</b>
<b>Section 6</b>	<b>- Characteristics of user data</b>	<b>70</b>
<b>28</b>	<b>Method of testing</b>	<b>70</b>
<b>28.1</b>	<b>Environment</b>	<b>70</b>
<b>28.2</b>	<b>Reference Drive</b>	<b>70</b>
<b>28.2.1</b>	<b>Optics and mechanics</b>	<b>70</b>
<b>28.2.2</b>	<b>Read power</b>	<b>70</b>
<b>28.2.3</b>	<b>Read amplifiers</b>	<b>70</b>
<b>28.2.4</b>	<b>Mark Quality</b>	<b>70</b>
<b>28.2.5</b>	<b>Channel bit clock</b>	<b>71</b>
<b>28.2.6</b>	<b>Binary-to-digital converters</b>	<b>71</b>
<b>28.2.7</b>	<b>Error correction</b>	<b>71</b>
<b>28.2.8</b>	<b>Tracking</b>	<b>71</b>
<b>29</b>	<b>Minimum quality of a sector</b>	<b>71</b>
<b>29.1</b>	<b>Headers</b>	<b>71</b>
<b>29.1.1</b>	<b>Sector Mark</b>	<b>71</b>
<b>29.1.2</b>	<b>ID fields</b>	<b>71</b>
<b>29.2</b>	<b>User-written data</b>	<b>71</b>
<b>29.2.1</b>	<b>Recording field</b>	<b>71</b>
<b>29.2.2</b>	<b>Byte errors</b>	<b>71</b>
<b>29.2.3</b>	<b>Modulation method offset</b>	<b>71</b>
<b>29.2.4</b>	<b>Timing jitter</b>	<b>72</b>
<b>29.3</b>	<b>Embossed data</b>	<b>72</b>
<b>29.3.1</b>	<b>Byte errors</b>	<b>72</b>
<b>30</b>	<b>Data interchange requirements</b>	<b>72</b>
<b>30.1</b>	<b>Tracking</b>	<b>72</b>
<b>30.2</b>	<b>User-written data</b>	<b>72</b>
<b>30.3</b>	<b>Embossed data</b>	<b>72</b>
<b>30.4</b>	<b>Quality of disk</b>	<b>72</b>
<b>Annexes</b>		
<b>A</b>	<b>- Edge distortion test</b>	<b>73</b>
<b>B</b>	<b>- Compliance test</b>	<b>75</b>
<b>C</b>	<b>- CRC for ID fields</b>	<b>77</b>
<b>D</b>	<b>- Interleave, CRC, ECC, Resync for the data field</b>	<b>78</b>
<b>E</b>	<b>- Contents of the Control Zone</b>	<b>84</b>
<b>F</b>	<b>- Determination of the Resync patterns</b>	<b>91</b>
<b>G</b>	<b>- Measurement of the figure of merit</b>	<b>96</b>

This is a preview of "INCITS/ISO/IEC 15041...". [Click here to purchase the full version from the ANSI store.](#)

<b>H</b> - Read Channel for measuring NBSNR and jitter	<b>97</b>
<b>J</b> - Implementation Independent Mark Quality Determination (IIMQD) for the interchange of recorded media	<b>100</b>
<b>K</b> - Air cleanliness class 100 000	<b>102</b>
<b>L</b> - Position of the cartridge relative to the reference planes	<b>103</b>
<b>M</b> - Relaxation by zones of the requirements for signals	<b>104</b>
<b>N</b> - Test method for measuring the adsorbent force of the hub	<b>105</b>
<b>P</b> - Measurement implementation for Cross-track signal	<b>107</b>
<b>Q</b> - Track deviation measurement	<b>108</b>
<b>R</b> - Derivation of the operating climatic environment	<b>112</b>
<b>S</b> - Transportation	<b>117</b>
<b>T</b> - Office environment	<b>118</b>
<b>U</b> - Values to be implemented in existing and future standards	<b>119</b>
<b>V</b> - Measurement of the vertical birefringence of the substrate	<b>120</b>
<b>W</b> - Sector retirement guidelines	<b>122</b>
<b>X</b> - Laser power calibration for evaluation of media power sensitivity	<b>123</b>