



IPC-2591-Version 1.3

Connected Factory Exchange (CFX)

Developed by the Connected Factory Initiative Subcommittee (2-17) and the Connected Factory Initiative Subcommittee – China (2-17CN) of the Electronic Product Data Description Committee (2-10) of IPC

Supersedes:

IPC-2591-Version 1.2 -

September 2020

IPC-2591-Version 1.1 -

January 2020

IPC-2591 - March 2019

Users of this publication are encouraged to participate in the development of future revisions.

Contact:

IPC

Table of Contents

1	SCOPE	1	2.3	International Organization for Standardization (ISO)	4
1.1	Purpose	1	2.4	SEMI	4
1.2	Application of This Standard	1	3	GENERAL REQUIREMENTS	5
1.3	CFX and the Hermes Standard	1	3.1	Guidance on the Use of This Standard	5
1.4	Updates to This Standard	1	3.1.1	Technical Reference	5
1.5	Definition of Requirements	2	3.1.2	Application Reference	5
1.6	Order of Precedence	2	3.2	Users of CFX	5
1.6.1	Conflict	2	3.2.1	Automated Assembly Processes	5
1.6.2	Clause References	2	3.2.2	In-House Manufacturing Solution Development	5
1.7	Measurement Units	2	3.2.3	MES Software Solutions	5
1.8	Acronyms	2	3.3	Software Development Environment	5
1.9	Terms and Definitions	2	3.4	CFX Support Declaration	5
1.9.1	Activity	2	4	CFX STRUCTURAL OVERVIEW	6
1.9.2	Component	3	4.1	Primary Transport Layer: AMQP v1.0	6
1.9.3	Dashboard	3	4.1.1	CFX Message Channels	6
1.9.4	Data Integrity	3	4.1.2	Channel Configuration	7
1.9.5	Endpoint	3	4.1.3	CFX Message Types	7
1.9.6	Factory Resource	3	4.1.4	CFX Compression	7
1.9.7	Lane	3	4.1.5	CFX – AMQP Message Properties	7
1.9.8	Lock	3	4.2	Encoding: JSON	8
1.9.9	Material Carrier	3	4.2.1	JSON Data Types	8
1.9.10	Material Chain	3	4.3	CFX-Defined Content	9
1.9.11	Material Location	3	4.4	CFX Key Parameters	9
1.9.12	Material Package	3	4.4.1	Endpoint Identification (CFX Handle)	9
1.9.13	Material Traceability	3	4.4.2	TransactionID	9
1.9.14	Materials	3	4.5	CFX Message Envelope	9
1.9.15	Operator	3	4.6	Operator Information	10
1.9.16	Process Endpoint (Station)	3	4.7	CFX Endpoint Configuration	10
1.9.17	Production Unit	3	4.7.1	Specific CFX Endpoint Configuration Addresses	11
1.9.18	Recipe	3	5	CFX OPERATIONAL MODELING	11
1.9.19	Root	4	5.1	Equipment State Model	11
1.9.20	Setup	4	5.2	Station Fault Event Model	14
1.9.21	State (Production State)	4	5.3	Production Unit Architecture	14
1.9.22	Station (Process Endpoint)	4	5.4	Production Station Process Model	16
1.9.23	Stage	4	6	CFX TOPICS AND DYNAMIC STRUCTURES	16
1.9.24	Subassembly	4	6.1	Hierarchy of CFX Topics	17
1.9.25	Symptom	4	6.1.1	CFX Topic Support Declaration	18
1.9.26	Tool	4	6.2	CFX Message Names	18
1.9.27	Transactional Endpoint	4	6.3	CFX Structures	18
2	APPLICABLE DOCUMENTS	4			
2.1	IPC	4			
2.2	ECMA International	4			

6.4	CFX Dynamic Structures	18	7.5.4	CFX.Production.LoadingAndUnloading (Level 2)	32
6.5	CFX Messaging Requirements by Equipment Type	18	7.5.5	CFX.Production.Processing (Level 2)	32
7	CFX MESSAGES	26	7.5.6	CFX.Production.TestAndInspection (Level 2)	32
7.1	Root Level Messages	26	7.6	CFX.ResourcePerformance (Level 1)	33
7.2	CFX.InformationSystem (Level 1)	26	7.6.1	CFX.ResourcePerformance.PressInsertion (Level 2)	33
7.2.1	CFX.InformationSystem.Production Scheduling (Level 2)	26	7.6.2	CFX.ResourcePerformance.SMTPlacement (Level 2)	34
7.2.2	CFX.InformationSystem.UnitValidation (Level 2)	26	7.6.3	CFX.ResourcePerformance.SolderPaste Printing (Level 2)	34
7.2.3	CFX.InformationSystemWorkOrder Management (Level 2)	27	7.6.4	CFX.ResourcePerformance.THTPlacement (Level 2)	34
7.3	CFX.Maintenance (Level 1)	27	7.7	CFX.Sensor (Level 1)	34
7.4	CFX.Materials (Level 1)	28	7.7.1	CFX.Sensor.Identification (Level 2)	34
7.4.1	CFX.Materials.Management (Level 2)	28	7.8	CFX Message Flow	35
7.4.2	CFX.Materials.Storage (Level 2)	29	7.8.1	Production Endpoint (Station) Connection	35
7.4.3	CFX.Materials.Transport (Level 2)	29	7.8.2	Station State Transition	36
7.5	CFX.Production (Level 1)	30	7.8.3	Station Processing	37
7.5.1	CFX.Production.Application (Level 2)	31	8	CFX TECHNICAL REFERENCE	38
7.5.2	CFX.Production.Assembly (Level 2)	31	APPENDIX A	Version Updates	39
7.5.3	CFX.Production.Hermes (Level 2)	31	APPENDIX B	Acronyms and Abbreviations	44

Figures			
Figure 1-1	Version Change Tracking Example	2	
Figure 4-1	CFX Channels Between Endpoints	7	
Figure 4-2	The CFX TransactionID	9	
Figure 5-1	SEMI E10 Equipment State Model	12	
Figure 5-2	Examples of Groupings of Production Units ...	15	
Figure 5-3	Panelized Printed Board	16	
Figure 5-4	CFX Unit Locations Identified on Multiple-Board Panel	16	
Figure 5-5	CFX Production Station Process Model	16	
Figure 7-1	CFX Station Connection Example Message Flow	35	
Figure 7-2	CFX Station State Transition Example Message Flow	36	
Figure 7-3	CFX Station Processing Example Message Flow	37	
Tables			
Table 4-1	Types of CFX Messages	8	
Table 4-2	CFX – AMQP Message Properties	8	
Table 4-3	CFX Message Envelope	10	
Table 5-1	Station Event Fault Model	14	
Table 6-1	CFX Capability Requirements by Equipment Type	19	
Table 6-2	Required Messages by Capability	21	
Table 7-1	CFX.Root Messages	26	
Table 7-2	CFX.InformationSystem.Production Scheduling Messages	26	
Table 7-3	CFX.InformationSystem.UnitValidation Messages	26	
Table 7-4	CFX.InformationSystem.WorkOrder Management Messages	27	
Table 7-5	CFX.Maintenance Messages	27	
Table 7-6	CFX.Materials.Management Messages	28	
Table 7-7	CFX.Materials.Management.MSD Management Messages	28	
Table 7-8	CFX.Materials.Storage Messages	29	
Table 7-9	CFX.Materials.Transport Messages	29	
Table 7-10	CFX.Production Messages	30	
Table 7-11	CFX.Production.Application Messages	31	
Table 7-12	CFX.Production.Assembly Messages	31	
Table 7-13	CFX.Production.Assembly.PressInsertion Messages	31	
Table 7-14	CFX.Production.Hermes Messages	31	
Table 7-15	CFX.Production.LoadingAndUnloading Messages	32	
Table 7-16	CFX.Production.Processing Messages	32	
Table 7-17	CFX.Production.TestAndInspection Messages	32	
Table 7-18	CFX.ResourcePerformance Messages	33	
Table 7-19	CFX.ResourcePerformance.PressInsertion Messages	33	
Table 7-20	CFX.ResourcePerformance.SMTPlacement Messages	34	
Table 7-21	CFX.ResourcePerformance.SolderPaste Printing Messages	34	
Table 7-22	CFX.ResourcePerformance.THTPlacement Messages	34	
Table 7-23	CFX.Sensor.Identification Messages	34	

Connected Factory Exchange (IPC-CFX)

1 SCOPE

This standard establishes the requirements for the omnidirectional exchange of information between manufacturing processes and associated host systems for assembly manufacturing. This standard applies to communication between all executable processes in the manufacture of printed board assemblies – automated, semiautomated and manual – and is applicable to related mechanical assembly and transactional processes.

1.1 Purpose With the growth and acceptance of digital modeling and practices in manufacturing, the lack of a holistic Industrial Internet of Things (IIoT) standard for the transfer of information between machines, systems and processes has become a severe limitation to the growth of digitization and computerization in the electronics manufacturing industry, inhibiting technology innovations such as Industry 4.0 and Smart Factories being available to all companies in the industry, regardless of size, sector and location.

This Connected Factory Exchange (CFX) standard provides a true “plug and play” Internet of Things (IoT) communication environment throughout manufacturing, where all equipment, manufacturing processes and transactional stations can communicate with each other without the need for the development and use of bespoke interfaces. CFX-enabled equipment and solutions from different vendors work seamlessly together.

There are many types of users of this CFX standard, including equipment vendors, solution providers, in-house information technology (IT) groups, etc. The many types of data included in CFX are used in different ways depending on the application; for example, closed-loop feedback systems, live production dashboards, traceability (IPC-1782), manufacturing execution systems (MES) control, lean supply chain management, active quality management, production control, etc.

As CFX data is fully omnidirectional, any CFX endpoint connection can consume data as well as create it. As an illustration, consider the scenario in which a single machine from a certain vendor is connected in-line with other machines from different vendors. CFX messages are sent from the single machine to other machines in the line, and to host systems such as MES. The single machine can also receive CFX messages from all other machines in the line, as well as from the host systems in order to optimize the machine operation and enable the vendor of the machines to create added-value functionality, such as to support machine-specific Industry 4.0. In this way, a smart, digital, Industry 4.0 factory will be comprised of many different Industry 4.0 computerization applications, each of which can be provided by different suppliers, at the machine, line, site and even enterprise levels, all working together, sharing data seamlessly through CFX.

This CFX standard supports the concept of big data by including data of different types from across the factory, including performance, materials, resources, users, quality events, product tracking, etc., all of which can be combined to create a big-data environment. CFX, therefore, provides many kinds of added value opportunities to the whole manufacturing operation, including, for example, improving operational efficiency and productivity, quality and reliability, agility and responsiveness. This CFX standard helps organizations ensure that end users/consumers will receive products and services that meet or exceed their expectations and in the timeliest and most economically viable method.

1.2 Application of This Standard This standard defines the communication protocol and content across all assembly production processes, irrespective of type or method of operation. It can also be applied to transactional operations. There are no restrictions in terms of product classification sector, size of operation or location. Surface-mount technology (SMT) production is not required to be a part of the factory. Though intended to support all aspects of printed board production, the use of CFX can be extended downstream to include, for example, mechanical assembly, personalization, packing and shipping, as well as upstream to include, for example, electrical and mechanical subassemblies.

1.3 CFX and the Hermes Standard This CFX standard is complementary to IPC-HERMES-9852. The Hermes Standard, as an advanced, intelligent Surface Mount Equipment Manufacturers Association (SMEMA) standard replacement, provides near-instant line control, passing information about production units as they pass down the line. CFX provides vertical messaging that is complementary to Hermes.

1.4 Updates to This Standard The IPC Connected Factory Exchange Initiative Subcommittee intends to make frequent incremental revisions to this standard to support additional machines and processes. Version updates are identified by version number and the change (added, removed, etc.), so the reader can easily identify changes in each version. See Figure 1-1 for an example of this version change tracking using a portion of the CFX.Maintenance table of this standard as an example.