



IPC-8921

Requirements for Woven and Knitted Electronic Textiles (E-Textiles) Integrated with Conductive Fibers, Conductive Yarns and/or Wires

Developed by the E-Textiles Materials Subcommittee (D-72) of the
E-Textiles Committee (D-70) of IPC

Users of this publication are encouraged to participate in the development of future revisions.

Contact:

IPC

Table of Contents

1 SCOPE	1	1.14 Classification for Woven and Knitted E-Textiles	5
1.1 Purpose	1	1.14.1 Woven E-Textiles	5
1.2 Classification	1	1.14.2 Knitted E-Textiles	5
1.3 Measurement Units	1	1.15 Classification for Finishes	6
1.4 Definition of Requirements	1	1.16 Manufacturing and Processing Conditions	6
1.5 Process Control Requirements	1		
1.6 Order of Precedence	2	2 APPLICABLE DOCUMENTS	6
1.6.1 Conflict	2	2.1 IPC	6
1.6.2 Clause References	2	2.2 American Association of Textile Chemists and Colorists (AATCC)	6
1.6.3 Procurement Documentation	2	2.3 ASTM	6
1.7 Quality Conformance	2	2.4 European Committee for Standardization (CEN)	7
1.8 Material Characteristics	2	2.5 International Electrotechnical Commission (IEC)	7
1.9 Abbreviations and Acronyms	2	2.6 International Special Committee on Radio Interference	8
1.10 Terms and Definitions	2	2.7 International Organization for Standardization (ISO)	8
1.10.1 As Agreed Between User and Supplier (AABUS)	2	2.8 National Conference of Standards Laboratories (NCSL)	8
1.10.2 Cable	2	2.9 National Fire Protection Association (NFPA)	8
1.10.3 Coated (Yarn or Fabric)	2		
1.10.4 Cross-section	2	3 GENERAL REQUIREMENTS	8
1.10.5 Denier	2	3.1 Marking	8
1.10.6 Durability	3	3.2 Workmanship Requirements	8
1.10.7 Fiber	3	3.3 Storage Conditions	8
1.10.8 Finish	3	3.4 Flammability and/or Arc Rating/Class	8
1.10.9 Interlace	3	3.5 Specimen Representation	8
1.10.10 Intermeshing	3	3.6 Chemical Compliance	8
1.10.11 Knit Structure	3		
1.10.12 Knitted E-Textile	3	4 KEY CHARACTERISTICS	8
1.10.13 Natural Fiber	3	4.1 Visual Inspection for Disruptions in Functionality	8
1.10.14 Twist	3	4.2 Electrical	9
1.10.15 Warp Knit	3	4.2.1 Electrical Resistivity, Surface or Volume	9
1.10.16 Weft Knit	3	4.2.2 Electromagnetic Immunity	12
1.10.17 Wire	4	4.3 Thermal Properties and Characterization Methods	14
1.10.18 Woven E-Textile	4	4.3.1 Thermal Conductivity	14
1.10.19 Wrinkle	4	4.3.2 Coefficient of Thermal Expansion (CTE)	14
1.10.20 Yarn	4	4.3.3 T_g and Melting Point	14
1.11 Classification for Fibers	4	4.4 Volatile Organic Compounds (VOCs)	14
1.11.1 Classification for Nonconductive Fibers	4	4.4.1 Outgassing	14
1.11.2 Classification for Conductive Fibers	4		
1.12 Classification for Yarn	4	5 DURABILITY	14
1.12.1 Conductive Yarn	4	5.1 Laundering	14
1.12.2 Nonconductive Yarn	4	5.2 Dry Cleaning	14
1.13 Classification for Wires	5		
1.13.1 Cables	5		

5.3	Water	15	6.9.1	Inspection of Product for Delivery	17
5.3.1	Repellence	15	6.9.2	Sample Unit	17
5.3.2	Hydrostatic	15	6.9.3	Group A Inspection	18
5.4	Microbes	15	6.10	Statistical Process Control (SPC)	18
5.5	UV Exposure	15	6.10.1	Reduction of Quality Conformance Testing	19
5.6	Abrasion	15			
5.7	Flexing	15			
5.8	Flexible Endurance	15			
5.9	Tensile Strength (Woven)	15			
5.10	Bursting Strength (Knit)	16			
5.11	Stretch	16			
5.12	Temperature and Humidity	16			
5.13	Thermal Shock	16			
5.14	Chemical Exposure	16			
5.14.1	Saltwater (Sea)	16			
5.14.2	Acid/Aalkali	16			
5.14.3	Perspiration	16			
6	QUALITY ASSURANCE PROVISIONS	16			
6.1	Responsibility for Inspection	17			
6.2	Test Equipment and Inspection Facilities	17			
6.3	Preparation of Samples	17			
6.4	Standard Laboratory Conditions	17			
6.5	Tolerances	17			
6.6	Classification of Inspection	17			
6.7	Material Inspection	17			
6.8	Qualification Inspection	17			
6.8.1	Characterization Testing	17			
6.8.2	Frequency	17			
6.9	Quality Conformance Inspection	17			
			7	PREPARATION FOR DELIVERY	19
			7.1	Packaging	19
			8	NOTES	19
			8.1	Ordering Data	19
			Appendix A	Index of Acronyms and Abbreviations	20
				Figures	
			Figure 1-1	Warp Knit Diagram	3
			Figure 1-2	Weft Knit Diagram	3
			Figure 1-3	Woven E-Textile Diagram	4
			Figure 4-1	Schematic Diagram of a Four-Point Probe	10
			Figure 4-2	Equivalent Circuit Diagram of a Four-Point Probe	10
			Figure 4-3	Probe Positioning and Dimensions for a Rectangular Sample	11
			Figure 4-4	E-Textile Ports	13
			Figure 4-5	Resistor-Capacitor (RC) Element of the Artificial Hand	14
				Tables	
			Table 4-1	Geometric Factors in Four-Point Resistivity Measurement	11
			Table 4-2	Thick Sample Correction Factors	12
			Table 6-1	Test Method Frequency	18

Requirements for Woven and Knitted Electronic Textiles (E-Textiles) Integrated with Conductive Fibers, Conductive Yarns and/or Wires

1 SCOPE

This standard establishes the classification system as well as qualification and quality conformance requirements affecting electrical/electronic performance of woven and knitted electronic textiles (e-textiles) integrated with conductive fibers, conductive yarns and/or wires.

This standard does not cover requirements for other types of e-textiles (e.g., nonwovens, coated/plated fabric, laminated, printed, braided, embroidered, etc.). This standard also does not cover non-electronically integrated textiles or nonconductive fibers or yarns.

1.1 Purpose The purpose of this standard is to provide and define test methods and guidance for key characteristics and durability of woven and knitted e-textiles integrated with conductive fibers, conductive yarns and/or wires.

1.2 Classification IPC standards recognize that electrical and electronic assemblies are subject to classifications by intended end-item use. Three general end-product classes have been established to reflect differences in manufacturability, complexity, functional performance requirements, and verification (inspection/test) frequency. It should be recognized that there may be overlaps of equipment between classes.

CLASS 1 General Electronic Products

Includes products suitable for applications where the major requirement is function of the completed assembly.

CLASS 2 Dedicated Service Electronic Products

Includes products where continued performance and extended life is required, and for which uninterrupted service is desired but not critical. Typically, the end-use environment would not cause failures.

CLASS 3 High Performance/Harsh Environment Electronic Products

Includes products where continued high performance or performance-on-demand is critical, equipment downtime cannot be tolerated, end-use environment may be uncommonly harsh, and the equipment must function when required, such as life support or other critical systems.

1.3 Measurement Units All dimensions and tolerances in this specification are expressed in hard SI (metric) units. Users of this specification are expected to use metric dimensions. All dimensions ≥ 1.0 mm will be expressed in mm. All dimensions < 1.0 mm will be expressed in μm .

1.4 Definition of Requirements The words **shall** or **shall not** are used in the text of this document wherever there is a requirement for materials, preparation, process control or acceptance.

The word **should** reflects recommendations and is used to reflect general industry practices and procedures for guidance only.

Line drawings and illustrations are depicted herein to assist in the interpretation of the written requirements of this standard. The text takes precedence over the figures.

1.5 Process Control Requirements The primary goal of process control is to continually reduce variation in the processes, products or services to provide products or processes meeting or exceeding user requirements. Process control tools such as IPC-9191 or other user-approved system may be used as guidelines for implementing process control.

A documented process control system, if established, **shall** define process control and corrective action limits.

This may or may not be a statistical process control (SPC) system. The use of SPC is optional and should be based on factors such as design stability, lot size, production quantities and the needs of the manufacturer (see 6.10).

When a decision or requirement is to use a documented process control system, failure to implement process corrective action and/or the use of continually ineffective corrective actions **shall** be grounds for disapproval of the process and associated documentation.