



Standards

Certification
Education & Training
Publishing
Conferences & Exhibits

Setting the Standard for Automation™

AMERICAN NATIONAL STANDARD

ANSI/ISA-96.03.01-2019

Guidelines for the Specification of Heavy Duty Pneumatically Powered Quarter Turn Scotch Yoke Valve Actuators

Approved 3 February 2020

NOTICE OF COPYRIGHT

This is a copyright document and may not be copied or distributed in any form or manner without the permission of ISA. This copy of the document was made for the sole use of the person to whom ISA provided it and is subject to the restrictions stated in ISA's license to that person. It may not be provided to any other person in print, electronic, or any other form. Violations of ISA's copyright will be prosecuted to the fullest extent of the law and may result in substantial civil and criminal penalties.

ANSI/ISA-96.03.01-2019

Guidelines for the Specification of Heavy Duty Pneumatically Powered Quarter Turn Scotch Yoke Valve Actuators

ISBN: 978-1-64331-074-9

Copyright © 2019 by ISA. All rights reserved. Not for resale. Printed in the United States of America. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means (electronic mechanical, photocopying, recording, or otherwise), without the prior written permission of the Publisher.

ISA
67 T.W. Alexander Drive
P.O. Box 12277
Research Triangle Park, North Carolina 27709

PREFACE

This preface, as well as all footnotes and annexes, is included for information purposes and is not part of ANSI/ISA-96.03-01-2019.

This document has been prepared as part of the service of ISA toward a goal of uniformity in the field of instrumentation. To be of real value, this document should not be static but should be subject to periodic review. Toward this end, the Society welcomes all comments and criticisms and asks that they be addressed to the Secretary, Standards and Practices Board; ISA; 67 T.W. Alexander Drive; P. O. Box 12277; Research Triangle Park, NC 27709; Telephone (919) 549-8411; Fax (919) 549-8288; E-mail: standards@isa.org.

The ISA Standards and Practices Department is aware of the growing need for attention to the metric system of units in general, and the International System of Units (SI) in particular, in the preparation of instrumentation standards. The Department is further aware of the benefits to USA users of ISA standards of incorporating suitable references to the SI (and the metric system) in their business and professional dealings with other countries. Toward this end, this Department will endeavor to introduce SI-acceptable metric units in all new and revised standards, recommended practices, and technical reports to the greatest extent possible. IEEE/ASTM SI 10, *American National Standard for Metric Practice*, and future revisions, will be the reference guide for definitions, symbols, abbreviations, and conversion factors.

It is the policy of ISA to encourage and welcome the participation of all concerned individuals and interests in the development of ISA standards, recommended practices, and technical reports. Participation in the ISA standards-making process by an individual in no way constitutes endorsement by the employer of that individual, of ISA, or of any of the standards, recommended practices, and technical reports that ISA develops.

CAUTION — ISA DOES NOT TAKE ANY POSITION WITH RESPECT TO THE EXISTENCE OR VALIDITY OF ANY PATENT RIGHTS ASSERTED IN CONNECTION WITH THIS DOCUMENT, AND ISA DISCLAIMS LIABILITY FOR THE INFRINGEMENT OF ANY PATENT RESULTING FROM THE USE OF THIS DOCUMENT. USERS ARE ADVISED THAT DETERMINATION OF THE VALIDITY OF ANY PATENT RIGHTS, AND THE RISK OF INFRINGEMENT OF SUCH RIGHTS, IS ENTIRELY THEIR OWN RESPONSIBILITY.

PURSUANT TO ISA'S PATENT POLICY, ONE OR MORE PATENT HOLDERS OR PATENT APPLICANTS MAY HAVE DISCLOSED PATENTS THAT COULD BE INFRINGED BY USE OF THIS DOCUMENT AND EXECUTED A LETTER OF ASSURANCE COMMITTING TO THE GRANTING OF A LICENSE ON A WORLDWIDE, NONDISCRIMINATORY BASIS, WITH A FAIR AND REASONABLE ROYALTY RATE AND FAIR AND REASONABLE TERMS AND CONDITIONS. FOR MORE INFORMATION ON SUCH DISCLOSURES AND LETTERS OF ASSURANCE, CONTACT ISA OR VISIT WWW.ISA.ORG/STANDARDSPATENTS.

OTHER PATENTS OR PATENT CLAIMS MAY EXIST FOR WHICH A DISCLOSURE OR LETTER OF ASSURANCE HAS NOT BEEN RECEIVED. ISA IS NOT RESPONSIBLE FOR IDENTIFYING PATENTS OR PATENT APPLICATIONS FOR WHICH A LICENSE MAY BE REQUIRED, FOR CONDUCTING INQUIRIES INTO THE LEGAL VALIDITY OR SCOPE OF PATENTS, OR DETERMINING WHETHER ANY LICENSING TERMS OR CONDITIONS PROVIDED IN CONNECTION WITH SUBMISSION OF A LETTER OF ASSURANCE, IF ANY, OR IN ANY LICENSING AGREEMENTS ARE REASONABLE OR NONDISCRIMINATORY.

ISA REQUESTS THAT ANYONE REVIEWING THIS DOCUMENT WHO IS AWARE OF ANY PATENTS THAT MAY IMPACT IMPLEMENTATION OF THE DOCUMENT NOTIFY THE ISA STANDARDS AND PRACTICES DEPARTMENT OF THE PATENT AND ITS OWNER.

ADDITIONALLY, THE USE OF THIS DOCUMENT MAY INVOLVE HAZARDOUS MATERIALS, OPERATIONS, OR EQUIPMENT. THE DOCUMENT CANNOT ANTICIPATE ALL POSSIBLE APPLICATIONS OR ADDRESS ALL POSSIBLE SAFETY ISSUES ASSOCIATED WITH USE IN HAZARDOUS CONDITIONS. THE USER OF THIS DOCUMENT MUST EXERCISE SOUND PROFESSIONAL JUDGMENT CONCERNING ITS USE AND APPLICABILITY UNDER THE USER'S PARTICULAR CIRCUMSTANCES. THE USER MUST ALSO CONSIDER THE APPLICABILITY OF ANY GOVERNMENTAL REGULATORY LIMITATIONS AND ESTABLISHED SAFETY AND HEALTH PRACTICES BEFORE IMPLEMENTING THIS DOCUMENT.

THE USER OF THIS DOCUMENT SHOULD BE AWARE THAT THIS DOCUMENT MAY BE AFFECTED BY ELECTRONIC SECURITY ISSUES. THE COMMITTEE HAS NOT YET ADDRESSED THE POTENTIAL ISSUES IN THIS VERSION.

ISA (www.isa.org) is a nonprofit professional association that sets the standard for those who apply engineering and technology to improve the management, safety, and cybersecurity of modern automation and control systems used across industry and critical infrastructure. Founded in 1945, ISA develops widely used global standards; certifies industry professionals; provides education and training; publishes books and technical articles; hosts conferences and exhibits; and provides networking and career development programs for its 40,000 members and 400,000 customers around the world.

ISA owns Automation.com, a leading online publisher of automation-related content, and is the founding sponsor of The Automation Federation (www.automationfederation.org), an association of nonprofit organizations serving as "The Voice of Automation." Through a wholly owned subsidiary, ISA bridges the gap between standards and their implementation with the ISA Security Compliance Institute (www.isasecure.org) and the ISA Wireless Compliance Institute (www.isa100wci.org).

The following people served as members of the ISA96.03 Working Group.

NAME	COMPANY
V. Mezzano, Chair	Fluor Corp.
W. Weidman, Managing Director	Consultant
M. Bober	SPX Flow Technology
S. Boyle	Consultant
K. Enos	Rexa, Inc.
E. Holtgraver	QTRCO Inc.
V. Kahnonen	Metso
G. Liu	Consultant
A. Michelson	Sunbelt Supply
S. Samy	IMI CCI
K. Walker	Flowserve Corp.
F. Washburn	Flowserve Corp.
J. Young	The Dow Chemical Co.

The following people served as members of the ISA96 Committee.

NAME	COMPANY
V. Mezzano, Chairman	Fluor Corp.
W. Weidman, Managing Director	Consultant
D. Anderson	Score Diagnostics Ltd.
M. Bober	SPX Flow Technology
S. Boyle	Consultant
K. Enos	Rexa, Inc.
P. Flanders	ATV HIPPS
S. Hale	MRC Global

L. Hilliard	Puffer Sweiven LP
E. Holtgraver	QTRCO Inc.
A. Izzeldin	Petronas
D. Leese	FloWorks International
G. Liu	Consultant
S. Meunier	Emerson
A. Michelson	Sunbelt Supply
S. Samy	IMI CCI
W. Tatum	Westlock Controls
F. Washburn	Flowserve Corp.
L. Winkel	Flowserve Corp.
Y. Yermanos	Ecopetrol S.A.
J. Young	The Dow Chemical Co.

This standard was approved for publication by the ISA Standards and Practices Board on 30 October 2019.

NAME	COMPANY
C. Monchinski, Vice President	Automated Control Concepts Inc.
D. Bartusiak	ExxonMobil Research & Engineering
D. Brandl	BR&L Consulting
P. Brett	Honeywell Inc.
E. Cosman	OIT Concepts, LLC
D. Dunn	Waldemar S. Nelson & Co.
J. Federlein	Federlein & Associates LLC
B. Fitzpatrick	Wood PLC
J-P Hauet	Hauet.com
D. Lee	Process Control Consultant
G. Lehmann	AECOM
T. McAvinew	Consultant
V. Mezzano	Fluor Corp.
G. Nasby	City of Guelph Water Services
M. Nixon	Emerson Process Management
D. Reed	Rockwell Automation
N. Sands	DuPont
H. Sasajima	Fieldcomm Group Inc. Asia-Pacific
H. Storey	Herman Storey Consulting
I. Verhappen	Industrial Automation Networks
D. Visnich	Burns & McDonnell
W. Weidman	Consultant
J. Weiss	Applied Control Solutions LLC
M. Wilkins	Yokogawa UK Ltd.
D. Zetterberg	Chevron Energy Technology Co.

This page intentionally left blank.

Contents

1	Scope	- 9 -
2	Purpose	- 9 -
3	Definitions	- 9 -
4	Design requirements	- 13 -
5	Construction.....	- 14 -
5.1	Center body	- 14 -
5.2	Cylinder module	- 14 -
6	Manual overrides	- 15 -
7	Corrosion protection.....	- 15 -
8	Valve actuator mounting hardware	- 15 -
9	Testing.....	- 16 -
10	Actuator selection (sizing)	- 16 -
10.1	Actuator sizing	- 16 -
10.2	Operation (assuming an actuator is operating a CW to close valve)	- 17 -
10.3	Safety factor	- 17 -
10.4	Other considerations	- 18 -
11	Marking/Tagging	- 18 -
11.1	Marking on actuators	- 18 -
12	Documentation	- 19 -
13	User-defined requirements	- 19 -

This page intentionally left blank.

1 Scope

This standard provides general requirements for the development of specifications for pneumatic scotch yoke actuators.

This document applies to actuators with a maximum allowable operating pressure (MAOP) of 250 psig with a compressed gas (i.e., instrument air).

2 Purpose

The purpose of this standard is to provide guidance to assist the user in specifying pneumatic scotch yoke actuators.

3 Definitions

For the purpose of the definitions below it is assumed that yoke rotation at start stroke is clockwise when viewed from the top of the actuator (i.e., looking down at valve stem).

3.1

scotch yoke actuator

an actuator that employs a scotch yoke mechanism to convert the linear motion of a piston into part-turn rotational motion

3.2

scotch yoke mechanism

a device that employs a sliding pin in a yoke such that the effective moment arm is constantly changing. The moment arm is longest at the start and end of each part-turn motion.

3.2.1

symmetrical scotch yoke

symmetric yokes allow for produced equal torque at both the start (break) and end positions




Figure 1 – Symmetric yoke

3.2.2

canted scotch yoke

canted yokes are a variation where the actuator is biased to deliver more torque at one extremity of stroke. Use of canted torque arms can reduce the cost, weight, and size of the actuator, where the valve torque demand is highest at one end of stroke (i.e., break to open and/or reseal to close).