Second edition 2012-12-01

Mechanical vibration and shock — Mechanical impedance of the human hand-arm system at the driving point

Vibrations et chocs mécaniques — Impédance mécanique du système main-bras au point d'entrée





COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Con	tent	S	Page
Forev	vord		iv
Intro	ductio	n	v
1	Scop	e	1
2	Term	is and definitions	2
3	Mech	anical impedance of the hand-arm system at the driving point	2
4	Appl	icability of values of impedance	8
5	Appl 5.1	ications General	10 10
	5.2	Evaluation of the transmissibility of resilient materials when loaded by the hand-	10
	5.3	arm system Models of the hand-arm system	
	5.4	Estimation of power absorbed in the hand-arm system and its frequency dependence	e11
Anne	x A (no hand	rmative) Reference values for the z_h-component of the mechanical impedance of -arm system	the 12
Anne	x B (in	formative) Model 1	14
Annex C (informative) Model 2		19	
Annex D (informative) Model 3			24
Annex E (informative) Model of the gloved hand-arm system			29
Anne	x F (inf powe	Formative) Examples of frequency dependence derived from vibration	32
Anne	x G (in	formative) Measurement of the mechanical impedance of the hand-arm system	
Biblic	ograph	y	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 10068 was prepared by Technical Committee ISO/TC 108, *Mechanical vibration, shock and condition monitoring*, Subcommittee SC 4, *Human exposure to mechanical vibration and shock*.

This second edition cancels and replaces the first edition (ISO 10068:1998), of which it constitutes a technical revision. The second edition includes the results of measurements of hand-arm impedance conducted since publication of the first edition, and it includes new models for apparent mass and mechanical impedance. The models now possess anatomic compatibility, and identify components for the fingers, palm, wrist and arm, and upper body. A model of the hand-arm system is provided when a glove is worn to estimate the transmissibility of vibration from a vibrating handle to the surface of the hand. The frequency dependency of the vibration power absorbed by the hand-arm system and by structures within the hand-arm system (i.e. fingers, palm and wrist, and arm) is also included. Information on methods for measuring the mechanical impedance of the hand-arm system is also provided in an annex.

Introduction

The mechanical impedance of the human hand-arm system at the driving point provides a measure of the overall biodynamic properties of the hand-arm system in specified conditions. When the hands are coupled to a vibrating tool or machine, the dynamic behaviour of the tool or machine could be affected by the biodynamic properties of the hand-arm system. Therefore, the mechanical impedance can be used to help design or develop:

- a) power tools, and tool handles;
- b) vibration-reducing and protective devices;
- c) testing apparatus with which to measure the handle vibration of power tools.

Values of the mechanical impedance can be used to establish mechanical-equivalent models of the handarm system. The models can be used to analyse the vibration of tools and anti-vibration devices, and to guide the construction of testing apparatus. The models can also be used to estimate biodynamic responses such as vibration power absorption and biodynamic forces acting at the hand-tool interfaces. Such knowledge can be used to help understand the mechanisms of vibration-induced disorders and discomfort, and to help develop frequency weightings for assessing these effects. The establishment of typical values for human hand-arm impedance will foster these applications.

The response of the hand-arm system to vibration depends not only on the mechanical properties of the hand and arm, but also on the coupling between the hand and the vibrating surface. The major factors that could influence the response are as follows:

- direction of vibration with respect to the hand-arm system;
- geometry of the object grasped;
- forces exerted by the hand on the object;
- hand and arm postures;
- individual differences, such as tissue properties and anthropometric characteristics of the hand-arm system;
- vibration magnitude, because of the nonlinear properties of tissues.

The forces exerted by the hand are usually described in terms of the grip force and feed force. The latter is often called the "thrust", "push" or "press" force.

In this International Standard, typical values for the mechanical impedance of the hand-arm system measured at the driving point of one bare hand are provided. They have been derived from the results of impedance measurements performed on groups of live male subjects by different investigators. Insufficient data are available from independent sources to specify hand-arm impedances for females.

There are large differences between the mean values of impedance reported in studies conducted independently, under nominally equivalent conditions. The variations have dictated the form in which the standardized male hand-arm impedance is presented. The most probable values of impedance modulus and phase are defined, as a function of frequency, by upper and lower envelopes, which encompass the mean values of all accepted data sets at each frequency. The envelopes have been constructed from segmental cubic spline functions, and define, at each frequency, the range of accepted values of the male hand-arm impedance. The mean of the accepted data sets, and standard deviation of the mean, are defined as a function of frequency, and represent the target values for all applications of this International Standard.

No impedance modulus or phase presented as a function of frequency in this International Standard corresponds precisely to the mean value measured in a single investigation involving human subjects, at all frequencies.