

This is a preview of "ISO 1070:2018". [Click here to purchase the full version from the ANSI store.](#)

Third edition
2018-11

Hydrometry — Slope-area method

Hydrometrie — Methode de la pente de la ligne d'eau



Reference number
ISO 1070:2018(E)

© ISO 2018



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

This is a preview of "ISO 1070:2018". Click here to purchase the full version from the ANSI store.

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle of the method of measurement	1
5 Selection and demarcation of site	3
5.1 Initial survey of site.....	3
5.2 Selection of site.....	3
5.3 Demarcation of site.....	4
6 Measurement of slope	4
6.1 High-water marks.....	4
6.2 Crest-stage gauges.....	4
6.3 Pressure transmitters.....	4
6.4 Reference gauge.....	4
7 Determination of slope	5
8 Cross sections of a stream	5
8.1 Number and location of cross sections.....	5
8.2 Measurement of cross-sectional profiles.....	5
9 Computation of discharge	5
9.1 General.....	5
9.2 Uniform cross sections.....	6
9.2.1 General.....	6
9.2.2 Determination of the mean cross-sectional area and mean wetted perimeter of the reach.....	6
9.2.3 Determination of hydraulic radius.....	6
9.2.4 Determination of the mean velocity in the reach.....	7
9.3 Non-uniform cross sections (2-cross-section formulation).....	8
9.3.1 General.....	8
9.3.2 Computation of conveyance.....	8
9.3.3 Evaluation of the friction slope.....	9
9.4 Composite cross sections.....	11
9.5 Computation of discharge using three or more cross sections.....	12
9.6 State of flow.....	13
10 Alternative methods to estimate conveyance	14
10.1 General.....	14
10.2 Divided channel method.....	14
10.3 Conveyance estimation system.....	14
11 Uncertainty in flow measurement	14
11.1 Definition of uncertainty.....	14
11.2 Sources of uncertainty for a uniform reach.....	15
11.2.1 General considerations.....	15
11.2.2 Uncertainty of the mean cross-sectional area.....	15
11.2.3 Uncertainty in the calculation of the mean wetted perimeter.....	15
11.2.4 Uncertainties in determination of the friction slope.....	16
11.2.5 Uncertainty due to the choice of the rugosity coefficient.....	16
11.2.6 Overall uncertainty in the measurement of discharge.....	16
Annex A (informative) Approximate value of coefficients n and C for open channels	17
Annex B (informative) Approximate value of Strickler-coefficients k_{St} for natural streams	20

This is a preview of "ISO 1070:2018". [Click here to purchase the full version from the ANSI store.](#)

Annex C (informative) US Soil Conservation Service method of estimating Manning's n	22
Annex D (informative) Conveyance estimation system	24
Bibliography	26

This is a preview of "ISO 1070:2018". Click here to purchase the full version from the ANSI store.

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 113, *Hydrometry*.

This third edition cancels and replaces the second edition (ISO 1070:1992), which has been technically revised. It also incorporates the amendment ISO 1070:1992/Amd.1:1997. The main changes compared to the previous edition are as follows:

- the document has been reorganized to first present two-section computations followed by multiple reach computations;
- a third governing formula has been added;
- three annexes have been added.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The slope–area method is an indirect method of determining discharge in open channels when direct measurement of the flow is not possible because of the timing of the flow or because the site is too hazardous for direct measurement techniques. The method is usually used to document the discharge of a flood and to extend the stage–discharge rating of a stream flow gauging station above direct measurements of discharge. The method can also be used at locations where bridge, cableway or boat measurements are not possible. Water discharge is computed using flow resistance formulae based on channel characteristics, water-surface profiles, and a roughness or friction coefficient.