

INTERNATIONAL ISO
STANDARDS

This is a preview of "ISO 11274:1998". [Click here to purchase the full version from the ANSI store.](#)

First edition
1998-07-01

Soil quality — Determination of the water-retention characteristic — Laboratory methods

Qualité du sol — Détermination de la caractéristique de la rétention en eau — Méthodes de laboratoire



Reference number
ISO 11274:1998(E)

Contents

Page

1	Scope	1
2	Definitions	1
3	Guidelines for choice of method	2
4	Sampling	3
5	Determination of the soil water characteristic using sand, kaolin and ceramic suction tables	5
6	Determination of soil water characteristic using a porous plate and burette	8
7	Determination of soil water characteristic by pressure plate extractor	11
8	Determination of soil water characteristic using pressure membrane cells	13
9	Precision	15
Annexes		
	A (informative) Construction of suction tables	16
	B (informative) Bibliography	20

© ISO 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet iso@iso.ch

Printed in Switzerland

This is a preview of "ISO 11274:1998". [Click here to purchase the full version from the ANSI store.](#)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 11274 was prepared by Technical Committee ISO/TC 190, *Soil quality*, Subcommittee SC 5, *Physical methods*.

Annexes A and B of this International Standard are for information only.

This is a preview of "ISO 11274:1998". [Click here to purchase the full version from the ANSI store.](#)

Introduction

Soil water content and matric pressure are related to each other and determine the water-retention characteristics of a soil. Soil water which is in equilibrium with free water is at zero matric pressure (or suction) and the soil is saturated. As the soil dries, matric pressure decreases (i.e. becomes more negative), and the largest pores empty of water. Progressive decreases in matric pressure will continue to empty finer pores until eventually water is held in only the finest pores. Not only is water removed from soil pores, but the films of water held around soil particles are reduced in thickness. Therefore a decreasing matric pressure is associated with a decreasing soil water content [5], [6]. Laboratory or field measurements of these two parameters can be made and the relationship plotted as a curve, called the soil water-retention characteristic. The relationship extends from saturated soil (approximately 0 kPa) to oven-dry soil (about -10^6 kPa).

The soil water-retention characteristic is different for each soil type. The shape and position of the curve relative to the axes depend on soil properties such as texture, density and hysteresis associated with the wetting and drying history. Individual points on the water-retention characteristic may be determined for specific purposes.

The results obtained using these methods can be used, for example:

- to provide an assessment of the equivalent pore size distribution (e.g. identification of macro- and micropores);
- to determine indices of plant-available water in the soil and to classify soil accordingly (e.g. for irrigation purposes);
- to determine the drainable pore space (e.g. for drainage design, pollution risk assessments);
- to monitor changes in the structure of a soil (caused by e.g. tillage, compaction or addition of organic matter or synthetic soil conditioners);
- to ascertain the relationship between the negative matric pressure and other soil physical properties (e.g. hydraulic conductivity, thermal conductivity);
- to determine water content at specific negative matric pressures (e.g. for microbiological degradation studies);
- to estimate other soil physical properties (e.g. hydraulic conductivity).