First edition 2010-05-15

Gas cylinders — 17E and 25E taper threads for connection of valves to gas cylinders —

Part 1: **Specifications**

Bouteilles à gaz — Filetages coniques 17E et 25E pour le raccordement des robinets sur les bouteilles à gaz —

Partie 1: Spécifications



Reference number ISO 11363-1:2010(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Cor	ntents	Page
Forev	word	iv
Intro	duction	V
1	Scope	1
2	Terms and definitions	1
_ 2.1	General	1
2.2	Terms relating to cones	
2.3	Terms relating to diameter	2
2.4	Terms relating to reference	3
3	Requirements	4
3.1	Thread handedness	
3.2	Taper	
3.3	Thread profile	4
3.4	Pitch, P	4
3.5	Dimensions	
4	Thread end finish	7
5	Marking	8
Biblio	ography	9

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 11363-1 was prepared by Technical Committee ISO/TC 58, *Gas cylinders*, Subcommittee SC 2, *Cylinder fittings*.

This first edition of ISO 11363-1 cancels and replaces ISO 10920:1997 and ISO 11116-1:1999.

ISO 11363 consists of the following parts, under the general title *Gas cylinders* — *17E and 25E taper threads for connection of valves to gas cylinders*:

- Part 1: Specifications
- Part 2: Inspection gauges

Introduction

Gas cylinders intended to contain compressed, liquefied or dissolved gas under pressure are fitted with accessories to allow release and refilling of gas. Hereinafter, the term "valve" will apply to such accessories.

The connection between cylinder and valve is obtained by assembly of two taper-threads (an external one on the valve stem and an internal one in the cylinder neck), both having the same nominal taper, thread pitch and thread profile.