Third edition 2005-02-15

# Road vehicles — Vehicle test methods for electrical disturbances from narrowband radiated electromagnetic energy —

## Part 1:

# General principles and terminology

Véhicules routiers — Méthodes d'essai d'un véhicule soumis à des perturbations électriques par rayonnement d'énergie électromagnétique en bande étroite —

Partie 1:Principes généraux et terminologie



Reference number ISO 11451-1:2005(E)

#### **PDF** disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

#### © ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Con	itents	Page
Forev	vord	iv
Introduction		v
1	Scope	1
2	Terms and definitions	1
3	General aim and practical use	4
4	General test conditions	5
5	Instrumentation — Test signal quality	8
6	Test procedure	8
Annex A (normative) Function performance status classification (FPSC)		11
Anne	x B (informative) Constant peak test level	14
Ribliography		17

## **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 11451-1 was prepared by Technical Committee ISO/TC 22, Road vehicles, Subcommittee SC 3, Electrical and electronic equipment.

This third edition cancels and replaces the second edition (ISO 11451-1:2001), which has been technically revised.

ISO 11451 consists of the following parts, under the general title *Road vehicles* — *Vehicle test methods for electrical disturbances from narrowband radiated electromagnetic energy:* 

- Part 1: General principles and terminology
- Part 2: Off-vehicle radiation source
- Part 3: On-board transmitter simulation
- Part 4: Bulk current injection (BCI)

### Introduction

In recent years, an increasing number of electronic devices for controlling, monitoring and displaying a variety of functions have been introduced into vehicle designs. It is necessary to consider the electrical and electromagnetic environment in which these devices operate.

Electrical and radio-frequency disturbances occur during the normal operation of many items of motor vehicle equipment. They are generated over a wide frequency range with various electrical characteristics and can be distributed to on-board electronic devices and systems by conduction, radiation or both. Narrowband signals generated from sources on or off the vehicle can also be coupled into the electrical and electronic system, affecting the normal performance of electronic devices. Such sources of narrowband electromagnetic disturbances include mobile radios and broadcast transmitters.

The characteristics of the immunity of a vehicle to radiated disturbances have to be established. ISO 11451 provides various test methods for the evaluation of vehicle immunity characteristics. Not all methods need be used for a given vehicle.

ISO 11451 is not intended as a product specification and cannot function as one (see A.1). Therefore, no specific values for the test severity level are given.

Annex A of this part of ISO 11451 specifies a general method for function performance status classification (FPSC), while Annex B explains the principle of constant peak test level. Typical severity levels are included in an annex of each of the other parts of ISO 11451.

Protection from potential disturbances needs to be considered in a total system validation, and this can be achieved using the various parts of ISO 11451.

NOTE Immunity measurements of complete vehicles are generally able to be carried out only by the vehicle manufacturer, owing to, for example, high costs of absorber-lined shielded enclosures, the desire to preserve the secrecy of prototypes or a large number of different vehicle models. ISO 11452 specifies test methods for the analysis of component immunity, which are better suited for supplier use.