

This is a preview of "ISO 12219-2:2012". [Click here to purchase the full version from the ANSI store.](#)

First edition
2012-06-15

Interior air of road vehicles —

Part 2:

Screening method for the determination of the emissions of volatile organic compounds from vehicle interior parts and materials — Bag method

Air intérieur des véhicules routiers —

*Partie 2: Méthode de criblage pour la détermination des émissions de
composés organiques volatils des parties et des matériaux intérieurs
des véhicules — Méthode du sac*



Reference number
ISO 12219-2:2012(E)

© ISO 2012

This is a preview of "ISO 12219-2:2012". [Click here to purchase the full version from the ANSI store.](#)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

This is a preview of "ISO 12219-2:2012". Click here to purchase the full version from the ANSI store.

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	2
5 Apparatus and materials	2
6 Test conditions	4
6.1 General	4
6.2 Test specimen size	4
6.3 Curing conditions (storage period and storage conditions)	4
6.4 Heating temperature	4
6.5 Heating time	4
6.6 Gas amount to be filled in a sampling bag	4
7 Verification of test conditions	5
7.1 Monitoring of test conditions	5
7.2 Recovery rate	5
8 Test method	5
8.1 Test equipment	5
8.2 Preparation for testing	5
8.3 Emission test	5
8.4 Gas collection	6
9 Analytical procedures	6
9.1 Analysis of VOCs	6
9.2 Analysis of formaldehyde and other carbonyl compounds	6
10 Calculation of sampling bag values	7
11 Test report	7
12 Quality assurance/quality control	8
Annex A (informative) General procedures for preparation and storage of test specimens	11
Annex B (informative) Additional information on test report and recovery rate	12
Bibliography	14

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12219-2 was prepared by Technical Committee ISO/TC 146, *Air quality*, Subcommittee SC 6, *Indoor air*, in collaboration with Technical Committee ISO/TC 22, *Road vehicles*.

ISO 12219 consists of the following parts, under the general title *Interior air of road vehicles*:

- *Part 1: Whole vehicle test chamber — Specification and method for the determination of volatile organic compounds in cabin interiors*
- *Part 2: Screening method for the determination of the emissions of volatile organic compounds from vehicle interior parts and materials — Bag method*
- *Part 3 Screening method for the determination of the emissions of volatile organic compounds from vehicle interior parts and materials — Micro-scale chamber method*
- *Part 4: Screening method for the determination of the emissions of volatile organic compounds from vehicle interior parts and materials — Small chamber method*

The following part is under preparation:

- *Part 5: Screening method for the determination of the emissions of volatile organic compounds from vehicle interior parts and materials — Static chamber method*

This is a preview of "ISO 12219-2:2012". [Click here to purchase the full version from the ANSI store.](#)

Introduction

Volatile organic compounds (VOCs) are widely used in industry and may be emitted by many everyday products and materials. They have attracted much attention in recent years because of their impact on indoor air quality. After homes and workplaces, people spend a lot of time in their vehicles. It is important to determine the material emissions of interior parts and to reduce them to an acceptable level, if required. Therefore it is necessary to obtain comprehensive and reliable information about the types of organic compounds in the interior air of vehicles and also their concentrations.

This part of ISO 12219 outlines the sampling bag test method for the screening of VOCs, formaldehyde and other carbonyl compounds which diffuse from vehicle interior parts into the air inside road vehicles.

Measuring VOCs from vehicle interior parts can be performed in several ways and the approach selected depends upon the desired outcome and the material type. For example, to obtain diffusion data from complete assemblies (e.g. instrument panel, seat etc.) it is necessary to employ chambers / bags that have sufficient volume to house the complete assembly. Meanwhile, to obtain diffusion data from representative samples of homogeneous vehicle interior materials, the micro-scale chamber method can be chosen.

Each measurement method such as bag/micro-scale chamber/small-chamber sampling offers a complementary approach.

ISO 16000-3, ISO 16000-5,^[2] ISO 16000-6, ISO 16000-9,^[3] ISO 16000-10,^[4] ISO 16000-11,^[5] ISO 16000-24,^[6] ISO 16000-25,^[7] as well as ISO 16017-1 and ISO 16017-2^[8] also focus on VOC measurements.