

This is a preview of "ISO 12780-2:2011". [Click here to purchase the full version from the ANSI store.](#)

First edition
2011-04-01

Geometrical product specifications (GPS) — Straightness —

Part 2: Specification operators

*Spécification géométrique des produits (GPS) — Rectitude —
Partie 2: Opérateurs de spécification*



Reference number
ISO 12780-2:2011(E)

© ISO 2011

This is a preview of "ISO 12780-2:2011". [Click here to purchase the full version from the ANSI store.](#)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2011

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

This is a preview of "ISO 12780-2:2011". Click here to purchase the full version from the ANSI store.

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Complete specification operator	1
4.1 General	1
4.2 Transmission band	2
4.3 Probing system	3
5 Compliance with specification	3
Annex A (informative) Harmonic content of a nominally straight workpiece	4
Annex B (informative) Relationship to the GPS matrix model	6
Bibliography	8

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12780-2 was prepared by Technical Committee ISO/TC 213, *Dimensional and geometrical product specifications and verification*.

This first edition of ISO 12780-2 cancels and replaces ISO/TS 12780-2:2003, which has been technically revised.

ISO 12780 consists of the following parts, under the general title *Geometrical product specifications (GPS) — Straightness*:

- *Part 1: Vocabulary and parameters of straightness*
- *Part 2: Specification operators*

This is a preview of "ISO 12780-2:2011". [Click here to purchase the full version from the ANSI store.](#)

Introduction

This part of ISO 12780 is a geometrical product specification (GPS) standard and is to be regarded as a general GPS standard (see ISO/TR 14638). It influences chain link 3 of the chain of standards on form of line independent of datum.

The ISO/GPS Masterplan given in ISO/TR 14638 gives an overview of the ISO/GPS system of which this document is a part. The fundamental rules of ISO/GPS given in ISO 8015 apply to this document and the default decision rules given in ISO 14253-1 apply to specifications made in accordance with this document, unless otherwise indicated.

For more detailed information on the relationship of this part of ISO 12780 to other standards and the GPS matrix model, see Annex B.

This part of ISO 12780 specifies the specification operators according to ISO 17450-2 for straightness of integral features.

This part of ISO 12780 does not specify defaults for filter cut-off, probe tip radius and method of association (reference line). This means that it is necessary for a straightness specification to explicitly state which values are to be used for these specification operations in order for it to be unique.

Consequently, if a specification does not explicitly state which values are to be used for one or more of these operators, the specification is ambiguous (see ISO 17450-2) and a supplier can use any value for the operator(s) not specified when proving conformance.

Extracting data always involves applying a certain filtering process. An additional filtering of the extracted data might or might not be applied. This additional filter can be a mean line filter (Gaussian, spline, wavelet, etc.) or a non-linear filter (e.g. morphological filter). The type of filtering influences the definition of straightness and the specification operators and, therefore, needs to be stated unambiguously.

NOTE 1 Stylus filtering is not sufficient on its own to smooth a profile. In certain circumstances, it can create spurious high-frequency content, thus giving incorrect values. To correct this, a longwave-pass filter can be employed. A Gaussian filter is used, since this is the state-of-the-art. This filter has some shortcomings, e.g. it can distort rather than eliminate some roughness features and it can distort rather than transmit correctly some waviness features. It is envisioned that new filters under development within ISO provide better solutions for several of these issues.

NOTE 2 If a smaller tip radius than the one specified is used for a given cut-off length, the resulting measured value is generally higher. This effect is usually insignificant. If a larger tip radius is used, the resulting measured value is generally lower. The amount of change is heavily dependent on the surface measured.

NOTE 3 The measuring force of 0 N is chosen to eliminate effects of elastic deformation of the workpiece from the specification operator. On metal surfaces with adequate thickness, the effect of normally occurring measuring forces is negligible.

NOTE 4 Aliasing and other problems during extraction (see Annex A), due to the higher harmonic content of the skin model, in the straightness directions, can cause specification uncertainty.

This part of ISO 12780 is not intended to disallow any means of measuring straightness.