First edition 2000-07-01

Textiles — Determination of fabric propensity to surface fuzzing and to pilling —

Part 2: **Modified Martindale method**

Textiles — Détermination de la propension des étoffes à l'ébouriffage en surface et au boulochage —

Partie 2: Méthode Martindale modifié



ISO 12945-2:2000(E)

This is a preview of "ISO 12945-2:2000". Click here to purchase the full version from the ANSI store.

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents Foreword		Page
		iv
1	Scope	
2	Normative references	1
3	Terms and definitions	1
4	Principle	2
5	Apparatus	2
6	Auxiliary materials	8
7	Conditioning and testing atmosphere	9
8	Preparation of test specimens	9
9	Procedure	
10	Assessment of fuzzing and/or pilling	10
11	Results	11
12	Test report	11
Annex A (normative) Categories of pilling test		12
Bibliography		

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 12945 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 12945-2 was prepared by Technical Committee ISO/TC 38, Textiles.

ISO 12945 consists of the following parts, under the general title *Textiles* — *Determination of fabric propensity to surface fuzzing and to pilling*:

- Part 1: Pilling box method
- Part 2: Modified Martindale method
- Part 3: Determination using a random tumble method

Annex A forms a normative part of this part of ISO 12945.

Introduction

Pills are formed when fibres on a fabric surface "tease out" and become entangled during wear. Such surface deterioration is generally undesirable, but the degree of consumer tolerance for a given level of pilling will depend on the garment type and fabric end use.

Generally the level of pilling which develops is determined by the rates of the following parallel processes:

- a) fibre entanglement leading to pill formation;
- b) development of more surface fibre;
- c) fibre and pill wear-off.

The rates of these processes depend on the fibre, yarn and fabric properties. Examples of extreme situations are found in fabrics containing strong fibres versus fabric containing weak fibres. A consequence of the strong fibre is a rate of pill formation that exceeds the rate of wear-off. This results in an increase of pilling with an increase of wear. With a weak fibre the rate of pill formation competes with the rate of wear-off. This would result in a fluctuation of pilling with an increase of wear. There are other constructions that the surface fibre wear-off occurs before pill formation. Each of these examples demonstrates the complexity of evaluating the surface change on different types of fabric.

The ideal laboratory test would accelerate the wear processes a), b) and c) by exactly the same factor and would be universally applicable to all fibre, yarn and fabric types. No such test has been developed. However, a test procedure has been established in which fabrics can be ranked in the same order of fuzzing and pilling propensity as is likely to occur in end-use wear.

The modification to the very widely adopted Martindale abrasion testing machine on which this part of ISO 12945 is based is described in a publication by H. Knecht: *Neue Methode zur Prüfung der Pillingneigung* in Wirkerei und Strickerei Technik, **38** (1988), 12, p. 1309.

© ISO 2000 – All rights reserved