

This is a preview of "ISO 132:2011". [Click here to purchase the full version from the ANSI store.](#)

Fifth edition  
2011-11-15

---

---

## **Rubber, vulcanized or thermoplastic — Determination of flex cracking and crack growth (De Mattia)**

*Caoutchouc vulcanisé ou thermoplastique — Détermination de la  
résistance au développement d'une craquelure (De Mattia)*

---

---

Reference number  
ISO 132:2011(E)

© ISO 2011

This is a preview of "ISO 132:2011". [Click here to purchase the full version from the ANSI store.](#)



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2011

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

This is a preview of "ISO 132:2011". Click [here](#) to purchase the full version from the ANSI store.

## Contents

Page

Foreword .....	iv
Introduction.....	v
1 Scope .....	1
2 Normative references.....	1
3 Apparatus .....	1
4 Calibration.....	2
5 Test pieces .....	2
5.1 Shape, dimensions and preparation .....	2
5.2 Preparation of test pieces for crack growth measurement.....	3
5.3 Time interval between vulcanization and testing.....	5
5.4 Conditioning .....	5
5.5 Number of test pieces.....	5
6 Test conditions .....	5
6.1 Temperature.....	5
6.2 Humidity .....	5
7 Procedure.....	5
7.1 General .....	5
7.2 Determination of flex cracking.....	6
7.3 Determination of crack growth .....	6
8 Expression of results .....	6
8.1 Determination of flex cracking.....	6
8.2 Determination of crack growth .....	7
9 Precision .....	7
10 Test report.....	7
Annex A (normative) Calibration schedule .....	9
Annex B (informative) Precision.....	11
Bibliography.....	15

This is a preview of "ISO 132:2011". [Click here to purchase the full version from the ANSI store.](#)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 132 was prepared by Technical Committee ISO/TC 45, *Rubber and rubber products*, Subcommittee SC 2, *Testing and analysis*.

This fifth edition cancels and replaces the fourth edition (ISO 132:2005), of which it constitutes a minor revision the main purpose of which was to add Annex A concerning calibration and Annex B with precision results.

This is a preview of "ISO 132:2011". [Click here to purchase the full version from the ANSI store.](#)

## Introduction

Repeated bending or flexing of a rubber causes cracks to develop in that part of the surface where tension stress is set up during flexing or, if this part of the surface contains a crack, causes this crack to extend in a direction perpendicular to the stress. Certain soft vulcanizates, for instance those prepared from styrene-butadiene rubber, show marked resistance to crack initiation, but it is possible for these vulcanizates to have a low resistance to growth (propagation) of cracks. It is important, therefore, to measure both the resistance to crack initiation by flexing and the resistance to crack propagation.

The method is suitable for rubbers that have reasonably stable stress-strain properties, at least after a period of cycling, and do not show undue stress softening or set, or highly viscous behaviour. The results obtained for some thermoplastic rubbers should be treated with caution if the elongation at yield is below, or close to, the maximum strain imposed during the test.