Second edition 2016-11-15

Road vehicles — Diagnostic communication over Internet Protocol (DoIP) —

Part 3:

Wired vehicle interface based on IEEE 802.3

Véhicules routiers — Communication de diagnostic au travers du protocole internet (DoIP) —

Partie 3: Interface du véhicule câblé sur la base de l'IEEE802.3



Reference number ISO 13400-3:2016(E)

ISO 13400-3:2016(E)

This is a preview of "ISO 13400-3:2016". Click here to purchase the full version from the ANSI store.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Contents						
Fore	eword		iv			
Intr	oductio	onv				
1	Scop	e	1			
2	Normative references					
3	Terms and definitions					
4	Abbreviated terms					
5	Conventions					
6	Document overview					
7	7.1 7.2 7.3 7.4 7.5	General information Ethernet physical layer requirements Ethernet data link layer requirements Ethernet PHY and MAC requirements Ethernet activation line requirements 7.5.1 Vehicle activation line requirements 7.5.2 Vehicle activation line circuit example – Option 1 requirements 7.5.3 Vehicle activation line circuit example – Option 2 requirements 7.5.4 Principles of activation line operation 7.5.5 External test equipment activation line requirements 7.5.6 Vehicle manufacturers activation line requirements				
	7.6 7.7	Spice simulation of activation line options				
	7.8	Cable definitions				
Bibl	Bibliography					

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*.

This second edition cancels and replaces the first edition (ISO 13400-3:2011), which has been technically revised.

A list of all parts in the ISO 13400 series can be found on the ISO website.

Introduction

Vehicle diagnostic communication has been developed starting with the introduction of the first legislated emissions-related diagnostics and has evolved over the years, now covering various use cases ranging from emission-related diagnostics to vehicle-manufacturer-specific applications like calibration or electronic component software updates.

With the introduction of new in-vehicle network communication technologies, the interface between the vehicle's electronic control units and the test equipment has been adapted several times to address the specific characteristics of each new network communication technology requiring optimized data link layer definitions and transport protocol developments in order to make the new in-vehicle networks usable for diagnostic communication.

With increasing memory size of electronic control units, the demand to update this increasing amount of software and an increasing number of functions provided by these control units, technology of the connecting network and buses has been driven to a level of complexity and speed similar to computer networks. New applications (x-by-wire, infotainment) require high band-width and real-time networks (like FlexRay, MOST), which cannot be adapted to provide the direct interface to a vehicle. This requires gateways to route and convert messages between the in-vehicle networks and the vehicle interface to test equipment.

The intent of ISO 13400 (all parts) is to describe a standardized vehicle interface which

- separates in-vehicle network technology from the external test equipment vehicle interface requirements to allow for a long-term stable external vehicle communication interface,
- utilizes existing industry standards to define a long-term stable state-of-the-art communication standard usable for legislated diagnostic communication, as well as for manufacturer-specific use cases, and
- can easily be adapted to new physical and data link layers, including wired and wireless connections, by using existing adaptation layers.

To achieve this, all parts of ISO 13400 are based on the Open Systems Interconnection (OSI) Basic Reference Model specified in ISO/IEC 7498-1 and ISO/IEC 10731, which structures communication systems into seven layers. When mapped on this model, the services specified by ISO 14229-1, ISO 14229-2 and ISO 14229-5 are divided into

- a) unified diagnostic services (layer 7), specified in ISO 14229-1, ISO 14229-5, ISO 27145-3,
- b) presentation (layer 6):
 - 1) for enhanced diagnostics, specified by the vehicle manufacturer,
 - 2) for WWH-OBD (World-Wide Harmonized On-Board Diagnostics), specified in ISO 27145-2, SAE J1930-DA, SAE J1939-DA (SPNs), SAE J1939-73:2010, Appendix A (FMI), SAE J1979-DA, SAE J2012-DA,
- c) session layer services (layer 5), specified in ISO 14229-2,
- d) transport protocol (layer 4), specified in ISO 13400-2,
- e) network layer (layer 3) services, specified in ISO 13400-2, and
- f) physical and data link services (layers 1 and 2), specified in this document,

in accordance with Table 1.

Table 1 — Enhanced and legislated WWH-OBD diagnostic specifications applicable to the OSI layers

OSI 7 layers ^a	Vehicle manufacturer enhanced diagnostics	WWH-OBD document reference		
Application (layer 7)	ISO 14229-1/ISO, 14229	ISO 14229-1/ISO, 27145		
Presentation (layer 6)	Vehicle manufacturer specific	ISO 27145-2, SAE J1930-DA, SAE J1939-DA (SPNs), SAE J1939–73:2010, Appendix A (FMIs), SAE J1979-DA, SAE J2012- DA		
Session (layer 5)	ISO 14229-2	ISO 14229-2		
Transport (layer 4)	ISO 13400-2 DoIP TCP and IP			
Network (layer 3)				
Data link (layer 2)	ISO 13400-3 DoIP, IEEE 802.3			
Physical (layer 1)				
Seven layers according to ISO/IEC 7498-1 and ISO/IEC 10731.				

The application layer services covered by ISO 14229-5 have been defined in compliance with diagnostic services established in ISO 14229-1, but are not limited to use only with them.

The transport and network layer services covered by ISO 13400-2 have been defined to be independent of the physical layer implemented.

For other application areas, this document can be used with any Ethernet physical layer.