

This is a preview of "ISO 14118:2017". [Click here to purchase the full version from the ANSI store.](#)

Second edition  
2017-12

---

---

## **Safety of machinery — Prevention of unexpected start-up**

*Sécurité des machines — Prévention de la mise en marche intempestive*



Reference number  
ISO 14118:2017(E)

© ISO 2017

This is a preview of "ISO 14118:2017". [Click here to purchase the full version from the ANSI store.](#)



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
copyright@iso.org  
www.iso.org

This is a preview of "ISO 14118:2017". Click here to purchase the full version from the ANSI store.

## Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 General measures to prevent unexpected start-up</b> .....	<b>2</b>
4.1 General.....	2
4.2 Manual measures for isolation and energy dissipation.....	3
4.3 Other means to prevent unexpected (unintended) start-up.....	3
4.4 Signalling and warning (delayed start).....	3
<b>5 Isolation and energy dissipation</b> .....	<b>3</b>
5.1 Prevention of unexpected start-up upon restoration of any power supplies.....	3
5.2 Devices for isolation from power supplies.....	3
5.3 Locking (securing) devices.....	4
5.4 Devices for stored-energy dissipation or restraint (containment).....	4
5.4.1 General.....	4
5.4.2 Mechanical elements.....	5
5.4.3 Locking or securing facilities for the restraint (containment) devices.....	5
<b>6 Other measures to prevent unexpected start-up</b> .....	<b>5</b>
6.1 Design strategy.....	5
6.2 Measures to prevent unintended generation of start commands.....	6
6.2.1 Measures to prevent unintended actuation of manual start controls.....	6
6.2.2 Design of safety-related parts of the control system.....	7
6.2.3 Selection and location of power control elements.....	7
6.3 Measures to maintain stop commands.....	7
6.3.1 Principle.....	7
6.3.2 Maintained stop command generated by a stop control device (level A).....	7
6.3.3 Maintained stop command generated by machine control (level B/C).....	8
6.3.4 Mechanical disconnection (level D; see <a href="#">Figure 1</a> ).....	8
6.3.5 Moving-part immobilization (level E; see <a href="#">Figure 1</a> ).....	8
6.4 Automatic monitoring of the safe state (stopped condition) during a category 2 stop.....	8
<b>7 Design requirements for verification</b> .....	<b>8</b>
7.1 General.....	8
7.2 Provisions for verifying isolation.....	9
7.3 Provisions for verifying energy dissipation or restraint (containment).....	9
<b>Annex A (informative) Examples of tasks which can require the presence of persons in danger zones</b> .....	<b>10</b>
<b>Bibliography</b> .....	<b>11</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 199, *Safety of machinery*.

This second edition cancels and replaces the first edition (ISO 14118:2000), which has been technically revised and contains the following changes:

- the text has been edited to facilitate implementation of this document;
- the Scope has been redefined to exclude the specification of performance levels or safety integrity levels for safety-related parts of control systems;
- [Figure 1](#) has been updated.

This is a preview of "ISO 14118:2017". [Click here to purchase the full version from the ANSI store.](#)

## Introduction

The structure of safety standards in the field of machinery is as follows:

- a) type-A standards (basic safety standards) giving basic concepts, principles for design, and general aspects that can be applied to all machinery;
- b) type-B standards (generic safety standards) dealing with one safety aspect or one or more type(s) of safeguard that can be used across a wide range of machinery:
  - type-B1 standards on particular safety aspects (e.g. safety distances, surface temperature, noise);
  - type-B2 standards on safeguards (e.g. two-hand controls, interlocking devices, pressure sensitive devices, guards);
- c) type-C standards (machine safety standards) dealing with detailed safety requirements for a particular machine or group of machines.

This document is a type-B standard as stated in ISO 12100.

This document is of relevance, in particular, for the following stakeholder groups representing the market players with regard to machinery safety:

- machine manufacturers (small, medium and large enterprises);
- health and safety bodies (regulators, accident prevention organizations, market surveillance, etc.)

Others can be affected by the level of machinery safety achieved with the means of the document by the above-mentioned stakeholder groups:

- machine users/employers (small, medium and large enterprises);
- machine users/employees (e.g. trade unions, organizations for people with special needs);
- service providers, e.g. for maintenance (small, medium and large enterprises);
- consumers (in case of machinery intended for use by consumers).

The above-mentioned stakeholder groups have been given the possibility to participate at the drafting process of this document.

In addition, this document is intended for standardization bodies elaborating type-C standards.

The requirements of this document can be supplemented or modified by a type-C standard.

For machines which are covered by the scope of a type-C standard and which have been designed and built according to the requirements of that standard, the requirements of that type-C standard take precedence.

Keeping a machine in a stopped condition while persons are present in danger zones is one of the most important conditions of the safe use of machinery and hence, one of the major aims of the machine designer and machine user.

In the past, the concepts of “operating machine” and “stopped machine” were generally unambiguous; a machine was

- operating when its movable elements or some of them were moving;
- stopped when its movable elements were at rest.

Machine automation has made the relationship between “operating” and “moving” on one hand and “stopped” and “at rest” on the other hand, more difficult to define. Automation has also increased the

This is a preview of "ISO 14118:2017". [Click here to purchase the full version from the ANSI store.](#)

potential for unexpected start-up and a significant number of hazardous events have occurred where machines, stopped for diagnostic work or corrective actions, started up unexpectedly.

Hazards other than mechanical hazards generated by movable elements (e.g. from a laser beam) also need to be taken into account.

The risk assessment relating to the presence of persons in a danger zone of a stopped machine needs to take into account the probability of an unexpected start-up of the hazard-generating elements.

This document provides machine designers and machinery safety standard technical committees with samples of built-in measures which can be used to prevent unexpected start-up.