

Third edition
2013-09-15

Photography — Electronic still picture imaging — Picture transfer protocol (PTP) for digital still photography devices

*Photographie — Imagerie des prises de vue électroniques —
Protocole de transfert d'images (PTP) pour les appareils
photographiques électroniques numériques*



Reference number
ISO 15740:2013(E)

© ISO 2013



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

This is a preview of "ISO 15740:2013". Click [here](#) to purchase the full version from the ANSI store.

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Digital still photography device model	5
4.1 Overview	5
4.2 Baseline requirements	6
5 Data format specification	6
5.1 General format	6
5.2 Data types.....	7
5.3 Simple types.....	9
5.4 Arrays.....	11
5.5 Data sets.....	12
6 Image and data object formats	21
6.1 Object usage	21
6.2 Thumbnail formats.....	22
6.3 ObjectFormatCodes.....	23
6.4 Object format version identification	23
6.5 Data object association	24
7 Transport requirements	26
7.1 Disconnection events.....	26
7.2 Reliable, error-free channel	27
7.3 Asynchronous event support.....	27
7.4 Device discovery and enumeration.....	27
7.5 Specific transports	27
8 Persistent storage	27
8.1 StorageID.....	27
8.2 Data object referencing.....	28
8.3 Receiver object placement.....	29
9 Communication protocol	30
9.1 Device roles.....	30
9.2 Sessions.....	30
9.3 Transactions.....	30
9.4 Operation flow.....	33
9.5 Vendor extensions.....	33
10 Operations	35
10.1 Operation overview	35
10.2 Operation parameters.....	35
10.3 OperationCode format.....	35
10.4 OperationCode summary	35
10.5 Operation descriptions	35
11 Responses	60
11.1 ResponseCode format.....	60
11.2 ResponseCode summary	60
11.3 Response descriptions	61
12 Events	66
12.1 Event usage	66
12.2 Event types.....	66

This is a preview of "ISO 15740:2013". Click [here](#) to purchase the full version from the ANSI store.

12.3	Event data set.....	66
12.4	EventCode format.....	67
12.5	EventCode summary.....	67
12.6	Event descriptions.....	67
13	Device properties.....	71
13.1	Device property usage.....	71
13.2	Values of a device property.....	71
13.3	Device property management requirements.....	72
13.4	Device property identification.....	72
13.5	Device property descriptions.....	76
14	Streaming (PTP v1.1 only).....	92
14.1	Streaming overview.....	92
14.2	Stream transfer.....	92
14.3	Multiplexing.....	92
14.4	Discovering and configuring stream capabilities.....	93
14.5	Data transfer mechanism.....	93
14.6	Packet layout.....	94
14.7	Frame layout.....	95
14.8	Enumerating supported streams.....	95
14.9	Retrieving stream information.....	95
15	Conformance section.....	95
Annex A (informative) Optional device features.....		98
Annex B (normative) Object referencing and format codes.....		100
Annex C (informative) Operation flow example scenarios.....		102
Annex D (informative) Filesystem implementation examples.....		106
Annex E (informative) Reference to OSI model.....		109
Annex F (informative) SendObject implementation example.....		112
Bibliography.....		115

This is a preview of "ISO 15740:2013". [Click here to purchase the full version from the ANSI store.](#)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. www.iso.org/directives

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. www.iso.org/patents

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

The committee responsible for this document is ISO/TC 42, *Photography*.

This third edition cancels and replaces the second edition (ISO 15740:2008), of which it constitutes a minor revision with the following changes:

- as the vendor extension ID registry formerly maintained by the I3A has been transferred to another organization, term [3.21](#) (I3A) was removed and the remaining terms renumbered;
- in [9.5.1](#), the fourth and fifth sentences were amended and combined to reflect that a new organization assigns and maintains VendorExtensionIDs.

Introduction

This third edition of ISO 15740 (hereinafter designated PTP v1.1) provides optional support for new increased performance and compatibility. All new constructs are fully backward compatible with the first edition (hereinafter designated PTP v1.0) and are optional. See [5.5.2](#) for standard version.

For the purposes of this International Standard, digital still photography devices (DSPDs) are defined as devices with persistent storage which capture a digital two-dimensional image at a discrete point in time. Most DSPDs include interfaces that can be used to connect to a host computer or other imaging device, such as a printer. A number of high speed interface transports has been developed, including USB, TCP/IP and IEEE 1394 (FireWire). This International Standard is designed to provide requirements for communicating with DSPDs. This includes communications with any type of device, including host computers, direct printers and other DSPDs over a suitable transport. The requirements include standard image referencing behaviour, operations, responses, events, device properties, data sets and data formats to ensure interoperability. This International Standard also provides optional operations and formats, as well as extension mechanisms.

This International Standard specifies the following:

- behaviour requirements for DSPDs; this includes the baseline features a device needs to support in order to provide interoperability over conforming transports;
- functional requirements needed by a transport to facilitate the creation of a transport-dependent implementation specification that conforms to this International Standard;
- a high-level protocol for communicating with and between DSPDs consisting of operation, data and response phases;
- sets of suggested data codes and their usages including
 - OperationCodes,
 - ResponseCodes,
 - ObjectFormatCodes,
 - DevicePropCodes,
 - EventCodes,
 - required data sets and their usages,
 - a means of describing data object associations and filesystems and
 - mechanisms for implementing extensibility.

This International Standard does not attempt to define any of the following:

- any sort of device discovery, enumeration or transport aggregation methods; implementation of this functionality is left to the transports and the platforms upon which support for this International Standard is implemented;
- an application programming interface; this is left to the platforms upon which support for this International Standard is implemented.

This International Standard has been designed to appropriately support popular image formats used in digital still cameras, including the Exif and TIFF/EP formats defined in ISO 12234-1[\[15\]](#) and ISO 12234-2, as well as the Design Rule for Camera Filesystem (DCF) and the Digital Print Order Format (DPOF).

The technical content of this International Standard is closely related to PIMA 15740:2000. The main difference is that PIMA 15740:2000 includes an informative annex describing a USB implementation of

This is a preview of "ISO 15740:2013". [Click here to purchase the full version from the ANSI store.](#)

ISO 15740. This information is not included in this International Standard, which instead references the USB still device class document developed by the Device Working Group of the USB Implementers Forum.

PTP v1.1 provides optional support for new increased performance and compatibility. All new constructs are fully backward compatible with PTP v1.0 and are optional.

— Performance Enhancements:

- Support for retrieval of ObjectHandles in enumerated chunks, via specification of three new optional operations and a new response code. This may reduce long response times for some initiators that possess large numbers of objects.
- Support for optional arbitrary resizing prior to image transmission via specification of a new operation GetResizedImageObject. In PTP v1.0, image sizes might be requested in full-resolution or thumbnail size only.
- Support for arrays of data sets. This can be used to reduce the number of required transactions necessary for device characterization from being a function of the number of objects on the device to one.
- An optional fast file characterization operation called GetFilesystemManifest that exploits data set arrays to request, in a single transaction, only the minimum data required to characterize a typical filesystem. Many initiators, particularly in printing scenarios, are interested in fast filesystem characterization for access to a specifically named file in a particular place. This capability can significantly improve end-user workflow latency. This single operation replaces the typical series of many GetObjectInfo requests with a binary filesystem manifest. This manifest is defined as a simple array of a subset of the standard ObjectInfo data set called the ObjectFilesystemInfo data set. This operation replaces the need for many GetObjectInfo calls, while also avoiding the need for responders to perform many internal file-opens on the fly, or to cache ObjectInfo image data that is often held persistently only “inside” internal image files (e.g. TIFF tags inside EXIF JPEGs), to quickly communicate only the fast filesystem information.

— Compatibility Enhancements:

- An optional mechanism to support multiple vendor extension sets. This is specified via the new VendorExtensionMap data set, and two new optional operations that may be invoked outside of a session (GetVendorExtensionMaps and GetVendorDeviceInfo).
- The optional fast file characterization method GetFilesystemManifest natively supports extremely large objects, by requiring 8-bytes for object size (UINT64), as opposed to the standard 4-bytes.
- A new standard ObjectFormatCode to support the Digital Negative file format (DNG).

— Feature Enhancement:

- An optional mechanism for handling streaming content. This is specified via the new StreamInfo data set, as well as the supporting GetStreamInfo and GetStream operations, as well as some optional new supporting DeviceProperties. This is described in a new Clause 14.