

First edition  
2003-11-15

---

---

# **Photography — Spatial resolution measurements of electronic scanners for photographic images —**

## **Part 1: Scanners for reflective media**

*Photographie — Mesurages de résolution spatiale de scanners  
électroniques pour images photographiques —*

*Partie 1: Scanners pour milieux réfléchissants*



Reference number  
ISO 16067-1:2003(E)

© ISO 2003

This is a preview of "ISO 16067-1:2003". [Click here to purchase the full version from the ANSI store.](#)

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

This is a preview of "ISO 16067-1:2003". Click here to purchase the full version from the ANSI store.

## Contents

Page

<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Test chart</b> .....	<b>4</b>
4.1 General .....	4
4.2 General characteristics .....	4
4.3 Test chart elements .....	6
<b>5 Test conditions</b> .....	<b>7</b>
5.1 General .....	7
5.2 Temperature and relative humidity .....	7
5.3 Luminance and colour measurements .....	8
5.4 Linearization .....	8
5.5 Scanner settings .....	8
<b>6 Measuring the scanner OECF</b> .....	<b>8</b>
<b>7 Limiting visual resolution and its relation to SFR</b> .....	<b>8</b>
<b>8 Edge SFR test measurement</b> .....	<b>9</b>
<b>9 Presentation of results</b> .....	<b>9</b>
9.1 General .....	9
9.2 Scanner OECF .....	10
9.3 Resolution measurements .....	11
<b>Annex A (normative) Scanner OECF Test Patches</b> .....	<b>13</b>
<b>Annex B (normative) SFR algorithm</b> .....	<b>14</b>
<b>Annex C (informative) Using slanted edge analysis for colour spatial registration measurement</b> .....	<b>17</b>
<b>Bibliography</b> .....	<b>19</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 16067-1 was prepared by Technical Committee ISO/TC 42, *Photography*.

ISO 16067 consists of the following parts, under the general title *Photography — Spatial resolution measurements of electronic scanners for photographic images*:

- *Part 1: Scanners for reflective media*
- *Part 2: Film scanners*

This is a preview of "ISO 16067-1:2003". [Click here to purchase the full version from the ANSI store.](#)

## Introduction

One of the most important characteristics of an electronic print scanner is the ability to capture the fine detail found in the original print. This ability to resolve detail is determined by a number of factors, including the performance of the scanner lens, the number of addressable photoelements in the image sensor(s) used in the scanner, and the electrical circuits in the scanner. Different measurement methods can yield different metrics that quantify the ability of the scanner to capture fine details.

This part of ISO 16067 specifies methods for measuring the limiting visual resolution and spatial frequency response calculated from a slanted edge (Edge SFR) imaged by a print scanner. The scanner measurements described in this part of ISO 16067 are performed in the digital domain, using digital analysis techniques. A test chart of appropriate size and characteristics is scanned and the resulting data analysed. The test chart described in this part of ISO 16067 is designed specifically for the evaluation of continuous tone print scanners. It is not designed for evaluating electronic still picture cameras, video cameras or bi-tonal document scanners.

The edge SFR measurement method described in this part of ISO 16067 uses a computer algorithm to analyse digital image data from the print scanner. Pixel values near slanted vertical and horizontal edges are used to compute the SFR values. The use of a slanted edge allows the edge gradient to be measured at many phases relative to the image sensor photoelements, so that the SFR can be determined at spatial frequencies higher than the half-sampling frequency, sometimes called the Nyquist limit. This technique is mathematically equivalent to a moving knife edge measurement.