

This is a preview of "ISO 16770:2019". [Click here to purchase the full version from the ANSI store.](#)

Second edition
2019-09

Plastics — Determination of environmental stress cracking (ESC) of polyethylene — Full-notch creep test (FNCT)

Plastiques — Détermination de la fissuration sous contrainte dans un environnement donné (ESC) du polyéthylène — Essai sur éprouvette entièrement entaillée (FNCT)



Reference number
ISO 16770:2019(E)

© ISO 2019



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

This is a preview of "ISO 16770:2019". Click here to purchase the full version from the ANSI store.

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	3
5 Apparatus	3
6 Test specimens	6
6.1 General.....	6
6.2 Test specimens geometry.....	6
6.3 Test specimen preparation.....	8
6.3.1 General.....	8
6.3.2 Test specimens machined from compression moulded sheets.....	8
6.3.3 Test specimens machined from injection-moulded type 1A multipurpose test specimen.....	8
6.3.4 Test specimens machined from finished products.....	8
6.4 Test specimen notching.....	8
6.5 Conditioning of the test specimens.....	9
7 Test environment	9
7.1 General.....	9
7.2 Recommended test environment.....	9
7.2.1 Test environment No. 1.....	9
7.2.2 Test environment No. 2.....	10
7.3 Other test environments.....	11
8 Test procedure	11
8.1 Selection of detergent, reference tensile stress and test temperature.....	11
8.2 Number of test specimens to be tested.....	11
8.3 Calculation of the test load.....	13
8.4 Application of the load to the test specimen.....	13
8.5 Removing individual specimens from a chamber.....	13
8.6 Measurement of the ligament area after failure.....	13
9 Expression of results	14
9.1 Calculation of the actual tensile stress.....	14
9.2 Calculation of time to failure at the reference tensile stress.....	14
10 Precision	15
11 Test report	15
Annex A (informative) Precision statement	17
Annex B (informative) Example of a recommended test report for FNCT determination	20
Annex C (informative) Practical examples of fracture surfaces and corresponding definition of failure mode	22
Bibliography	25

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 61, *Plastics*, Subcommittee SC 9, *Thermoplastics*.

This second edition cancels and replaces the first edition (ISO 16770:2004), which has been technically revised.

The main changes compared to the previous edition are as follows:

- the test conditions for bimodal PE materials with substantially increased crack-resistance have been extended on an alternative more aggressive detergent;
- the compression moulding conditions for 10 mm × 10 mm test specimen (Type A) have been modified;
- the specimen types have been updated, with injection moulded test specimens being included;
- precision data (repeatability) from interlaboratory testing have been included for Type A test specimen.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

This is a preview of "ISO 16770:2019". [Click here to purchase the full version from the ANSI store.](#)

Introduction

Since mid-2000, the full-notch creep test (FNCT) has been widely used as one of the tests characterizing the environmental stress cracking (ESC) of polyethylene (PE) materials used in demanding applications. Among current ESC tests, the FNCT is relatively simple, easy to perform and still a sensitive laboratory scale test method to characterize ESC resistance of PE materials. The advantage of FNCT is that it enables the evaluation of the whole PE product range by variation of test conditions (test specimen geometry, temperature, medium and load conditions).

The FNCT method was standardized in 2004 as a PE material property, with partial precision statement based on the repeatability for a 6 mm × 6 mm-cross-sectional test specimen (Type B). Since then, several interlaboratory tests have been performed, resulting in a repeatability statement for 10 mm × 10 mm-cross-sectional test specimen (Type A). Type A specimen is prepared by using modified compression moulding conditions, which give more consistent test results compared to the original moulding conditions.

In addition, due to recent development of new PE pipe materials, known as PE 100 RC, which exhibit substantially improved crack resistance, it became necessary to define test conditions for these materials. Testing of these materials using the conditions specified in the previous edition of this document (i.e. ISO 16770:2004) resulted in failure times of one year or longer. As a consequence, this document includes extended test conditions to cover PE materials with substantially increased crack resistance. This accelerated test procedure using extended test conditions allows failure times to be reduced substantially compared to conventional test conditions given in ISO 16770:2004. In addition, a good correlation between accelerated and conventional test methods was derived; see References [4], [7] and [9].

The FNCT is a material characterization and production monitoring test, which, by strictly maintaining the test conditions defined, enables relevant and reliable comparison among similar PE materials or group of PE materials.