

Third edition  
2022-01

---

---

## Hydraulic fluid power — Filters — Multi-pass method for evaluating filtration performance of a filter element

*Transmissions hydrauliques — Filtres — Évaluation des  
performances par la méthode de filtration en circuit fermé*



Reference number  
ISO 16889:2022(E)

© ISO 2022



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

This is a preview of "ISO 16889:2022". [Click here to purchase the full version from the ANSI store.](#)

## Contents

Page

<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>2</b>
3.1 General terms.....	2
3.2 Terms related to differential pressure.....	2
<b>4 Symbols</b> .....	<b>4</b>
<b>5 General procedures</b> .....	<b>5</b>
<b>6 Test equipment</b> .....	<b>5</b>
<b>7 Measuring instrument accuracy and test condition variations</b> .....	<b>6</b>
<b>8 Filter performance test circuit validation procedures</b> .....	<b>7</b>
8.1 Filter test system validation.....	7
8.2 Validation of contaminant injection system.....	8
<b>9 Summary of information required prior to testing</b> .....	<b>9</b>
<b>10 Preliminary preparation</b> .....	<b>9</b>
10.1 Test filter assembly.....	9
10.2 Contaminant injection system.....	10
10.3 Filter test system.....	11
<b>11 Filter performance test</b> .....	<b>12</b>
<b>12 Calculations</b> .....	<b>13</b>
<b>13 Data presentation</b> .....	<b>15</b>
<b>14 Identification statement</b> .....	<b>17</b>
<b>Annex A (normative) Base test-fluid properties</b> .....	<b>20</b>
<b>Annex B (informative) Test system design guide</b> .....	<b>22</b>
<b>Annex C (informative) Examples of report calculations and graphs</b> .....	<b>28</b>
<b>Annex D (informative) Summary of data from the interlaboratory test programme conducted to verify the procedure in this document</b> .....	<b>37</b>
<b>Bibliography</b> .....	<b>43</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 6, *Contamination control*.

This third edition cancels and replaces the second edition (ISO 16889:2008), which has been technically revised. It also incorporates the Amendment ISO 16889:2008/Amd 1:2018.

The main changes are as follows:

- deletion of Table 4 (previous references to Table 4 replaced by references to ISO 11943:2021, Table C.2);
- harmonization of conductivity levels with ISO 23369.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

This is a preview of "ISO 16889:2022". [Click here to purchase the full version from the ANSI store.](#)

## Introduction

In hydraulic fluid power systems, one of the functions of the hydraulic fluid is to separate and lubricate the moving parts of the components. The presence of solid particulate contamination produces wear, resulting in loss of efficiency, reduced component life and subsequent unreliability.

A hydraulic filter is provided to control the number of particles circulating within the system to a level that is commensurate with the degree of sensitivity of the components to the contaminant and the level of reliability required by the users.

To enable the comparison of the relative performance of filters so that the most appropriate filter can be selected, it is necessary that test procedures be available. The performance characteristics of a filter are a function of the element (its medium and geometry) and the housing (its general configuration and seal design).

In practice, a filter is subjected to a continuous flow of contaminant entrained in the hydraulic fluid until some specified terminal differential pressure (relief-valve cracking pressure or differential-pressure indicator setting) is reached.

Both the length of operating time (prior to reaching terminal pressure) and the contaminant level at any point in the system are functions of the rate of contaminant addition (ingression plus generation rates) and the performance characteristics of the filter.

Therefore, it is necessary that a realistic laboratory test to establish the relative performance of a filter provide the test filter with a continuous supply of ingressed contaminant and allow the periodic monitoring of the filtration performance characteristics of the filter.

It is also necessary that the test provide an acceptable level of repeatability and reproducibility, and that a standard test contaminant, the ISO medium test dust (ISO MTD) in accordance with ISO 12103-1, be featured. This product has been shown to have a consistent particle-size distribution and is available worldwide. The filtration performance of the filter is determined by measurement of the upstream and downstream particle-size distributions using automatic particle counters validated according to ISO International Standards.

This test is intended to differentiate filter elements according to their functional performance but is not intended to represent performance under actual field operating conditions. Test conditions are steady-state, and the dynamic characteristics of industrial hydraulic systems are not represented. Other test protocols exist or are under development to evaluate performance with cyclic flow, high viscosity, flow fatigue, etc.

ISO 23369 (multi-pass testing method for evaluating the performance of hydraulic fluid power filter elements under cyclic-flow conditions) has been developed to supplement the steady-state testing of ISO 16889.