



**ISO 17987-6**

**Road vehicles — Local Interconnect  
Network (LIN) —**

Part 6:  
**Protocol conformance test  
specification**

*Véhicules routiers — Réseau Internet local (LIN) —*

*Partie 6: Spécification du protocole d'essai de conformité*

**Second edition  
2025-05**

This is a preview of ISO 17987-6:2025. [Click here to purchase the full version from the ANSI store.](#)



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

<b>Foreword</b> .....	<b>vii</b>
<b>Introduction</b> .....	<b>viii</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms, definitions, symbols and abbreviated terms</b> .....	<b>1</b>
3.1 Terms and definitions.....	1
3.2 Symbols.....	2
3.3 Abbreviated terms.....	3
<b>4 Conventions</b> .....	<b>4</b>
<b>5 General test specification considerations</b> .....	<b>5</b>
5.1 General.....	5
5.2 Test conditions.....	5
5.3 Mandatory requirements for IUT as commander.....	5
5.4 Mandatory requirements for IUT as responder.....	5
5.5 Test case architecture.....	5
5.6 Classification.....	6
5.7 Test system requirements.....	6
5.7.1 Generation of LIN frames.....	6
5.7.2 Common requirements for the test cases.....	6
5.7.3 Common requirements for bit timing testing.....	6
5.7.4 Test system for IUT as responder node.....	7
5.7.5 Sleep state verification for IUT as responder node.....	7
5.8 Test system definition.....	8
5.9 Global predefinitions for the test setup.....	8
5.9.1 Configuration of IUT and test system.....	8
5.9.2 Default delays for frame headers.....	9
5.9.3 Default bit rate.....	9
5.9.4 Time measurement.....	9
5.9.5 Default spaces between the different frame parts of a LIN message.....	10
<b>6 Essential test cases before test start</b> .....	<b>10</b>
6.1 General.....	10
6.2 [PT-CT 1] Diagnostic frame “commander request”, IUT as responder.....	10
6.3 [PT-CT 2] Diagnostic frame “responder response”, IUT as responder.....	10
6.4 [PT-CT 3] Error in received frame, IUT as responder.....	11
<b>7 Timing parameters</b> .....	<b>11</b>
7.1 General.....	11
7.2 [PT-CT 4] Length of break field low phase, IUT as commander.....	11
7.3 [PT-CT 5] Variation of length of break field low phase, IUT as responder.....	12
7.4 [PT-CT 6] Length of break delimiter, IUT as commander.....	12
7.5 [PT-CT 7] Variation of length of break delimiter, IUT as responder.....	13
7.6 [PT-CT 8] Inconsistent break field error, IUT as responder.....	14
7.7 [PT-CT 9] Inconsistent sync byte field error, IUT as responder.....	14
7.8 [PT-CT 10] Bit rate detection, IUT as responder with making use of detection.....	14
7.9 [PT-CT 10] Verification of the sync byte field, IUT as commander.....	16
7.10 [PT-CT 11] Incomplete frame reception, IUT as responder.....	16
7.11 [PT-CT 12] Unknown frame reception, IUT as responder.....	17
7.12 [PT-CT 13] Length of header, IUT as commander.....	17
7.13 [PT-CT 14] Variation of length of header, IUT as responder.....	18
7.14 [PT-CT 15] Bit rate tolerance, IUT as commander.....	18
7.15 [PT-CT 16] Bit rate tolerance, IUT as responder without making use of synchronization.....	19
7.16 [PT-CT 17] Bit rate tolerance, IUT as responder with making use of synchronization.....	19
7.17 Length of response.....	20

This is a preview of ISO 17987-6:2025. [Click here to purchase the full version from the ANSI store.](#)

7.17.3	[PT-CT 20] Acceptance of response field, IUT as responder .....	21
7.18	Verification of schedule table timing.....	22
7.18.1	[PT-CT 21] Verification of jitter, IUT as commander .....	22
7.18.2	[PT-CT 22] Schedule table management, IUT as commander .....	23
7.19	[PT-CT 23] Sample point test, IUT as responder .....	24
7.20	[PT-CT 24] Initialization time, IUT as responder.....	25
<b>8</b>	<b>Communication without failure .....</b>	<b>26</b>
8.1	Variation of LIN identifier.....	26
8.1.1	[PT-CT 25] Variation of LIN PID, IUT as commander.....	26
8.1.2	[PT-CT 26] Variation of LIN PIDs of subscribed frames, IUT as responder .....	26
8.1.3	[PT-CT 27] Variation of LIN identifier of published frames, IUT as responder .....	27
8.2	Transmission of the checksum byte.....	27
8.2.1	[PT-CT 28] Transmission of the checksum byte “classic checksum”, IUT as responder.....	27
8.2.2	[PT-CT 29] Transmission of the checksum byte “enhanced checksum”, IUT as responder.....	28
8.2.3	[PT-CT 30] Transmission of the checksum byte “classic checksum”, IUT as commander.....	28
8.2.4	[PT-CT 31] Transmission of the checksum byte of unconditional frames, IUT as commander.....	28
8.3	Unused bits .....	29
8.3.1	[PT-CT 32] Unused bits, IUT as commander .....	29
8.3.2	[PT-CT 33] Unused bits, IUT as responder .....	29
8.4	Reserved frame.....	30
8.4.1	[PT-CT 34] Reserved frame, IUT as responder.....	30
8.5	[PT-CT 35] Diagnostic frame commander request, IUT as commander .....	30
8.6	Supported frames according to the IUT specification .....	31
8.6.1	[PT-CT 36] Supported Tx frames according to the IUT specification, IUT as responder.....	31
8.6.2	[PT-CT 37] Supported Rx frames according to the IUT specification, IUT as responder.....	31
<b>9</b>	<b>Communication with failure .....</b>	<b>32</b>
9.1	General.....	32
9.2	[PT-CT 38] Bit error, IUT as responder.....	32
9.3	[PT-CT 39] Framing error in header of published frame, IUT as responder .....	33
9.4	[PT-CT 40] Framing error in response field of subscribed frame, IUT as responder.....	34
9.5	[PT-CT 41] Checksum error by inversion, IUT as responder.....	34
9.6	[PT-CT 42] Checksum error by carry, IUT as responder.....	35
9.7	[PT-CT 43] Communication robustness, IUT as responder .....	35
<b>10</b>	<b>Event triggered frames .....</b>	<b>35</b>
10.1	General.....	35
10.2	[PT-CT 44] Event triggered frame, IUT as responder.....	36
10.3	Event triggered frame with collision.....	36
10.3.1	[PT-CT 45] Event triggered frame with collision resolving, IUT as responder.....	36
10.3.2	[PT-CT 46] Event triggered frame with errors in collision resolving, IUT as responder.....	37
10.3.3	[PT-CT 47] Event triggered frame with collision resolving, IUT as commander.....	37
10.3.4	[PT-CT 48] Error in transmitted frame with collision, IUT as responder .....	38
<b>11</b>	<b>Status management .....</b>	<b>38</b>
11.1	[PT-CT 49] Error in received frame, IUT as responder .....	38
11.2	[PT-CT 50] Error in transmitted frame, IUT as responder .....	38
11.3	[PT-CT 51] response_error signal handling, IUT as responder.....	39
<b>12</b>	<b>Sleep/wake-up/power mode tests .....</b>	<b>39</b>
12.1	[PT-CT 52] Send “go-to-sleep command”, IUT as commander .....	39

This is a preview of ISO 17987-6:2025. [Click here to purchase the full version from the ANSI store.](#)

12.4	[PT-CT 55] Receive a wake-up signal, IUT as responder .....	41
12.5	Send a wake-up signal .....	42
12.5.1	[PT-CT 56] Send a wake-up signal, IUT as commander and IUT as responder .....	42
12.5.2	[PT-CT 57] Send a block of wake-up signals, IUT as responder .....	42
12.5.3	[PT-CT 58] Wait after one block of wake-up signals, IUT as responder .....	43
12.5.4	[PT-CT 59] Trigger wake-up signal followed by a frame header from commander, IUT as responder .....	43
12.6	[PT-CT 60] ECU power loss, IUT as commander .....	44
12.7	[PT-CT 61] Powered up with LIN shorted, IUT as commander .....	44
12.8	[PT-CT 62] LIN shorted before scheduling, IUT as commander .....	45
12.9	[PT-CT 63] LIN shorted after start of scheduling, IUT as commander .....	45
<b>13</b>	<b>Sleep state after bus idle .....</b>	<b>46</b>
13.1	[PT-CT 64] Sleep state after event and bus idle, IUT as responder .....	46
13.2	[PT-CT 65] Sleep state after bus idle with power up and wake-up signal, IUT as responder .....	47
13.3	[PT-CT 66] Timeout after bus idle, IUT as responder .....	48
<b>14</b>	<b>Frame ID range assignment .....</b>	<b>48</b>
14.1	[PT-CT 67] Frame ID range assignment with indirect response, IUT as responder .....	48
14.2	[PT-CT 68] Frame ID range unassignment with indirect response, IUT as responder .....	49
<b>15</b>	<b>Wildcards .....</b>	<b>50</b>
15.1	[PT-CT 69] Request with direct response, IUT as responder .....	50
<b>16</b>	<b>ReadByIdentifier command .....</b>	<b>50</b>
16.1	LIN product identification .....	50
16.1.1	[PT-CT 70] LIN product identification request with direct response, IUT as responder .....	50
16.1.2	[PT-CT 71] LIN product identification — With interleaved unconditional frame, IUT as responder .....	51
16.2	[PT-CT 72] ReadByIdentifier command with correct NAD, IUT as responder .....	51
16.3	[PT-CT 73] ReadByIdentifier command with incorrect addressing, IUT as responder .....	52
<b>17</b>	<b>NAD assignment .....</b>	<b>53</b>
17.1	General .....	53
17.2	[PT-CT 74] NAD assignment — Followed by ReadByIdentifier service, IUT as responder .....	53
17.3	[PT-CT 75] NAD assignment — With positive response, IUT as responder .....	53
17.4	[PT-CT 76] NAD assignment — Initial NAD, IUT as responder .....	53
<b>18</b>	<b>Save Configuration .....</b>	<b>54</b>
18.1	General .....	54
18.2	[PT-CT 77] Save configuration — With positive response, IUT as responder .....	54
18.3	[PT-CT 78] Save configuration — Save a new NAD, IUT as responder .....	54
18.4	[PT-CT 79] Save configuration — Save new frame identifiers, IUT as responder .....	55
<b>19</b>	<b>Transport protocol .....</b>	<b>56</b>
19.1	[PT-CT 80] Transport layer functional request, IUT as responder .....	56
19.2	[PT-CT 81] Abort diagnostic communication with new diagnostic request, IUT as responder .....	56
19.3	[PT-CT 82] IUT receives a segmented request as specified, IUT as responder .....	56
19.4	[PT-CT 83] IUT receives a segmented request interleaved with unconditional frame, IUT as responder .....	57
19.5	[PT-CT 84] IUT receives a segmented request with interleaved functional request, IUT as responder .....	58
19.6	IUT shall ignore request after timeout .....	59
19.6.1	[PT-CT 85] IUT shall ignore segmented requests on $N_{Cr_{max}}$ timeout, IUT as responder .....	59
19.6.2	[PT-CT 86] IUT shall observe transport layer $N_{As_{max}}$ timeout, IUT as responder .....	60

This is a preview of ISO 17987-6:2025. [Click here to purchase the full version from the ANSI store.](#)

19.8	[PT-CT 88] IUT shall respond with correct segmented response, IUT as responder.....	62
19.9	IUT sends a segmented response with interleaved unconditional frames.....	63
19.9.1	[PT-CT 89] IUT sends a segmented response with interleaved unconditional frame, IUT as responder.....	63
19.9.2	[PT-CT 90] IUT sends a segmented response with interleaved functional request, IUT as responder.....	64
19.10	[PT-CT 91] IUT shall not respond to responder response header if there is no request before, IUT as responder.....	65
19.11	[PT-CT 92] IUT shall not respond to responder response header if the response is already sent, IUT as responder.....	65
19.12	[PT-CT 93] IUT shall abort segmented response on $N_{Cs_{max}}$ timeout, IUT as responder.....	66
<b>Annex A (normative) LIN AA procedure C protocol conformance test plan.....</b>		<b>68</b>
<b>Annex B (normative) LIN AA procedure D protocol conformance test plan.....</b>		<b>75</b>
<b>Annex C (normative) LIN AA procedure E protocol conformance test plan.....</b>		<b>81</b>
<b>Bibliography.....</b>		<b>104</b>

This is a preview of ISO 17987-6:2025. [Click here to purchase the full version from the ANSI store.](#)

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at [www.iso.org/patents](http://www.iso.org/patents). ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*.

This second edition cancels and replaces the first edition (ISO 17987-6:2016), which has been technically revised.

The main changes are as follows:

- master and slave terms used for the LIN node types in the ISO 17987 series are replaced within this document with inclusive language terms commander and responder. This also applies for abbreviations and file formats NCF and LDF;
- variables and formulae aligned with the ISO/IEC Directives, Part 2;
- adoptions based on updates in the corresponding requirement document (ISO 17987-2);
- editorial updates and several statements improved to avoid ambiguities.

A list of all parts in the ISO 17987 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

This is a preview of ISO 17987-6:2025. [Click here to purchase the full version from the ANSI store.](#)

The LIN protocol as proposed is an automotive focused low speed universal asynchronous receiver transmitter (UART) based network. Some of the key characteristics of the LIN protocol are signal-based communication, schedule table-based frame transfer, commander/responder communication with error detection, node configuration and diagnostic service transportation.

The LIN protocol is for low-cost automotive control applications as, for example, door module and air conditioning systems. It serves as a communication infrastructure for low-speed control applications in vehicles by providing:

- signal-based communication to exchange information between applications in different nodes;
- bit rate support from 1 kbit/s to 20 kbit/s;
- deterministic schedule table-based frame communication;
- network management that wakes up and puts the LIN cluster into sleep state in a controlled manner;
- status management that provides error handling and error signalling;
- transport layer that allows large amount of data to be transported (such as diagnostic services);
- specification of how to handle diagnostic services;
- electrical physical layer specifications;
- node description language describing properties of responder nodes;
- network description file describing behaviour of communication;
- application programming interface.

The ISO 17987 series is based on the open systems interconnection (OSI) basic reference model as specified in ISO/IEC 7498-1 which structures communication systems into seven layers.

The OSI model structures data communication into seven layers called (top down) application layer (layer 7), presentation layer, session layer, transport layer, network layer, data link layer and physical layer (layer 1). A subset of these layers is used in the ISO 17987 series.

The ISO 17987 series distinguishes between the services provided by a layer to the layer above it and the protocol used by the layer to send a message between the peer entities of that layer. The reason for this distinction is to make the services, especially the application layer services and the transport layer services, reusable also for other types of networks than LIN. In this way, the protocol is hidden from the service user and it is possible to change the protocol if special system requirements demand it.

The ISO 17987 series provides all documents and references required to support the implementation of the requirements related to the following.

- ISO 17987-1: provides an overview of the ISO 17987 series and structure along with the use case definitions and a common set of resources (definitions, references) for use by all subsequent parts.
- ISO 17987-2: specifies the requirements related to the transport protocol and the network layer requirements to transport the PDU of a message between LIN nodes.
- ISO 17987-3: specifies the requirements for implementations of the LIN protocol on the logical level of abstraction. Hardware related properties are hidden in the defined constraints.
- ISO 17987-4: specifies the requirements for implementations of active hardware components which are necessary to interconnect the protocol implementation.

This is a preview of ISO 17987-6:2025. [Click here to purchase the full version from the ANSI store.](#)

define how a responder node is configured and how a responder node uses the identification service.

- ISO 17987-6 (this document): specifies tests to check the conformance of the LIN protocol implementation according to ISO 17987-2 and ISO 17987-3. This comprises tests for the data link layer, the network layer and the transport layer.
- ISO 17987-7: specifies tests to check the conformance of the LIN electrical physical layer implementation (logical level of abstraction) according to ISO 17987-4.