

This is a preview of "ISO 1817:2022". [Click here to purchase the full version from the ANSI store.](#)

Seventh edition
2022-06

Rubber, vulcanized or thermoplastic — Determination of the effect of liquids

*Caoutchouc vulcanisé ou thermoplastique — Détermination de
l'action des liquides*



Reference number
ISO 1817:2022(E)

© ISO 2022

This is a preview of "ISO 1817:2022". Click here to purchase the full version from the ANSI store.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

This is a preview of "ISO 1817:2022". [Click here to purchase the full version from the ANSI store.](#)

Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Apparatus.....	1
4.1 General.....	1
4.2 Apparatus for method A.....	2
4.3 Apparatus for method B.....	2
4.4 Apparatus for method C.....	2
4.5 Apparatus for method D.....	2
4.6 Apparatus for method E.....	3
4.7 Additional equipment.....	4
5 Calibration.....	4
6 Test liquids.....	4
7 Test pieces.....	5
7.1 Preparation.....	5
7.2 Dimensions.....	5
7.3 Time interval between vulcanization and testing.....	6
7.4 Conditioning.....	6
8 Immersion in the test liquid.....	6
8.1 Temperature.....	6
8.2 Duration.....	6
9 Procedure.....	7
9.1 General.....	7
9.2 Replacement of test liquid.....	8
9.3 Change in mass.....	8
9.4 Change in volume.....	8
9.5 Change in dimensions.....	9
9.6 Change in surface area.....	10
9.7 Change in hardness.....	10
9.8 Change in tensile stress-strain properties.....	11
9.9 Testing with liquid on one surface only.....	11
9.10 Determination of extractable matter.....	12
9.10.1 General.....	12
9.10.2 By weighing the dried test piece.....	12
9.10.3 By evaporating the test liquid.....	12
10 Precision.....	12
11 Test report.....	13
Annex A (normative) Reference liquids.....	14
Annex B (normative) Calibration schedule.....	17
Annex C (informative) Precision.....	19
Bibliography.....	25

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 45, *Rubber and rubber products*, Subcommittee SC 2, *Testing and analysis*.

This seventh edition cancels and replaces the sixth edition (ISO 1817:2015), which has been technically revised.

The main changes are as follows:

- [Clause 2](#), normative references, has been updated;
- methods A to E have been defined and the apparatus to be used has been updated in [Clause 4](#);
- the question about liquid replacement or not has been clarified in [9.2](#).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

This is a preview of "ISO 1817:2022". [Click here to purchase the full version from the ANSI store.](#)

Introduction

The action of a liquid on vulcanized or thermoplastic rubber can generally result in:

- a) absorption of the liquid by the rubber;
- b) extraction of soluble constituents from the rubber;
- c) a chemical reaction with the rubber.

The amount of absorption [a]) is usually larger than that of extraction [b]) so that the net result is an increase in volume, commonly termed "swelling". The absorption of liquid can profoundly alter physical and chemical properties and hence change tensile strength, extensibility, and hardness of the rubber, so it is important to measure these properties after treatment of the rubber. The extraction of soluble constituents, especially plasticizers and antidegradants, can likewise alter the rubber's physical properties and chemical resistance after drying (assuming the liquid to be volatile). Therefore, it is necessary to test these properties following immersion and drying of the rubber. This document describes the methods necessary for determining the changes in the following properties:

- change in mass, volume and dimensions;
- extractable matter;
- change in hardness and tensile stress-strain properties after immersion and after immersion and drying.

Although in some respects these tests may simulate service conditions, no direct correlation with service behaviour is implied. Thus, the rubber giving the lowest change in volume is not necessarily the best one in service. The thickness of the rubber needs to be taken into account since the rate of penetration of liquid is time-dependent and the bulk of a very thick rubber product may remain unaffected for the whole of the projected service life, especially with viscous liquids. Moreover, it is known that the action of a liquid on rubber, especially at high temperatures, can be affected by the presence of atmospheric oxygen. The tests described in this document can, however, provide valuable information on the suitability of a rubber for use with a given liquid and in particular, constitute a useful control when used for developing rubbers resistant to oils, fuels, or other service liquids.

The effect of a liquid may depend on the nature and magnitude of any stress within the rubber. In this document, test pieces are tested in an unstressed condition.