

First edition
2006-06-01

Textiles — Quantitative chemical analysis —

Part 2: Ternary fibre mixtures

Textiles — Analyses chimiques quantitatives —

Partie 2: Mélanges ternaires de fibres



Reference number
ISO 1833-2:2006(E)

© ISO 2006

This is a preview of "ISO 1833-2:2006". [Click here to purchase the full version from the ANSI store.](#)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

This is a preview of "ISO 1833-2:2006". Click here to purchase the full version from the ANSI store.

Contents

Page

Foreword.....	iv
Introduction	vi
1 Scope	1
2 Normative references	1
3 Principle.....	1
4 Reagents and apparatus	1
5 Conditioning and testing atmosphere.....	1
6 Sampling and pre-treatment of sample	1
7 Procedure	2
8 Calculation and expression of results.....	2
9 Method of analysis by a combination of manual separation and chemical means.....	7
10 Precision of methods	7
11 Test report	7
Annex A (informative) Examples of the calculation of percentages of the components of certain ternary mixtures using some of the variants described in 8.2	8
Annex B (informative) Table of typical ternary mixtures which may be analysed using methods of analysis of binary mixtures specified in the parts of ISO 1833	11
Bibliography	14

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 1833-2 was prepared by Technical Committee ISO/TC 38, *Textiles*.

This first edition cancels and replaces ISO 5088:1976, which has been withdrawn.

ISO 1833 consists of the following parts, under the general title *Textiles — Quantitative chemical analysis*:

- *Part 1: General principles of testing*
- *Part 2: Ternary fibre mixtures*
- *Part 3: Mixtures of acetate and certain other fibres (method using acetone)*
- *Part 4: Mixtures of certain protein and certain other fibres (method using hypochlorite)*
- *Part 5: Mixtures of viscose, cupro or modal and cotton fibres (method using sodium zincate)*
- *Part 7: Mixtures of polyamide and certain other fibres (method using formic acid)*
- *Part 8: Mixtures of acetate and triacetate fibres (method using acetone)*
- *Part 9: Mixtures of acetate and triacetate fibres (method using benzyl alcohol)*
- *Part 10: Mixtures of triacetate or polylactide and certain other fibres (method using dichloromethane)*
- *Part 11: Mixtures of cellulose and polyester fibres (method using sulfuric acid)*
- *Part 12: Mixtures of acrylic, certain modacrylics, certain chlorofibres, certain elastanes and certain other fibres (method using dimethylformamide)*
- *Part 13: Mixtures of certain chlorofibres and certain other fibres (method using carbon disulfide /acetone)*
- *Part 14: Mixtures of acetate and certain chlorofibres (method using acetic acid)*
- *Part 15: Mixtures of jute and certain animal fibres (method by determining nitrogen content)*

This is a preview of "ISO 1833-2:2006". [Click here to purchase the full version from the ANSI store.](#)

- *Part 16: Mixtures of polypropylene fibres and certain other fibres (method using xylene)*
- *Part 17: Mixtures of chlorofibres (homopolymers of vinyl chloride) and certain other fibres (method using sulfuric acid)*
- *Part 18: Mixtures of silk and wool or hair (method using sulfuric acid)*
- *Part 19: Mixtures of cellulose fibres and asbestos (method by heating)*
- *Part 21: Mixtures of chlorofibres, certain modacrylics, certain elastanes, acetates, triacetates and certain other fibres (method using cyclohexanone)*

The following parts are under preparation:

- *Part 6: Mixtures of viscose or certain types of cupro or modal or lyocell and cotton fibres (method using formic acid and zinc chloride)*
- *Part 20: Mixtures of elastane and certain other fibres (method using dimethylacetamide)*
- *Part 22: Mixtures of viscose or certain types of cupro or modal or lyocell and flax fibres (method using formic acid and zinc chlorate)*
- *Part 23: Mixtures of polyethylene and polypropylene (method using cyclohexanone)*
- *Part 24: Mixtures of polyester and some other fibres (method using phenol and tetrachloroethane)*

Introduction

The methods of quantitative analysis of mixtures of textile fibres are based on two processes: the manual separation and the chemical separation of fibre types.

The method of manual separation should be used whenever possible, since it generally gives more accurate results than the chemical method. It can be used for all textiles whose component fibres do not form an intimate mixture, as, for example, in the case of yarns composed of several elements each of which is made up of one type of fibre, or fabrics in which the warp is of a different type of fibre from the weft, or knitted fabrics capable of being unravelled and made up of yarns of different types.

In general, the methods for quantitative chemical analysis of ternary fibre mixtures are based on the selective solution of the individual components of the mixture. Four variants of this procedure are possible.

- Variant 1: Using two different test specimens, component (a) is dissolved from the first test specimen and component (b) from the second test specimen. The insoluble residues of each test specimen are weighed and the percentage of each soluble component is calculated from the respective losses in mass. The percentage of the third component (c) is calculated by difference.
- Variant 2: Using two different test specimens, a component (a) is dissolved from the first test specimen, and two components (a and b) from the second test specimen. The insoluble residue of the first test specimen is weighed and the percentage of the component (a) is calculated from the loss in mass. The insoluble residue of the second test specimen is weighed: it corresponds to component (c). The percentage of the third component (b) is calculated by difference.
- Variant 3: Using two different test specimens, two components (a and b) are dissolved from the first test specimen and two components (b and c) from the second test specimen. The insoluble residues correspond to the two components (c) and (a) respectively. The percentage of the third component (b) is calculated by difference.
- Variant 4: Using only one test specimen, one of the components is removed, after which the insoluble residue formed by the two other fibres is weighed and the percentage of the soluble component is calculated from the loss in mass. One of the two fibres of the residue is dissolved, the insoluble component is weighed and the percentage of the second soluble component is calculated from the loss in mass.

Where a choice is possible, it is advisable to use one of the first three variants. Where chemical analysis is used, take care to choose methods prescribing solvents which dissolve only the required fibre or fibres, and leave undissolved the other fibre or fibres.

By way of example, Annex B contains a certain number of ternary mixtures, together with methods for analysing binary mixtures which can, in principle, be used for analysing these ternary mixtures.

In order to reduce the possibility of error to a minimum, it is recommended that, whenever possible, chemical analysis using at least two of the four above-mentioned variants should be made.

Mixtures of fibres used during processing and, to a lesser extent, in finished textiles may contain non-fibrous matter such as fats, waxes or dressings, or water-soluble matter either occurring naturally or added to facilitate processing. Non-fibrous matter should be removed before analysis. A method of pre-treatment for removing oils, fats, waxes and water-soluble matter is given in ISO 1833-1:2006, Annex A.

In addition, textiles may contain resins or other matter added to confer special properties. Such matter, including dyestuffs in exceptional cases, may interfere with the action of the reagent on the soluble components and/or it may be partially or completely removed by the reagents.

This is a preview of "ISO 1833-2:2006". [Click here to purchase the full version from the ANSI store.](#)

This type of added matter may thus cause errors and should be removed before the sample is analysed. If it is impossible to remove such added matter, the methods for quantitative chemical analysis given in Annex B are no longer applicable.

Dye in dyed fibre is considered to be an integral part of the fibre and is not removed.

Analyses are conducted on the basis of dry mass and a procedure is given for its determination.

The result is expressed by reference to the dry mass or by reference to this mass after application of the conventional recovery rate.

Before proceeding with any analysis, all the fibres present in the mixture should be identified. In some chemical methods, the insoluble components of a mixture may be partially dissolved in the reagent used to dissolve the soluble component or components. Whenever possible, reagents have been chosen that have little or no effect on the insoluble fibres. If a loss in mass is known to occur during the analysis, the result should be corrected; correction factors are given for this purpose. These factors have been determined in several laboratories by treating, with the appropriate reagent as specified in the method of analysis, fibres cleaned by the pre-treatment. These correction factors apply only to undegraded fibres and different correction factors may be necessary if the fibres have been degraded before or during processing. If the fourth variant, in which a textile fibre is subjected to the successive action of two different solvents, should be used, correction factors should be applied for possible losses in mass undergone by the fibre in the two treatments.

At least two determinations should be made, both in the case of manual separation and in the case of chemical separation.